
AMICI Documentation

Release 0.11.27

The AMICI developers

Apr 07, 2022

ABOUT

1	About AMICI	3
1.1	Features	3
1.2	Interfaces & workflow	4
2	Availability	5
2.1	Source code	5
2.2	Python package	5
2.3	Installation instructions	5
3	License conditions	7
3.1	AMICI	7
3.2	AMICI Logo	7
3.3	Dependencies	8
4	How to cite AMICI	9
5	References	11
6	Background	13
6.1	Publications on various features of AMICI	13
6.2	Third-Party numerical algorithms used by AMICI	13
7	Changelog	15
7.1	v0.X Series	15
8	Glossary	45
9	Contributing	47
9.1	Contributing to AMICI	47
9.2	Code of Conduct	47
10	Python interface	49
10.1	Installing the AMICI Python package	49
10.2	Using AMICI's Python interface	55
10.3	FAQ	138
10.4	AMICI Python API	139
11	C++ interface	281
11.1	Building the C++ library	281
11.2	Using AMICI's C++ interface	282
11.3	AMICI C++ API	284

12 Matlab interface	531
12.1 Installing the AMICI MATLAB toolbox	531
12.2 Using AMICI's MATLAB interface	531
12.3 FAQ	538
12.4 AMICI Matlab API	539
13 AMICI developer's guide	573
13.1 Branches / releases	573
13.2 When starting to work on some issue	573
13.3 Code contributions	573
13.4 Further topics	575
14 Handling of Discontinuities	583
14.1 Mathematical Considerations	583
14.2 Algorithmic Considerations	583
15 Indices and tables	585
Python Module Index	587
Index	589

Version: 0.11.27

Source code: <https://github.com/AMICI-dev/amici>

ABOUT AMICI

AMICI provides a multi-language (Python, C++, Matlab) interface to the *SUNDIALS* solvers *CVODES* (for *ODEs*) and *IDAS* (for *DAEs*). AMICI allows the user to read differential equation models specified as *SBML* or *PySB* and automatically compiles such models into Python modules, C++ libraries or *.mex* simulation files (Matlab).

In contrast to the (no longer maintained) *sundialsTB* Matlab interface, all necessary functions are transformed into native C++ code, which allows for a significantly faster simulation.

Beyond forward integration, the compiled simulation file also allows for forward sensitivity analysis, steady state sensitivity analysis and adjoint sensitivity analysis for likelihood-based output functions.


The interface was designed to provide routines for efficient gradient computation in parameter estimation of biochemical reaction models but it is also applicable to a wider range of differential equation constrained optimization problems.

1.1 Features

- *SBML* import
- *PySB* import
- Generation of C++ code for model simulation and sensitivity computation
- Access to and high customizability of *CVODES* and *IDAS* solver
- Python, C++, Matlab interface
- Sensitivity analysis
 - forward
 - steady state
 - adjoint
 - first- and second-order (second-order Matlab-only)
- Pre-equilibration and pre-simulation conditions
- Support for discrete events and logical operations

1.2 Interfaces & workflow

The AMICI workflow starts with importing a model from either *SBML* (Matlab, Python), *PySB* (Python), or a Matlab definition of the model (Matlab-only). From this input, all equations for model simulation are derived symbolically and C++ code is generated. This code is then compiled into a C++ library, a Python module, or a Matlab *.mex* file and is then used for model simulation.



The functionality of the Python, Matlab and C++ interfaces slightly differ, as shown in the following table:

Feature \ Interface	Python	C++	Matlab
<i>SBML</i> import	yes (<i>details</i>)	no	yes (<=R2017b)
<i>PySB</i> import	yes	no	no
<i>DAE</i> import	no	no	yes
Forward sensitivities	yes	yes	yes
Adjoint sensitivities	yes	yes	yes
Steadystate sensitivities	yes	yes	yes
Second-order sensitivities	no	no	yes
Events	yes	yes	yes
<i>preequilibration</i>	yes	yes	yes
<i>presimulation</i>	yes	yes	no

AVAILABILITY

2.1 Source code

The AMICI source code is available as

- [tar archive](#)
- [zip archive](#)
- Git repository on [GitHub](#)

If AMICI was downloaded as an archive, it needs to be unpacked. If AMICI was obtained via cloning the Git repository, no further unpacking is necessary.

2.1.1 Obtaining AMICI via the Git version control system

In order to always stay up-to-date with the latest AMICI versions, simply pull it from our Git repository and recompile it when a new version is available. For more information about Git, check out their [website](#).

The Git repository can currently be found at <https://github.com/AMICI-dev/AMICI> and clone is done via:

```
git clone https://github.com/AMICI-dev/AMICI.git AMICI
```

2.2 Python package

A Python package is available on [PyPI](#).

2.3 Installation instructions

Installation instructions are available for

- *Python*
- *C++*
- *Matlab*

LICENSE CONDITIONS

3.1 AMICI

AMICI is released under the 3-Clause BSD License (BSD-3-Clause) with the following terms:

Copyright (c) 2015-2020, Fabian Fröhlich, Jan Hasenauer, Daniel Weindl and Paul Stapor All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

3.2 AMICI Logo

The AMICI logo is released under the Creative Commons CC0 1.0 Universal (CC0 1.0) license with the terms given in [documentation/gfx/LICENSE.md](#).

3.3 Dependencies

- Parts of the *SUNDIALS* solver suite are redistributed under the BSD 3-Clause License (BSD-3-Clause) with terms given in `ThirdParty/SuiteSparse/LICENSE.txt`
- Parts of *SuiteSparse* are redistributed under the various licenses with the terms given in `ThirdParty/SuiteSparse/LICENSE.txt`
- *gsl-lite* is redistributed under the MIT License (MIT) with the terms given in `ThirdParty/gsl/gsl/gsl-lite.hpp`
- *xml2struct* and *struct2xml* are redistributed under the BSD 2-Clause License (BSD-2-Clause) with terms given in `matlab/auxiliary/xml2struct/license.txt` and `matlab/auxiliary/struct2xml/license.txt`
- *CalcMD5* is redistributed under the BSD 2-Clause License (BSD-2-Clause) with terms given in `matlab/auxiliary/CalcMD5/license.txt`

HOW TO CITE AMICI

Citable DOI for the latest AMICI release:

There is a list of [publications using AMICI](#). If you used AMICI in your work, we are happy to include your project, please let us know via a Github issue.

When using AMICI in your project, please cite

- Fröhlich, F., Weindl, D., Schälte, Y., Pathirana, D., Paszkowski, Ł., Lines, G.T., Stapor, P. and Hasenauer, J., 2021. AMICI: High-Performance Sensitivity Analysis for Large Ordinary Differential Equation Models. *Bioinformatics*, btab227, DOI:10.1093/bioinformatics/btab227.

```
@article{frohlich2020amici,  
  title={AMICI: High-Performance Sensitivity Analysis for Large Ordinary  
↪ Differential Equation Models},  
  author={Fr{"o}hlich, Fabian and Weindl, Daniel and Sch{"a}lte, Yannik and  
↪ Pathirana, Dilan and Paszkowski, {\L}ukasz and Lines, Glenn Terje and Stapor,  
↪ Paul and Hasenauer, Jan},  
  journal = {Bioinformatics},  
  year = {2021},  
  month = {04},  
  issn = {1367-4803},  
  doi = {10.1093/bioinformatics/btab227},  
  note = {btab227},  
  eprint = {https://academic.oup.com/bioinformatics/advance-article-pdf/doi/10.1093/  
↪ bioinformatics/btab227/36866220/btab227.pdf},  
}
```

When presenting work that employs AMICI, feel free to use one of the icons in [documentation/gfx/](#), which are available under a [CC0](#) license:



REFERENCES

List of publications using AMICI. Total number is 66.

If you applied AMICI in your work and your publication is missing, please let us know via a new Github issue.

BACKGROUND

This section is to be extended.

6.1 Publications on various features of AMICI

Some mathematical background for AMICI is provided in the following publications:

- Fröhlich, F., Kaltenbacher, B., Theis, F. J., & Hasenauer, J. (2017). Scalable Parameter Estimation for Genome-Scale Biochemical Reaction Networks. *PLOS Computational Biology*, 13(1), e1005331. doi:[10.1371/journal.pcbi.1005331](https://doi.org/10.1371/journal.pcbi.1005331).
- Fröhlich, F., Theis, F. J., Rädler, J. O., & Hasenauer, J. (2017). Parameter estimation for dynamical systems with discrete events and logical operations. *Bioinformatics*, 33(7), 1049-1056. doi:[10.1093/bioinformatics/btw764](https://doi.org/10.1093/bioinformatics/btw764).
- Terje Lines, Glenn, Łukasz Paszkowski, Leonard Schmiester, Daniel Weindl, Paul Stapor, and Jan Hasenauer. 2019. “Efficient Computation of Steady States in Large-Scale Ode Models of Biochemical Reaction Networks. *IFAC-PapersOnLine* 52 (26): 32–37. DOI: [10.1016/j.ifacol.2019.12.232](https://doi.org/10.1016/j.ifacol.2019.12.232).
- Stapor, Paul, Fabian Fröhlich, and Jan Hasenauer. 2018. “Optimization and Profile Calculation of ODE Models Using Second Order Adjoint Sensitivity Analysis.” *Bioinformatics* 34 (13): i151–i159. DOI: [10.1093/bioinformatics/bty230](https://doi.org/10.1093/bioinformatics/bty230).

Note: Implementation details of the latest AMICI versions may differ from the ones given in the references manuscripts.

6.2 Third-Party numerical algorithms used by AMICI

AMICI uses the following packages from SUNDIALS:

- CVODES:
The sensitivity-enabled ODE solver in SUNDIALS. Radu Serban and Alan C. Hindmarsh. *ASME 2005 International Design Engineering Technical Conferences and Computers and Information in Engineering Conference*. American Society of Mechanical Engineers, 2005. [PDF](#)
- IDAS

AMICI uses the following packages from SuiteSparse:

- Algorithm 907: **KLU** A Direct Sparse Solver for Circuit Simulation Problems. Timothy A. Davis, Ekanathan Palamadai Natarajan, *ACM Transactions on Mathematical Software*, Vol 37, Issue 6, 2010, pp 36:1-36:17. [PDF](#)

- Algorithm 837: **AMD**, an approximate minimum degree ordering algorithm, Patrick R. Amestoy, Timothy A. Davis, Iain S. Duff, *ACM Transactions on Mathematical Software*, Vol 30, Issue 3, 2004, pp 381-388. [PDF](#)
- Algorithm 836: **COLAMD**, a column approximate minimum degree ordering algorithm, Timothy A. Davis, John R. Gilbert, Stefan I. Larimore, Esmond G. Ng *ACM Transactions on Mathematical Software*, Vol 30, Issue 3, 2004, pp 377-380. [PDF](#)

Others:

- SuperLU_MT
“A general purpose library for the direct solution of large, sparse, nonsymmetric systems of linear equations” (https://crd-legacy.lbl.gov/~xiaoye/SuperLU/#superlu_mt). SuperLU_MT is optional and is so far only available from the C++ interface.

CHANGELOG

7.1 v0.X Series

7.1.1 v0.11.27 (2022-04-04)

New features:

- Checking condition number when computing sensitivities via Newton by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1730>
- Removed SPBCG solver by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1729>
- Added Newton step convergence checks to steadystate solver by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1737>
- Removed legacy options/members `amioption.newton_preeq` and ``Solver::r...` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1744>
- Added `ReturnData::cpu_time_total` to track total time spent in `runAmiciSimulation` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1743>
- SBML import: Alternative algorithm for identifying conservation laws by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1748>
- Use `amici.AmiciVersionError` to indicate version mismatch by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1764>

Performance:

- Optional parallel computation of derivatives during model import by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1740>
- Sparsify jacobian by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1766>
- Speedup for models with conservation laws by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1765>
- Speedup conservation law computation by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1754>
- Exploit stoichiometric matrix in `pysb` import by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1761>
- Speedup edata construction from `petab` problems by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1746>

Fixes:

- Fixed `get_model_settings` that would to setting incorrect initial states and initial state sensitivities for models with parameter-dependent initial states by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1751>

- Use correct tolerances for convergence check in Newton solver by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1728>
- Harmonized convergence checks by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1731>
- Made sundials' KLU_INDEXTYPE match actual klu index type by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1733>
- Fixed `Model::setStateIsNonNegative` logic that would raise exceptions in cases where it shouldn't by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1736>
- Fixed undefined reference to `dladdr` by @kristianmeyerr in <https://github.com/AMICI-dev/AMICI/pull/1738>
- Fixed HDF5 OSX intermediate group creation errors by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1741>
- Fixed recent cmake-based build issues due to changed sundials library directory by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1756>
- Updated Windows installation instructions by @paulflang in <https://github.com/AMICI-dev/AMICI/pull/1763>

... and other contributions by @FFroehlich, @dweindl

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.26...v0.11.27>

7.1.2 v0.11.26 (2022-03-14)

New features:

- Import of BioNetGenLanguage (BNGL) models by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1709>
- Added support for observable-dependent sigmas by @dweindl, @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1692>
- Added support for pysb local functions by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1666>
- Added experimental support for conservation laws for non-constant species to SBML import: conservation laws for non-constant species by @stephanmg, @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1669> Enable this feature by setting environment variable `AMICI_EXPERIMENTAL_SBML_NONCONST_CLS` to any value
 - Allow using states eliminated by conservation laws to be used in root functions by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1677>
 - Added support for parameter-dependent conservation laws by @dweindl, @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1678>
- Added optional caching for symbolic simplifications in ODE export by @dilpath in <https://github.com/AMICI-dev/AMICI/pull/1672>
- Added CLI option `--no-sensitivities` to `amici_import_petab` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1688>

Fixes:

- SBML import: Raise in case of nested observables by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1690>
- Sympy 1.10 compatibility by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1694>

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.25...v0.11.26>

7.1.3 v0.11.25 (2022-02-09)

- Fixed a bug where `Model::setStateIsNonNegative(Model::getStateIsNonNegative())` would raise an exception in case conservation laws were enabled - by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1648>
- Fixed a bug where `Model::setStateIsNonNegative` would be ignored in certain model expressions - by @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1650>
- Fixed a bug where special function parsing inside `min()` and `max()` would not be parsed correctly - by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1655>
- Fixed a numpy dependency issues for Mac+ARM systems - by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1657>
- Fixed convergence check in Newton method - by @plakrisenko in <https://github.com/AMICI-dev/AMICI/pull/1663>
- Add `AMICI_CXX_OPTIONS` to pass libamici-specific compiler options during CMake-based builds - by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1664>
- Fixed various warnings and updated documentation - by @dweindl

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.24...v0.11.25>

7.1.4 v0.11.24 (2022-02-01)

Features:

- Introduced environment variable `AMICI_DLL_DIRS` to control DLL directories on Windows (useful for setting BLAS library directory, as required by Python>=3.8) by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1637>
- Dropped Python3.7 support by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1635>
- Include header files in CMake targets for better IDE integration by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1639>

Fixes:

- Fixed an issue in PETab import where all-integer parameters would previously result in a `TypeError` by @stephanmg in <https://github.com/AMICI-dev/AMICI/pull/1634>
- Fixed tempdir deletion issues for test suite on Windows by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1636>
- Added functions to provide state IDs/names for `x_solver` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1638>
- Fixed docs on RTD by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1643>

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.23...v0.11.24>

7.1.5 v0.11.23 (2022-01-11)

Features:

- Added overload for `Model::setParameterScale` with vector by @dilpath in <https://github.com/AMICI-dev/AMICI/pull/1614>
- Removed `assert_fun` argument from gradient checking, improve output by @dweindl, @FFroehlich in <https://github.com/AMICI-dev/AMICI/pull/1609>
- Added `get_expressions_as_dataframe` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1621>
- Added `id` field to `ExpData` and `ReturnData` by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1622>
- Included condition `id` in dataframes by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1623>

Fixes:

- C++: Fixed `SUNMatrixWrapper` ctor for size 0 matrices by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1608>
- Python: Handle `TemporaryDirectory` cleanup failures on Windows by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1617>
- Python: `pysb.Model.initial_conditions` throws a `DeprecationWarning` by @PaulJonasJost in <https://github.com/AMICI-dev/AMICI/pull/1620>
- Fixed wrong array size in warnings by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1624>

NOTE: AMICI 0.11.23 requires `numpy<1.22.0`

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.22...v0.11.23>

7.1.6 v0.11.22 (2021-12-02)

- **Require** `sympy>=1.9,pysb>=1.13.1` by @FFroehlich, @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1599>
- Fixed sympy deprecation warning by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1600>
- Updated Windows installation instructions for Python>=3.8 by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1597>
- Fixed plot labels by @dweindl in <https://github.com/AMICI-dev/AMICI/pull/1598>

Full Changelog: <https://github.com/AMICI-dev/AMICI/compare/v0.11.21...v0.11.22>

7.1.7 v0.11.21 (2021-11-21)

Fixes:

- Fixed a bug in recursion depth computation for model expressions. This may have resulted in incorrect sensitivities for models with expressions nested more than 2 levels. (#1595)
- Fixed improper handling of Piecewise functions in PySB import which may have produced incorrect simulation results. (#1594)
- Fixed changed googletest reference which broke the CMake-based build if tests were enabled (#1592)

New:

- It's now possible to build AMICI using Ninja (#1593)

7.1.8 v0.11.20 (2021-11-12)

New:

- Changed parameter mappings such that unassigned values have non-nan default values. This fixes erroneous evaluation of 11h as NaN in some situations (#1574)
- Added support for Python 3.10 (#1555)

Fixes:

- Fixed a bug when simulation start time was not transferred when copying a solver instance (#1573)
- Fixed a bug which led to incorrect sensitivities for models with multiple assignment rules or rate rules (#1584)

Other:

- Update CI and documentation settings (#1569, #1527, #1572, #1575, #1579, #1580, #1589, #1581)
- Extend set of validated benchmark models that is checked during CI (#1571, #1577)
- Fixed string formatting in derivative checks (#1585)
- Added helper methods to save and restore model instance-only settings (#1576)

7.1.9 v0.11.19 (2021-10-13)

New:

- Added support for observable transformations (lin/log/log10) (#1567). Thereby supporting additional noise distributions in combination with least squares solvers.

Fixes:

- Fixed a bug when Newton sensitivity computation was activated despite specifying `newton_steps == 0`. The error occurs when simulation converges to a steadystate but simulation sensitivities are not converged according to convergence criteria. In that case simulation returned failure, but the newton rootfinding “finds” a steadystate even before the iteration check, leading to the erroneous computation of sensitivities via Newton/IFT. For singular jacobians this means the overall simulation still fails, but a different, more informative error message is displayed. (#1541)
- Fixed a bug where argument “outdir” in `ODEExporter.init` would not be used (#1543)

Other:

- Improve checking support for SBML extensions (#1546)
- SBML import: Use more descriptive IDs for flux expressions (#1551)
- Optimized `SUNMatrixWrapper` functions (#1538)
- C++: Changed test suite from `CppUTest` to `gtest` (#1532)
- Add `CITATION.cff` (#1559)
- Updated documentation (#1563, #1554, #1536)
- Removed `distutils` dependency (#1557)
- Require `sympy<1.9`

7.1.10 v0.11.18 (2021-07-12)

New:

- Allow specifying maximum integration time via `amici::Solver::setMaxTime()` (#1530)
- Py: Add `failfast` and `num_threads` argument to `simulate_petab` (#1528, #1524)
- Enable typehints / static type checking for AMICI-generated model modules (#1514) (`amici.ModelModule`, available with Python \geq 3.8)

Fixes:

- Python: Fix unused argument `generate_sensitivity_code` in `pysb2amici` (#1526)
- Python: Fix C(++) stdout redirection which could have led to deadlocks in exotic situations (#1529)
- Py: Fixed deprecation warning (#1525)
- Py: Proper typehints for SWIG interface (#1523), enabling better static type checking and IDE integration (available with Python \geq 3.9)
- C++: Fixed clang compiler warning (#1521)
- C++: Fix inherited variadic ctor in exception class (#1520)
- PETab: More informative output for unhandled species overrides (#1519)
- Return `SbmlImporter` from PETab model import (#1517)

7.1.11 v0.11.17 (2021-05-30)

Fixes:

- Fix “maybe-uninitialized” compiler warning (#1495)
- Fix substitution of expressions in ``drootdt_total`` (#1512)
- C++: Fix serialization and `==` operator (#1493)
- C++: Avoid `w` in `root` and `stau` headers (refactor) (#1503)

Documentation:

- Updated OpenBLAS Windows installation instructions (#1496)
- Updated how-to-cite to Bioinformatics paper (#1499)
- Updated list of papers using AMICI (#1509)

Other:

- Remove `sllh` computation from `petab_objective.simulate_petab` (#1498)
- Add `main.py` to Python package to provide info on AMICI installation via `python -m amici` (#1500)

7.1.12 v0.11.16 (2021-04-13)

Fixes:

- Fixed serialization bug (#1490)

New:

- Construction of condition specific plist for parameter mappings (#1487, #1488)
- **Add support for error residuals** (#1489)

7.1.13 v0.11.15 (2021-03-31)

Fixes:

- Fixed initial state sensitivities in adjoint preequilibration (#1468)
- Fixed various model import / parameter mapping issues (#1469, #1473, #1475)

New:

- New AMICI releases will automatically trigger releases at <https://biosimulators.org/simulators/amici/latest>
- Transparent logo

7.1.14 v0.11.14 (2021-03-16)

New features:

- **Python import now supports SBML Events** (#1443)
- Implement support for compilation without sensitivities (#1454)

Fixes:

- Issue #1446: Check whether constant parameters are valid targets (#1450)
- Issue #1422: Fix Steadystate solver failing if preequilibration starts in steadystate (#1461)
- Issue #1401: Ensure diagnostics variables in ReturnData are always of expected length (#1438, #1447)
- Fix FIM approximation for parameter dependent sigma (#1441)
- Fix invalid SBML in PETab/PySB import (#1433)
- Fix: No context for inspect.getouterframes (#1432)

Documentation:

- Added this CHANGELOG
- Added feature request issue template (#1437)
- Updated reference list (#1430)
- Overhauled experimental conditions notebook (#1460)

CI:

- Test Matlab interface on GHA (#1451)
- Include componentTags in SBML test suite output (#1462)
- Split SBML semantic test suite into multiple jobs (#1452)

- Fix Crauste ref val, fixes #1458 (#1459)

Misc:

- Various cleanup (#1465, #1448, #1455)
- Micro-optimize SUNMatrixWrapper::transpose (#1439)
- Remove constant triggers from roots in Heaviside (#1440)

7.1.15 v0.11.13 (2021-02-20)

Breaking changes:

- AMICI requires Python \geq 3.7
- Updated package installation (PEP517/518): Creating source distributions requires <https://github.com/pypa/build> (#1384) (but now handles all package building dependencies properly)

Features:

- More flexible state reinitialization (#1417)

Updated dependencies:

- Upgrade to sundials 5.7.0 (#1392)

Fixes:

- Python: account for heaviside functions in expressions (#1382)
- Python: allow loading of existing models in import_petab_problem (#1383)
- Python: Don't override user-provided compiler/linker flags (#1389)
- Python: PETab import reinitialization fixes (#1417)
- Python: Fix PETab observables for pysb models (#1390)
- Python: Substitute expressions in event condition expressions (#1404)
- Python: Unspecified initial states in PETab conditions table default to SBML initial value (#1397)
- C++: Fix timepoint out of bounds access (#1402)
- C++: Fix exported CMake config (#1388)
- Fixed Dockerfile: add python3-venv (#1398, #1408)

Other:

- Slim exported swig interface (#1425)
- Updated documentation
 - Getting started tutorial (#1423)
 - List supported SBML test tags (#1428)
 - Add AMICI C++/Python/Matlab feature comparison (#1409)
 - ...
- Various minor CI improvements
- ...

7.1.16 v0.11.12 (2021-01-26)

Features:

- Add expression IDs and names to generated models (#1374)

Fixes:

- Raise minimum sympy version to 1.7.1 (Closes #1367)
- Fix species assignment rules in reactions (#1372)
- Fix id vector for DAEs (#1376)

Docs:

- Update how-to-cite (#1378)

7.1.17 v0.11.11 (2020-12-15)

Python

- Restore support for species references (#1358)
- Add support for noise models in pysb (#1360)
- Proper handling of discontinuities in the ODE rhs (#1352)
- Fix directly calling AMICI from snakemake (#1348)
- Extend mathml function support, particularly for numerical arguments (#1357)
- Restore support for sympy 1.6 (#1356)

C++

- Fix some compiler related warnings (#1349, #1362)
- Fix a rare segfault for adjoint sensitivities (#1351)

CI

- Move windows tests to GHA (#1354)
- Pin breathe to 4.24.1

Docker

- Update ubuntu to 20.04

7.1.18 v0.11.10 (2020-11-30)

Bugfix release that restores compatibility with sympy 1.7

7.1.19 v0.11.9 (2020-11-29)

Python

- General improvements to SBML import (#1312, #1316, #1315, #1322 , #1324 #1333, #1329)
- Small bugfixes and improvements (#1321)
- Improve derivative computation for instances of `power` (#1320)

C++

- Fix FIM and residual computation for models with parameter dependent sigma. (#1338)
- Disable chi2/residual/FIM computation for non-gaussian objective functions. (#1338)
- Bugfix for integration failure during adjoint solve (#1327)

Doc

- Update references (#1331, #1336)

CI

- Update OpenBLAS for windows (#1334)

7.1.20 v0.11.8 (2020-10-21)

Python

- Fix pysb-petab support (#1288)
- Fix ExpData constructor overloading (#1299)
- Fix support for positivity enforcement (#1306)
- **Refactor SBML import, adds support for parameter rate rules and initial assignments** (#1284, #1296, #1304)
- Improve model generation for models with many parameters (#1300)
- Add support for PEtab based synthetic data generation (#1283)

C++

- Make HDF5 an optional dependency (#1285)

Doc

- General Improvements to Documentation (#1289, #1291, #1292, #1293, #1294, #1286, #1277, #1281)

CI

- Add python 3.9 support test (#1282)
- Allow manual triggering of GitHub actions (#1287)
- Remove appveyor config (#1295)
- Update GHA env and path management (#1302)

7.1.21 v0.11.7 (2020-09-22)

Python

- Improve and extend available objective functions (#1235)
- Fix processing of compartment definitions (#1223)
- Fix replacement of reserved symbols (#1265)
- Use Hierarchical Derivatives for Expressions (#1224, #1246)
- Fix duplicate running of swig (#1216)
- Overload python interface functions for amici.{Model,Solver,ExpData} and amici.{Model,Solver,ExpData}Ptr (#1271)

C++

- Fix and extend use of sparse matrix operations (#1230, #1240, #1244, #1247, #1271)
- **Fix application of maximal number of steps.** MaxNumStep parameter now limit total number of steps, not number of steps between output times. (#1267)

Doc

- Move all Documentation to RTD (#1229, #1241)
- General Improvements to Documentation (#1225, #1227, #1219, #1228, #1232, #1233, #1234, #1237, #1238, #1239, #1243, #1253, #1255, #1262)

CI

- Better check for doc building (#1226)
- Add more gradient checks (#1213)
- Update GHA to Ubuntu 20.04 (#1268)

7.1.22 v0.11.6 (2020-08-20)

Python

- Bugfix for piecewise functions (#1199)
- Refactor swigging - generate one single wrapper (#1213)

C++

- Fix warnings: account for zero indexing in nan/inf error (#1112)

Doc

- Update Windows build instructions (#1200, #1202)
- Update README: Projects using AMICI (#1209)
- Add CODE_OF_CONDUCT.md (#1210)
- Update documentation for Python interface (#1208)

CI

- Create sdist on GHA using swig4.0.1 (#1204) (Fixing broken pypi package)
- Fix links after repository move
- Speed-up swig build: disable all languages except python (#1211)
- Fix doc generation on readthedocs (#1196)

7.1.23 v0.11.5 (2020-08-07)

General

- Move repo to new organization (#1193)
- Update Bibliography

Python

- Fix bug for energyPySB models (#1191)

CI

- Fix release deployment (#1189)

7.1.24 v0.11.4 (2020-08-06)

Python

- Skip unnecessary expressions in pysb models (#1185)
- MSVC compiler support (this time for real... #1152)

CI

- Implement MSVC tests (#1152)
- Rename and group GitHub actions (#1186)
- Fix release deployment (#1186)

7.1.25 v0.11.3 (2020-08-06)

Python

- Fix simplification for pysb models (#1168)
- Pass verbosity flags to pysb network generation (#1173)
- Enable experimental pysb-petab support (#1175)
- Add installation instructions for Fedora (#1177)
- Implement support for SBML rate-references (#1180)

C++

- Refactoring (#1162, #1163)

CI

- Move majority of tests to Github Actions (#1166, #1160)
- Improve reporting of skipped tests in SBML testsuite (#1183)

7.1.26 v0.11.2 (2020-07-17)

Python

- Speed up model import, compilation (#1123, #1112)
- Improve/Add steady-state solver documentation (#1102)
- Improve extension import (#1141)
- Bugfixes SBML import (#1135, #1134, #1145, #1154)
- Fixed issue that prevented simplification (#1158)

C++

- Bugfixes (#1121, #1125, #1131, #1132, #1136)
- Enable openMP by default (#1118)
- Improve memory footprint for simulations with replicates (#1153)
- Improve steady-state solver and add option to to adjoint-steadystate hybrid (#1143, #1099, #1129, #1146)

CI

- Store build artifacts from github actions (#1138)

7.1.27 v0.11.1 (2020-06-05)

Python

- Upgrade to sympy 1.6.0, which is now required minimum version (#1098, #1103)
- Speed up model import
 - Speed-up computation of `sx0`, reduce file size (#1109)
 - Replace terribly slow `sympy.MutableDenseMatrix.is_zero_matrix` by custom implementation (#1104)
- speedup dataframe creation in `get*AsDataFrame` (#1088)
- Allow caching edatas for `simulate_petab` (#1106)
- Fix wrong deprecation warning (Fixes #1093)
- Fix segmentation faults in `NewtonSolver` under certain conditions (#1089, #1090, #1097)
- fix wrong power function call in `unscale_parameter` (#1094)
- Fix MathML conversion (#1086)
- Fix deepcopy of SymPy objects (#1091)

Matlab

- handle empty `rdata->{pre|post}eq_numlinsteps` (Closes #1113), which previously made the matlab interface unusable
- Fix generation of `compileMexFile.m` for matlab compilation of python code (#1115)

C++

- Reduce memory requirements and speedup compilation of large models (#1105)
- Place generated code into own namespace (#937) (#1112)
- Fix several msvc compiler warnings (#1116) (Note that MSVC support is still experimental) **breaking change for users of C++ interface**
- Fix swig warning: ensure base class `ContextManager` is known before use (Fixes #1092) (#1101)

CI

- Don't install/run valgrind on travis CI (done with github actions... (#1111)

7.1.28 v0.11.0 (2020-05-10)

Python:

- **Implement support for variable compartments (#1036)**
- Better handling of constant species (#1047)
- **Better handling of C++ enums, this makes `amici.SensitivityMethod_forward` available as `amici.SensitivityMethod.forward` (#1042)**
- Improve installation routines (#1055, #1056, #1058, #1076)
- Add option to reduce memory usage (#1044)
- **Fix handling of symbolic expressions in nested rules (#1081, 1069)**

Library:

- Update Sundials to 5.2.0 (#1039)
- Update SuiteSparse to 5.4.0 (#1040)
- Refactor use of `ReturnData`, now completely created post-hoc (#1002)
- **Fix propagation of reinitialization in `ExpData` constructor (#1041)**
- **Fix issue where `InternalSensitivityParameter` was sometimes not set (#1075)**
- **Fix or disable certain combinations of equilibration, presimulation and adjoint sensitivity analysis**

CI:

- Move from Codacy to Sonarcloud (#1065)
- Run SBML Testsuite when appropriate (#1058)

7.1.29 v0.10.21 (2020-04-04)

Library:

- Fix: Handle paths with blanks in build scripts
- Feature: Add function to write amici::Solver settings to HDF5 (#1023)
- Fix: typehints (#1018, #1022)
- Refactor: Move creation of parameter mapping for objective<->simulation to classes (#1020)

CI:

- Refactor: Cleanup and reorganize tests (#1026)
- Fix: benchmark problem test should fail on missing files (Closes #1015)

7.1.30 v0.10.20 (2020-03-18)

- Fixed (re)initialization of sensitivities if ExpData::fixedParametersPreequilibration is set (#994)
- Fixed sensitivities for parameters in sigma expressions for Python/SBML in case provided expression was not just a single parameter ID
- Enable parallel compilation of model files from Python (#997) based on AMICI_PARALLEL_COMPILE environment variable
- Fixed computation of log-likelihood for log10-normal distributed noise
- Added `reinitializeFixedParameterInitialStates` to ExpData (#1000) (**breaking change**: overrides settings in `amici::Model`)
- Python model import now verifies that chosen model name is a valid identifier (Closes #928)
- Made `w` available in ReturnData (Closes #990) (#992)
- Fixed setting of log level when passing boolean values to verbose (#991)
- Documentation now on ReadTheDocs <https://amici.readthedocs.io/en/>
- Use proper state/observable names in plotting functions (#979)
- PETab support:
 - Adapt to most recent PETab (0.1.5)
 - Extended support for import of PETab models
 - Added support for computing cost function based on PETab problem
 - Implemented handling of species in condition table
 - `petab_import.import_model` now provides reproducible parameter list (Closes #976)
 - Fix python import error in `import_petab_problem`: Add absolute paths to python path, invalidate caches and reload (#970)
 - Added example notebook
- CI: PETab test suite integrated in CI workflow
- Added AMICI dockerfile and image deployment to dockerhub (#948)
- Removed mention of ‘mex’ in warning/error ids (#968)
- More informative errors on SWIG interface import failures (#959)

7.1.31 v0.10.19 (2020-02-13)

Python:

- Fix logo display on pypi
- Fix deadlocks in multithreaded python environments when using openMP parallelization

Matlab:

- Fix compilation errors due to switch to C++14

7.1.32 v0.10.18 (2020-02-11)

General:

- AMICI now comes with a logo
- implement getName function for models
- Updated documentation / examples

Python:

- Enable MSVC compilation of Python extensions (#847)
- Always recompile clibs and extensions (Closes #700)
- Extended PETab support (Running
- enable multithreading in swig (#938)
- Fixes pysb (#902) (#907)

C++

- Build optimized AMICI and sundials by default (Closes #934)

Matlab:

- Fix(matlab) Compile CalcMD5 on demand (Fixes #914)
- Don't pass empty include strings to mex
- Fix Matlab compilation error if AMICI or model path contains blanks

CI:

- Running additional test models

... and various minor fixes/updates

7.1.33 v0.10.17 (2020-01-15)

- **added python 3.8 support, dropped python 3.6 support** (#898)
- Added logging functionality (#900)
- Fixes PySB import (#879, #902)
- Fixes symbolic processing (#899)
- Improved build scripts (#894,
- Improved petab support (#886, #888, #891)

- CI related fixes (#865, #896)

7.1.34 v0.10.16 (2019-12-11)

- **Sparsify dwdp to reduce computation time for adjoints (#858)**
- Fix(matlab) update example name example_dae_events->example_calvetti (Closes #866)
- Fix nullptr deferencing for simulations with events when no measurements are provided (Fixes #866)
- Fix accessing empty vector during adjoint state event update (Closes #866)
- Fix pysb_import (fixes #878)

7.1.35 v0.10.15 (2019-12-03)

Bugfix release due to incorrect sensitivities w.r.t. sigmas introduced in 0.10.14.

No other changes.

7.1.36 v0.10.14 (2019-12-02)

NOTE: For Python-imported SBML-models this release may compute incorrect sensitivities w.r.t. sigma. Bug introduced in 0.10.14, fixed in 0.10.15.

Python:

- Don't require use of ModelPtr.get to call ExpData(Model)
- Fix import in generated model Python package
- Setup AMICI standalone scripts as setuptools entrypoints
- Simplify symbolic sensitivity expressions during Python SBML import Fixes Infs in the Jacobian when using Hill-functions with states of 0.0.
- Extended Newton solver #848The changes that allow performing Newton tests from the paper:G. T. Lines, Ł. Paszkowski, L. Schmiester, D. Weindl, P. Stapor, and J. Hasenauer. Efficient computation of steady states in large-scale ODE models of biochemical reaction networks. accepted for Proceedings of the 8th IFAC Conference on Foundations of Systems Biology in Engineering (FOSBE), Valencia, Spain, October 2019.
- Use SWIG>=4.0 on travis to include PyDoc in sdist / pypi package (#841)
- **Fix choice of likelihood formula; failed if observable names were not equal to observable IDs**
- Fix(sbml-import) Compartment IDs in right-hand side of Rules are not replaced and lead to undefined identifiers in c++ files
- Fix invalid logging level
- Speed up sympy simplification (#871)

C++:

- Performance: Avoid unnecessary repeated function calls for SUNMatrixWrapper dimensions
- Add AmiciApplication class as context for handling so far global settings. This allows for example setting custom logging functions for concurrent AMICI runs, e.g. in multi-thread applications (Closes #576).

Misc:

- Setup performance test on github actions (#853)

- Update documentation and FAQ for CBLAS requirement and others
- Update reference list

7.1.37 v0.10.13 (2019-10-09)

- BREAKING CHANGE: Renaming {get|set}tNewtonPreequilibration to {get|set}Preequilibration (Closes #720)
- Make wurlitzer non-optional requirement for AMICI python package (Fixes missing AMICI errors when running from jupyter notebooks)
- Compute initial state for Model::getInitialStates if not already set (Fixes #818)
- Make swig generate pydoc comments from doxygen comments #830 (Closes #745) to provide Python docstrings for C++ wrapper functions
- feature(cmake) Add option to disable compiler optimizations for wrapfunctions.cpp (Fixes #828) (#829)
- Change SBML test suite to pytest to allow for parallel test execution... (#824)
- Fix(cmake): -E option is not available in all sed versions. Neither is the equivalent -r. Use --regexp-extended instead (Closes #826)
- Refactor(python) Move PETab import code from command line script... (#825)
- Fix(core) Fix regular expressions for intel compiler (Closes #754) (#822)
- Update workflow figure to include PySB (Closes #799)
- Fix compiler warnings

7.1.38 v0.10.12 (2019-09-28)

- Fix handling of species specified in PETab condition table (#813)
- Fix some Visual C++ issues, update cppcheck handling, cleanup (VisualC++ still not fully supported)
- Minor fixups (#801)
- Create SBML test suite result files for upload to <http://sbml.org/Facilities/Database/> (#798)

7.1.39 v0.10.11 (2019-08-31)

- Fixed setting initial conditions for preequilibration (#784)
- Fixed species->parameter conversion during PETab import (#782)
- Set correct Matlab include directories in CMake (#793)
- Extended and updated documentation (#785, #787)
- Fix various SBML import issues
- Run SBML test suite using github actions instead of travisCI (#789)

7.1.40 v0.10.10 (2019-08-07)

- Simplify/fix AMICI installation
 - If available use environment modules to detect dependencies
 - Add SWIG installation script
- Update list of publication
- Update documentation
 - Update doc for SWIG build and custom SWIG location.
 - Add AMICI interface overview / workflow figure and show in README
 - Document environment variables for model/core compilation (Closes #737)
- Added handling of abs function, since there seem to be problems with case sensitivity (#713) Closes #770

Details: * cmake: Use package_ROOT environment variables * fix(cmake) Fix finding version.txt * cmake: Auto-detect loaded MKL environment module * cmake: Use new FindPython3 modules where possible * fix(python) Restore python3.6 compatibility * Inside venv, use pip instead of pip3 which should point to the correct version * fix(python) Workaround for missing ensurepip during venv creation [ci skip] * feature(python) Use MKL from environment modules to provide cblas * fix(python) Fix define_macros not being passed to setuptools for Extension * fix(python) Fix define_macros not being passed to setuptools for clibs * Do not always add 'cblas' library since users may want to override that by a cblas-compatible library with a different name (closes #736) * Update HDF5 path hints; use shared library if static is not available. * Check for HDF5_BASE from environment module * Fix system-dependent sundials library directory (Fixes #749) (#750) * Handle OSTYPE==linux in scripts/buildBNGL.sh (Fixes #751) * Add SWIG download and build script * Improve finding swig executable and allow user override via SWIG environment variable * Provide installation hints if no SWIG found (Closes #724) * Allow overriding cmake executable with environment variables in build scripts (Closes #738)

7.1.41 v0.10.9 (2019-07-24)

Fixup for missing version bump in v0.10.8 release. No code changes compared to v0.10.8.

7.1.42 v0.10.8 (2019-07-24)

Changes in this release:

All:

- Updated / extended documentation
- Fix reuse of Solver instances (#541)

C++:

- Check for correct AMICI version for model in CMake
- Add reporting of computation times (#699)

Python:

- Fix manifest file (#698)
- Fix initial amounts/concentrations in SBML import

... and various other minor fixes/improvements

7.1.43 v0.10.7 (2019-05-01)

Python

- fix unset noise distribution when automatically generating observables in case None are passed (#691)

7.1.44 v0.10.6 (2019-04-19)

C++

- Add SuperLUMT support (#681)
- Sparsified dJydy (#686)
- Enabled support of impulse-free events for DAE models (#687) - thanks to Sebastien Sten for providing a testcase for this

Python

- Enabled support for piecewise functions in SBML import (#662)
- Fix numeric type when constructing ExpData from Dataframes (#690)
- Fix dynamic override in PETab

7.1.45 v0.10.5 (2019-04-08)

Bugfix release

Doc

- Update documentation of Windows installation

C++

- Fix missing source files in CMakeLists.txt (#658)
- Set CMake policies to prevent warnings (Closes #676) (#677)
- Start using gsl::span instead of raw pointers (#393) (#678)

Python

- PySB parsing fix (#669)
- Fix failure to propagate BLAS_LIBS contents (#665)
- Require setuptools at setup (#673)
- Updated PETab import to allow for different noise models

7.1.46 v0.10.4 (2019-03-21)

Features / improvements:

- Implement ReturnData and ExpData wrappers as more efficient views (#657)
- Add list of references using AMICI (#659)
- Custom llh (normal/laplace, lin/log/log10) (#656)

Bugfixes:

- Speedup and fix travis build

7.1.47 v0.10.3 (2019-03-13)

Features / improvements:

- adds the option for early termination on integration failures for `runAmiciSimulations`
- improve runtime of `SUNMatrixWrapper::multiply`
- expose finite difference routines in public API
- enable parallel compilation of clib source files

Bugfixes:

- fixed symbolic processing for unreleased pysb features

7.1.48 v0.10.2 (2019-03-07)

Features / improvements:

- extended `ExpData` interface to allow for condition specific parameters, parameter scales, parameter lists, initial conditions and initial condition sensitivities.

Bugfixes:

- fixed output values of `ReturnData::x_ss` and `ReturnData::sx_ss`

7.1.49 v0.10.1 (2019-03-04)

- travis-ci.com migration
- fix problem with `has{variable}` functions
- allow to import sbml model from string, not only file

7.1.50 v0.10.0 (2019-03-01)

Features / improvements:

- updated sundials to 4.1.0
- updated SuiteSparse to 5.4.0
- added generic implementations for symbolic expressions that were sparse matrix vector products

Bugfixes:

- fixed return value of `rz` when no data is provided.

7.1.51 v0.9.5 (2019-02-26)

Features / improvements:

- allow python installations without compilation of c++ extension
- improvements to ExpData <-> pandas.DataFrame interface
- allow generation of matlab models from python
- implement CLI interface for PETab
- improve computation time for conservation laws from pysb import

Bugfixes:

- Fix sign in undamped Newton step.

Maintenance:

- use newer CI images

7.1.52 v0.9.4 (2019-02-11)

Minor fixes only:

- fix(core) Get solver diagnostics for first(last) timepoint (#588) (Closes #586)
- fix(ci) Fix autodeploy (Closes #589)

7.1.53 v0.9.3 (2019-02-07)

CRITICAL FIXES

- **fix(python) fix symbolic computations for adjoint (#583)**

Features

- feature(python) Check for matching AMICI versions when importing model (Closes #556). Set exact AMICI version as model package requirement.
- feature(core) Add option to rethrow AMICI exception (Closes #552)
- feature(python) Redirect C/C++ output in stdout is redirected (e.g. in ipython notebooks) (Closes #456)

Minor fixes

- fix(python) Fix doc and rename sys_pipes to something more meaningful
- fix(ci) Fix premature exit of scripts/runNotebook.sh
- fix(deploy) Update pyenv shims to find twine

7.1.54 v0.9.2 (2019-01-30)

Bugfixes:

- fixes a critical bug in the newton solver
- fixes multiple bugs in sbml import for degenerate models, empty stoichiometry assignments and conversion factors
- improved error messages for sbml import
- #560
- #557
- #559

7.1.55 v0.9.1 (2019-01-21)

Features / improvements:

- make pure steadystate results available as `rdata['x_ss']` and `rdata['sx_ss']`
- add option to specify integration tolerances for the adjoint problem via `atolB` and `rtolB`

Bugfixes:

- improved conservation law identification to also account for constant species.
- fixed a bug where simulation results were written into results of the second newton solver attempt
- fixed an openMP related warning

Maintenance:

- attempt to fix automatic deploy to pypi via travis

7.1.56 v0.9.0 (2019-01-18)

Features / improvements:

- Allow computation and application of conservation laws for pysb importet models. This enables use of Newton-Solver for preequilibration for models where it was previously not possible.
- Use `klu_refactor` in the sparse Newton solver instead of always using `klu_factor` and only perform symbolic factorization once (#421)
- Allow more detailed finiteness checks (#514)

Bugfixes:

- #491

Maintenance:

- Several improvements to travis log sizes and folding
- Use default copy constructor for Model by implementing class wrappers for sundials matrix types (#516)
- Reenable run of SBML testsuite

7.1.57 v0.8.2 (2019-01-07)

Features / improvements:

- Speedup symbolic processing for ODE generation in python

Bugfixes:

- Fix(python) Add missing deepcopy (introduced in 6847ba675f2088854db583199b8754aaa6e01576)
- Fix(core) Prevent parameter scaling length mismatch (#488)
- Fix(python) Set distutils dependency to current version to fix `</usr/lib/python3.6/distutils/dist.py:261: UserWarning: Unknown distribution option: 'long_description_content_type'>`
- fix(python) add symlink to version.txt to be included in package

Backwards-compatibility:

- Replace 'newline' by literal to restore <R2016b compatibility (Fixes #493)

Maintenance:

- Remove obsolete swig library build via cmake and related file copying
- Provide issue template for bug reports
- Providing valid SBML document to import is not optional anymore
- Update documentation and tests
- Add python version check and raise required version to 3.6 to prevent cryptic error messages when encountering f-strings

7.1.58 v0.8.1 (2018-11-25)

- [all] **critical** Fix long standing bugs in solving steadystate problems (including preequilibration) (#471)
- [all] Fix AmiVector constructor from `std::vector` (#471)
- [python] Reenable Solver and Model copy constructors
- Update documentation

7.1.59 v0.8.0 (2018-11-25)

- replaced symengine by sympy for symbolic processing in python *which fixes several critical bugs* that were due to bugs in symengine (#467)

7.1.60 v0.7.13 (2018-11-18)

- fixes a critical bug in objective function computation for models compiled using `sbml2amici` and `pysb2amici` that was introduced in v0.7.12
- fixes a critical bug in sensitivity computation when `model.reinitializeFixedParameterInitialStates` was set to true
- readds the python interface to the `ExpData` copy constructor that was inadvertently removed in 0.7.12 and streamlines the respective convenience wrapper to provide access to the full range of constructors.

7.1.61 v0.7.12 (2018-11-17)

- fixed a critical bug in `amici.constructEdataFromDataFrame`
- enabled multithreaded simulation of multiple experiments (requires compilation with openMP)
- modularized sbml import and added pysb import

7.1.62 v0.7.11 (2018-10-15)

- [python] Added numpy and python wrappers that provide a more user friendly python API
- [python] Enable import of SBML models with non-float assignment rules
- [python] Enable handling of exceptions in python
- [python] Enable native python access to `std::vector` data-structures
- [core] Provide an API for more fine-grained control over sensitivity tolerances and steady-state tolerances
- [core] Provide an API to specify non-negative state variables (this feature is still preliminary)

7.1.63 v0.7.10 (2018-08-29)

- Fixed python SBML import `log()` issues (#412)

7.1.64 v0.7.9 (2018-08-24)

- fixes MATLAB compilation of models
- adds option to perform steady state sensitivity analysis via FSA
- condition dependent initial conditions are now newly set after preequilibration is done

7.1.65 v0.7.8 (2018-08-19)

- bugfixes for the ExpData interface
- created build configuration that enables debugging of c++ extensions on os x
- fixed python sbml import when stoichiometry is empty

7.1.66 v0.7.7 (2018-08-17)

Fixes a couple of bugs just introduced in v0.7.6

7.1.67 v0.7.6 (2018-08-13)

Important: Use AMICI v0.7.7 due to <https://github.com/ICB-DCM/AMICI/pull/403/commits/3a495d3db2fdbba70c2b0d52a3d465>

Bug fixes:

- Python import: Fix log10 issues in observables (#382)
- Matlab: Fix broken model compilation (#392)
- Fixed simulation for models without observables (#390)
- Fixed potential matlab memory leaks (#392)

Breaking C++ API changes:

- Revised ExpData interface (#388)

7.1.68 v0.7.5 (2018-07-30)

Features/enhancements:

- Add computation of residuals, residuals sensitivity, Fisher information matrix (#223)
- More efficient conversion of std::vector to numpy ndarray (#375)
- Allow specifying timepoints in ExpData (#370)

Minor fixes:

- Condition parameters in ExpData now only temporarily override Model parameters (#371)
- Ensure non-negative states for Newton solver (#378)

7.1.69 v0.7.4 (2018-07-27)

Features/enhancements:

- Check SBML model validity (#343)
- Allow per-parameter setting of amioptions::pscale from matlab interface (#350)
- Documentation

Major fixes:

- Don't compile main.cpp into python model module which broke modules if amici was compiled without libhdf5 (#363)

Minor fixes:

- Fix compiler warnings (#353)
- Plotting, SBML example mode, ...

7.1.70 v0.7.3 (2018-07-13)

Features:

- Added symbol names to python-wrapped models and make available via `Model.getParameterNames()`, `model.getStateNames()`, ...
- Extended Python interface example

Python package available via pypi: <https://pypi.org/project/amici/0.7.3/>

7.1.71 v0.7.2 (2018-07-03)

Features:

- Python package: more flexible HDF5 library localization
- Extended CI: python tests, preequilibration tests, run in venv

Major bugfixes:

- Fix python sbml model import / compilation error (undefined function)
- Fix model preequilibration

Minor fixes:

- Various fixes for mingw compilation of python source distribution
- Cmake compatibility with < 3.8 restored

7.1.72 v0.7.1 (2018-06-12)

Features:

- Allow specifying sigma-parameters from Python interface

Major bugfixes:

- Fix `dsigma_y/dp` and downstream sensitivity errors

7.1.73 v0.7.0 (2018-06-09)

- Major revision of documentation
- Improved Python interface
- More comprehensive Python interface example
- Fixed sensitivity computation in Python-generated models
- Various other bug fixes

WARNING:

- For models with sigma-parameters and `dsigma_y/dp != 0`, `dsigma_y/dp` was computed incorrectly. This propagates to all dependent sensitivities. This applies also to some older releases and has been fixed in v0.7.1.

7.1.74 v0.6.0 (2018-05-22)

Implement experimental support for python via swig. Python interface is now usable, but API will still receive some updates in the future.

WARNING:

- There is a bug in sensitivity computation for Python-generated models
- Matlab C++ compilation will fail due to undefined M_PI -> Please use v0.7.0

7.1.75 v0.5.0 (2018-03-15)

Main new features are:

- Reimplemented support for DAE equations
- Added newton solver for steady state calculation and preequilibration
- Better caching for recompilation of models
- Blas support to allow compilation of large models with many observables
- Improved SBML support
- Added c++ interface
- Added support for second order adjoint computation
- Rewrote large parts of the code as proper c++11 code to allow easier code maintenance
- Substantially extended testing in continuous integration to assure code quality

7.1.76 v0.4.0 (2017-05-15)

- First citable version of AMICI (via zenodo integration).
- Better support for standalone compilation
- Improved SBML import scripts
- General Code Cleanup

7.1.77 v0.3.0 (2016-09-05)

This update comes with many improvements, bug fixes and several new features. Most notably:

1. AMICI should now run on older versions of MATLAB (back to R2014a)
2. AMICI now compiles using older versions of Visual Studio
3. AMICI now also supports second order adjoint sensitivities (full (via the o2flag = 1 and as a vector product via o2flag = 2)
4. AMICI now supports more SBML, SBML v2 and rate rules

7.1.78 0.2.1 (2016-05-09)

Bugfix release. This release also includes some changes that should improve the performance on the new R2016a release of MATLAB.

7.1.79 v0.2 (2016-03-17)

This update comes with many improvements to the computation time for both compilation and simulation. Moreover several new features were included:

1. Hessian Vector products for second order forward sensitivities
2. Correct treatment of parameter/state dependent discontinuities for both forward and adjoint sensitivities

7.1.80 v0.1 (2015-11-05)

This is the initial release of the toolbox

GLOSSARY

BNGL **BioNetGenLanguage** is a language for modular, structure-based modeling of biochemical reaction networks.

CVODES **CVODES** is a solver for stiff and non-stiff *ODE* systems with sensitivity analysis capabilities and is used by AMICI. It is part of the *SUNDIALS* solver suite.

DAE Differential-Algebraic Equation

fixed parameters In AMICI, *fixed parameters* are parameters with respect to which no sensitivities are computed. They usually correspond to experimental conditions. For fixed parameters, different values can be set for *preequilibration*, *presimulation* and simulation.

IDAS **IDAS** is a solver *DAE* systems with sensitivity analysis capabilities and is used by AMICI. It is part of the *SUNDIALS* solver suite.

ODE Ordinary Differential Equation

PEtab **PEtab** is a format for specifying parameter estimation problems. It is based on an *SBML* model and tab-separated value files specifying the observation model and experimental conditions.

preequilibration Simulating or solving the dynamical system for the steadystate.

presimulation Simulation for a fixed time before the regular simulation. Can be used to specify pretreatments.

PySB **PySB** is a tool for specifying rule-based systems biology models as Python code.

SBML The **Systems Biology Markup Language** is a commonly used format for specifying systems biology models.

SUNDIALS **SUNDIALS**: **SU**ite of **N**onlinear and **D**ifferential/**AL**gebraic equation **S**olvers. Provides the *CVODES* and *IDAS* solvers used by AMICI.

SWIG **SWIG** is a tool that creates interfaces for C(++) code to a variety of languages. Much of the AMICI Python interface is generated by SWIG.

CONTRIBUTING

9.1 Contributing to AMICI

We are happy about contributions to AMICI in any form, be it new functionality, documentation, bug reports, or anything else.

If you would to contribute to AMICI, a good start is looking for issues tagged `good first issue` or `help wanted`. For other ideas or questions, just post an issue.

For code contributions, please read our [developer's guide](#) first.

9.2 Code of Conduct

9.2.1 Our Pledge

In the interest of fostering an open and welcoming environment, we as contributors and maintainers pledge to making participation in our project and our community a harassment-free experience for everyone, regardless of age, body size, disability, ethnicity, sex characteristics, gender identity and expression, level of experience, education, socio-economic status, nationality, personal appearance, race, religion, or sexual identity and orientation.

9.2.2 Our Standards

Examples of behavior that contributes to creating a positive environment include:

- Using welcoming and inclusive language
- Being respectful of differing viewpoints and experiences
- Gracefully accepting constructive criticism
- Focusing on what is best for the community
- Showing empathy towards other community members

Examples of unacceptable behavior by participants include:

- The use of sexualized language or imagery and unwelcome sexual attention or advances
- Trolling, insulting/derogatory comments, and personal or political attacks
- Public or private harassment
- Publishing others' private information, such as a physical or electronic address, without explicit permission
- Other conduct which could reasonably be considered inappropriate in a professional setting

9.2.3 Our Responsibilities

Project maintainers are responsible for clarifying the standards of acceptable behavior and are expected to take appropriate and fair corrective action in response to any instances of unacceptable behavior.

Project maintainers have the right and responsibility to remove, edit, or reject comments, commits, code, wiki edits, issues, and other contributions that are not aligned to this Code of Conduct, or to ban temporarily or permanently any contributor for other behaviors that they deem inappropriate, threatening, offensive, or harmful.

9.2.4 Scope

This Code of Conduct applies both within project spaces and in public spaces when an individual is representing the project or its community. Examples of representing a project or community include using an official project e-mail address, posting via an official social media account, or acting as an appointed representative at an online or offline event. Representation of a project may be further defined and clarified by project maintainers.

9.2.5 Enforcement

Instances of abusive, harassing, or otherwise unacceptable behavior may be reported by contacting the project team at froehlichfab@gmail.com. All complaints will be reviewed and investigated and will result in a response that is deemed necessary and appropriate to the circumstances. The project team is obligated to maintain confidentiality with regard to the reporter of an incident. Further details of specific enforcement policies may be posted separately.

Project maintainers who do not follow or enforce the Code of Conduct in good faith may face temporary or permanent repercussions as determined by other members of the project's leadership.

9.2.6 Attribution

This Code of Conduct is adapted from the [Contributor Covenant](https://www.contributor-covenant.org/version/1/4/code-of-conduct.html), version 1.4, available at <https://www.contributor-covenant.org/version/1/4/code-of-conduct.html>

For answers to common questions about this code of conduct, see <https://www.contributor-covenant.org/faq>

PYTHON INTERFACE

10.1 Installing the AMICI Python package

10.1.1 Short guide

Installation of the AMICI Python package has the following prerequisites:

- Python \geq 3.8
- *SWIG* \geq 3.0
- CBLAS compatible BLAS library (e.g., OpenBLAS, CBLAS, Atlas, Accelerate, Intel MKL)
- a C++14 compatible C++ compiler and a C compiler (e.g., g++, clang, Intel C++ compiler, mingw)

If these requirements are fulfilled and all relevant paths are setup properly, AMICI can be installed using:

```
pip3 install amici
```

If this worked, you can now import the Python module via:

```
import amici
```

If this does not work for you, please follow the full instructions below.

10.1.2 Installation on Linux

Ubuntu 20.04

Install the AMICI dependencies via apt (this requires superuser privileges):

```
sudo apt install libatlas-base-dev swig  
  
# optionally for HDF5 support:  
sudo apt install libhdf5-serial-dev
```

Install AMICI:

```
pip3 install amici
```

Fedora 32

Install the AMICI dependencies via apt (this requires superuser privileges):

```
sudo dnf install blas-devel swig
```

Install AMICI:

```
pip3 install amici
```

10.1.3 Installation on OSX

Install the AMICI dependencies using homebrew:

```
brew install swig

# optionally for HDF5 support:
brew install hdf5

# optionally for parallel simulations:
brew install libomp
```

Install AMICI:

```
pip3 install amici
```

10.1.4 Installation on Windows

Some general remarks:

- Install all libraries in a path not containing white spaces, e.g. directly under C:.
- Replace the following paths according to your installation.
- Slashes can be preferable to backslashes for some environment variables.
- See also [#425](<https://github.com/AMICI-dev/amici/issues/425>) for further discussion.

Using the MinGW compilers

- Install [MinGW-W64](#) (the 32bit version will succeed to compile, but fail during linking).
MinGW-W64 GCC-8.1.0 for x86_64-posix-sjlj ([direct link](#)) has been shown to work on Windows 7 and 10 test systems.
- Add the following directory to your PATH: C:\mingw-w64\x86_64-8.1.0-posix-sjlj-rt_v6-rev0\mingw64\bin
- Make sure that this is the compiler that is found by the system (e.g. where gcc in a cmd should point to this installation).
- Download CBLAS headers and libraries, e.g. [OpenBLAS](#), binary distribution 0.2.19.

Set the following environment variables:

```
- BLAS_CFLAGS=-IC:/OpenBLAS-v0.2.19-Win64-int32/include
```

```
- BLAS_LIBS=-Wl,-Bstatic -LC:/OpenBLAS-v0.2.19-Win64-int32/lib -lopenblas -Wl,  
-Bdynamic
```

- Install [SWIG](#) and add the SWIG directory to PATH (e.g. C:\swigwin-3.0.12 for version 3.0.12)
- Install AMICI using:

```
pip install --global-option="build_clib" \  
            --global-option="--compiler=mingw32" \  
            --global-option="build_ext" \  
            --global-option="--compiler=mingw32" \  
amici --no-cache-dir --verbose`
```

Note: Possible sources of errors:

- On recent Windows versions, `anaconda3\Lib\distutils\cygwinccompiler.py` fails linking `msvcr140.dll` with `[...] x86_64-w64-mingw32/bin/ld.exe: cannot find -lmsvcr140`. This is not required for amici, so in `cygwinccompiler.py` return `['msvcr140']` can be changed to return `[]`.
- If you use a python version where `python/cpython#880` has not been fixed yet, you need to disable `define_hypot_hypot` in `anaconda3\include\pyconfig.h` yourself.
- `import amici` in Python resulting in the very informative

ImportError: DLL load failed: The specified module could not be found.

means that some amici module dependencies were not found (not the AMICI module itself). [DependencyWalker](#) can show you which ones.

Using the Microsoft Visual Studio

Note: Support for MSVC is experimental.

We assume that Visual Studio (not to be confused with Visual Studio Code) is already installed. Using Visual Studio Installer, the following components need to be included:

- Microsoft Visual C++ (MSVC). This is part of multiple packages, including Desktop Development with C++.
- Windows Universal C Runtime. This is an individual component and installs some DLLs that we need.

OpenBLAS

There are prebuilt OpenBLAS binaries available, but they did not seem to work well here. Therefore, we recommend building OpenBLAS from scratch.

To build OpenBLAS, download the following scripts from the AMICI repository:

- <https://github.com/AMICI-dev/AMICI/blob/master/scripts/installOpenBLAS.ps1>
- <https://github.com/AMICI-dev/AMICI/blob/master/scripts/compileBLAS.cmd>

The first script needs to be called in Powershell, and it needs to call `compileBLAS.cmd`, so you will need to modify line 11:

```
cmd /c "scriptscompileBLAS.cmd $version"
```

so that it matches your directory structure. This will download OpenBLAS and compile it, creating

```
C:\BLAS\lib\openblas.lib C:\BLAS\bin\openblas.dll
```

You will also need to define two environment variables:

```
BLAS_LIBS="/LIBPATH:C:\BLAS\lib openblas.lib"
BLAS_CFLAGS="/IC:/BLAS/OpenBLAS-0.3.19/OpenBLAS-0.3.19"
```

One way to do that is to run a PowerShell script with the following commands:

```
[System.Environment]::SetEnvironmentVariable("BLAS_LIBS", "/LIBPATH:C:/BLAS/lib openblas.
↪lib", [System.EnvironmentVariableTarget]::User)
[System.Environment]::SetEnvironmentVariable("BLAS_LIBS", "/LIBPATH:C:/BLAS/lib openblas.
↪lib", [System.EnvironmentVariableTarget]::Process)
[System.Environment]::SetEnvironmentVariable("BLAS_CFLAGS", "-IC:/BLAS/OpenBLAS-0.3.19/
↪OpenBLAS-0.3.19", [System.EnvironmentVariableTarget]::User)
[System.Environment]::SetEnvironmentVariable("BLAS_CFLAGS", "-IC:/BLAS/OpenBLAS-0.3.19/
↪OpenBLAS-0.3.19", [System.EnvironmentVariableTarget]::Process)
```

The call ending in `Process` sets the environment variable in the current process, and it is no longer in effect in the next process. The call ending in `User` is permanent, and takes effect the next time the user logs on.

Now you need to make sure that all required DLLs are within the scope of the `PATH` variable. In particular, the following directories need to be included in `PATH`:

```
C:\BLAS\bin C:\Program Files (x86)\Windows Kits\10\Redist\ucrt\DLLs\x64
```

The first one is needed for `openblas.dll` and the second is needed for the Windows Universal C Runtime.

If any DLLs are missing in the `PATH` variable, Python will return the following error upon `import amici`:

```
ImportError: DLL load failed: The specified module could not be found.
```

Almost all of the DLLs are standard Windows DLLs and should be included in either Windows or Visual Studio. But, in case it is necessary to test this, here is a list of some DLLs required by AMICI (when compiled with MSVC):

- `openblas.dll`
- `python37.dll`
- `MSVCP140.dll`
- `KERNEL32.dll`
- `VCRUNTIME140_1.dll`
- `VCRUNTIME140.dll`
- `api-ms-win-crt-convert-l1-1-0.dll`
- `api-ms-win-crt-heap-l1-1-0.dll`
- `api-ms-win-crt-stdio-l1-1-0.dll`
- `api-ms-win-crt-string-l1-1-0.dll`
- `api-ms-win-crt-runtime-l1-1-0.dll`
- `api-ms-win-crt-time-l1-1-0.dll`
- `api-ms-win-crt-math-l1-1-0.dll`

MSVCP140.dll, VCRUNTIME140.dll, and VCRUNTIME140_1.dll are needed by MSVC (see Visual Studio above). KERNEL32.dll is part of Windows and in C:\Windows\System32. The api-ms-win-crt-XXX-l1-1-0.dll are needed by openblas.dll and are part of the Windows Universal C Runtime.

Note: Since Python 3.8, the library directory needs to be set either from Python:

```
import os
# directory containing `openblas.dll`
os.add_dll_directory("C:\\BLAS\\bin")
import amici
```

or via the environment variable AMICI_DLL_DIRS.

If Python returns the following error upon `import amici`, try updating to the latest Python version.

OSError: [WinError 87] The parameter is incorrect: “

10.1.5 Further topics

Installation of development versions

To install development versions which have not been released to PyPI yet, you can install AMICI with pip directly from GitHub using:

```
pip3 install -e git+https://github.com/AMICI-dev/amici.git@develop#egg=amici\&
↪subdirectory=python/sdist
```

Replace develop by the branch or commit you want to install.

Note that this will only work on Windows if you have enabled developer mode, because symlinks are not supported by default ([more information](#)).

Light installation

In case you only want to use the AMICI Python package for generating model code for use with Matlab or C++ and don't want to be bothered with any unnecessary dependencies, you can run

```
pip3 install --install-option --no-libs amici
```

Note: Following this installation, you will not be able to simulate the imported models in Python.

Note: If you run into an error with above installation command, install all AMICI dependencies listed in [setup.py](#) manually, and try again. (This is because `pip --install-option` is applied to *all* installed packages, including dependencies.)

Custom installation

Installation of the AMICI Python package can be customized using a number of environment variables:

Variable	Purpose	Example
SWIG	Path to the <i>SWIG</i> executable	SWIG=\$HOME/bin/swig4.0
CC	Setting the C(++) compiler	CC=/usr/bin/g++
CFLAGS	Extra compiler flags used in every compiler invocation	
BLAS_CFLAGS	Compiler flags for, e.g. BLAS include directories	
BLAS_LIBS	Flags for linking BLAS	
ENABLE_GCOV_COVERAGE	Set to build AMICI to generate code coverage information	ENABLE_GCOV_COVERAGE=TRUE
ENABLE_AMICI_DEBUGGING	Set to build AMICI with debugging symbols	ENABLE_AMICI_DEBUGGING=TRUE
AMICI_PARALLEL_COMPILE	Set to the number of parallel processes to be used for C(++) compilation (defaults to 1)	AMICI_PARALLEL_COMPILE=4

Installation under Anaconda

To use an Anaconda installation of Python <https://www.anaconda.com/distribution/>, Python>=3.7), proceed as follows:

Since Anaconda provides own versions of some packages which might not work with AMICI (in particular the gcc compiler), create a minimal virtual environment via:

```
conda create --name ENV_NAME pip python
```

Here, replace ENV_NAME by some name for the environment.

To activate the environment, run:

```
source activate ENV_NAME
```

(and `conda deactivate` later to deactivate it again).

SWIG must be installed and available in your PATH, and a CBLAS-compatible BLAS must be available. You can also use conda to install the latter locally, using:

```
conda install -c conda-forge openblas
```

To make AMICI use openblas, set the following environment variable:

```
export BLAS_LIBS=-lopenblas
```

BLAS_LIBS needs to be set during installation of the AMICI package, as well as during any future model import.

To install AMICI, now run:

```
pip install amici
```

The pip option `--no-cache` may be helpful here to make sure the installation is done completely anew.

Now, you are ready to use AMICI in the virtual environment.

Note: Anaconda on Mac

If the above installation does not work for you, try installing AMICI via:

```
CFLAGS="-stdlib=libc++" CC=clang CXX=clang pip3 install --verbose amici
```

This will use the clang compiler.

You will have to pass the same options when compiling any model later on. This can be done by inserting the following code before model import:

```
import os
os.environ['CC'] = 'clang'
os.environ['CXX'] = 'clang'
os.environ['CFLAGS'] = '-stdlib=libc++'
```

(For further discussion see <https://github.com/AMICI-dev/AMICI/issues/357>)

Optional Boost support

Boost is an optional C++ dependency only required for special functions (including e.g. gamma derivatives) in the Python interface. Boost can be installed via package managers via

```
apt-get install libboost-math-dev
```

or

```
brew install boost
```

As only headers are required, also a [source code](#) download suffices. The compiler must be able to find the module in the search path.

10.2 Using AMICI's Python interface

In the following we will give a detailed overview how to specify models in Python and how to call the generated simulation files.

10.2.1 Model definition

This document provides an overview of different interfaces to import models in AMICI. Further examples are available in the AMICI repository in the [python/examples](#) directory.

SBML import

AMICI can import *SBML* models via the `amici.sbml_import.SbmlImporter()` class.

Status of SBML support in Python-AMICI

Python-AMICI currently **passes 996 out of the 1780 (~56%) test cases** from the semantic *SBML Test Suite* ([current status](#)).

The following SBML test suite tags are currently supported (i.e., at least one test case with the respective test passes; [tag descriptions](#)):

Component tags:

- AssignmentRule
- Compartment
- CSymbolAvogadro
- CSymbolTime
- EventNoDelay
- FunctionDefinition
- InitialAssignment
- Parameter
- RateRule
- Reaction
- Species

Test tags:

- 0D-Compartment
- Amount
- AssignedConstantStoichiometry
- AssignedVariableStoichiometry
- BoolNumericSwap
- BoundaryCondition
- Concentration
- ConstantSpecies
- ConversionFactors
- EventT0Firing
- HasOnlySubstanceUnits
- InitialValueReassigned
- L3v2MathML
- LocalParameters
- MultiCompartment

- NoMathML
- NonConstantCompartment
- NonConstantParameter
- NonUnityCompartment
- NonUnityStoichiometry
- ReversibleReaction
- SpeciesReferenceInMath
- UncommonMathML
- VolumeConcentrationRates

In addition, we currently plan to add support for the following features (see corresponding [issues](#) for details and progress):

- Algebraic rules ([#760](#))

However, the following features are unlikely to be supported:

- any SBML extensions
- *factorial()*, *ceil()*, *floor()*, due to incompatibility with symbolic sensitivity computations
- *delay()* due to missing *SUNDIALS* solver support
- events with delays, events with non-persistent triggers

Tutorials

A basic tutorial on how to import and simulate SBML models is available in the [Getting Started notebook](#), while a more detailed example including customized import and sensitivity computation is available in the [Example Steadystate notebook](#).

PySB import

AMICI can import *PySB* models via `amici.pysb_import.pysb2amici()`.

BNGL import

AMICI can import *BNGL* models via `amici.bngl_import.bngl2amici()`.

PEtab import

AMICI can import *PEtab*-based model definitions and run simulations for the specified simulations conditions. For usage, see [python/examples/example_petab/petab.ipynb](#).

Importing plain ODEs

The AMICI Python interface does not currently support direct import of ODEs. However, it is straightforward to encode them as RateRules in an SBML model. The [yaml2sbml](#) package may come in handy, as it facilitates generating SBML models from a YAML-based specification of an ODE model. Besides the SBML model it can also create [PEtab](#) files.

SED-ML import

We also plan to implement support for the [Simulation Experiment Description Markup Language \(SED-ML\)](#).

10.2.2 Examples

Getting Started in AMICI

This notebook is a brief tutorial for new users that explains the first steps necessary for model simulation in AMICI, including pointers to documentation and more advanced notebooks.

Model Compilation

Before simulations can be run, the model must be imported and compiled. In this process, AMICI performs all symbolic manipulations that later enable scalable simulations and efficient sensitivity computation. The first towards model compilation is the creation of an [SbmlImporter](#) instance, which requires an SBML Document that specifies the model using the [Systems Biology Markup Language \(SBML\)](#).

For the purpose of this tutorial, we will use `model_steadystate_scaled.xml`, which is contained in the same directory as this notebook.

```
[1]: import amici
sbml_importer = amici.SbmlImporter('model_steadystate_scaled.xml')
```

Next, we will compile the model as python extension using the `amici.SbmlImporter.sbml2amici` method. The first two arguments of this method are the name of the model, which will also be the name of the generated python module, and the model directory, which defines the directory in which the model module will be placed. Compilation will take a couple of seconds.

```
[2]: model_name = 'model_steadystate'
model_dir = 'model_dir'
sbml_importer.sbml2amici(model_name, model_dir)
```

Loading the model module

To run simulations, we need to instantiate [amici.Model](#) and [amici.Solver](#) instances. As simulations requires instances matching the imported model, they have to be imported from the generated model module.

```
[3]: # load the model module
model_module = amici.import_model_module(model_name, model_dir)
# instantiate model
model = model_module.getModel()
# instantiate solver
solver = model.getSolver()
```

The model allows the user to manipulate model related properties of simulations. This includes the values of model parameters that can be set by using `amici.Model.setParameterByName`. Here, we set the model parameter `p1` to a value of $1e-3$.

```
[4]: model.setParameterByName('p1', 1e-3)
```

In contrast, the solver instance allows the specification of simulation related properties. This includes setting options for the SUNDIALS solver such as absolute tolerances via `amici.Solver.setAbsoluteTolerance`. Here we set the absolute integration tolerances to $1e-10$.

```
[5]: solver.setAbsoluteTolerance(1e-10)
```

Running Model Simulations

Model simulations can be executed using the `amici.runAmiciSimulations` routine. By default the model does not contain any timepoints for which the model is to be simulated. Here we define a simulation timecourse with two timepoints at 0 and 1 and then run the simulation.

```
[6]: # set timepoints
model.setTimepoints([0,1])
rdata = amici.runAmiciSimulation(model, solver)
```

Simulation results are returned as `ReturnData` instance. The simulated SBML species are stored as `x` attribute, where rows correspond to the different timepoints and columns correspond to different species.

```
[7]: rdata.x
[7]: array([[0.1      , 0.4      , 0.7      ],
          [0.98208413, 0.51167992, 0.10633388]])
```

All results attributes are always ordered according to the model. For species, this means that the columns of `rdata.x` match the ordering of species in the model, which can be accessed as `amici.Model.getStateNames`

```
[8]: model.getStateNames()
[8]: ('x1', 'x2', 'x3')
```

This notebook only explains the basics of AMICI simulations. In general, AMICI simulations are highly customizable and can also be used to simulate sensitivities. The [ExampleSteadystate](#) notebook in this folder gives more detail about the model employed here and goes into the basics of sensitivity analysis. The [ExampleEquilibrationLogic](#) notebook, builds on this by using a modified version of this model to give detailed insights into the methods and options to compute steady states before and after simulations, as well as respective sensitivities. The [ExampleExperimentalConditions](#) notebook, goes into the details of how even more complex experimental setups, such as addition of drugs at predefined timepoints, can be simulated in AMICI. Finally, the [petab](#) notebook explains how standardized definitions of experimental data and conditions in the [PEtab](#) format can be imported in AMICI.

AMICI Python example “steadystate”

This is an example using the [model_steadystate_scaled.sbml] model to demonstrate and test SBML import and AMICI Python interface.

```
[1]: # SBML model we want to import
sbml_file = 'model_steadystate_scaled_without_observables.xml'
# Name of the model that will also be the name of the python module
model_name = 'model_steadystate_scaled'
# Directory to which the generated model code is written
model_output_dir = model_name

import libsbml
import importlib
import amici
import os
import sys
import numpy as np
import matplotlib.pyplot as plt
```

The example model

Here we use libsbml to show the reactions and species described by the model (this is independent of AMICI).

```
[2]: sbml_reader = libsbml.SBMLReader()
sbml_doc = sbml_reader.readSBML(sbml_file)
sbml_model = sbml_doc.getModel()
dir(sbml_doc)

print('Species: ', [s.getId() for s in sbml_model.getListOfSpecies()])

print('\nReactions:')
for reaction in sbml_model.getListOfReactions():
    reactants = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 1
→1 else '', r.getSpecies()) for r in reaction.getListOfReactants()])
    products = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 1
→1 else '', r.getSpecies()) for r in reaction.getListOfProducts()])
    reversible = '<' if reaction.getReversible() else ''
    print('%3s: %10s %1s->%10s\t\t[%s]' % (reaction.getId(),
        reactants,
        reversible,
        products,
        libsbml.formulaToL3String(reaction.getKineticLaw().getMath())))
```

Species: ['x1', 'x2', 'x3']

Reactions:

r1:	2 x1	->	x2	[p1 * x1^2]
r2:	x1 + x2	->	x3	[p2 * x1 * x2]
r3:	x2	->	2 x1	[p3 * x2]
r4:	x3	->	x1 + x2	[p4 * x3]

(continues on next page)

(continued from previous page)

```

r5:      x3  ->      [k0 * x3]
r6:      ->      x1    [p5]

```

Importing an SBML model, compiling and generating an AMICI module

Before we can use AMICI to simulate our model, the SBML model needs to be translated to C++ code. This is done by `amici.SbmlImporter`.

```
[3]: # Create an SbmlImporter instance for our SBML model
sbml_importer = amici.SbmlImporter(sbml_file)
```

In this example, we want to specify fixed parameters, observables and a σ parameter. Unfortunately, the latter two are not part of the [SBML standard](#). However, they can be provided to `amici.SbmlImporter.sbml2amici` as demonstrated in the following.

Constant parameters

Constant parameters, i.e. parameters with respect to which no sensitivities are to be computed (these are often parameters specifying a certain experimental condition) are provided as a list of parameter names.

```
[4]: constantParameters = ['k0']
```

Observables

Specifying observables is beyond the scope of SBML. Here we define them manually.

If you are looking for a more scalable way for defining observables, then checkout [PEtab](#). Another possibility is using SBML's `AssignmentRules` https://sbml.org/software/libsbml/5.18.0/docs/formatted/python-api/classlibsbml_1_1_assignment_rule.html to specify model outputs within the SBML file.

```
[5]: # Define observables
observables = {
    'observable_x1': {'name': '', 'formula': 'x1'},
    'observable_x2': {'name': '', 'formula': 'x2'},
    'observable_x3': {'name': '', 'formula': 'x3'},
    'observable_x1_scaled': {'name': '', 'formula': 'scaling_x1 * x1'},
    'observable_x2_offsetted': {'name': '', 'formula': 'offset_x2 + x2'},
    'observable_x1withsigma': {'name': '', 'formula': 'x1'}
}
```

σ parameters

To specify measurement noise as a parameter, we simply provide a dictionary with (preexisting) parameter names as keys and a list of observable names as values to indicate which sigma parameter is to be used for which observable.

```
[6]: sigmas = {'observable_x1withsigma': 'observable_x1withsigma_sigma'}
```

Generating the module

Now we can generate the python module for our model. `amici.SbmlImporter.sbml2amici` will symbolically derive the sensitivity equations, generate C++ code for model simulation, and assemble the python module. Standard logging verbosity levels can be passed to this function to see timestamped progression during code generation.

```
[7]: import logging
      sbml_importer.sbml2amici(model_name,
                              model_output_dir,
                              verbose=logging.INFO,
                              observables=observables,
                              constant_parameters=constantParameters,
                              sigmas=sigmas)
```

```
2021-11-30 16:57:57.997 - amici.sbml_import - INFO - Finished gathering local SBML
↳ symbols + (8.05E-03s)
2021-11-30 16:57:58.047 - amici.sbml_import - INFO - Finished processing SBML parameters
↳ + (4.64E-02s)
2021-11-30 16:57:58.054 - amici.sbml_import - INFO - Finished processing SBML
↳ compartments + (2.69E-04s)
2021-11-30 16:57:58.063 - amici.sbml_import - INFO - Finished processing SBML species
↳ initials ++ (1.47E-03s)
2021-11-30 16:57:58.067 - amici.sbml_import - INFO - Finished processing SBML rate rules
↳ ++ (7.65E-05s)
2021-11-30 16:57:58.068 - amici.sbml_import - INFO - Finished processing SBML species
↳ + (9.09E-03s)
2021-11-30 16:57:58.076 - amici.sbml_import - INFO - Finished processing SBML reactions
↳ + (4.32E-03s)
2021-11-30 16:57:58.086 - amici.sbml_import - INFO - Finished processing SBML rules
↳ + (6.88E-03s)
2021-11-30 16:57:58.093 - amici.sbml_import - INFO - Finished processing SBML initial
↳ assignments + (5.51E-05s)
2021-11-30 16:57:58.097 - amici.sbml_import - INFO - Finished processing SBML species
↳ references + (8.19E-04s)
2021-11-30 16:57:58.105 - amici.sbml_import - INFO - Finished processing SBML events
↳ + (1.00E-04s)
2021-11-30 16:57:58.105 - amici.sbml_import - INFO - Finished importing SBML
↳ (1.19E-01s)
2021-11-30 16:57:58.180 - amici.sbml_import - INFO - Finished processing SBML
↳ observables (6.99E-02s)
2021-11-30 16:57:58.202 - amici.ode_export - INFO - Finished running smart_multiply
↳ + (3.40E-03s)
2021-11-30 16:57:58.210 - amici.ode_export - INFO - Finished importing SbmlImporter
↳ (1.42E-02s)
2021-11-30 16:57:58.286 - amici.ode_export - INFO - Finished simplifying Jy
↳ +++ (6.10E-02s)
```

(continues on next page)

(continued from previous page)

```

2021-11-30 16:57:58.288 - amici.ode_export - INFO - Finished computing Jy
↳      ++ (6.69E-02s)
2021-11-30 16:57:58.299 - amici.ode_export - INFO - Finished simplifying y
↳      +++ (6.08E-04s)
2021-11-30 16:57:58.300 - amici.ode_export - INFO - Finished computing y
↳      ++ (5.38E-03s)
2021-11-30 16:57:58.308 - amici.ode_export - INFO - Finished simplifying sigmay
↳      +++ (1.19E-04s)
2021-11-30 16:57:58.310 - amici.ode_export - INFO - Finished computing sigmay
↳      ++ (5.58E-03s)
2021-11-30 16:57:58.351 - amici.ode_export - INFO - Finished writing Jy.cpp
↳      + (1.33E-01s)
2021-11-30 16:57:58.421 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (5.81E-02s)
2021-11-30 16:57:58.452 - amici.ode_export - INFO - Finished simplifying dJydsigma
↳      +++ (2.69E-02s)
2021-11-30 16:57:58.453 - amici.ode_export - INFO - Finished computing dJydsigma
↳      ++ (9.43E-02s)
2021-11-30 16:57:58.466 - amici.ode_export - INFO - Finished writing dJydsigma.cpp
↳      + (1.09E-01s)
2021-11-30 16:57:58.505 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (2.48E-02s)
2021-11-30 16:57:58.559 - amici.ode_export - INFO - Finished simplifying dJydy
↳      +++ (4.86E-02s)
2021-11-30 16:57:58.560 - amici.ode_export - INFO - Finished computing dJydy
↳      ++ (8.27E-02s)
2021-11-30 16:57:58.586 - amici.ode_export - INFO - Finished writing dJydy.cpp
↳      + (1.12E-01s)
2021-11-30 16:57:58.599 - amici.ode_export - INFO - Finished simplifying root
↳      +++ (5.50E-05s)
2021-11-30 16:57:58.600 - amici.ode_export - INFO - Finished computing root
↳      ++ (4.63E-03s)
2021-11-30 16:57:58.601 - amici.ode_export - INFO - Finished writing root.cpp
↳      + (8.96E-03s)
2021-11-30 16:57:58.624 - amici.ode_export - INFO - Finished simplifying w
↳      ++++ (7.65E-03s)
2021-11-30 16:57:58.626 - amici.ode_export - INFO - Finished computing w
↳      +++ (1.21E-02s)
2021-11-30 16:57:58.641 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (1.04E-02s)
2021-11-30 16:57:58.647 - amici.ode_export - INFO - Finished simplifying dwdp
↳      +++ (1.45E-03s)
2021-11-30 16:57:58.648 - amici.ode_export - INFO - Finished computing dwdp
↳      ++ (3.77E-02s)
2021-11-30 16:57:58.658 - amici.ode_export - INFO - Finished writing dwdp.cpp
↳      + (5.28E-02s)
2021-11-30 16:57:58.680 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (1.15E-02s)
2021-11-30 16:57:58.687 - amici.ode_export - INFO - Finished simplifying dwdx
↳      +++ (1.95E-03s)
2021-11-30 16:57:58.687 - amici.ode_export - INFO - Finished computing dwdx
↳      ++ (2.17E-02s)

```

(continues on next page)

(continued from previous page)

```

2021-11-30 16:57:58.696 - amici.ode_export - INFO - Finished writing dwdx.cpp
↳      + (3.37E-02s)
2021-11-30 16:57:58.705 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (1.05E-04s)
2021-11-30 16:57:58.710 - amici.ode_export - INFO - Finished simplifying dwdw
↳      +++ (6.07E-04s)
2021-11-30 16:57:58.711 - amici.ode_export - INFO - Finished computing dwdw
↳      ++ (8.67E-03s)
2021-11-30 16:57:58.713 - amici.ode_export - INFO - Finished writing dwdw.cpp
↳      + (1.25E-02s)
2021-11-30 16:57:58.729 - amici.ode_export - INFO - Finished simplifying xdot
↳      ++++ (5.40E-03s)
2021-11-30 16:57:58.729 - amici.ode_export - INFO - Finished computing xdot
↳      +++ (8.78E-03s)
2021-11-30 16:57:58.746 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (1.30E-02s)
2021-11-30 16:57:58.752 - amici.ode_export - INFO - Finished simplifying dxdotdw
↳      +++ (2.97E-04s)
2021-11-30 16:57:58.753 - amici.ode_export - INFO - Finished computing dxdotdw
↳      ++ (3.42E-02s)
2021-11-30 16:57:58.765 - amici.ode_export - INFO - Finished writing dxdotdw.cpp
↳      + (4.89E-02s)
2021-11-30 16:57:58.777 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (9.65E-05s)
2021-11-30 16:57:58.780 - amici.ode_export - INFO - Finished simplifying dxdotdx_
↳ explicit      +++ (7.85E-05s)
2021-11-30 16:57:58.781 - amici.ode_export - INFO - Finished computing dxdotdx_explicit
↳      ++ (8.68E-03s)
2021-11-30 16:57:58.782 - amici.ode_export - INFO - Finished writing dxdotdx_explicit.
↳ cpp      + (1.24E-02s)
2021-11-30 16:57:58.793 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (9.18E-05s)
2021-11-30 16:57:58.797 - amici.ode_export - INFO - Finished simplifying dxdotdp_
↳ explicit      +++ (1.22E-04s)
2021-11-30 16:57:58.798 - amici.ode_export - INFO - Finished computing dxdotdp_explicit
↳      ++ (8.08E-03s)
2021-11-30 16:57:58.799 - amici.ode_export - INFO - Finished writing dxdotdp_explicit.
↳ cpp      + (1.36E-02s)
2021-11-30 16:57:58.816 - amici.ode_export - INFO - Finished running smart_jacobian
↳      ++++ (1.92E-03s)
2021-11-30 16:57:58.821 - amici.ode_export - INFO - Finished simplifying dydx
↳      ++++ (1.55E-04s)
2021-11-30 16:57:58.822 - amici.ode_export - INFO - Finished computing dydx
↳      +++ (1.20E-02s)
2021-11-30 16:57:58.832 - amici.ode_export - INFO - Finished running smart_jacobian
↳      ++++ (1.11E-04s)
2021-11-30 16:57:58.837 - amici.ode_export - INFO - Finished simplifying dydw
↳      ++++ (4.09E-04s)
2021-11-30 16:57:58.837 - amici.ode_export - INFO - Finished computing dydw
↳      +++ (9.68E-03s)
2021-11-30 16:57:58.844 - amici.ode_export - INFO - Finished simplifying dydx
↳      +++ (1.97E-04s)

```

(continues on next page)

(continued from previous page)

```

2021-11-30 16:57:58.845 - amici.ode_export - INFO - Finished computing dydx
↳ ++ (3.77E-02s)
2021-11-30 16:57:58.849 - amici.ode_export - INFO - Finished writing dydx.cpp
↳ + (4.51E-02s)
2021-11-30 16:57:58.862 - amici.ode_export - INFO - Finished running smart_jacobian
↳ ++++ (1.74E-03s)
2021-11-30 16:57:58.866 - amici.ode_export - INFO - Finished simplifying dydp
↳ ++++ (3.88E-04s)
2021-11-30 16:57:58.867 - amici.ode_export - INFO - Finished computing dydp
↳ +++ (9.93E-03s)
2021-11-30 16:57:58.872 - amici.ode_export - INFO - Finished simplifying dydp
↳ +++ (1.78E-04s)
2021-11-30 16:57:58.873 - amici.ode_export - INFO - Finished computing dydp
↳ ++ (1.84E-02s)
2021-11-30 16:57:58.876 - amici.ode_export - INFO - Finished writing dydp.cpp
↳ + (2.33E-02s)
2021-11-30 16:57:58.887 - amici.ode_export - INFO - Finished running smart_jacobian
↳ +++ (1.58E-03s)
2021-11-30 16:57:58.892 - amici.ode_export - INFO - Finished simplifying dsigmaydp
↳ +++ (2.41E-04s)
2021-11-30 16:57:58.893 - amici.ode_export - INFO - Finished computing dsigmaydp
↳ ++ (1.08E-02s)
2021-11-30 16:57:58.894 - amici.ode_export - INFO - Finished writing dsigmaydp.cpp
↳ + (1.50E-02s)
2021-11-30 16:57:58.901 - amici.ode_export - INFO - Finished writing sigmay.cpp
↳ + (2.68E-03s)
2021-11-30 16:57:58.909 - amici.ode_export - INFO - Finished computing stau
↳ ++ (1.35E-04s)
2021-11-30 16:57:58.910 - amici.ode_export - INFO - Finished writing stau.cpp
↳ + (4.10E-03s)
2021-11-30 16:57:58.916 - amici.ode_export - INFO - Finished computing deltax
↳ ++ (1.34E-04s)
2021-11-30 16:57:58.916 - amici.ode_export - INFO - Finished writing deltax.cpp
↳ + (3.34E-03s)
2021-11-30 16:57:58.924 - amici.ode_export - INFO - Finished computing deltasx
↳ ++ (1.99E-04s)
2021-11-30 16:57:58.925 - amici.ode_export - INFO - Finished writing deltasx.cpp
↳ + (3.88E-03s)
2021-11-30 16:57:58.934 - amici.ode_export - INFO - Finished writing w.cpp
↳ + (5.23E-03s)
2021-11-30 16:57:58.945 - amici.ode_export - INFO - Finished simplifying x0
↳ +++ (7.68E-05s)
2021-11-30 16:57:58.946 - amici.ode_export - INFO - Finished computing x0
↳ ++ (4.22E-03s)
2021-11-30 16:57:58.949 - amici.ode_export - INFO - Finished writing x0.cpp
↳ + (1.04E-02s)
2021-11-30 16:57:58.961 - amici.ode_export - INFO - Finished simplifying x0_
↳ fixedParameters +++ (4.96E-05s)
2021-11-30 16:57:58.962 - amici.ode_export - INFO - Finished computing x0_
↳ fixedParameters ++ (4.51E-03s)
2021-11-30 16:57:58.963 - amici.ode_export - INFO - Finished writing x0_fixedParameters.
↳ cpp + (8.84E-03s)

```

(continues on next page)

(continued from previous page)

```

2021-11-30 16:57:58.982 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (2.15E-04s)
2021-11-30 16:57:58.987 - amici.ode_export - INFO - Finished simplifying sx0
↳      +++ (1.20E-04s)
2021-11-30 16:57:58.988 - amici.ode_export - INFO - Finished computing sx0
↳      ++ (9.27E-03s)
2021-11-30 16:57:58.989 - amici.ode_export - INFO - Finished writing sx0.cpp
↳      + (2.26E-02s)
2021-11-30 16:57:58.999 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (3.06E-05s)
2021-11-30 16:57:59.003 - amici.ode_export - INFO - Finished running smart_jacobian
↳      +++ (2.44E-05s)
2021-11-30 16:57:59.008 - amici.ode_export - INFO - Finished simplifying sx0_
↳fixedParameters      +++ (6.08E-05s)
2021-11-30 16:57:59.009 - amici.ode_export - INFO - Finished computing sx0_
↳fixedParameters      ++ (1.28E-02s)
2021-11-30 16:57:59.009 - amici.ode_export - INFO - Finished writing sx0_fixedParameters.
↳cpp      + (1.59E-02s)
2021-11-30 16:57:59.021 - amici.ode_export - INFO - Finished writing xdot.cpp
↳      + (7.26E-03s)
2021-11-30 16:57:59.028 - amici.ode_export - INFO - Finished writing y.cpp
↳      + (2.13E-03s)
2021-11-30 16:57:59.036 - amici.ode_export - INFO - Finished simplifying x_rdata
↳      +++ (5.62E-05s)
2021-11-30 16:57:59.038 - amici.ode_export - INFO - Finished computing x_rdata
↳      ++ (5.16E-03s)
2021-11-30 16:57:59.041 - amici.ode_export - INFO - Finished writing x_rdata.cpp
↳      + (9.60E-03s)
2021-11-30 16:57:59.050 - amici.ode_export - INFO - Finished simplifying total_cl
↳      +++ (4.08E-05s)
2021-11-30 16:57:59.051 - amici.ode_export - INFO - Finished computing total_cl
↳      ++ (3.64E-03s)
2021-11-30 16:57:59.052 - amici.ode_export - INFO - Finished writing total_cl.cpp
↳      + (7.19E-03s)
2021-11-30 16:57:59.064 - amici.ode_export - INFO - Finished simplifying x_solver
↳      +++ (7.69E-05s)
2021-11-30 16:57:59.065 - amici.ode_export - INFO - Finished computing x_solver
↳      ++ (4.62E-03s)
2021-11-30 16:57:59.068 - amici.ode_export - INFO - Finished writing x_solver.cpp
↳      + (1.13E-02s)
2021-11-30 16:57:59.079 - amici.ode_export - INFO - Finished generating cpp code
↳      (8.66E-01s)
2021-11-30 16:58:07.834 - amici.ode_export - INFO - Finished compiling cpp code
↳      (8.75E+00s)

```

Importing the module and loading the model

If everything went well, we need to add the previously selected model output directory to our PYTHON_PATH and are then ready to load newly generated model:

```
[8]: sys.path.insert(0, os.path.abspath(model_output_dir))
model_module = importlib.import_module(model_name)
```

And get an instance of our model from which we can retrieve information such as parameter names:

```
[9]: model = model_module.getModel()

print("Model name:", model.getName())
print("Model parameters:", model.getParameterIds())
print("Model outputs:  ", model.getObservableIds())
print("Model states:   ", model.getStateIds())

Model name: model_steadystate_scaled
Model parameters: ('p1', 'p2', 'p3', 'p4', 'p5', 'scaling_x1', 'offset_x2', 'observable_
↪ x1withsigma_sigma')
Model outputs:    ('observable_x1', 'observable_x2', 'observable_x3', 'observable_x1_
↪ scaled', 'observable_x2_offsetted', 'observable_x1withsigma')
Model states:     ('x1', 'x2', 'x3')
```

Running simulations and analyzing results

After importing the model, we can run simulations using `amici.runAmiciSimulation`. This requires a `Model` instance and a `Solver` instance. Optionally you can provide measurements inside an `ExpData` instance, as shown later in this notebook.

```
[10]: # Create Model instance
model = model_module.getModel()

# set timepoints for which we want to simulate the model
model.setTimepoints(np.linspace(0, 60, 60))

# Create solver instance
solver = model.getSolver()

# Run simulation using default model parameters and solver options
rdata = amici.runAmiciSimulation(model, solver)

[11]: print('Simulation was run using model default parameters as specified in the SBML model:
↪ ')
print(model.getParameters())

Simulation was run using model default parameters as specified in the SBML model:
(1.0, 0.5, 0.4, 2.0, 0.1, 2.0, 3.0, 0.2)
```

Simulation results are provided as `numpy.ndarrays` in the returned dictionary:


```
[12]: #np.set_printoptions(threshold=8, edgeitems=2)
for key, value in rdata.items():
    print('%12s: ' % key, value)

        ts: [ 0.          1.01694915  2.03389831  3.05084746  4.06779661  5.08474576
  6.10169492  7.11864407  8.13559322  9.15254237 10.16949153 11.18644068
 12.20338983 13.22033898 14.23728814 15.25423729 16.27118644 17.28813559
 18.30508475 19.3220339  20.33898305 21.3559322  22.37288136 23.38983051
 24.40677966 25.42372881 26.44067797 27.45762712 28.47457627 29.49152542
 30.50847458 31.52542373 32.54237288 33.55932203 34.57627119 35.59322034
 36.61016949 37.62711864 38.6440678  39.66101695 40.6779661  41.69491525
 42.71186441 43.72881356 44.74576271 45.76271186 46.77966102 47.79661017
 48.81355932 49.83050847 50.84745763 51.86440678 52.88135593 53.89830508
 54.91525424 55.93220339 56.94915254 57.96610169 58.98305085 60.          ]
        x: [[0.1          0.4          0.7          ]
 [0.57995052 0.73365809 0.0951589 ]
 [0.55996496 0.71470091 0.0694127 ]
 [0.5462855  0.68030366 0.06349394]
 [0.53561883 0.64937432 0.05923555]
 [0.52636487 0.62259567 0.05568686]
 [0.51822013 0.59943346 0.05268079]
 [0.51103767 0.57935661 0.05012037]
 [0.5047003  0.56191592 0.04793052]
 [0.49910666 0.54673518 0.0460508 ]
 [0.49416809 0.53349812 0.04443205]
 [0.48980687 0.52193767 0.04303399]
 [0.48595476 0.51182731 0.04182339]
 [0.48255176 0.50297412 0.04077267]
 [0.47954511 0.49521318 0.03985882]
 [0.47688833 0.48840304 0.03906254]
 [0.47454049 0.48242198 0.03836756]
 [0.47246548 0.47716502 0.0377601 ]
 [0.47063147 0.47254128 0.03722844]
 [0.46901037 0.46847202 0.03676259]
 [0.46757739 0.46488881 0.03635397]
 [0.46631065 0.46173207 0.03599523]
 [0.46519082 0.45894987 0.03568002]
 [0.46420083 0.45649684 0.03540285]
 [0.4633256  0.45433332 0.03515899]
 [0.4625518  0.45242457 0.03494429]
 [0.46186768 0.45074016 0.03475519]
 [0.46126282 0.44925337 0.03458856]
 [0.46072804 0.44794075 0.03444166]
 [0.46025521 0.44678168 0.03431212]
 [0.45983714 0.44575804 0.03419784]
 [0.45946749 0.44485388 0.03409701]
 [0.45914065 0.44405514 0.03400802]
 [0.45885167 0.44334947 0.03392946]
 [0.45859615 0.44272595 0.03386009]
 [0.45837021 0.44217497 0.03379883]
 [0.45817043 0.44168805 0.03374473]
 [0.45799379 0.44125772 0.03369693]
 [0.4578376  0.44087738 0.03365471]
```

(continues on next page)

(continued from previous page)

```

[0.45769949 0.44054121 0.0336174 ]
[0.45757737 0.44024405 0.03358444]
[0.45746939 0.43998137 0.03355531]
[0.45737391 0.43974917 0.03352956]
[0.45728948 0.43954389 0.03350681]
[0.45721483 0.43936242 0.0334867 ]
[0.45714882 0.43920198 0.03346892]
[0.45709045 0.43906014 0.03345321]
[0.45703884 0.43893474 0.03343932]
[0.4569932 0.43882387 0.03342704]
[0.45695285 0.43872584 0.03341618]
[0.45691717 0.43863917 0.03340658]
[0.45688561 0.43856254 0.0333981 ]
[0.45685771 0.43849478 0.0333906 ]
[0.45683304 0.43843488 0.03338397]
[0.45681123 0.4383819 0.0333781 ]
[0.45679194 0.43833507 0.03337292]
[0.45677488 0.43829365 0.03336833]
[0.4567598 0.43825703 0.03336428]
[0.45674646 0.43822466 0.0333607 ]
[0.45673467 0.43819603 0.03335753]]
    x0: [0.1 0.4 0.7]
    x_ss: [nan nan nan]
    sx: None
    sx0: None
    sx_ss: None
    y: [[0.1      0.4      0.7      0.2      3.4      0.1      ]
[0.57995052 0.73365809 0.0951589 1.15990103 3.73365809 0.57995052]
[0.55996496 0.71470091 0.0694127 1.11992992 3.71470091 0.55996496]
[0.5462855 0.68030366 0.06349394 1.092571 3.68030366 0.5462855 ]
[0.53561883 0.64937432 0.05923555 1.07123766 3.64937432 0.53561883]
[0.52636487 0.62259567 0.05568686 1.05272975 3.62259567 0.52636487]
[0.51822013 0.59943346 0.05268079 1.03644027 3.59943346 0.51822013]
[0.51103767 0.57935661 0.05012037 1.02207533 3.57935661 0.51103767]
[0.5047003 0.56191592 0.04793052 1.00940059 3.56191592 0.5047003 ]
[0.49910666 0.54673518 0.0460508 0.99821331 3.54673518 0.49910666]
[0.49416809 0.53349812 0.04443205 0.98833618 3.53349812 0.49416809]
[0.48980687 0.52193767 0.04303399 0.97961374 3.52193767 0.48980687]
[0.48595476 0.51182731 0.04182339 0.97190952 3.51182731 0.48595476]
[0.48255176 0.50297412 0.04077267 0.96510352 3.50297412 0.48255176]
[0.47954511 0.49521318 0.03985882 0.95909022 3.49521318 0.47954511]
[0.47688833 0.48840304 0.03906254 0.95377667 3.48840304 0.47688833]
[0.47454049 0.48242198 0.03836756 0.94908097 3.48242198 0.47454049]
[0.47246548 0.47716502 0.0377601 0.94493095 3.47716502 0.47246548]
[0.47063147 0.47254128 0.03722844 0.94126293 3.47254128 0.47063147]
[0.46901037 0.46847202 0.03676259 0.93802074 3.46847202 0.46901037]
[0.46757739 0.46488881 0.03635397 0.93515478 3.46488881 0.46757739]
[0.46631065 0.46173207 0.03599523 0.9326213 3.46173207 0.46631065]
[0.46519082 0.45894987 0.03568002 0.93038164 3.45894987 0.46519082]
[0.46420083 0.45649684 0.03540285 0.92840166 3.45649684 0.46420083]
[0.4633256 0.45433332 0.03515899 0.92665119 3.45433332 0.4633256 ]
[0.4625518 0.45242457 0.03494429 0.9251036 3.45242457 0.4625518 ]

```

(continues on next page)

(continued from previous page)

[illegible]

(continues on next page)

(continues on next page)

(continued from previous page)

```

[3.49521318 0.47954511 0.95909022 0.49521318 0.47954511 0.03985882
 0.22996351 0.11873853 0.19808527 0.07971763 0.03985882 0.1      ]
[3.48840304 0.47688833 0.95377667 0.48840304 0.47688833 0.03906254
 0.22742248 0.11645686 0.19536122 0.07812507 0.03906254 0.1      ]
[3.48242198 0.47454049 0.94908097 0.48242198 0.47454049 0.03836756
 0.22518867 0.11446438 0.19296879 0.07673511 0.03836756 0.1      ]
[3.47716502 0.47246548 0.94493095 0.47716502 0.47246548 0.0377601
 0.22322363 0.112722  0.19086601 0.0755202  0.0377601  0.1      ]
[3.47254128 0.47063147 0.94126293 0.47254128 0.47063147 0.03722844
 0.22149398 0.1111964 0.18901651 0.07445688 0.03722844 0.1      ]
[3.46847202 0.46901037 0.93802074 0.46847202 0.46901037 0.03676259
 0.21997073 0.10985912 0.18738881 0.07352518 0.03676259 0.1      ]
[3.46488881 0.46757739 0.93515478 0.46488881 0.46757739 0.03635397
 0.21862862 0.10868575 0.18595552 0.07270794 0.03635397 0.1      ]
[3.46173207 0.46631065 0.9326213  0.46173207 0.46631065 0.03599523
 0.21744562 0.10765529 0.18469283 0.07199046 0.03599523 0.1      ]
[3.45894987 0.46519082 0.93038164 0.45894987 0.46519082 0.03568002
 0.2164025  0.10674963 0.18357995 0.07136003 0.03568002 0.1      ]
[3.45649684 0.46420083 0.92840166 0.45649684 0.46420083 0.03540285
 0.21548241 0.10595311 0.18259874 0.0708057  0.03540285 0.1      ]
[3.45433332 0.4633256  0.92665119 0.45433332 0.4633256  0.03515899
 0.21467061 0.10525213 0.18173333 0.07031797 0.03515899 0.1      ]
[3.45242457 0.4625518  0.9251036  0.45242457 0.4625518  0.03494429
 0.21395417 0.1046349  0.18096983 0.06988859 0.03494429 0.1      ]
[3.45074016 0.46186768 0.92373536 0.45074016 0.46186768 0.03475519
 0.21332175 0.10409116 0.18029606 0.06951039 0.03475519 0.1      ]
[3.44925337 0.46126282 0.92252564 0.44925337 0.46126282 0.03458856
 0.21276339 0.10361194 0.17970135 0.06917712 0.03458856 0.1      ]
[3.44794075 0.46072804 0.92145608 0.44794075 0.46072804 0.03444166
 0.21227033 0.10318943 0.1791763  0.06888332 0.03444166 0.1      ]
[3.44678168 0.46025521 0.92051041 0.44678168 0.46025521 0.03431212
 0.21183485 0.1028168  0.17871267 0.06862424 0.03431212 0.1      ]
[3.44575804 0.45983714 0.91967427 0.44575804 0.45983714 0.03419784
 0.21145019 0.10248805 0.17830322 0.06839569 0.03419784 0.1      ]
[3.44485388 0.45946749 0.91893498 0.44485388 0.45946749 0.03409701
 0.21111037 0.10219795 0.17794155 0.06819402 0.03409701 0.1      ]
[3.44405514 0.45914065 0.91828131 0.44405514 0.45914065 0.03400802
 0.21081014 0.10194188 0.17762206 0.06801603 0.03400802 0.1      ]
[3.44334947 0.45885167 0.91770333 0.44334947 0.45885167 0.03392946
 0.21054485 0.10171582 0.17733979 0.06785891 0.03392946 0.1      ]
[3.44272595 0.45859615 0.91719229 0.44272595 0.45859615 0.03386009
 0.21031042 0.10151621 0.17709038 0.06772018 0.03386009 0.1      ]
[3.44217497 0.45837021 0.91674042 0.44217497 0.45837021 0.03379883
 0.21010325 0.10133992 0.17686999 0.06759766 0.03379883 0.1      ]
[3.44168805 0.45817043 0.91634087 0.44168805 0.45817043 0.03374473
 0.20992015 0.1011842  0.17667522 0.06748945 0.03374473 0.1      ]
[3.44125772 0.45799379 0.91598758 0.44125772 0.45799379 0.03369693
 0.20975831 0.10104665 0.17650309 0.06739386 0.03369693 0.1      ]
[3.44087738 0.4578376  0.9156752  0.44087738 0.4578376  0.03365471
 0.20961527 0.10092512 0.17635095 0.06730942 0.03365471 0.1      ]
[3.44054121 0.45769949 0.91539898 0.44054121 0.45769949 0.0336174
 0.20948882 0.10081774 0.17621648 0.0672348  0.0336174  0.1      ]

```

(continues on next page)

(continued from previous page)

```

[3.44024405 0.45757737 0.91515474 0.44024405 0.45757737 0.03358444
 0.20937705 0.10072286 0.17609762 0.06716887 0.03358444 0.1      ]
[3.43998137 0.45746939 0.91493878 0.43998137 0.45746939 0.03355531
 0.20927824 0.10063901 0.17599255 0.06711061 0.03355531 0.1      ]
[3.43974917 0.45737391 0.91474782 0.43974917 0.45737391 0.03352956
 0.20919089 0.1005649 0.17589967 0.06705912 0.03352956 0.1      ]
[3.43954389 0.45728948 0.91457897 0.43954389 0.45728948 0.03350681
 0.20911367 0.1004994 0.17581756 0.06701361 0.03350681 0.1      ]
[3.43936242 0.45721483 0.91442966 0.43936242 0.45721483 0.0334867
 0.2090454 0.10044151 0.17574497 0.06697339 0.0334867 0.1      ]
[3.43920198 0.45714882 0.91429764 0.43920198 0.45714882 0.03346892
 0.20898505 0.10039033 0.17568079 0.06693784 0.03346892 0.1      ]
[3.43906014 0.45709045 0.91418091 0.43906014 0.45709045 0.03345321
 0.20893168 0.1003451 0.17562406 0.06690641 0.03345321 0.1      ]
[3.43893474 0.45703884 0.91407768 0.43893474 0.45703884 0.03343932
 0.2088845 0.10030511 0.1755739 0.06687863 0.03343932 0.1      ]
[3.43882387 0.4569932 0.91398641 0.43882387 0.4569932 0.03342704
 0.20884279 0.10026976 0.17552955 0.06685407 0.03342704 0.1      ]
[3.43872584 0.45695285 0.9139057 0.43872584 0.45695285 0.03341618
 0.20880591 0.10023851 0.17549034 0.06683236 0.03341618 0.1      ]
[3.43863917 0.45691717 0.91383433 0.43863917 0.45691717 0.03340658
 0.2087733 0.10021088 0.17545567 0.06681317 0.03340658 0.1      ]
[3.43856254 0.45688561 0.91377123 0.43856254 0.45688561 0.0333981
 0.20874446 0.10018646 0.17542502 0.0667962 0.0333981 0.1      ]
[3.43849478 0.45685771 0.91371543 0.43849478 0.45685771 0.0333906
 0.20871897 0.10016486 0.17539791 0.0667812 0.0333906 0.1      ]
[3.43843488 0.45683304 0.91366609 0.43843488 0.45683304 0.03338397
 0.20869643 0.10014577 0.17537395 0.06676793 0.03338397 0.1      ]
[3.4383819 0.45681123 0.91362246 0.4383819 0.45681123 0.0333781
 0.2086765 0.10012889 0.17535276 0.0667562 0.0333781 0.1      ]
[3.43833507 0.45679194 0.91358388 0.43833507 0.45679194 0.03337292
 0.20865887 0.10011396 0.17533403 0.06674583 0.03337292 0.1      ]
[3.43829365 0.45677488 0.91354976 0.43829365 0.45677488 0.03336833
 0.20864329 0.10010077 0.17531746 0.06673667 0.03336833 0.1      ]
[3.43825703 0.4567598 0.9135196 0.43825703 0.4567598 0.03336428
 0.20862951 0.1000891 0.17530281 0.06672856 0.03336428 0.1      ]
[3.43822466 0.45674646 0.91349292 0.43822466 0.45674646 0.0333607
 0.20861733 0.10007878 0.17528986 0.06672139 0.0333607 0.1      ]
[3.43819603 0.45673467 0.91346934 0.43819603 0.45673467 0.03335753
 0.20860656 0.10006966 0.17527841 0.06671506 0.03335753 0.1      ]]
preeq_wrms: nan
preeq_t: nan
preeq_numlinsteps: None
preeq_numsteps: [[0 0 0]]
preeq_numstepsB: 0.0
preeq_status: [[0 0 0]]
preeq_cpu_time: 0.0
preeq_cpu_timeB: 0.0
posteq_wrms: nan
posteq_t: nan
posteq_numlinsteps: None
posteq_numsteps: [[0 0 0]]

```


(continues on next page)

[illegible]

```
print(model.getParameters())
```

```
(1.0, 0.5, 0.4, 2.0, 0.1, 2.0, 3.0, 0.2)
```

```
import amici.plotting
amici.plotting.plotStateTrajectories(rdata, model = None)
amici.plotting.plotObservableTrajectories(rdata, model = None)
```



Computing likelihood

Often model parameters need to be inferred from experimental data. This is commonly done by maximizing the likelihood of observing the data given to current model parameters. AMICI will compute this likelihood if experimental data is provided to `amici.runAmiciSimulation` as optional third argument. Measurements along with their standard deviations are provided through an `amici.ExpData` instance.

```
[15]: # Create model instance and set time points for simulation
model = model_module.getModel()
model.setTimepoints(np.linspace(0, 10, 11))

# Create solver instance, keep default options
solver = model.getSolver()

# Run simulation without experimental data
```

(continues on next page)

(continued from previous page)

```

rdata = amici.runAmiciSimulation(model, solver)

# Create ExpData instance from simulation results
edata = amici.ExpData(rdata, 1.0, 0.0)

# Re-run simulation, this time passing "experimental data"
rdata = amici.runAmiciSimulation(model, solver, edata)

print('Log-likelihood %f' % rdata['llh'])
Log-likelihood -97.118555

```

Simulation tolerances

Numerical error tolerances are often critical to get accurate results. For the state variables, integration errors can be controlled using `setRelativeTolerance` and `setAbsoluteTolerance`. Similar functions exist for sensitivities, steadystates and quadratures. We initially compute a reference solution using extremely low tolerances and then assess the influence on integration error for different levels of absolute and relative tolerance.

```

[16]: solver.setRelativeTolerance(1e-16)
solver.setAbsoluteTolerance(1e-16)
solver.setSensitivityOrder(amici.SensitivityOrder.none)
rdata_ref = amici.runAmiciSimulation(model, solver, edata)

def get_simulation_error(solver):
    rdata = amici.runAmiciSimulation(model, solver, edata)
    return np.mean(np.abs(rdata['x']-rdata_ref['x'])), np.mean(np.abs(rdata['llh']-rdata_ref['llh']))

def get_errors(tolfun, tols):
    solver.setRelativeTolerance(1e-16)
    solver.setAbsoluteTolerance(1e-16)
    x_errs = []
    llh_errs = []
    for tol in tols:
        getattr(solver, tolfun)(tol)
        x_err, llh_err = get_simulation_error(solver)
        x_errs.append(x_err)
        llh_errs.append(llh_err)
    return x_errs, llh_errs

atols = np.logspace(-5, -15, 100)
atol_x_errs, atol_llh_errs = get_errors('setAbsoluteTolerance', atols)

rtols = np.logspace(-5, -15, 100)
rtol_x_errs, rtol_llh_errs = get_errors('setRelativeTolerance', rtols)

fig, axes = plt.subplots(1, 2, figsize=(15, 5))

def plot_error(tols, x_errs, llh_errs, tolname, ax):
    ax.plot(tols, x_errs, 'r-', label='x')

```

(continues on next page)

(continued from previous page)



```

ax.plot(tols, llh_errs, 'b-', label='llh')
ax.set_xscale('log')
ax.set_yscale('log')
ax.set_xlabel(f'{tolname} tolerance')
ax.set_ylabel('average numerical error')
ax.legend()

plot_error(atols, atol_x_errs, atol_llh_errs, 'absolute', axes[0])
plot_error(rtols, rtol_x_errs, rtol_llh_errs, 'relative', axes[1])

# reset relative tolerance to default value
solver.setRelativeTolerance(1e-8)
solver.setRelativeTolerance(1e-16)

```



Sensitivity analysis

AMICI can provide first- and second-order sensitivities using the forward- or adjoint-method. The respective options are set on the Model and Solver objects.

Forward sensitivity analysis

```

[17]: model = model_module.getModel()
model.setTimepoints(np.linspace(0, 10, 11))
model.requireSensitivitiesForAllParameters()           # sensitivities w.r.t. all_
↳ parameters
# model.setParameterList([1, 2])                       # sensitivities
# w.r.t. the specified parameters
model.setParameterScale(amici.ParameterScaling.none)   # parameters are used as-is_
↳ (not log-transformed)

solver = model.getSolver()
solver.setSensitivityMethod(amici.SensitivityMethod.forward) # forward_
↳ sensitivity analysis
solver.setSensitivityOrder(amici.SensitivityOrder.first) # first-order sensitivities

```

(continues on next page)

(continued from previous page)

```

rdata = amici.runAmiciSimulation(model, solver)

# print sensitivity-related results
for key, value in rdata.items():
    if key.startswith('s'):
        print('%12s: ' % key, value)

        sx: [[[ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]]

[[-2.00747250e-01  1.19873139e-01 -9.44167985e-03]
 [-1.02561396e-01 -1.88820454e-01  1.01855972e-01]
 [ 4.66193077e-01 -2.86365372e-01  2.39662449e-02]
 [ 4.52560294e-02  1.14631370e-01 -3.34067919e-02]
 [ 4.00672911e-01  1.92564093e-01  4.98877759e-02]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]]

[[-2.23007240e-01  1.53979022e-01 -1.26885280e-02]
 [-1.33426939e-01 -3.15955239e-01  9.49575030e-02]
 [ 5.03470377e-01 -3.52731535e-01  2.81567412e-02]
 [ 3.93630714e-02  1.10770683e-01 -1.05673869e-02]
 [ 5.09580304e-01  4.65255489e-01  9.24843702e-02]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]]

[[-2.14278104e-01  1.63465064e-01 -1.03268418e-02]
 [-1.60981967e-01 -4.00490452e-01  7.54810648e-02]
 [ 4.87746419e-01 -3.76014315e-01  2.30919334e-02]
 [ 4.28733680e-02  1.15473583e-01 -6.63571687e-03]
 [ 6.05168647e-01  7.07226039e-01  1.23870914e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]]

[[-2.05888038e-01  1.69308689e-01 -7.93085660e-03]
 [-1.84663809e-01 -4.65451966e-01  5.95026117e-02]
 [ 4.66407064e-01 -3.87612079e-01  1.76410128e-02]
 [ 4.52451104e-02  1.19865712e-01 -4.73313094e-03]
 [ 6.90798449e-01  9.20396633e-01  1.49475827e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]]

```

(continues on next page)

(continued from previous page)

```

[[-1.98803165e-01  1.73327268e-01 -6.03008179e-03]
 [-2.04303740e-01 -5.16111388e-01  4.68785776e-02]
 [ 4.47070326e-01 -3.94304029e-01  1.32107437e-02]
 [ 4.69732048e-02  1.22961727e-01 -3.35899442e-03]
 [ 7.68998995e-01  1.10844286e+00  1.70889328e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

[[-1.92789113e-01  1.75978657e-01 -4.54517629e-03]
 [-2.20500138e-01 -5.55540705e-01  3.68776526e-02]
 [ 4.30424855e-01 -3.97907706e-01  9.75257113e-03]
 [ 4.82793652e-02  1.24952071e-01 -2.30991637e-03]
 [ 8.40805131e-01  1.27504628e+00  1.89020151e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

[[-1.87672774e-01  1.77588334e-01 -3.38318222e-03]
 [-2.33807210e-01 -5.86081383e-01  2.89236334e-02]
 [ 4.16201399e-01 -3.99295277e-01  7.06598588e-03]
 [ 4.92546648e-02  1.26089711e-01 -1.50412006e-03]
 [ 9.06806543e-01  1.42334018e+00  2.04522708e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

[[-1.83320440e-01  1.78410042e-01 -2.47240692e-03]
 [-2.44690164e-01 -6.09568485e-01  2.25774266e-02]
 [ 4.04061655e-01 -3.99063012e-01  4.97908386e-03]
 [ 4.99612484e-02  1.26581014e-01 -8.85891342e-04]
 [ 9.67473970e-01  1.55589415e+00  2.17895305e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

[[-1.79620591e-01  1.78640114e-01 -1.75822439e-03]
 [-2.53540123e-01 -6.27448857e-01  1.75019839e-02]
 [ 3.93704970e-01 -3.97656641e-01  3.35895484e-03]
 [ 5.04492282e-02  1.26586733e-01 -4.13401240e-04]
 [ 1.02322336e+00  1.67481439e+00  2.29524046e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

[[-1.76478441e-01  1.78430281e-01 -1.19867662e-03]
 [-2.60686971e-01 -6.40868686e-01  1.34365068e-02]
 [ 3.84873835e-01 -3.95414931e-01  2.10369522e-03]
 [ 5.07601805e-02  1.26231631e-01 -5.46465317e-05]
 [ 1.07443160e+00  1.78183962e+00  2.39710937e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00]]

```

(continues on next page)

(continued from previous page)

```

[ 0.00000000e+00 0.00000000e+00 0.00000000e+00]]]
      sx0: [[0. 0. 0.]
[0. 0. 0.]
[0. 0. 0.]
[0. 0. 0.]
[0. 0. 0.]
[0. 0. 0.]
[0. 0. 0.]]
      sx_ss: [[nan nan nan]
[nan nan nan]
[nan nan nan]
[nan nan nan]
[nan nan nan]
[nan nan nan]
[nan nan nan]]
      sigmay: [[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]
[1. 1. 1. 1. 1. 0.2]]
      sy: [[[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 1.00000000e-01
0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
0.00000000e+00 0.00000000e+00]]]

[[-2.00747250e-01 1.19873139e-01 -9.44167985e-03 -4.01494500e-01
1.19873139e-01 -2.00747250e-01]
[-1.02561396e-01 -1.88820454e-01 1.01855972e-01 -2.05122791e-01
-1.88820454e-01 -1.02561396e-01]
[ 4.66193077e-01 -2.86365372e-01 2.39662449e-02 9.32386154e-01
-2.86365372e-01 4.66193077e-01]
[ 4.52560294e-02 1.14631370e-01 -3.34067919e-02 9.05120589e-02

```

(continues on next page)

(continued from previous page)

```

1.14631370e-01 4.52560294e-02]
[ 4.00672911e-01 1.92564093e-01 4.98877759e-02 8.01345822e-01
 1.92564093e-01 4.00672911e-01]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 5.80072436e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-2.23007240e-01 1.53979022e-01 -1.26885280e-02 -4.46014480e-01
 1.53979022e-01 -2.23007240e-01]
[-1.33426939e-01 -3.15955239e-01 9.49575030e-02 -2.66853878e-01
 -3.15955239e-01 -1.33426939e-01]
[ 5.03470377e-01 -3.52731535e-01 2.81567412e-02 1.00694075e+00
 -3.52731535e-01 5.03470377e-01]
[ 3.93630714e-02 1.10770683e-01 -1.05673869e-02 7.87261427e-02
 1.10770683e-01 3.93630714e-02]
[ 5.09580304e-01 4.65255489e-01 9.24843702e-02 1.01916061e+00
 4.65255489e-01 5.09580304e-01]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 5.60534516e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-2.14278104e-01 1.63465064e-01 -1.03268418e-02 -4.28556209e-01
 1.63465064e-01 -2.14278104e-01]
[-1.60981967e-01 -4.00490452e-01 7.54810648e-02 -3.21963935e-01
 -4.00490452e-01 -1.60981967e-01]
[ 4.87746419e-01 -3.76014315e-01 2.30919334e-02 9.75492839e-01
 -3.76014315e-01 4.87746419e-01]
[ 4.28733680e-02 1.15473583e-01 -6.63571687e-03 8.57467361e-02
 1.15473583e-01 4.28733680e-02]
[ 6.05168647e-01 7.07226039e-01 1.23870914e-01 1.21033729e+00
 7.07226039e-01 6.05168647e-01]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 5.46870655e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-2.05888038e-01 1.69308689e-01 -7.93085660e-03 -4.11776077e-01
 1.69308689e-01 -2.05888038e-01]
[-1.84663809e-01 -4.65451966e-01 5.95026117e-02 -3.69327617e-01
 -4.65451966e-01 -1.84663809e-01]
[ 4.66407064e-01 -3.87612079e-01 1.76410128e-02 9.32814128e-01
 -3.87612079e-01 4.66407064e-01]
[ 4.52451104e-02 1.19865712e-01 -4.73313094e-03 9.04902208e-02
 1.19865712e-01 4.52451104e-02]]

```

(continues on next page)

(continued from previous page)

```

[ 6.90798449e-01  9.20396633e-01  1.49475827e-01  1.38159690e+00
  9.20396633e-01  6.90798449e-01]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  5.36280366e-01
  0.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  1.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  0.00000000e+00  0.00000000e+00]]

[[-1.98803165e-01  1.73327268e-01 -6.03008179e-03 -3.97606330e-01
  1.73327268e-01 -1.98803165e-01]
[-2.04303740e-01 -5.16111388e-01  4.68785776e-02 -4.08607480e-01
 -5.16111388e-01 -2.04303740e-01]
[ 4.47070326e-01 -3.94304029e-01  1.32107437e-02  8.94140651e-01
 -3.94304029e-01  4.47070326e-01]
[ 4.69732048e-02  1.22961727e-01 -3.35899442e-03  9.39464097e-02
  1.22961727e-01  4.69732048e-02]
[ 7.68998995e-01  1.10844286e+00  1.70889328e-01  1.53799799e+00
  1.10844286e+00  7.68998995e-01]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  5.27091252e-01
  0.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  1.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  0.00000000e+00  0.00000000e+00]]

[[-1.92789113e-01  1.75978657e-01 -4.54517629e-03 -3.85578227e-01
  1.75978657e-01 -1.92789113e-01]
[-2.20500138e-01 -5.55540705e-01  3.68776526e-02 -4.41000277e-01
 -5.55540705e-01 -2.20500138e-01]
[ 4.30424855e-01 -3.97907706e-01  9.75257113e-03  8.60849709e-01
 -3.97907706e-01  4.30424855e-01]
[ 4.82793652e-02  1.24952071e-01 -2.30991637e-03  9.65587304e-02
  1.24952071e-01  4.82793652e-02]
[ 8.40805131e-01  1.27504628e+00  1.89020151e-01  1.68161026e+00
  1.27504628e+00  8.40805131e-01]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  5.18989205e-01
  0.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  1.00000000e+00  0.00000000e+00]
[ 0.00000000e+00  0.00000000e+00  0.00000000e+00  0.00000000e+00
  0.00000000e+00  0.00000000e+00]]

[[-1.87672774e-01  1.77588334e-01 -3.38318222e-03 -3.75345548e-01
  1.77588334e-01 -1.87672774e-01]
[-2.33807210e-01 -5.86081383e-01  2.89236334e-02 -4.67614420e-01
 -5.86081383e-01 -2.33807210e-01]
[ 4.16201399e-01 -3.99295277e-01  7.06598588e-03  8.32402797e-01
 -3.99295277e-01  4.16201399e-01]
[ 4.92546648e-02  1.26089711e-01 -1.50412006e-03  9.85093296e-02
  1.26089711e-01  4.92546648e-02]
[ 9.06806543e-01  1.42334018e+00  2.04522708e-01  1.81361309e+00

```

(continues on next page)

(continued from previous page)

```

1.42334018e+00 9.06806543e-01]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 5.11829985e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-1.83320440e-01 1.78410042e-01 -2.47240692e-03 -3.66640879e-01
 1.78410042e-01 -1.83320440e-01]
[-2.44690164e-01 -6.09568485e-01 2.25774266e-02 -4.89380329e-01
 -6.09568485e-01 -2.44690164e-01]
[ 4.04061655e-01 -3.99063012e-01 4.97908386e-03 8.08123310e-01
 -3.99063012e-01 4.04061655e-01]
[ 4.99612484e-02 1.26581014e-01 -8.85891342e-04 9.99224969e-02
 1.26581014e-01 4.99612484e-02]
[ 9.67473970e-01 1.55589415e+00 2.17895305e-01 1.93494794e+00
 1.55589415e+00 9.67473970e-01]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 5.05500234e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-1.79620591e-01 1.78640114e-01 -1.75822439e-03 -3.59241183e-01
 1.78640114e-01 -1.79620591e-01]
[-2.53540123e-01 -6.27448857e-01 1.75019839e-02 -5.07080247e-01
 -6.27448857e-01 -2.53540123e-01]
[ 3.93704970e-01 -3.97656641e-01 3.35895484e-03 7.87409940e-01
 -3.97656641e-01 3.93704970e-01]
[ 5.04492282e-02 1.26586733e-01 -4.13401240e-04 1.00898456e-01
 1.26586733e-01 5.04492282e-02]
[ 1.02322336e+00 1.67481439e+00 2.29524046e-01 2.04644672e+00
 1.67481439e+00 1.02322336e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 4.99901907e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]

[[-1.76478441e-01 1.78430281e-01 -1.19867662e-03 -3.52956882e-01
 1.78430281e-01 -1.76478441e-01]
[-2.60686971e-01 -6.40868686e-01 1.34365068e-02 -5.21373942e-01
 -6.40868686e-01 -2.60686971e-01]
[ 3.84873835e-01 -3.95414931e-01 2.10369522e-03 7.69747670e-01
 -3.95414931e-01 3.84873835e-01]
[ 5.07601805e-02 1.26231631e-01 -5.46465317e-05 1.01520361e-01
 1.26231631e-01 5.07601805e-02]
[ 1.07443160e+00 1.78183962e+00 2.39710937e-01 2.14886320e+00
 1.78183962e+00 1.07443160e+00]]

```

(continues on next page)

(continued from previous page)

```

[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 4.94949118e-01
 0.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 1.00000000e+00 0.00000000e+00]
[ 0.00000000e+00 0.00000000e+00 0.00000000e+00 0.00000000e+00
 0.00000000e+00 0.00000000e+00]]]
ssigmay: [[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]

```

(continues on next page)

(continued from previous page)

```
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 1.]

[[0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1.]]

[[0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 0.]
 [0. 0. 0. 0. 0. 1.]]]
```

(continues on next page)

[illegible]

(continued from previous page)

```
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
[0. 0. 0. 0. 0. 0. 0. 0. 0.]
```

Adjoint sensitivity analysis

```
[18]: # Set model options
model = model_module.getModel()
p_orig = np.array(model.getParameters())
p_orig[list(model.getParameterIds()).index('observable_x1withsigma_sigma')] = 0.1 #_
↳ Change default parameter
model.setParameters(p_orig)
model.setParameterScale(amici.ParameterScaling.none)
model.setTimepoints(np.linspace(0, 10, 21))

solver = model.getSolver()
solver.setMaxSteps(10**4) # Set maximum number of steps for the solver

# simulate time-course to get artificial data
rdata = amici.runAmiciSimulation(model, solver)
edata = amici.ExpData(rdata, 1.0, 0)
edata.fixedParameters = model.getFixedParameters()
# set sigma to 1.0 except for observable 5, so that p[7] is used instead
# (if we have sigma parameterized, the corresponding ExpData entries must NaN, otherwise_
↳ they will override the parameter)
edata.setObservedDataStdDev(rdata['t']*0+np.nan,
                             list(model.getObservableIds()).index('observable_x1withsigma
↳ '))

# enable sensitivities
solver.setSensitivityOrder(amici.SensitivityOrder.first) # First-order ...
solver.setSensitivityMethod(amici.SensitivityMethod.adjoint) # ... adjoint_
↳ sensitivities
```

(continues on next page)

(continued from previous page)

```

model.requireSensitivitiesForAllParameters()           # ... w.r.t. all parameters

# compute adjoint sensitivities
rdata = amici.runAmiciSimulation(model, solver, edata)
#print(rdata['sigmay'])
print('Log-likelihood: %f\nGradient: %s' % (rdata['llh'], rdata['sllh']))

Log-likelihood: -1190.452734
Gradient: [-8.18063367e+01 -7.40378749e+01  1.87640047e+02  2.07890554e+01
 2.62573207e+02  1.77402064e-01  1.15646253e+01  2.11221869e+04]

```

Finite differences gradient check

Compare AMICI-computed gradient with finite differences

```

[19]: from scipy.optimize import check_grad

def func(x0, symbol='llh', x0full=None, plist=[], verbose=False):
    p = x0[:]
    if len(plist):
        p = x0full[:]
        p[plist] = x0
    verbose and print('f: p=%s' % p)

    old_parameters = model.getParameters()
    solver.setSensitivityOrder(amici.SensitivityOrder.none)
    model.setParameters(p)
    rdata = amici.runAmiciSimulation(model, solver, edata)

    model.setParameters(old_parameters)

    res = np.sum(rdata[symbol])
    verbose and print(res)
    return res

def grad(x0, symbol='llh', x0full=None, plist=[], verbose=False):
    p = x0[:]
    if len(plist):
        model.setParameterList(plist)
        p = x0full[:]
        p[plist] = x0
    else:
        model.requireSensitivitiesForAllParameters()
    verbose and print('g: p=%s' % p)

    old_parameters = model.getParameters()
    solver.setSensitivityMethod(amici.SensitivityMethod.forward)
    solver.setSensitivityOrder(amici.SensitivityOrder.first)
    model.setParameters(p)
    rdata = amici.runAmiciSimulation(model, solver, edata)

```

(continues on next page)

(continued from previous page)

```

model.setParameters(old_parameters)

res = rdata['s%s' % symbol]
if not isinstance(res, float):
    if len(res.shape) == 3:
        res = np.sum(res, axis=(0, 2))
    verbose and print(res)
return res

epsilon = 1e-4
err_norm = check_grad(func, grad, p_orig, 'llh', epsilon=epsilon)
print('sllh: |error|_2: %f' % err_norm)
# assert err_norm < 1e-6
print()

for ip in range(model.np()):
    plist = [ip]
    p = p_orig.copy()
    err_norm = check_grad(func, grad, p[plist], 'llh', p, [ip], epsilon=epsilon)
    print('sllh: p[%d]: |error|_2: %f' % (ip, err_norm))

print()
for ip in range(model.np()):
    plist = [ip]
    p = p_orig.copy()
    err_norm = check_grad(func, grad, p[plist], 'y', p, [ip], epsilon=epsilon)
    print('sy: p[%d]: |error|_2: %f' % (ip, err_norm))

print()
for ip in range(model.np()):
    plist = [ip]
    p = p_orig.copy()
    err_norm = check_grad(func, grad, p[plist], 'x', p, [ip], epsilon=epsilon)
    print('sx: p[%d]: |error|_2: %f' % (ip, err_norm))

print()
for ip in range(model.np()):
    plist = [ip]
    p = p_orig.copy()
    err_norm = check_grad(func, grad, p[plist], 'sigmay', p, [ip], epsilon=epsilon)
    print('ssigmay: p[%d]: |error|_2: %f' % (ip, err_norm))

```

```
sllh: |error|_2: 31.850873
```

```

sllh: p[0]: |error|_2: 0.006287
sllh: p[1]: |error|_2: 0.016510
sllh: p[2]: |error|_2: 0.017028
sllh: p[3]: |error|_2: 0.009608
sllh: p[4]: |error|_2: 0.083404
sllh: p[5]: |error|_2: 0.000280

```

(continues on next page)

(continued from previous page)

```

sllh: p[6]: |error|_2: 0.001050
sllh: p[7]: |error|_2: 31.850739

sy: p[0]: |error|_2: 0.002974
sy: p[1]: |error|_2: 0.002717
sy: p[2]: |error|_2: 0.001308
sy: p[3]: |error|_2: 0.000939
sy: p[4]: |error|_2: 0.006106
sy: p[5]: |error|_2: 0.000000
sy: p[6]: |error|_2: 0.000000
sy: p[7]: |error|_2: 0.000000

sx: p[0]: |error|_2: 0.001033
sx: p[1]: |error|_2: 0.001076
sx: p[2]: |error|_2: 0.000121
sx: p[3]: |error|_2: 0.000439
sx: p[4]: |error|_2: 0.001569
sx: p[5]: |error|_2: 0.000000
sx: p[6]: |error|_2: 0.000000
sx: p[7]: |error|_2: 0.000000

ssigmay: p[0]: |error|_2: 0.000000
ssigmay: p[1]: |error|_2: 0.000000
ssigmay: p[2]: |error|_2: 0.000000
ssigmay: p[3]: |error|_2: 0.000000
ssigmay: p[4]: |error|_2: 0.000000
ssigmay: p[5]: |error|_2: 0.000000
ssigmay: p[6]: |error|_2: 0.000000
ssigmay: p[7]: |error|_2: 0.000000

```

```

[20]: eps=1e-4
op=model.getParameters()

solver.setSensitivityMethod(amici.SensitivityMethod.forward) # forward sensitivity_
↪analysis
solver.setSensitivityOrder(amici.SensitivityOrder.first) # first-order sensitivities
model.requireSensitivitiesForAllParameters()
solver.setRelativeTolerance(1e-12)
rdata = amici.runAmiciSimulation(model, solver, edata)

def fd(x0, ip, eps, symbol='llh'):
    p = list(x0[:])
    old_parameters = model.getParameters()
    solver.setSensitivityOrder(amici.SensitivityOrder.none)
    p[ip]+=eps
    model.setParameters(p)
    rdata_f = amici.runAmiciSimulation(model, solver, edata)
    p[ip]-=2*eps
    model.setParameters(p)
    rdata_b = amici.runAmiciSimulation(model, solver, edata)

```

(continues on next page)

(continued from previous page)

```

model.setParameters(old_parameters)
return (rdata_f[symbol]-rdata_b[symbol])/(2*eps)

def plot_sensitivities(symbol, eps):
    fig, axes = plt.subplots(4,2, figsize=(15,10))
    for ip in range(4):
        fd_approx = fd(model.getParameters(), ip, eps, symbol=symbol)


        axes[ip,0].plot(edata.getTimepoints(), rdata[f's{symbol}'][:,ip,:], 'r-')
        axes[ip,0].plot(edata.getTimepoints(), fd_approx, 'k--')
        axes[ip,0].set_ylabel(f'sensitivity {symbol}')
        axes[ip,0].set_xlabel('time')

        axes[ip,1].plot(edata.getTimepoints(), np.abs(rdata[f's{symbol}'][:,ip,:]-fd_
→approx), 'k-')
        axes[ip,1].set_ylabel('difference to fd')
        axes[ip,1].set_xlabel('time')
        axes[ip,1].set_yscale('log')


    plt.tight_layout()
    plt.show()

```

[21]: plot_sensitivities('x', eps)




```
[22]: plot_sensitivities('y', eps)
```



Export as DataFrame

Experimental data and simulation results can both be exported as pandas DataFrame to allow for an easier inspection of numeric values

```
[23]: # run the simulation
rdata = amici.runAmiciSimulation(model, solver, edata)
```

```
[24]: # look at the ExpData as DataFrame
df = amici.getDataObservablesAsDataFrame(model, [edata])
df
```

```
[24]:
```

	time	datatype	t_presim	k0	k0_preeq	k0_presim	observable_x1 \
0	0.0	data	0.0	1.0	NaN	NaN	-1.191094
1	0.5	data	0.0	1.0	NaN	NaN	-1.599410
2	1.0	data	0.0	1.0	NaN	NaN	1.522095
3	1.5	data	0.0	1.0	NaN	NaN	2.455856
4	2.0	data	0.0	1.0	NaN	NaN	-0.600864
5	2.5	data	0.0	1.0	NaN	NaN	1.422341
6	3.0	data	0.0	1.0	NaN	NaN	-0.672523
7	3.5	data	0.0	1.0	NaN	NaN	2.278515
8	4.0	data	0.0	1.0	NaN	NaN	0.078411
9	4.5	data	0.0	1.0	NaN	NaN	0.074017

(continues on next page)

(continued from previous page)

10	5.0	data	0.0	1.0	NaN	NaN	0.537820
11	5.5	data	0.0	1.0	NaN	NaN	0.498204
12	6.0	data	0.0	1.0	NaN	NaN	2.345616
13	6.5	data	0.0	1.0	NaN	NaN	0.995109
14	7.0	data	0.0	1.0	NaN	NaN	1.363276
15	7.5	data	0.0	1.0	NaN	NaN	0.190180
16	8.0	data	0.0	1.0	NaN	NaN	-0.362771
17	8.5	data	0.0	1.0	NaN	NaN	0.884408
18	9.0	data	0.0	1.0	NaN	NaN	-1.554260
19	9.5	data	0.0	1.0	NaN	NaN	0.492781
20	10.0	data	0.0	1.0	NaN	NaN	-0.964663
	observable_x2	observable_x3	observable_x1_scaled		\		
0	0.281469	0.033354	1.645144				
1	1.140165	1.368902	1.535490				
2	2.020846	1.109229	0.594295				
3	0.961785	0.052925	1.839501				
4	0.021845	0.220294	-0.110990				
5	0.045064	1.361070	0.945899				
6	0.873615	1.560601	2.677974				
7	-0.005105	0.799689	1.240916				
8	0.979531	1.745795	0.858134				
9	0.226267	0.604246	-0.091356				
10	1.233766	0.194859	-0.345351				
11	3.218945	0.190730	0.462838				
12	0.956306	-1.770517	0.761754				
13	-0.151091	0.805937	2.929645				
14	1.622225	0.030980	-0.082327				
15	0.962294	1.425918	1.106591				
16	-0.251576	0.540826	1.507657				
17	0.930074	0.510605	2.012371				
18	1.449906	-1.477985	0.871124				
19	0.700873	0.242116	0.279648				
20	-0.485664	2.087815	2.328707				
	observable_x2_offsetted	observable_x1withsigma	observable_x1_std		\		
0	3.900680	-0.518642	1.0				
1	5.678167	0.694825	1.0				
2	3.230374	1.275482	1.0				
3	2.783796	0.085480	1.0				
4	5.003351	2.020780	1.0				
5	4.589646	-0.593535	1.0				
6	2.187698	1.054870	1.0				
7	4.268726	0.491755	1.0				
8	4.609529	0.620844	1.0				
9	3.652345	0.261807	1.0				
10	4.477322	3.378227	1.0				
11	5.946970	1.310100	1.0				
12	3.894865	1.546055	1.0				
13	4.348557	0.234915	1.0				
14	3.761730	0.724608	1.0				
15	4.175984	0.245791	1.0				

(continues on next page)

(continued from previous page)

16	3.871633	2.260562	1.0
17	2.593086	-0.654355	1.0
18	5.497123	0.232772	1.0
19	4.236658	-0.889212	1.0
20	4.787617	0.395106	1.0

	observable_x2_std	observable_x3_std	observable_x1_scaled_std \
0	1.0	1.0	1.0
1	1.0	1.0	1.0
2	1.0	1.0	1.0
3	1.0	1.0	1.0
4	1.0	1.0	1.0
5	1.0	1.0	1.0
6	1.0	1.0	1.0
7	1.0	1.0	1.0
8	1.0	1.0	1.0
9	1.0	1.0	1.0
10	1.0	1.0	1.0
11	1.0	1.0	1.0
12	1.0	1.0	1.0
13	1.0	1.0	1.0
14	1.0	1.0	1.0
15	1.0	1.0	1.0
16	1.0	1.0	1.0
17	1.0	1.0	1.0
18	1.0	1.0	1.0
19	1.0	1.0	1.0
20	1.0	1.0	1.0

	observable_x2_offsetted_std	observable_x1withsigma_std
0	1.0	NaN
1	1.0	NaN
2	1.0	NaN
3	1.0	NaN
4	1.0	NaN
5	1.0	NaN
6	1.0	NaN
7	1.0	NaN
8	1.0	NaN
9	1.0	NaN
10	1.0	NaN
11	1.0	NaN
12	1.0	NaN
13	1.0	NaN
14	1.0	NaN
15	1.0	NaN
16	1.0	NaN
17	1.0	NaN
18	1.0	NaN
19	1.0	NaN
20	1.0	NaN

```
[25]: # from the exported dataframe, we can actually reconstruct a copy of the ExpData instance
reconstructed_edata = amici.getEdataFromDataFrame(model, df)
```

```
[26]: # look at the States in rdata as DataFrame
amici.getResidualsAsDataFrame(model, [edata], [rdata])
```

```
[26]:
```

	time	t_presim	k0	k0_preeq	k0_presim	observable_x1	observable_x2	\
0	0.0	0.0	1.0	NaN	NaN	1.291094	0.118531	
1	0.5	0.0	1.0	NaN	NaN	2.138777	0.455486	
2	1.0	0.0	1.0	NaN	NaN	0.942023	1.287558	
3	1.5	0.0	1.0	NaN	NaN	1.885457	0.231133	
4	2.0	0.0	1.0	NaN	NaN	1.161398	0.693991	
5	2.5	0.0	1.0	NaN	NaN	0.869285	0.653687	
6	3.0	0.0	1.0	NaN	NaN	1.219394	0.191652	
7	3.5	0.0	1.0	NaN	NaN	1.737155	0.671214	
8	4.0	0.0	1.0	NaN	NaN	0.457870	0.328229	
9	4.5	0.0	1.0	NaN	NaN	0.457522	0.411248	
10	5.0	0.0	1.0	NaN	NaN	0.010728	0.609084	
11	5.5	0.0	1.0	NaN	NaN	0.024710	2.606212	
12	6.0	0.0	1.0	NaN	NaN	1.826626	0.354703	
13	6.5	0.0	1.0	NaN	NaN	0.479809	0.742320	
14	7.0	0.0	1.0	NaN	NaN	0.851446	1.040670	
15	7.5	0.0	1.0	NaN	NaN	0.318388	0.389765	
16	8.0	0.0	1.0	NaN	NaN	0.868271	0.815679	
17	8.5	0.0	1.0	NaN	NaN	0.381793	0.373840	
18	9.0	0.0	1.0	NaN	NaN	2.054162	0.901024	
19	9.5	0.0	1.0	NaN	NaN	0.004569	0.158864	
20	10.0	0.0	1.0	NaN	NaN	1.459612	1.021246	

	observable_x3	observable_x1_scaled	observable_x2_offsetted	\
0	0.666646	1.445144	0.500680	
1	1.177412	0.456756	1.993488	
2	1.012805	0.565850	0.502913	
3	0.023151	0.698703	0.946856	
4	0.150600	1.232059	1.287515	
5	1.294769	0.160213	0.890895	
6	1.496868	1.584233	1.494264	
7	0.738182	0.158196	0.602617	
8	1.686301	0.214427	0.958227	
9	0.546593	1.154432	0.014831	
10	0.138899	1.399534	0.852641	
11	0.136330	0.582991	2.334237	
12	1.823477	0.276225	0.293262	
13	0.754307	1.899046	0.757328	
14	0.019418	1.105987	0.180175	
15	1.376658	0.089456	0.603455	
16	0.492622	0.496656	0.307529	
17	0.463381	1.007140	0.963148	
18	1.524300	0.128680	1.948242	
19	0.196646	0.715052	0.694649	
20	2.043129	1.338809	1.252036	


```
observable_x1withsigma
```

(continues on next page)

(continued from previous page)

```

0          6.186425
1          1.554579
2          6.954092
3          4.849190
4          14.602456
5          11.465911
6          5.079991
7          0.496051
8          0.845638
9          2.697316
10         28.511357
11          7.871853
12         10.270655
13          2.803840
14          2.127777
15          2.627767
16         17.550614
17         11.569706
18          2.671303
19         13.865618
20          0.998435

```

```

[27]: # look at the Observables in rdata as DataFrame
      amici.getSimulationObservablesAsDataFrame(model, [edata], [rdata])

```

```

[27]:   time    datatype  t_presim  k0  k0_preeq  k0_presim  observable_x1  \
0    0.0  simulation      0.0  1.0        NaN        NaN      0.100000
1    0.5  simulation      0.0  1.0        NaN        NaN      0.539367
2    1.0  simulation      0.0  1.0        NaN        NaN      0.580072
3    1.5  simulation      0.0  1.0        NaN        NaN      0.570399
4    2.0  simulation      0.0  1.0        NaN        NaN      0.560535
5    2.5  simulation      0.0  1.0        NaN        NaN      0.553056
6    3.0  simulation      0.0  1.0        NaN        NaN      0.546871
7    3.5  simulation      0.0  1.0        NaN        NaN      0.541360
8    4.0  simulation      0.0  1.0        NaN        NaN      0.536280
9    4.5  simulation      0.0  1.0        NaN        NaN      0.531538
10   5.0  simulation      0.0  1.0        NaN        NaN      0.527091
11   5.5  simulation      0.0  1.0        NaN        NaN      0.522914
12   6.0  simulation      0.0  1.0        NaN        NaN      0.518989
13   6.5  simulation      0.0  1.0        NaN        NaN      0.515299
14   7.0  simulation      0.0  1.0        NaN        NaN      0.511830
15   7.5  simulation      0.0  1.0        NaN        NaN      0.508568
16   8.0  simulation      0.0  1.0        NaN        NaN      0.505500
17   8.5  simulation      0.0  1.0        NaN        NaN      0.502615
18   9.0  simulation      0.0  1.0        NaN        NaN      0.499902
19   9.5  simulation      0.0  1.0        NaN        NaN      0.497350
20  10.0  simulation      0.0  1.0        NaN        NaN      0.494949

      observable_x2  observable_x3  observable_x1_scaled  \
0          0.400000      0.700000      0.200000
1          0.684679      0.191491      1.078734
2          0.733287      0.096424      1.160145

```

(continues on next page)

(continued from previous page)

3	0.730652	0.076076	1.140799
4	0.715836	0.069694	1.121069
5	0.698751	0.066301	1.106112
6	0.681963	0.063733	1.093741
7	0.666109	0.061506	1.082720
8	0.651302	0.059495	1.072561
9	0.637515	0.057653	1.063076
10	0.624681	0.055960	1.054183
11	0.612733	0.054400	1.045829
12	0.601603	0.052960	1.037978
13	0.591229	0.051629	1.030598
14	0.581555	0.050399	1.023660
15	0.572529	0.049259	1.017136
16	0.564103	0.048203	1.011000
17	0.556234	0.047224	1.005231
18	0.548881	0.046315	0.999804
19	0.542008	0.045471	0.994700
20	0.535581	0.044686	0.989898

	observable_x2_offsetted	observable_x1withsigma	observable_x1_std \
0	3.400000	0.100000	1.0
1	3.684679	0.539367	1.0
2	3.733287	0.580072	1.0
3	3.730652	0.570399	1.0
4	3.715836	0.560535	1.0
5	3.698751	0.553056	1.0
6	3.681963	0.546871	1.0
7	3.666109	0.541360	1.0
8	3.651302	0.536280	1.0
9	3.637515	0.531538	1.0
10	3.624681	0.527091	1.0
11	3.612733	0.522914	1.0
12	3.601603	0.518989	1.0
13	3.591229	0.515299	1.0
14	3.581555	0.511830	1.0
15	3.572529	0.508568	1.0
16	3.564103	0.505500	1.0
17	3.556234	0.502615	1.0
18	3.548881	0.499902	1.0
19	3.542008	0.497350	1.0
20	3.535581	0.494949	1.0

	observable_x2_std	observable_x3_std	observable_x1_scaled_std \
0	1.0	1.0	1.0
1	1.0	1.0	1.0
2	1.0	1.0	1.0
3	1.0	1.0	1.0
4	1.0	1.0	1.0
5	1.0	1.0	1.0
6	1.0	1.0	1.0
7	1.0	1.0	1.0
8	1.0	1.0	1.0

(continues on next page)

(continued from previous page)

9	1.0	1.0	1.0
10	1.0	1.0	1.0
11	1.0	1.0	1.0
12	1.0	1.0	1.0
13	1.0	1.0	1.0
14	1.0	1.0	1.0
15	1.0	1.0	1.0
16	1.0	1.0	1.0
17	1.0	1.0	1.0
18	1.0	1.0	1.0
19	1.0	1.0	1.0
20	1.0	1.0	1.0

	observable_x2_offsetted_std	observable_x1withsigma_std
0	1.0	0.1
1	1.0	0.1
2	1.0	0.1
3	1.0	0.1
4	1.0	0.1
5	1.0	0.1
6	1.0	0.1
7	1.0	0.1
8	1.0	0.1
9	1.0	0.1
10	1.0	0.1
11	1.0	0.1
12	1.0	0.1
13	1.0	0.1
14	1.0	0.1
15	1.0	0.1
16	1.0	0.1
17	1.0	0.1
18	1.0	0.1
19	1.0	0.1
20	1.0	0.1

```
[28]: # look at the States in rdata as DataFrame
      amici.getSimulationStatesAsDataFrame(model, [edata], [rdata])
```

```
[28]:
```

	time	t_presim	k0	k0_preeq	k0_presim	x1	x2	x3
0	0.0	0.0	1.0	NaN	NaN	0.100000	0.400000	0.700000
1	0.5	0.0	1.0	NaN	NaN	0.539367	0.684679	0.191491
2	1.0	0.0	1.0	NaN	NaN	0.580072	0.733287	0.096424
3	1.5	0.0	1.0	NaN	NaN	0.570399	0.730652	0.076076
4	2.0	0.0	1.0	NaN	NaN	0.560535	0.715836	0.069694
5	2.5	0.0	1.0	NaN	NaN	0.553056	0.698751	0.066301
6	3.0	0.0	1.0	NaN	NaN	0.546871	0.681963	0.063733
7	3.5	0.0	1.0	NaN	NaN	0.541360	0.666109	0.061506
8	4.0	0.0	1.0	NaN	NaN	0.536280	0.651302	0.059495
9	4.5	0.0	1.0	NaN	NaN	0.531538	0.637515	0.057653
10	5.0	0.0	1.0	NaN	NaN	0.527091	0.624681	0.055960

(continues on next page)

(continued from previous page)

11	5.5	0.0	1.0	NaN	NaN	0.522914	0.612733	0.054400
12	6.0	0.0	1.0	NaN	NaN	0.518989	0.601603	0.052960
13	6.5	0.0	1.0	NaN	NaN	0.515299	0.591229	0.051629
14	7.0	0.0	1.0	NaN	NaN	0.511830	0.581555	0.050399
15	7.5	0.0	1.0	NaN	NaN	0.508568	0.572529	0.049259
16	8.0	0.0	1.0	NaN	NaN	0.505500	0.564103	0.048203
17	8.5	0.0	1.0	NaN	NaN	0.502615	0.556234	0.047224
18	9.0	0.0	1.0	NaN	NaN	0.499902	0.548881	0.046315
19	9.5	0.0	1.0	NaN	NaN	0.497350	0.542008	0.045471
20	10.0	0.0	1.0	NaN	NaN	0.494949	0.535581	0.044686

Using PETab

This notebook illustrates how to use [PETab](#) with AMICI.

```
[1]: from amici.petab_import import import_petab_problem
from amici.petab_objective import simulate_petab
import petab

import os
```

We use an example model from the [benchmark collection](#):

```
[2]: !git clone --depth 1 https://github.com/Benchmarking-Initiative/Benchmark-Models-PETab.
git tmp/benchmark-models || (cd tmp/benchmark-models && git pull)
```

```
Cloning into 'tmp/benchmark-models'...
remote: Enumerating objects: 142, done.
remote: Counting objects: 100% (142/142), done.
remote: Compressing objects: 100% (122/122), done.
remote: Total 142 (delta 41), reused 104 (delta 18), pack-reused 0
Receiving objects: 100% (142/142), 648.29 KiB | 1.23 MiB/s, done.
Resolving deltas: 100% (41/41), done.
```

```
[3]: folder_base = "tmp/benchmark-models/Benchmark-Models/"
!ls -l $folder_base
```

```
total 68
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Alkan_SciSignal2018
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Beer_MolBioSystems2014
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Boehm_JProteomeRes2014
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Borghans_BiophysChem1997
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Brannmark_JBC2010
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Bruno_JExpBio2016
-rwxr-xr-x 1 yannik yannik  654 Mär 17 15:27 checkBenchmarkModels.py
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Chen_MSB2009
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Crauste_CellSystems2017
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Elowitz_Nature2000
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Fiedler_BMC2016
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Fujita_SciSignal2010
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Perelson_Science1996
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Rahman_MBS2016
```

(continues on next page)

(continued from previous page)

```
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Sneyd_PNAS2002
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Weber_BMC2015
drwxr-xr-x 2 yannik yannik 4096 Mär 17 15:27 Zheng_PNAS2012
```

We import a model to PETab from a provided yaml file:

```
[4]: model_name = "Boehm_JProteomeRes2014"
yaml_file = os.path.join(folder_base, model_name, model_name + ".yaml")
petab_problem = petab.Problem.from_yaml(yaml_file)
```

Next, we import the model to amici, compile it and obtain a function handle:

```
[5]: amici_model = import_petab_problem(petab_problem)

2020-03-17 15:27:27.586 - amici.petab_import - INFO - Importing model ...
2020-03-17 15:27:27.593 - amici.petab_import - INFO - Model name is 'Boehm_
↳ JProteomeRes2014'. Writing model code to '/home/yannik/amici/python/examples/amici_
↳ models/Boehm_JProteomeRes2014'.
2020-03-17 15:27:27.598 - amici.petab_import - INFO - Species: 8
2020-03-17 15:27:27.599 - amici.petab_import - INFO - Global parameters: 9
2020-03-17 15:27:27.599 - amici.petab_import - INFO - Reactions: 9
2020-03-17 15:27:27.715 - amici.petab_import - INFO - Observables: 3
2020-03-17 15:27:27.715 - amici.petab_import - INFO - Sigmas: 3
2020-03-17 15:27:27.722 - amici.petab_import - DEBUG - Adding output parameters to model:
↳ OrderedDict([('noiseParameter1_pSTAT5A_rel', None), ('noiseParameter1_pSTAT5B_rel',
↳ None), ('noiseParameter1_rSTAT5A_rel', None)])
2020-03-17 15:27:27.725 - amici.petab_import - DEBUG - Condition table: (1, 1)
2020-03-17 15:27:27.726 - amici.petab_import - DEBUG - Fixed parameters are []
2020-03-17 15:27:27.728 - amici.petab_import - INFO - Overall fixed parameters: 0
2020-03-17 15:27:27.729 - amici.petab_import - INFO - Variable parameters: 12
2020-03-17 15:27:27.735 - amici.sbml_import - INFO - Finished processing SBML parameters
↳ (1.25E-03s)
2020-03-17 15:27:27.749 - amici.sbml_import - INFO - Finished processing SBML species
↳ (1.26E-02s)
2020-03-17 15:27:27.829 - amici.sbml_import - INFO - Finished processing SBML reactions
↳ (7.41E-02s)
2020-03-17 15:27:27.833 - amici.sbml_import - INFO - Finished processing SBML
↳ compartments (4.23E-04s)
2020-03-17 15:27:27.898 - amici.sbml_import - INFO - Finished processing SBML rules
↳ (6.47E-02s)
2020-03-17 15:27:28.012 - amici.sbml_import - INFO - Finished processing SBML
↳ observables (6.77E-02s)
2020-03-17 15:27:28.139 - amici.ode_export - INFO - Finished writing J.cpp
↳ (1.14E-01s)
2020-03-17 15:27:28.160 - amici.ode_export - INFO - Finished writing JB.cpp
↳ (2.04E-02s)
2020-03-17 15:27:28.167 - amici.ode_export - INFO - Finished writing JDiag.cpp
↳ (6.41E-03s)
2020-03-17 15:27:28.187 - amici.ode_export - INFO - Finished writing JSparse.cpp
↳ (1.91E-02s)
2020-03-17 15:27:28.217 - amici.ode_export - INFO - Finished writing JSparseB.cpp
↳ (2.73E-02s)
2020-03-17 15:27:28.236 - amici.ode_export - INFO - Finished writing Jy.cpp
↳ (1.65E-02s)
```

(continues on next page)

(continued from previous page)

```

2020-03-17 15:27:28.344 - amici.ode_export - INFO - Finished writing dJydsigmay.cpp
↳ (1.07E-01s)
2020-03-17 15:27:28.389 - amici.ode_export - INFO - Finished writing dJydy.cpp
↳ (3.99E-02s)
2020-03-17 15:27:28.466 - amici.ode_export - INFO - Finished writing dwdp.cpp
↳ (7.61E-02s)
2020-03-17 15:27:28.473 - amici.ode_export - INFO - Finished writing dwdx.cpp
↳ (5.87E-03s)
2020-03-17 15:27:28.497 - amici.ode_export - INFO - Finished writing dxdotdw.cpp
↳ (2.32E-02s)
2020-03-17 15:27:28.533 - amici.ode_export - INFO - Finished writing dxdotdp_explicit.
↳ cpp (3.38E-02s)
2020-03-17 15:27:28.756 - amici.ode_export - INFO - Finished writing dydx.cpp
↳ (1.98E-01s)
2020-03-17 15:27:28.910 - amici.ode_export - INFO - Finished writing dydp.cpp
↳ (1.53E-01s)
2020-03-17 15:27:28.926 - amici.ode_export - INFO - Finished writing dsigmaydp.cpp
↳ (1.40E-02s)
2020-03-17 15:27:28.931 - amici.ode_export - INFO - Finished writing sigmay.cpp
↳ (2.46E-03s)
2020-03-17 15:27:28.950 - amici.ode_export - INFO - Finished writing w.cpp
↳ (1.55E-02s)
2020-03-17 15:27:28.967 - amici.ode_export - INFO - Finished writing x0.cpp
↳ (1.57E-02s)
2020-03-17 15:27:28.975 - amici.ode_export - INFO - Finished writing x0_fixedParameters.
↳ cpp (4.78E-03s)
2020-03-17 15:27:29.027 - amici.ode_export - INFO - Finished writing sx0.cpp
↳ (5.01E-02s)
2020-03-17 15:27:29.069 - amici.ode_export - INFO - Finished writing sx0_fixedParameters.
↳ cpp (3.14E-02s)
2020-03-17 15:27:29.104 - amici.ode_export - INFO - Finished writing xdot.cpp
↳ (3.43E-02s)
2020-03-17 15:27:29.129 - amici.ode_export - INFO - Finished writing y.cpp
↳ (2.16E-02s)
2020-03-17 15:27:29.136 - amici.ode_export - INFO - Finished writing x_rdata.cpp
↳ (4.95E-03s)
2020-03-17 15:27:29.138 - amici.ode_export - INFO - Finished writing total_cl.cpp
↳ (6.59E-04s)
2020-03-17 15:27:29.147 - amici.ode_export - INFO - Finished writing x_solver.cpp
↳ (7.72E-03s)
2020-03-17 15:27:29.166 - amici.ode_export - INFO - Finished generating cpp code
↳ (1.14E+00s)
2020-03-17 15:27:46.200 - amici.ode_export - INFO - Finished compiling cpp code
↳ (1.70E+01s)
2020-03-17 15:27:46.204 - amici.petab_import - INFO - Finished Importing PEtab model
↳ (1.86E+01s)
2020-03-17 15:27:46.209 - amici.petab_import - INFO - Successfully loaded model Boehm_
↳ JProteomeRes2014 from /home/yannik/amici/python/examples/amici_models/Boehm_
↳ JProteomeRes2014.

```

```

running build_ext
building 'Boehm_JProteomeRes2014._Boehm_JProteomeRes2014' extension

```

(continues on next page)

(continued from previous page)

```

swigging swig/Boehm_JProteomeRes2014.i to swig/Boehm_JProteomeRes2014_wrap.cpp
swig -python -c++ -modern -outdir Boehm_JProteomeRes2014 -I/home/yannik/amici/python/
↳ sdist/amici/swig -I/home/yannik/amici/python/sdist/amici/include -o swig/Boehm_
↳ JProteomeRes2014_wrap.cpp swig/Boehm_JProteomeRes2014.i
creating build
creating build/temp.linux-x86_64-3.7
creating build/temp.linux-x86_64-3.7/swig
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c swig/Boehm_JProteomeRes2014_wrap.cpp -o build/temp.linux-x86_64-
↳ 3.7/swig/Boehm_JProteomeRes2014_wrap.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdw.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_dxdotdw.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_total_cl.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_total_cl.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_x_rdata.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_x_rdata.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdp_implicit_colptrs.cpp -o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_implicit_colptrs.o -std=c++14

```

(continued from previous page)

```

cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dsigmaydp.cpp -o build/temp.linux-x86_64-
↳ 3.7/Boehm_JProteomeRes2014_dsigmaydp.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_y.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_y.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dydp.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dydp.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_w.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_w.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparseB_rowvals.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_JSparseB_rowvals.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++

```

(continues on next page)

(continued from previous page)

```

gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdw_rowvals.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_dxdotdw_rowvals.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdx_rowvals.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dwdx_rowvals.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_x0.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_x0.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdx.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dwdx.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dJydy_colptrs.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dJydy_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparseB.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_JSparseB.o -std=c++14

```


(continued from previous page)

```

cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparseB_colptrs.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_JSparseB_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdp_explicit_colptrs.cpp -o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_explicit_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_sx0_fixedParameters.cpp -o build/temp.
↳ linux-x86_64-3.7/Boehm_JProteomeRes2014_sx0_fixedParameters.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparse_rowvals.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_JSparse_rowvals.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdp_explicit.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_explicit.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++

```

(continues on next page)

(continued from previous page)

```

gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dJydy.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dJydy.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdp_colptrs.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dwdp_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_x0_fixedParameters.cpp -o build/temp.
↳ linux-x86_64-3.7/Boehm_JProteomeRes2014_x0_fixedParameters.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdw_colptrs.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_dxdotdw_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dJydsigmay.cpp -o build/temp.linux-x86_64-
↳ 3.7/Boehm_JProteomeRes2014_dJydsigmay.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdp_implicit_rowvals.cpp -o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_implicit_rowvals.o -std=c++14

```

(continued from previous page)

```

cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdp.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dwdp.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_sx0.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_sx0.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JB.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_JB.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdx_colptrs.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dwdx_colptrs.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c wrapfunctions.cpp -o build/temp.linux-x86_64-3.7/wrapfunctions.o
↳ -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++

```

(continues on next page)

(continued from previous page)

```

gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_x_solver.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_x_solver.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparse.cpp -o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_JSparse.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_xdot.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_xdot.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dJdy_rowvals.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dJdy_rowvals.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dwdp_rowvals.cpp -o build/temp.linux-x86_
↳ 64-3.7/Boehm_JProteomeRes2014_dwdp_rowvals.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JSparse_colptrs.cpp -o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_JSparse_colptrs.o -std=c++14

```

(continued from previous page)

```

cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_J.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_J.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dydx.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dydx.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_JDiag.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_JDiag.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_Jy.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_Jy.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_sigmay.cpp -o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_sigmay.o -std=c++14
cc1plus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++

```

(continues on next page)

(continued from previous page)

```

gcc -pthread -B /home/yannik/anaconda3/compiler_compat -Wl,--sysroot=/ -Wsign-compare -
↳ DNDEBUG -g -fwrapv -O3 -Wall -Wstrict-prototypes -fPIC -I/home/yannik/amici/python/
↳ examples/amici_models/Boehm_JProteomeRes2014 -I/home/yannik/amici/python/sdist/amici/
↳ include -I/home/yannik/amici/python/sdist/amici/ThirdParty/gsl -I/home/yannik/amici/
↳ python/sdist/amici/ThirdParty/sundials/include -I/home/yannik/amici/python/sdist/amici/
↳ ThirdParty/SuiteSparse/include -I/usr/include/hdf5/serial -I/home/yannik/anaconda3/
↳ include/python3.7m -c Boehm_JProteomeRes2014_dxdotdp_explicit_rowvals.cpp -o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_explicit_rowvals.o -std=c++14
cclplus: warning: command line option '-Wstrict-prototypes' is valid for C/ObjC but not
↳ for C++
g++ -pthread -shared -B /home/yannik/anaconda3/compiler_compat -L/home/yannik/anaconda3/
↳ lib -Wl,-rpath=/home/yannik/anaconda3/lib -Wl,--no-as-needed -Wl,--sysroot=/ build/
↳ temp.linux-x86_64-3.7/swig/Boehm_JProteomeRes2014_wrap.o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dxdotdw.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_
↳ total_cl.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_x_rdata.o build/temp.
↳ linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_implicit_colptrs.o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_dsigmaydp.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_y.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dydp.o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_w.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_JSparseB_rowvals.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_
↳ dxdotdw_rowvals.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dwdx_rowvals.o
↳ build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_x0.o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dwdx.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dJydy_
↳ colptrs.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_JSparseB.o build/temp.
↳ linux-x86_64-3.7/Boehm_JProteomeRes2014_JSparseB_colptrs.o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dxdotdp_explicit_colptrs.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_sx0_fixedParameters.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_JSparse_rowvals.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_
↳ dxdotdp_explicit.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dJydy.o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dwdp_colptrs.o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_x0_fixedParameters.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_dxdotdw_colptrs.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_
↳ dJydsigmay.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dxdotdp_implicit_
↳ rowvals.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dwdp.o build/temp.linux-
↳ x86_64-3.7/Boehm_JProteomeRes2014_sx0.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_JB.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_dwdx_colptrs.
↳ o build/temp.linux-x86_64-3.7/wrapfunctions.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_x_solver.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_JSparse.
↳ o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_xdot.o build/temp.linux-x86_64-3.
↳ 7/Boehm_JProteomeRes2014_dJydy_rowvals.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_dwdp_rowvals.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_
↳ JSparse_colptrs.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_J.o build/temp.
↳ linux-x86_64-3.7/Boehm_JProteomeRes2014_dydx.o build/temp.linux-x86_64-3.7/Boehm_
↳ JProteomeRes2014_JDiag.o build/temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_Jy.o build/
↳ temp.linux-x86_64-3.7/Boehm_JProteomeRes2014_sigmay.o build/temp.linux-x86_64-3.7/
↳ Boehm_JProteomeRes2014_dxdotdp_explicit_rowvals.o -L/usr/lib/x86_64-linux-gnu/hdf5/
↳ serial -L/home/yannik/amici/python/sdist/amici/libs -lamici -lsundials -lsuitesparse -
↳ lcbblas -lhdf5_hl_cpp -lhdf5_hl -lhdf5_cpp -lhdf5 -o /home/yannik/amici/python/examples/
↳ amici_models/Boehm_JProteomeRes2014/Boehm_JProteomeRes2014/_Boehm_JProteomeRes2014.
↳ cpython-37m-x86_64-linux-gnu.so

```

That's it. Now, we can use the model to perform simulations. For more involved purposes, consider using the objective

function provided by `pyPESTO`. For simple simulations, a function `simulate_petab` is available:

```
[6]: simulate_petab(petab_problem, amici_model)
[6]: {'llh': -138.22199570334107,
      'sllh': None,
      'rdatas': [<amici.numpy.ReturnDataView at 0x7f030e1a0fd0>]}
```

This performs a simulation at the nominal parameters. Parameters can also be directly specified, both scaled and unscaled:

```
[7]: parameters = {
      x_id: x_val for x_id, x_val in
      zip(petab_problem.x_ids, petab_problem.x_nominal_scaled)
    }
    simulate_petab(petab_problem, amici_model, problem_parameters=parameters, scaled_
    ↪ parameters=True)
[7]: {'llh': -138.22199570334107,
      'sllh': None,
      'rdatas': [<amici.numpy.ReturnDataView at 0x7f030e198590>]}
```

For further information, see the [documentation](#).

AMICI Python example “Experimental Conditions”

In this example we will explore some more options for the initialization of experimental conditions, including how to reset initial conditions based on changing values for `fixedParameters` as well as an additional presimulation phase on top of preequilibration. This notebook is expected to run from the `python/example_presimulation` directory.

```
[1]: # SBML model we want to import
      sbml_file = 'model_presimulation.xml'
      # Name of the model that will also be the name of the python module
      model_name = 'model_presimulation'
      # Directory to which the generated model code is written
      model_output_dir = model_name

      import libsbml
      import amici
      import amici.plotting
      import os
      import sys
      import importlib
      import numpy as np
      import pandas as pd
      import matplotlib.pyplot as plt
      from pprint import pprint
```

Model Loading

Here we load a simple model of protein phosphorylation that can be inhibited by a drug. This model was created using PySB (see `createModel.py`)

```
[2]: sbml_reader = libsbml.SBMLReader()
sbml_doc = sbml_reader.readSBML(sbml_file)
sbml_model = sbml_doc.getModel()

print('Species:')
pprint([(s.getId(),s.getName()) for s in sbml_model.getListOfSpecies()])

print('\nReactions:')
for reaction in sbml_model.getListOfReactions():
    reactants = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 1
→ else '', r.getSpecies()) for r in reaction.getListOfReactants()])
    products = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 1
→ else '', r.getSpecies()) for r in reaction.getListOfProducts()])
    reversible = '<' if reaction.getReversible() else ''
    print('%3s: %10s %1s->%10s\t\t[%s]' % (reaction.getName(),
        reactants,
        reversible,
        products,
        libsbml.formulaToL3String(reaction.getKineticLaw().getMath()))

print('Parameters:')
pprint([(p.getId(),p.getName()) for p in sbml_model.getListOfParameters()])

Species:
[('__s0', "PROT(kin=None, drug=None, phospho='u')"),
 ('__s1', 'DRUG(bound=None)'),
 ('__s2', 'KIN(bound=None)'),
 ('__s3', "DRUG(bound=1) ._br_PROT(kin=None, drug=1, phospho='u')"),
 ('__s4', "KIN(bound=1) ._br_PROT(kin=1, drug=None, phospho='u')"),
 ('__s5', "PROT(kin=None, drug=None, phospho='p')")]

Reactions:
PROT_DRUG_bind: __s0 + __s1 <-> __s3          [-(koff_prot_drug * __s3) + kon_
→prot_drug * __s0 * __s1]
PROT_KIN_bind: __s0 + __s2 -> __s4             [kon_prot_kin * __s0 * __s2]
PROT_KIN_phospho: __s4 -> __s2 + __s5          [kphospho_prot_kin * __s4]
PROT_dephospho: __s5 -> __s0                  [kdephospho_prot * __s5]

Parameters:
[('initProt', 'initProt'),
 ('initDrug', 'initDrug'),
 ('initKin', 'initKin'),
 ('pPROT_obs', 'pPROT_obs'),
 ('PROT_0', 'PROT_0'),
 ('DRUG_0', 'DRUG_0'),
 ('KIN_0', 'KIN_0'),
 ('kon_prot_drug', 'kon_prot_drug'),
 ('koff_prot_drug', 'koff_prot_drug'),
 ('kon_prot_kin', 'kon_prot_kin'),
 ('kphospho_prot_kin', 'kphospho_prot_kin'),
```

(continues on next page)

(continued from previous page)

```
( 'kdephospho_prot', 'kdephospho_prot'),
( '__obs0', 'pPROT'),
( '__obs1', 'tPROT')]
```

```
[3]: # Create an SbmlImporter instance for our SBML model
sbml_importer = amici.SbmlImporter(sbml_file)
```

For this example we want specify the initial drug and kinase concentrations as experimental conditions. Accordingly we specify them as `fixedParameters`. The meaning of `fixedParameters` is defined in the [Glossary](https://amici.readthedocs.io/en/latest/glossary.html#term-fixed-parameters), which we display here for convenience.

```
[4]: from IPython.display import IFram
IFrame('https://amici.readthedocs.io/en/latest/glossary.html#term-fixed-parameters',
      ↪width=600, height=175)
```

```
[4]: <IPython.lib.display.IFrame at 0x10ce15b50>
```

```
[5]: fixedParameters = ['DRUG_0', 'KIN_0']
```

The SBML model specifies a single observable named `pPROT` which describes the fraction of phosphorylated Protein. We load this observable using `amici.assignmentRules2observables`.

```
[6]: # Retrieve model output names and formulae from AssignmentRules and remove the
      ↪respective rules
observables = amici.assignmentRules2observables(
    sbml_importer.sbml, # the libsbml model object
    filter_function=lambda variable: variable.getName() == 'pPROT'
)
print('Observables:')
pprint(observables)
```

```
Observables:
{'__obs0': {'formula': '__s5', 'name': 'pPROT'}}
```

Now the model is ready for compilation using `sbml2amici`. Note that we here pass `fixedParameters` as arguments to `constant_parameters`, which ensures that `amici` is aware that we want to have them as `fixedParameters`:

```
[7]: sbml_importer.sbml2amici(model_name,
                             model_output_dir,
                             verbose=False,
                             observables=observables,
                             constant_parameters=fixedParameters)
# load the generated module
model_module = amici.import_model_module(model_name, model_output_dir)
```


To simulate the model we need to create an instance via the `getModel()` method in the generated model module.

```
[8]: # Create Model instance
model = model_module.getModel()

# Create solver instance
solver = model.getSolver()
```


The only thing we need to simulate the model is a timepoint vector, which can be specified using the `setTimepoints` method. If we do not specify any additional options, the default values for `fixedParameters` and `parameters` that were specified in the SBML file will be used.

```
[9]: # Run simulation using default model parameters and solver options
model.setTimepoints(np.linspace(0, 60, 60))
rdata = amici.runAmiciSimulation(model, solver)
amici.plotting.plotObservableTrajectories(rdata)
```




Simulation options can be specified either in the `Model` or in an `ExpData` instance. The `ExpData` instance can also carry experimental data. To initialize an `ExpData` instance from simulation results, amici offers some [convenient constructors](#). In the following we will initialize an `ExpData` object from simulation results, but add noise with standard deviation 0.1 and specify the standard deviation accordingly. Moreover, we will specify custom values for `DRUG_0=0` and `KIN_0=2`. If `fixedParameter` is specified in an `ExpData` instance, `runAmiciSimulation` will use those parameters instead of the ones specified in the `Model` instance.

```
[10]: edata = amici.ExpData(rdata, 0.1, 0.0)
edata.fixedParameters = [0,2]
rdata = amici.runAmiciSimulation(model, solver, edata)
amici.plotting.plotObservableTrajectories(rdata)
```

For many biological systems, it is reasonable to assume that they start in a steady state. In this example we want to specify an experiment where a pretreatment with a drug is performed *before* the kinase is added. We assume that the pretreatment is sufficiently long such that the system reaches steady state before the kinase is added. To implement this in amici, we can specify `fixedParametersPreequilibration` in the `ExpData` object. This automatically adds a preequilibration phase where the model is run to steady state, before regular simulation starts. Here we set `DRUG_0=3` and `KIN_0=0` for the preequilibration. This means that there is no kinase available in the preequilibration phase.

```
[11]: edata.fixedParametersPreequilibration = [3,0]
      rdata = amici.runAmiciSimulation(model, solver, edata)
      amici.plotting.plotObservableTrajectories(rdata)
```




The resulting trajectory is definitely not what one may expect. The problem is that the `DRUG_0` and `KIN_0` set initial conditions for species in the model. By default these initial conditions are only applied at the very beginning of the simulation, i.e., before the preequilibration. Accordingly, the `fixedParameters` that we specified do not have any effect. To fix this, we need to set the `reinitializeFixedParameterInitialStates` attribute to `True`, to specify that AMICI reinitializes all states that have `fixedParameter`-dependent initial states.


```
[12]: edata.reinitializeFixedParameterInitialStates = True
```

With this option activated, the kinase concentration will be reinitialized after the preequilibration and we will see the expected change in fractional phosphorylation:


```
[13]: rdata = amici.runAmiciSimulation(model, solver, edata)
      amici.plotting.plotObservableTrajectories(rdata)
```



On top of preequilibration, we can also specify presimulation. This option can be used to specify pretreatments where the system is not assumed to reach steadystate. Presimulation can be activated by specifying `t_presim` and `edata.fixedParametersPresimulation`. If both `fixedParametersPresimulation` and `fixedParametersPreequilibration` are specified, preequilibration will be performed first, followed by presimulation, followed by regular simulation. For this example we specify `DRUG_0=10` and `KIN_0=0` for the presimulation and `DRUG_0=10` and `KIN_0=2` for the regular simulation. We do not overwrite the `DRUG_0=3` and `KIN_0=0` that was previously specified for preequilibration.

```
[14]: edata.t_presim = 10
      edata.fixedParametersPresimulation = [10.0, 0.0]
      edata.fixedParameters = [10.0, 2.0]
      print(edata.fixedParametersPreequilibration)
      print(edata.fixedParametersPresimulation)
      print(edata.fixedParameters)
      rdata = amici.runAmiciSimulation(model, solver, edata)
      amici.plotting.plotObservableTrajectories(rdata)
```

```
(3.0, 0.0)
(10.0, 0.0)
(10.0, 2.0)
```



AMICI documentation example of the steady state solver logic

This is an example to document the internal logic of the steady state solver, which is used in preequilibration and postequilibration.

Steady states of dynamical system

Not every dynamical system needs to run into a steady state. Instead, it may exhibit

- continuous growth, e.g.,

$$\dot{x} = x, \quad x_0 = 1$$

- a finite-time blow up, e.g.,

$$\dot{x} = x^2, \quad x_0 = 1$$

- oscillations, e.g.,

$$\ddot{x} = -x, \quad x_0 = 1$$

- chaotic behaviour, e.g., the Lorentz attractor

If the considered dynamical system has a steady state for positive times, then integrating the ODE long enough will equilibrate the system to this steady state. However, this may be computationally more demanding than other approaches and may fail, if the maximum number of integration steps is exceeded before reaching the steady state.

In general, Newton's method will find the steady state faster than forward simulation. However, it only converges if started close enough to the steady state. Moreover, it will not work, if the dynamical system has conserved quantities which were not removed prior to steady state computation: Conserved quantities will cause singularities in the Jacobian of the right hand side of the system, such that the linear problem within each step of Newton's method can not be solved.


Logic of the steady state solver

If AMICI has to equilibrate a dynamical system, it can do this either via simulating until the right hand side of the system becomes small, or it can try to find the steady state directly by Newton's method. Amici decides automatically which approach is chosen and how forward or adjoint sensitivities are computed, if requested. However, the user can influence this behavior, if prior knowledge about the dynamical is available.

The logic which AMICI will follow to equilibrate the system works as follows:

```
[1]: from IPython.display import Image
fig = Image(filename='../documentation/gfx/steadystate_solver_workflow.png')
fig
```

[1]:



The example model

We will use the example model `model_constant_species.xml`, which has conserved species. Those are automatically removed in the SBML import of AMICI, but they can also be kept in the model to demonstrate the failure of Newton's method due to a singular right hand side Jacobian.

```
[2]: import libsbml
import importlib
import amici
import os
import sys
import numpy as np
import matplotlib.pyplot as plt

# SBML model we want to import
sbml_file = 'model_constant_species.xml'

# Name of the models that will also be the name of the python module
model_name = 'model_constant_species'
model_reduced_name = model_name + '_reduced'

# Directories to which the generated model code is written
model_output_dir = model_name
model_reduced_output_dir = model_reduced_name

# Read the model and give some output
sbml_reader = libsbml.SBMLReader()
sbml_doc = sbml_reader.readSBML(sbml_file)
sbml_model = sbml_doc.getModel()
dir(sbml_doc)

print('Species: ', [s.getId() for s in sbml_model.getListOfSpecies()])

print('\nReactions:')
for reaction in sbml_model.getListOfReactions():
    reactants = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 0
→1 else '', r.getSpecies()) for r in reaction.getListOfReactants()])
    products = ' + '.join(['%s %s'%(int(r.getStoichiometry()) if r.getStoichiometry() > 0
→1 else '', r.getSpecies()) for r in reaction.getListOfProducts()])
    reversible = '<' if reaction.getReversible() else ''
    print('%3s: %10s %1s->%10s\t\t[%s]' % (reaction.getId(),
        reactants,
        reversible,
        products,
        libsbml.formulaToL3String(reaction.getKineticLaw().getMath()))

Species:  ['substrate', 'enzyme', 'complex', 'product']

Reactions:
creation:          -> substrate          [compartment * (synthesis_substrate + k_
→create)]
binding: substrate + enzyme <-> complex          [compartment * (k_bind *
→substrate * enzyme - k_unbind * complex)]
conversion: complex -> enzyme + product          [compartment * k_convert *
→complex]
```

(continues on next page)

(continued from previous page)

```
decay:      product  ->                [compartment * k_decay * product]
```

```
[3]: # Create an SbmlImporter instance for our SBML model
sbml_importer = amici.SbmlImporter(sbml_file)

# specify observables and constant parameters
constantParameters = ['synthesis_substrate', 'init_enzyme']
observables = {
    'observable_product': {'name': '', 'formula': 'product'},
    'observable_substrate': {'name': '', 'formula': 'substrate'},
}
sigmas = {'observable_product': 1.0, 'observable_substrate': 1.0}

# import the model
sbml_importer.sbml2amici(model_reduced_name,
                          model_reduced_output_dir,
                          observables=observables,
                          constantParameters=constantParameters,
                          sigmas=sigmas)
sbml_importer.sbml2amici(model_name,
                          model_output_dir,
                          observables=observables,
                          constantParameters=constantParameters,
                          sigmas=sigmas,
                          compute_conservation_laws=False)

[4]: # import the models and run some test simulations
model_reduced_module = amici.import_model_module(model_reduced_name, os.path.
↳ abspath(model_reduced_output_dir))
model_reduced = model_reduced_module.getModel()


model_module = amici.import_model_module(model_name, os.path.abspath(model_output_dir))
model = model_module.getModel()


# simulate model with conservation laws
model_reduced.setTimepoints(np.linspace(0, 2, 100))
solver_reduced = model_reduced.getSolver()
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced)

# simulate model without conservation laws
model.setTimepoints(np.linspace(0, 2, 100))
solver = model.getSolver()
rdata = amici.runAmiciSimulation(model, solver)

# plot trajectories
import amici.plotting
amici.plotting.plotStateTrajectories(rdata_reduced, model=model_reduced)
amici.plotting.plotObservableTrajectories(rdata_reduced, model=model_reduced)

amici.plotting.plotStateTrajectories(rdata, model=model)
amici.plotting.plotObservableTrajectories(rdata, model=model)
```





Inferring the steady state of the system (postequilibration)

First, we want to demonstrate that Newton's method will fail with the unreduced model due to a singular right hand side Jacobian.

```
[5]: # Call postequilibration by setting an infinity timepoint
model.setTimepoints(np.full(1, np.inf))

# set the solver
solver = model.getSolver()
solver.setNewtonMaxSteps(10)
solver.setMaxSteps(1000)
rdata = amici.runAmiciSimulation(model, solver)

#np.set_printoptions(threshold=8, edgeitems=2)
```

(continues on next page)

(continued from previous page)

```

for key, value in rdata.items():
    print('%12s: ' % key, value)

    ts: [inf]
    x: [[0.11      2.          0.2          2.000000002]]
    x0: [5. 2. 0. 0.]
    x_ss: [nan nan nan nan]
    sx: None
    sx0: None
    sx_ss: None
    y: [[2.000000002 0.11      ]]
    sigmay: [[1. 1.]]
    sy: None
    ssigmay: None
    z: None
    rz: None
    sigmaz: None
    sz: None
    srz: None
    ssigmaz: None
    sllh: None
    s2llh: None
    J: [[-20.    0.   20.    0. ]
[-1.1  0.    1.1  0. ]
[ 1.    0.  -11.  10. ]
[ 0.    0.    0.  -1. ]]
    xdot: [ 0.000000000e+00  0.000000000e+00  2.22044605e-16 -2.24170307e-08]
    status: 0.0
    llh: nan
    chi2: nan
    res: [0. 0.]
    sres: None
    FIM: None
    w: [[2.          2.          2.          2.000000002]]
    preeq_wrms: nan
    preeq_t: nan
    preeq_numlinsteps: None
    preeq_numsteps: [[0 0 0]]
    preeq_numstepsB: 12.0
    preeq_status: [[0 0 0]]
    preeq_cpu_time: 0.0
    preeq_cpu_timeB: 0.0
    posteq_wrms: 0.5604257578208488
    posteq_t: 19.2252094591474
    posteq_numlinsteps: None
    posteq_numsteps: [[ 0 417  0]]
    posteq_numstepsB: 0.0
    posteq_status: [[-3 1 0]]
    posteq_cpu_time: 2.315
    posteq_cpu_timeB: 0.0
    numsteps: None
    numrhsevals: None

```

(continues on next page)

(continued from previous page)

```

numerrtestfails: None
numnonlinsolvconvfails: None
    order: None
    cpu_time: 0.0
    numstepsB: None
numrhsevalsB: None
numerrtestfailsB: None
numnonlinsolvconvfailsB: None
    cpu_timeB: 0.0

```

The fields `posteq_status` and `posteq_numsteps` in `rdata` tells us how postequilibration worked:

- the first entry informs us about the status/number of steps in Newton's method (here 0, as Newton's method did not work)
- the second entry tells us, the status/how many integration steps were taken until steady state was reached
- the third entry informs us about the status/number of Newton steps in the second launch, after simulation

The status is encoded as an Integer flag with the following meanings:

- 1: Successful run
- 0: Did not run
- -1: Error: No further specification is given, the error message should give more information.
- -2: Error: The method did not converge to a steady state within the maximum number of steps (Newton's method or simulation).
- -3: Error: The Jacobian of the right hand side is singular (only Newton's method)
- -4: Error: The damping factor in Newton's method was reduced until it met the lower bound without success (Newton's method only)
- -5: Error: The model was simulated past the timepoint $t=1e100$ without finding a steady state. Therefore, it is likely that the model has not steady state for the given parameter vector.

Here, only the second entry of `posteq_status` contains a positive integer: The first run of Newton's method failed due to a Jacobian, which could not be factorized, but the second run (simulation) contains the entry 1 (success). The third entry is 0, thus Newton's method was not launched for a second time. More information can be found in `posteq_numsteps`: Also here, only the second entry contains a positive integer, which is smaller than the maximum number of steps taken (<1000). Hence steady state was reached via simulation, which corresponds to the simulated time written to `posteq_time`.

We want to demonstrate a complete failure if inferring the steady state by reducing the number of integration steps to a lower value:

```

[6]: # reduce maxsteps for integration
solver.setMaxSteps(100)
rdata = amici.runAmiciSimulation(model, solver)
print('Status of postequilibration:', rdata['posteq_status'])
print('Number of steps employed in postequilibration:', rdata['posteq_numsteps'])

```

```

Status of postequilibration: [[-3 -2 -3]]
Number of steps employed in postequilibration: [[ 0 100  0]]

```

```

[Warning] AMICI:simulation: AMICI simulation failed:
Steady state computation failed. First run of Newton solver failed: RHS could not be
↪factorized. Simulation to steady state failed: No convergence was achieved. Second run
↪of Newton solver failed: RHS could not be factorized.

```

(continues on next page)

(continued from previous page)

Error occurred in:

```

0      0x1060f7913 amici::SteadystateProblem::handleSteadyStateFailure(amici::Solver_
↳const*, amici::Model*) + 531
1      0x1060f6b3c amici::SteadystateProblem::findSteadyState(amici::Solver*, amici::
↳NewtonSolver*, amici::Model*, int) + 332
2      0x1060f6882 amici::SteadystateProblem::workSteadyStateProblem(amici::Solver*,
↳amici::Model*, int) + 322
3      0x1060a4615 amici::AmiciApplication::runAmiciSimulation(amici::Solver&, amici:
↳:ExpData const*, amici::Model&, bool) + 405
4

```

However, the same logic works, if we use the reduced model. For sufficiently many Newton steps, postequilibration is achieved by Newton's method in the first run. In this specific example, the steady state is found within one step.

```

[7]: # Call postequilibration by setting an infinity timepoint
model_reduced.setTimepoints(np.full(1, np.inf))

# set the solver
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setMaxSteps(100)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced)

print('Status of postequilibration:', rdata_reduced['posteq_status'])
print('Number of steps employed in postequilibration:', rdata_reduced['posteq_numsteps'])

Status of postequilibration: [[1 0 0]]
Number of steps employed in postequilibration: [[2 0 0]]

```

Postequilibration with sensitivities

Equilibration is possible with forward and adjoint sensitivity analysis. As for the main simulation part, adjoint sensitivity analysis yields less information than forward sensitivity analysis, since no state sensitivities are computed. However, it has a better scaling behavior towards large model sizes.

Postequilibration with forward sensitivities

If forward sensitivity analysis is used, then state sensitivities at the timepoint `np.inf` will be computed. This can be done in (currently) two different ways:

1. If the Jacobian $\nabla_x f$ of the right hand side f is not (close to) singular, the most efficient approach will be solving the linear system of equations, which defines the steady state sensitivities:

$$0 = \dot{s}^x = (\nabla_x f) s^x + \frac{\partial f}{\partial \theta} \quad \Rightarrow \quad (\nabla_x f) s^x = -\frac{\partial f}{\partial \theta}$$

This approach will always be chosen by AMICI, if the option `model.SteadyStateSensitivityMode` is set to `SteadyStateSensitivityMode.newtonOnly`. Furthermore, it will also be chosen, if the steady state was found by Newton's method, as in this case, the Jacobian is at least not singular (but may still be poorly conditioned). A check for the condition number of the Jacobian is currently missing, but will soon be implemented.

2. If the Jacobian is poorly conditioned or singular, then the only way to obtain a reliable result will be integrating the state variables with state sensitivities until the norm of the right hand side becomes small. This

approach will be chosen by AMICI, if the steady state was found by simulation and the option `model.SteadyStateSensitivityMode` is set to `SteadyStateSensitivityMode.simulationFSA`. This approach is numerically more stable, but the computation time for large models may be substantial.

Side remark:

A possible third way may consist in a (relaxed) Richardson iteration type approach, which interprets the entries of the right hand side f as residuals and minimizes the squared residuals $\|f\|^2$ by a Levenberg-Marquart-type algorithm. This approach would also work for poorly conditioned (and even for singular Jacobians if additional constraints are implemented as Lagrange multipliers) while being faster than a long forward simulation.

We want to demonstrate both possibilities to find the steady state sensitivities, as well as the failure of their computation if the Jacobian is singular and the `newtonOnly` setting was used.

```
[8]: # Call simulation with singular Jacobian and integrateIfNewtonFails mode
model.setTimepoints(np.full(1, np.inf))
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.
    ↪integrateIfNewtonFails)
solver = model.getSolver()
solver.setNewtonMaxSteps(10)
solver.setSensitivityMethod(amici.SensitivityMethod.forward)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
solver.setMaxSteps(10000)
rdata = amici.runAmiciSimulation(model, solver)

print('Status of postequilibration:', rdata['posteq_status'])
print('Number of steps employed in postequilibration:', rdata['posteq_numsteps'])
print('Computed state sensitivities:')
print(rdata['sx'][0,:,:])
```

```
Status of postequilibration: [[-3  1  0]]
Number of steps employed in postequilibration: [[ 0 1026  0]]
Computed state sensitivities:
[[-1.10000000e-02  0.00000000e+00 -6.70507402e-18 -1.20114408e-11]
 [ 1.00000000e-02  0.00000000e+00 -8.22965063e-19  1.20114329e-11]
 [-1.00000000e-03  0.00000000e+00 -2.00000000e-02 -2.40228711e-11]
 [ 5.50000000e-02  0.00000000e+00  1.00000000e-01  9.99999999e-01]
 [ 0.00000000e+00  0.00000000e+00  0.00000000e+00 -2.00000004e+00]]
```

```
[9]: # Call simulation with singular Jacobian and newtonOnly mode (will fail)
model.setTimepoints(np.full(1, np.inf))
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.newtonOnly)
solver = model.getSolver()
solver.setSensitivityMethod(amici.SensitivityMethod.forward)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
solver.setMaxSteps(10000)
rdata = amici.runAmiciSimulation(model, solver)

print('Status of postequilibration:', rdata['posteq_status'])
print('Number of steps employed in postequilibration:', rdata['posteq_numsteps'])
print('Computed state sensitivities:')
print(rdata['sx'][0,:,:])
```

```
Status of postequilibration: [[-2 -1  1]]
Number of steps employed in postequilibration: [[ 0 543  0]]
Computed state sensitivities:
```

(continues on next page)

(continued from previous page)

```
[[0. 0. 0. 0.]
 [0. 0. 0. 0.]
 [0. 0. 0. 0.]
 [0. 0. 0. 0.]
 [0. 0. 0. 0.]]
```

```
[Warning] AMICI:simulation: AMICI simulation failed:
Steady state sensitivitiy computation failed due to unsuccessful factorization of RHS
↳ Jacobian
Error occured in:
0      0x1060f698b amici::SteadystateProblem::workSteadyStateProblem(amici::Solver*,
↳ amici::Model*, int) + 587
1      0x1060a4615 amici::AmiciApplication::runAmiciSimulation(amici::Solver&, amici:
↳ :ExpData const*, amici::Model&, bool) + 405
2      0x1060a4474 amici::runAmiciSimulation(amici::Solver&, amici::ExpData const*,
↳ amici::Model&, bool) + 36
3      0x106061005 _wrap_runAmiciSimulation(_object*, _object*) + 549
4      0x1021b2309 cfunction_call_varargs + 320
5
```

```
[10]: # Call postequilibration by setting an infinity timepoint
model_reduced.setTimepoints(np.full(1, np.inf))
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.newtonOnly)
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.forward)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
solver_reduced.setMaxSteps(1000)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced)

print('Status of postequilibration:', rdata_reduced['posteq_status'])
print('Number of steps employed in postequilibration:', rdata_reduced['posteq_numsteps'])
print('Computed state sensitivities:')
print(rdata_reduced['sx'][0,:,:])

Status of postequilibration: [[1 0 0]]
Number of steps employed in postequilibration: [[2 0 0]]
Computed state sensitivities:
[[-1.1e-02  0.0e+00 -0.0e+00 -0.0e+00]
 [ 1.0e-02  0.0e+00 -0.0e+00 -0.0e+00]
 [-1.0e-03  0.0e+00 -2.0e-02 -0.0e+00]
 [ 5.5e-02  0.0e+00  1.0e-01  1.0e+00]
 [-0.0e+00  0.0e+00 -0.0e+00 -2.0e+00]]
```

Postequilibration with adjoint sensitivities

Postequilibration also works with adjoint sensitivities. In this case, it is exploited that the ODE of the adjoint state p will always have the steady state 0, since it's a linear ODE:

$$\frac{d}{dt}p(t) = J(x^*, \theta)^T p(t),$$

where x^* denotes the steady state of the system state. Since the Eigenvalues of the Jacobian are negative and since the Jacobian at steady state is a fixed matrix, this system has a simple algebraic solution:

$$p(t) = e^{tJ(x^*, \theta)^T} p_{\text{end}}.$$

As a consequence, the quadratures in adjoint computation also reduce to a matrix-vector product:

$$Q(x, \theta) = Q(x^*, \theta) = p_{\text{integral}} * \frac{\partial f}{\partial \theta}$$

with

$$p_{\text{integral}} = \int_0^\infty p(s) ds = (J(x^*, \theta)^T)^{-1} p_{\text{end}}.$$

However, this solution is given in terms of a linear system of equations defined by the transposed Jacobian of the right hand side. Hence, if the (transposed) Jacobian is singular, it is not applicable. In this case, standard integration must be carried out.

```
[11]: # Call adjoint postequilibration by setting an infinity timepoint
# and create an edata object, which is needed for adjoint computation
edata = amici.ExpData(2, 0, 0, np.array([float('inf')]))
edata.setObservedData([1.8] * 2)
edata.fixedParameters = np.array([3., 5.])

model_reduced.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.newtonOnly)
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
solver_reduced.setMaxSteps(1000)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

print('Status of postequilibration:', rdata_reduced['posteq_status'])
print('Number of steps employed in postequilibration:', rdata_reduced['posteq_numsteps'])
print('Number of backward steps employed in postequilibration:', rdata_reduced['posteq_
    ↳ numstepsB'])
print('Computed gradient:', rdata_reduced['sllh'])

Status of postequilibration: [[1 0 0]]
Number of steps employed in postequilibration: [[2 0 0]]
Number of backward steps employed in postequilibration: 0.0
Computed gradient: [-1.859000e-02  1.690000e-02 -1.690000e-03 -3.16282e+00  1.600000e+01]
```

If we carry out the same computation with a system that has a singular Jacobian, then `posteq_numstepsB` will not be 0 any more (which indicates that the linear system solve was used to compute backward postequilibration). Now, integration is carried out and hence `posteq_numstepsB > 0`

```
[12]: # Call adjoint postequilibration with model with singular Jacobian
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.newtonOnly)
solver = model.getSolver()
solver.setNewtonMaxSteps(10)
solver.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
rdata = amici.runAmiciSimulation(model, solver, edata)

print('Status of postequilibration:', rdata['posteq_status'])
print('Number of steps employed in postequilibration:', rdata['posteq_numsteps'])
print('Number of backward steps employed in postequilibration:', rdata['posteq_numstepsB
↪'])
print('Computed gradient:', rdata['sllh'])

Status of postequilibration: [[-3 -1  1]]
Number of steps employed in postequilibration: [[ 0 479  0]]
Number of backward steps employed in postequilibration: 3076.0
Computed gradient: [-1.85899987e-02  1.68999988e-02 -1.69000055e-03 -3.16282001e+00
1.60000000e+01]
```


Preequilibrating the model

Sometimes, we want to launch a solver run from a steady state which was inferred numerically, i.e., the system was preequilibrated. In order to do this with AMICI, we need to pass an ExpData object, which contains fixed parameter for the actual simulation and for preequilibration of the model.

```
[13]: # create edata, with 3 timepoints and 2 observables:
edata = amici.ExpData(2, 0, 0,
                      np.array([0., 0.1, 1.]))
edata.setObservedData([1.8] * 6)
edata.fixedParameters = np.array([3., 5.])
edata.fixedParametersPreequilibration = np.array([0., 2.])
edata.reinitializeFixedParameterInitialStates = True
```

```
[14]: # create the solver object and run the simulation
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

amici.plotting.plotStateTrajectories(rdata_reduced, model = model_reduced)
amici.plotting.plotObservableTrajectories(rdata_reduced, model = model_reduced)
```



We can also combine pre- and postequilibration.

```
[15]: # Change the last timepoint to an infinity timepoint.
      edata.setTimepoints(np.array([0., 0.1, float('inf')]))

      # run the simulation
      rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)
```


Preequilibration with sensitivities

Beyond the need for an `ExpData` object, the steady state solver logic in preequilibration is the same as in postequilibration, also if sensitivities are requested. The computation will fail for singular Jacobians, if `SteadyStateSensitivityMode` is set to `newtonOnly`, or if not enough steps can be taken. However, if forward simulation with steady state sensitivities is allowed, or if the Jacobian is not singular, it will work.

Prequilibration with forward sensitivities

```
[16]: # No postquilibration this time.
edata.setTimepoints(np.array([0., 0.1, 1.]))

# create the solver object and run the simulation, singular Jacobian, enforce Newton
↳ solver for sensitivities
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.newtonOnly)
solver = model.getSolver()
solver.setNewtonMaxSteps(10)
solver.setSensitivityMethod(amici.SensitivityMethod.forward)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
rdata = amici.runAmiciSimulation(model, solver, edata)

for key, value in rdata.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)

        preeq_wrms: 0.5604257578208488
        preeq_t: 19.2252094591474
preeq_numlinsteps: None
preeq_numsteps: [[ 0 417 0]]
preeq_numstepsB: 0.0
preeq_status: [[-3 1 0]]
preeq_cpu_time: 1.723
preeq_cpu_timeB: 0.0

[Warning] AMICI:simulation: AMICI simulation failed:
Steady state sensitvitiy computation failed due to unsuccessful factorization of RHS
↳ Jacobian
Error occured in:
0      0x1060f698b amici::SteadystateProblem::workSteadyStateProblem(amici::Solver*,
↳ amici::Model*, int) + 587
1      0x1060a456f amici::AmiciApplication::runAmiciSimulation(amici::Solver&, amici:
↳ :ExpData const*, amici::Model&, bool) + 239
2      0x1060a4474 amici::runAmiciSimulation(amici::Solver&, amici::ExpData const*,
↳ amici::Model&, bool) + 36
3      0x106061005 _wrap_runAmiciSimulation(_object*, _object*) + 549
4      0x1021b2309 cfunction_call_varargs + 320
5
```

```
[17]: # Singluar Jacobian, use simulation
model.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.
↳ integrateIfNewtonFails)
solver = model.getSolver()
```

(continues on next page)

(continued from previous page)

```

solver.setNewtonMaxSteps(10)
solver.setSensitivityMethod(amici.SensitivityMethod.forward)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
rdata = amici.runAmiciSimulation(model, solver, edata)

```

```

for key, value in rdata.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)

```

```

        preeq_wrms: 0.9920376238481097
        preeq_t: 21.270502326483026
preeq_numlinsteps: None
        preeq_numsteps: [[ 0 1026 0]]
        preeq_numstepsB: 0.0
        preeq_status: [[-3 1 0]]
        preeq_cpu_time: 12.439
        preeq_cpu_timeB: 0.0

```

[18]: *# Non-singular Jacobian, use Newton solver*

```

solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.forward)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

```

```

for key, value in rdata_reduced.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)

```

```

        preeq_wrms: 0.0
        preeq_t: nan
preeq_numlinsteps: None
        preeq_numsteps: [[2 0 0]]
        preeq_numstepsB: 0.0
        preeq_status: [[1 0 0]]
        preeq_cpu_time: 0.036
        preeq_cpu_timeB: 0.0

```

Preequilibration with adjoint sensitivities

When using preequilibration, adjoint sensitivity analysis can be used for simulation. This is a particularly interesting case: Standard adjoint sensitivity analysis requires the initial state sensitivities `sx0` to work, at least if data is given for finite (i.e., not exclusively postequilibration) timepoints: For each parameter, a contribution to the gradient is given by the scalar product of the corresponding state sensitivity vector at timepoint $t = 0$, (column in `sx0`), with the adjoint state ($p(t = 0)$). Hence, the matrix `sx0` is needed. This scalar product “closes the loop” from forward to adjoint simulation.

By default, if adjoint sensitivity analysis is called with preequilibration, the initial state sensitivities are computed in just the same way as if this way done for forward sensitivity analysis. The only difference in the internal logic is that, if the steady state gets inferred via simulation, a separate solver object is used in order to ensure that the steady state simulation does not interfere with the snapshotting of the forward trajectory from the actual time course.

However, also an adjoint version of preequilibration is possible: In this case, the “loop” from forward to adjoint sim-

ulation needs no closure: The simulation time is extended by preequilibration: forward from $t = -\infty$ to $t = 0$, and after adjoint simulation also backward from $t = 0$ to $t = -\infty$. Similar to adjoint postequilibration, the steady state of the adjoint state (at $t = -\infty$) is $p = 0$, hence the scalar product (at $t = -\infty$) for the initial state sensitivities of preequilibration with the adjoint state vanishes. Instead, this gradient contribution is covered by additional quadratures $\int_{-\infty}^0 p(s) ds \cdot \frac{\partial f}{\partial \theta}$. In order to compute these quadratures correctly, the adjoint state from the main adjoint simulation must be passed on to the initial adjoint state of backward preequilibration.

However, as the adjoint state must be passed on from backward computation to preequilibration, it is currently not allowed to alter (reinitialize) states of the model at $t = 0$, unless these states are constant, as otherwise this alteration would lead to a discontinuity in the adjoints state as well and hence to an incorrect gradient.

```
[19]: # Non-singular Jacobian, use Newton solver and adjoints with initial state sensitivities
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

for key, value in rdata_reduced.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)
print('Gradient:', rdata_reduced['sllh'])
```

```

    preeq_wrms:  0.0
    preeq_t:    nan
    preeq_numlinsteps:  None
    preeq_numsteps:  [[2  0  0]]
    preeq_numstepsB:  0.0
    preeq_status:   [[1  0  0]]
    preeq_cpu_time:  0.039
    preeq_cpu_timeB:  0.0
Gradient: [-0.05528395  0.0461776 -0.03354519 -2.34602219  6.314481  ]
```

```
[20]: # Non-singular Jacobian, use simulation solver and adjoints with initial state_
      ↪sensitivities
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(0)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

for key, value in rdata_reduced.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)
print('Gradient:', rdata_reduced['sllh'])
```

```

    preeq_wrms:  0.8470065245264354
    preeq_t:    19.213162474372176
    preeq_numlinsteps:  None
    preeq_numsteps:  [[  0 426  0]]
    preeq_numstepsB:  0.0
    preeq_status:   [[-2  1  0]]
    preeq_cpu_time:  1.753
    preeq_cpu_timeB:  0.0
Gradient: [-0.05528395  0.0461776 -0.03354519 -2.34602226  6.3144812  ]
```

```
[21]: # Non-singular Jacobian, use Newton solver and adjoints with fully adjoint_
↳preequilibration
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(10)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver_reduced.setSensitivityMethodPreequilibration(amici.SensitivityMethod.adjoint)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)
rdata_reduced = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

for key, value in rdata_reduced.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)
print('Gradient:', rdata_reduced['sllh'])
```

```

    preeq_wrms: 0.0
    preeq_t: nan
    preeq_numlinsteps: None
    preeq_numsteps: [[2 0 0]]
    preeq_numstepsB: 0.0
    preeq_status: [[1 0 0]]
    preeq_cpu_time: 0.042
    preeq_cpu_timeB: 0.009
Gradient: [-0.05528395  0.0461776 -0.03354519 -2.34602219  6.314481  ]
```

As for postquilibration, adjoint preequilibration has an analytic solution (via the linear system), which will be preferred. If used for models with singular Jacobian, numerical integration will be carried out, which is indicated by `preeq_numstepsB`.

```
[22]: # Non-singular Jacobian, use Newton solver and adjoints with fully adjoint_
↳preequilibration
solver = model.getSolver()
solver.setNewtonMaxSteps(10)
solver.setSensitivityMethod(amici.SensitivityMethod.adjoint)
solver.setSensitivityMethodPreequilibration(amici.SensitivityMethod.adjoint)
solver.setSensitivityOrder(amici.SensitivityOrder.first)
rdata = amici.runAmiciSimulation(model, solver, edata)

for key, value in rdata.items():
    if key[0:6] == 'preeq_':
        print('%20s: ' % key, value)
print('Gradient:', rdata['sllh'])
```

```

    preeq_wrms: 0.9986067660342685
    preeq_t: 36.94272314329062
    preeq_numlinsteps: None
    preeq_numsteps: [[ 0 417 0]]
    preeq_numstepsB: 1371.0
    preeq_status: [[-3 1 0]]
    preeq_cpu_time: 2.488
    preeq_cpu_timeB: 5.016
Gradient: [-0.05528395  0.04617759 -0.03354518 -2.34602224  6.3144811  ]
```

Controlling the error tolerances in pre- and postequilibration

When solving ODEs or DAEs, AMICI uses the default logic of CVODES and IDAS to control error tolerances. This means that error weights are computed based on the absolute error tolerances and the product of current state variables of the system and their respective relative error tolerances. If this error combination is then controlled.

The respective tolerances for equilibrating a system with AMICI can be controlled by the user via the getter/setter functions `[get|set][Absolute|Relative]ToleranceSteadyState[Sensi]`:

```
[23]: # Non-singular Jacobian, use simulaiton
model_reduced.setSteadyStateSensitivityMode(amici.SteadyStateSensitivityMode.
↳ integrateIfNewtonFails)
solver_reduced = model_reduced.getSolver()
solver_reduced.setNewtonMaxSteps(0)
solver_reduced.setSensitivityMethod(amici.SensitivityMethod.forward)
solver_reduced.setSensitivityOrder(amici.SensitivityOrder.first)

# run with lax tolerances
solver_reduced.setRelativeToleranceSteadyState(1e-2)
solver_reduced.setAbsoluteToleranceSteadyState(1e-3)
solver_reduced.setRelativeToleranceSteadyStateSensi(1e-2)
solver_reduced.setAbsoluteToleranceSteadyStateSensi(1e-3)
rdata_reduced_lax = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

# run with strict tolerances
solver_reduced.setRelativeToleranceSteadyState(1e-12)
solver_reduced.setAbsoluteToleranceSteadyState(1e-16)
solver_reduced.setRelativeToleranceSteadyStateSensi(1e-12)
solver_reduced.setAbsoluteToleranceSteadyStateSensi(1e-16)
rdata_reduced_strict = amici.runAmiciSimulation(model_reduced, solver_reduced, edata)

# compare ODE outputs
print('\nODE solver steps, which were necessary to reach steady state:')
print('lax tolerances: ', rdata_reduced_lax['preeq_numsteps'])
print('strict tolerances: ', rdata_reduced_strict['preeq_numsteps'])

print('\nsimulation time corresponding to steady state:')
print(rdata_reduced_lax['preeq_t'])
print(rdata_reduced_strict['preeq_t'])

print('\ncomputation time to reach steady state:')
print(rdata_reduced_lax['preeq_cpu_time'])
print(rdata_reduced_strict['preeq_cpu_time'])
```

ODE solver steps, which were necessary to reach steady state:

lax tolerances: [[0 733 0]]

strict tolerances: [[0 1031 0]]

simulation time correpsponding to steady state:

6.002011407974004

31.0689293433781

computation time to reach steady state:

(continues on next page)

(continued from previous page)

```
7.646
7.837
```

10.2.3 Miscellaneous

OpenMP support for parallelized simulation for multiple experimental conditions

AMICI can be built with OpenMP support, which allows to parallelize model simulations for multiple experimental conditions.

On Linux and OSX this is enabled by default. This can be verified using:

```
import amici
amici.compiledWithOpenMP()
```

If not already enabled by default, you can enable OpenMP support by setting the environment variables `AMICI_CXXFLAGS` and `AMICI_LDFLAGS` to the correct OpenMP flags of your compiler and linker, respectively. This has to be done for both AMICI package installation *and* model compilation. When using gcc on Linux, this would be:

```
# on your shell:
AMICI_CXXFLAGS=-fopenmp AMICI_LDFLAGS=-fopenmp pip3 install amici
```

```
# in python, before model compilation:
import os
os.environ['AMICI_CXXFLAGS'] = '-fopenmp'
os.environ['AMICI_LDFLAGS'] = '-fopenmp'
```

10.3 FAQ

Q: I am trying to install the AMICI Python package, but installation fails with something like

```
amici/src/cblas.cpp:16:13: fatal error: cblas.h: No such file or directory
#include <cblas.h>
          ^~~~~~
compilation terminated.
error: command 'x86_64-linux-gnu-gcc' failed with exit status 1
```

A: You will have to install a CBLAS-compatible BLAS library and/or set `BLAS_CFLAGS` as described in the [installation guide](#).

Q: Importing my model fails with something like `ImportError: _someModelName.cpython-37m-x86_64-linux-gnu.so: undefined symbol: omp_get_thread_num`.

A: You probably installed the AMICI package with OpenMP support, but did not have the relevant compiler/linker flags set when importing/building the model. See [here](#).

10.4 AMICI Python API

Modules

<code>amici</code>	AMICI
<code>amici.amici</code>	Core C++ bindings This module encompasses the complete public C++ API of AMICI, which was exposed via swig. All functions listed here are directly accessible in the main amici package, i.e., <code>amici.amici.ExpData</code> is available as <code>amici.ExpData</code> . Usage of functions and classes from the base amici package is generally recommended as they often include convenience wrappers that avoid common pitfalls when accessing C++ types from python and implement some nonstandard type conversions.
<code>amici.sbml_import</code>	SBML Import This module provides all necessary functionality to import a model specified in the Systems Biology Markup Language (SBML).
<code>amici.pysb_import</code>	PySB Import This module provides all necessary functionality to import a model specified in the <code>pysb.core.Model</code> format.
<code>amici.bngl_import</code>	BNGL Import This module provides all necessary functionality to import a model specified in the BNGL format.
<code>amici.petab_import</code>	PETab Import Import a model in the petab (https://github.com/PETab-dev/PETab) format into AMICI.
<code>amici.petab_import_pysb</code>	PySB-PETab Import Import a model in the PySB-adapted petab (https://github.com/PETab-dev/PETab) format into AMICI.
<code>amici.petab_objective</code>	PETab Objective Functionality related to running simulations or evaluating the objective function as defined by a PETab problem
<code>amici.petab_simulate</code>	PETab Simulate Functionality related to the use of AMICI for simulation with PETab's Simulator class.
<code>amici.import_utils</code>	Miscellaneous functions related to model import, independent of any specific model format
<code>amici.ode_export</code>	C++ Export This module provides all necessary functionality specify an ODE model and generate executable C++ simulation code. The user generally won't have to directly call any function from this module as this will be done by <code>amici.pysb_import.pysb2amici()</code> , <code>amici.sbml_import.SbmlImporter.sbml2amici()</code> and <code>amici.petab_import.import_model()</code> .
<code>amici.ode_model</code>	Objects for AMICI's internal ODE model representation
<code>amici.plotting</code>	Plotting Plotting related functions

continues on next page

Table 1 – continued from previous page

<i>amici.pandas</i>	Pandas Wrappers This module contains convenience wrappers that allow for easy interconversion between C++ objects from amici.amici and pandas DataFrames
<i>amici.logging</i>	Logging This module provides custom logging functionality for other amici modules
<i>amici.gradient_check</i>	Finite Difference Check This module provides functions to automatically check correctness of amici computed sensitivities using finite difference approximations
<i>amici.parameter_mapping</i>	Parameter mapping
<i>amici.conserverved_quantities_demartino</i>	
<i>amici.conserverved_quantities_rref</i>	Find conserved quantities deterministically

10.4.1 amici

AMICI

The AMICI Python module provides functionality for importing SBML or PySB models and turning them into C++ Python extensions.

var amici_path absolute root path of the amici repository or Python package

var amiciSwigPath absolute path of the amici swig directory

var amiciSrcPath absolute path of the amici source directory

var amiciModulePath absolute root path of the amici module

var hdf5_enabled boolean indicating if amici was compiled with hdf5 support

var has_clibs boolean indicating if this is the full package with swig interface or the raw package without

Classes

<i>ModelModule</i> (*args, **kwargs)	Enable Python static type checking for AMICI-generated model modules
<i>add_path</i> (path)	Context manager for temporarily changing PYTHON-PATH

amici.ModelModule

```
class amici.ModelModule(*args, **kwargs)
    Enable Python static type checking for AMICI-generated model modules
    __init__(*args, **kwargs)
```

Methods Summary

```
__init__(*args, **kwargs)
```

```
getModel()
```

rtype `amici.amici.Model`

Methods

```
__init__(*args, **kwargs)
```

```
getModel()
```

Return type `amici.amici.Model`

amici.add_path

```
class amici.add_path(path)
    Context manager for temporarily changing PYTHONPATH
    __init__(path)
```

Methods Summary

```
__init__(path)
```

Methods

```
__init__(path)
```

Functions Summary

<code>import_model_module(module_name[, ule_path])</code>	mod-	Import Python module of an AMICI model
---------------------------------------------------------------	------	----------------------------------------

Functions

`amici.import_model_module(module_name, module_path=None)`
Import Python module of an AMICI model

Parameters

- **module_name** (`str`) – Name of the python package of the model
- **module_path** (`typing.Optional[str]`) – Absolute or relative path of the package directory

Return type `amici.ModelModule`

Returns The model module

10.4.2 amici.amici

Core C++ bindings

This module encompasses the complete public C++ API of AMICI, which was exposed via swig. All functions listed here are directly accessible in the main amici package, i.e., `amici.amici.ExpData` is available as `amici.ExpData`. Usage of functions and classes from the base amici package is generally recommended as they often include convenience wrappers that avoid common pitfalls when accessing C++ types from python and implement some nonstandard type conversions.

Classes

<code>BoolVector(*args)</code>	Swig-Generated class templating common python types including Iterable [<code>bool</code>] and <code>numpy.array [bool]</code> to facilitate interfacing with C++ bindings.
<code>DoubleVector(*args)</code>	Swig-Generated class templating common python types including Iterable [<code>float</code>] and <code>numpy.array [float]</code> to facilitate interfacing with C++ bindings.
<code>ExpData(*args)</code>	ExpData carries all information about experimental or condition-specific data
<code>ExpDataPtr(*args)</code>	Swig-Generated class that implements smart pointers to ExpData as objects.
<code>ExpDataPtrVector(*args)</code>	Swig-Generated class templating common python types including Iterable [<code>amici.amici.ExpData</code>] and <code>numpy.array [amici.amici.ExpData]</code> to facilitate interfacing with C++ bindings.
<code>FixedParameterContext(value)</code>	An enumeration.
<code>IntVector(*args)</code>	Swig-Generated class templating common python types including Iterable [<code>int</code>] and <code>numpy.array [int]</code> to facilitate interfacing with C++ bindings.

continues on next page

Table 6 – continued from previous page

<i>InternalSensitivityMethod</i> (value)	An enumeration.
<i>InterpolationType</i> (value)	An enumeration.
<i>LinearMultistepMethod</i> (value)	An enumeration.
<i>LinearSolver</i> (value)	An enumeration.
<i>Model</i> (*args, **kwargs)	The Model class represents an AMICI ODE/DAE model.
<i>ModelDimensions</i> (*args)	Container for model dimensions.
<i>ModelPtr</i> (*args)	Swig-Generated class that implements smart pointers to Model as objects.
<i>NewtonDampingFactorMode</i> (value)	An enumeration.
<i>NonlinearSolverIteration</i> (value)	An enumeration.
<i>ObservableScaling</i> (value)	An enumeration.
<i>ParameterScaling</i> (value)	An enumeration.
<i>ParameterScalingVector</i> (*args)	
<i>RDataReporting</i> (value)	An enumeration.
<i>ReturnData</i> (*args)	Stores all data to be returned by <code>amici.amici.runAmiciSimulation()</code> .
<i>ReturnDataPtr</i> (*args)	Swig-Generated class that implements smart pointers to ReturnData as objects.
<i>SecondOrderMode</i> (value)	An enumeration.
<i>SensitivityMethod</i> (value)	An enumeration.
<i>SensitivityOrder</i> (value)	An enumeration.
<i>SimulationParameters</i> (*args)	Container for various simulation parameters.
<i>Solver</i> (*args, **kwargs)	The Solver class provides a generic interface to CVODES and IDAS solvers, individual realizations are realized in the CNodeSolver and the IDASolver class.
<i>SolverPtr</i> (*args)	Swig-Generated class that implements smart pointers to Solver as objects.
<i>SteadyStateSensitivityMode</i> (value)	An enumeration.
<i>SteadyStateStatus</i> (value)	An enumeration.
<i>SteadyStateStatusVector</i> (*args)	
<i>StringDoubleMap</i> (*args)	Swig-Generated class templating Dict [<code>str</code> , <code>float</code>] to facilitate interfacing with C++ bindings.
<i>StringVector</i> (*args)	Swig-Generated class templating common python types including Iterable [<code>str</code>] and <code>numpy.array</code> [<code>str</code>] to facilitate interfacing with C++ bindings.

amici.amici.BoolVector

class `amici.amici.BoolVector(*args)`

Swig-Generated class templating common python types including Iterable [`bool`] and `numpy.array` [`bool`] to facilitate interfacing with C++ bindings.

amici.amici.DoubleVector

```
class amici.amici.DoubleVector(*args)
```

Swig-Generated class templating common python types including `Iterable [float]` and `numpy.array [float]` to facilitate interfacing with C++ bindings.

amici.amici.ExpData

```
class amici.amici.ExpData(*args)
```

ExpData carries all information about experimental or condition-specific data

```
__init__(*args)
```

Overload 1:

default constructor

Overload 2:

Copy constructor, needs to be declared to be generated in swig

Overload 3:

constructor that only initializes dimensions

Parameters

- **nytrue** (*int*) – Number of observables
- **nztrue** (*int*) – Number of event outputs
- **nmaxevent** (*int*) – Maximal number of events to track

Overload 4:

constructor that initializes timepoints from vectors

Parameters

- **nytrue** (*int*) – Number of observables
- **nztrue** (*int*) – Number of event outputs
- **nmaxevent** (*int*) – Maximal number of events to track
- **ts** (**DoubleVector**) – Timepoints (dimension: nt)

Overload 5:

constructor that initializes timepoints and fixed parameters from vectors

Parameters

- **nytrue** (*int*) – Number of observables
- **nztrue** (*int*) – Number of event outputs
- **nmaxevent** (*int*) – Maximal number of events to track
- **ts** (*DoubleVector*) – Timepoints (dimension: nt)
- **fixedParameters** (*DoubleVector*) – Model constants (dimension: nk)

Overload 6:

constructor that initializes timepoints and data from vectors

Parameters

- **nytrue** (*int*) – Number of observables
- **nztrue** (*int*) – Number of event outputs
- **nmaxevent** (*int*) – Maximal number of events to track
- **ts** (*DoubleVector*) – Timepoints (dimension: nt)
- **observedData** (*DoubleVector*) – observed data (dimension: nt x nytrue, row-major)
- **observedDataStdDev** (*DoubleVector*) – standard deviation of observed data (dimension: nt x nytrue, row-major)
- **observedEvents** (*DoubleVector*) – observed events (dimension: nmaxevents x nztrue, row-major)
- **observedEventsStdDev** (*DoubleVector*) – standard deviation of observed events/roots (dimension: nmaxevents x nztrue, row-major)

Overload 7:

constructor that initializes with Model

Parameters **model** (*Model*) – pointer to model specification object

Overload 8:

constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** (*ReturnData*) – return data pointer with stored simulation results
- **sigma_y** (*float*) – scalar standard deviations for all observables
- **sigma_z** (*float*) – scalar standard deviations for all event observables

Overload 9:

constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** (*ReturnData*) – return data pointer with stored simulation results
- **sigma_y** (*DoubleVector*) – vector of standard deviations for observables (dimension: nytrue or nt x nytrue, row-major)
- **sigma_z** (*DoubleVector*) – vector of standard deviations for event observables (dimension: nztrue or nmaxevent x nztrue, row-major)

Methods Summary

<code>__init__(*args)</code>	<i>Overload 1:</i>
<code>getObservedData()</code>	get function that copies data from ExpData::observedData to output
<code>getObservedDataPtr(it)</code>	get function that returns a pointer to observed data at index
<code>getObservedDataStdDev()</code>	get function that copies data from ExpData::observedDataStdDev to output
<code>getObservedDataStdDevPtr(it)</code>	get function that returns a pointer to standard deviation of observed data at index
<code>getObservedEvents()</code>	get function that copies data from ExpData::mz to output
<code>getObservedEventsPtr(ie)</code>	get function that returns a pointer to observed data at ieth occurrence
<code>getObservedEventsStdDev()</code>	get function that copies data from ExpData::observedEventsStdDev to output
<code>getObservedEventsStdDevPtr(ie)</code>	get function that returns a pointer to standard deviation of observed event data at ie-th occurrence
<code>getTimepoint(it)</code>	get function that returns timepoint at index
<code>getTimepoints()</code>	get function that copies data from ExpData::ts to output
<code>isSetObservedData(it, iy)</code>	get function that checks whether data at specified indices has been set
<code>isSetObservedDataStdDev(it, iy)</code>	get function that checks whether standard deviation of data at specified indices has been set
<code>isSetObservedEvents(ie, iz)</code>	get function that checks whether event data at specified indices has been set
<code>isSetObservedEventsStdDev(ie, iz)</code>	get function that checks whether standard deviation of even data at specified indices has been set

continues on next page

Table 7 – continued from previous page

<code>nmaxevent()</code>	maximal number of events to track
<code>nt()</code>	number of timepoints
<code>nytrue()</code>	number of observables of the non-augmented model
<code>nztrue()</code>	number of event observables of the non-augmented model
<code>reinitializeAllFixedParameterDependentInitialStates()</code>	Set reinitialization of all states based on model constants for all simulation phases.
<code>reinitializeAllFixedParameterDependentInitialStatesPresim()</code>	Set reinitialization of all states based on model constants for presimulation (only meaningful if preequilibration is performed).
<code>reinitializeAllFixedParameterDependentInitialStatesMain()</code>	Set reinitialization of all states based on model constants for the 'main' simulation (only meaningful if presimulation or preequilibration is performed).
<code>setObservedData(*args)</code>	<i>Overload 1:</i>
<code>setObservedDataStdDev(*args)</code>	<i>Overload 1:</i>
<code>setObservedEvents(*args)</code>	<i>Overload 1:</i>
<code>setObservedEventsStdDev(*args)</code>	<i>Overload 1:</i>
<code>setTimepoints(ts)</code>	Set function that copies data from input to <code>ExpData::ts</code>

Attributes

<code>fixedParameters</code>	Model constants
<code>fixedParametersPreequilibration</code>	Model constants for pre-equilibration
<code>fixedParametersPresimulation</code>	Model constants for pre-simulation
<code>id</code>	Arbitrary (not necessarily unique) identifier.
<code>parameters</code>	Model parameters
<code>plist</code>	Parameter indices w.r.t.
<code>pscale</code>	Parameter scales
<code>reinitialization_state_idxes_presim</code>	Indices of states to be reinitialized based on provided presimulation constants / fixed parameters.
<code>reinitialization_state_idxes_sim</code>	Indices of states to be reinitialized based on provided constants / fixed parameters.
<code>reinitializeFixedParameterInitialStates</code>	Flag indicating whether reinitialization of states depending on fixed parameters is activated
<code>sx0</code>	Initial state sensitivities
<code>t_presim</code>	Duration of pre-simulation.
<code>ts_</code>	Timepoints for which model state/outputs/.
<code>tstart_</code>	starting time
<code>x0</code>	Initial state

Methods

`__init__`(**args*)

Overload 1:

default constructor

Overload 2:

Copy constructor, needs to be declared to be generated in swig

Overload 3:

constructor that only initializes dimensions

Parameters

- **`nytrue`** (*int*) – Number of observables
- **`nztrue`** (*int*) – Number of event outputs
- **`nmaxevent`** (*int*) – Maximal number of events to track

Overload 4:

constructor that initializes timepoints from vectors

Parameters

- **`nytrue`** (*int*) – Number of observables
- **`nztrue`** (*int*) – Number of event outputs
- **`nmaxevent`** (*int*) – Maximal number of events to track
- **`ts`** (*DoubleVector*) – Timepoints (dimension: nt)

Overload 5:

constructor that initializes timepoints and fixed parameters from vectors

Parameters

- **`nytrue`** (*int*) – Number of observables
- **`nztrue`** (*int*) – Number of event outputs

- **nmaxevent** (*int*) – Maximal number of events to track
- **ts** (*DoubleVector*) – Timepoints (dimension: nt)
- **fixedParameters** (*DoubleVector*) – Model constants (dimension: nk)

Overload 6:

constructor that initializes timepoints and data from vectors

Parameters

- **nytrue** (*int*) – Number of observables
- **nztrue** (*int*) – Number of event outputs
- **nmaxevent** (*int*) – Maximal number of events to track
- **ts** (*DoubleVector*) – Timepoints (dimension: nt)
- **observedData** (*DoubleVector*) – observed data (dimension: nt x nytrue, row-major)
- **observedDataStdDev** (*DoubleVector*) – standard deviation of observed data (dimension: nt x nytrue, row-major)
- **observedEvents** (*DoubleVector*) – observed events (dimension: nmaxevents x nztrue, row-major)
- **observedEventsStdDev** (*DoubleVector*) – standard deviation of observed events/roots (dimension: nmaxevents x nztrue, row-major)

Overload 7:

constructor that initializes with Model

Parameters **model** (*Model*) – pointer to model specification object

Overload 8:

constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** (*ReturnData*) – return data pointer with stored simulation results
- **sigma_y** (*float*) – scalar standard deviations for all observables
- **sigma_z** (*float*) – scalar standard deviations for all event observables

Overload 9:

constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** (*ReturnData*) – return data pointer with stored simulation results
- **sigma_y** (*DoubleVector*) – vector of standard deviations for observables (dimension: nytrue or nt x nytrue, row-major)
- **sigma_z** (*DoubleVector*) – vector of standard deviations for event observables (dimension: nztrue or nmaxevent x nztrue, row-major)

getObservedData() → *amici.amici.DoubleVector*

get function that copies data from ExpData::observedData to output

Return type *DoubleVector*

Returns observed data (dimension: nt x nytrue, row-major)

getObservedDataPtr(it: int) → Iterable[float]

get function that returns a pointer to observed data at index

Parameters **it** (int) – timepoint index

Return type float

Returns pointer to observed data at index (dimension: nytrue)

getObservedDataStdDev() → *amici.amici.DoubleVector*

get function that copies data from ExpData::observedDataStdDev to output

Return type *DoubleVector*

Returns standard deviation of observed data

getObservedDataStdDevPtr(it: int) → Iterable[float]

get function that returns a pointer to standard deviation of observed data at index

Parameters **it** (int) – timepoint index

Return type float

Returns pointer to standard deviation of observed data at index

getObservedEvents() → *amici.amici.DoubleVector*

get function that copies data from ExpData::mz to output

Return type *DoubleVector*

Returns observed event data

getObservedEventsPtr(ie: int) → Iterable[float]

get function that returns a pointer to observed data at ieth occurrence

Parameters **ie** (int) – event occurrence

Return type float

Returns pointer to observed event data at ieth occurrence

getObservedEventsStdDev() → *amici.amici.DoubleVector*

get function that copies data from ExpData::observedEventsStdDev to output

Return type *DoubleVector*

Returns standard deviation of observed event data

getObservedEventsStdDevPtr(*ie*: *int*) → Iterable[float]

get function that returns a pointer to standard deviation of observed event data at ie-th occurrence

Parameters *ie* (*int*) – event occurrence

Return type float

Returns pointer to standard deviation of observed event data at ie-th occurrence

getTimepoint(*it*: *int*) → float

get function that returns timepoint at index

Parameters *it* (*int*) – timepoint index

Return type float

Returns timepoint timepoint at index

getTimepoints() → *amici.amici.DoubleVector*

get function that copies data from ExpData::ts to output

Return type *DoubleVector*

Returns ExpData::ts

isSetObservedData(*it*: *int*, *iy*: *int*) → bool

get function that checks whether data at specified indices has been set

Parameters

- *it* (*int*) – time index
- *iy* (*int*) – observable index

Return type boolean

Returns boolean specifying if data was set

isSetObservedDataStdDev(*it*: *int*, *iy*: *int*) → bool

get function that checks whether standard deviation of data at specified indices has been set

Parameters

- *it* (*int*) – time index
- *iy* (*int*) – observable index

Return type boolean

Returns boolean specifying if standard deviation of data was set

isSetObservedEvents(*ie*: *int*, *iz*: *int*) → bool

get function that checks whether event data at specified indices has been set

Parameters

- *ie* (*int*) – event index
- *iz* (*int*) – event observable index

Return type boolean

Returns boolean specifying if data was set

isSetObservedEventsStdDev(*ie*: *int*, *iz*: *int*) → bool

get function that checks whether standard deviation of even data at specified indices has been set

Parameters

- **ie** (*int*) – event index
- **iz** (*int*) – event observable index

Return type *boolean*

Returns *boolean* specifying if standard deviation of event data was set

nmaxevent() → *int*

maximal number of events to track

Return type *int*

Returns maximal number of events to track

nt() → *int*

number of timepoints

Return type *int*

Returns number of timepoints

nytrue() → *int*

number of observables of the non-augmented model

Return type *int*

Returns number of observables of the non-augmented model

nztrue() → *int*

number of event observables of the non-augmented model

Return type *int*

Returns number of event observables of the non-augmented model

reinitializeAllFixedParameterDependentInitialStates(*nx_rdata: int*) → *None*

Set reinitialization of all states based on model constants for all simulation phases.

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters *nx_rdata* (*int*) – Number of states (Model::nx_rdata)

Return type *None*

reinitializeAllFixedParameterDependentInitialStatesForPresimulation(*nx_rdata: int*) → *None*

Set reinitialization of all states based on model constants for presimulation (only meaningful if preequilibration is performed).

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters *nx_rdata* (*int*) – Number of states (Model::nx_rdata)

Return type *None*

reinitializeAllFixedParameterDependentInitialStatesForSimulation(*nx_rdata: int*) → *None*

Set reinitialization of all states based on model constants for the ‘main’ simulation (only meaningful if presimulation or preequilibration is performed).

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters *nx_rdata* (*int*) – Number of states (Model::nx_rdata)

Return type *None*

setObservedData(*args) → `None`

Overload 1:

set function that copies data from input to `ExpData::my`

Parameters **observedData** (`DoubleVector`) – observed data (dimension: `nt` x `nytrue`, row-major)

Overload 2:

set function that copies observed data for specific observable

Parameters

- **observedData** (`DoubleVector`) – observed data (dimension: `nt`)
- **iy** (`int`) – observed data index

Return type `None`

setObservedDataStdDev(*args) → `None`

Overload 1:

set function that copies data from input to `ExpData::observedDataStdDev`

Parameters **observedDataStdDev** (`DoubleVector`) – standard deviation of observed data (dimension: `nt` x `nytrue`, row-major)

Overload 2:

set function that sets all `ExpData::observedDataStdDev` to the input value

Parameters **stdDev** (`float`) – standard deviation (dimension: scalar)

Overload 3:

set function that copies standard deviation of observed data for specific observable

Parameters

- **observedDataStdDev** (`DoubleVector`) – standard deviation of observed data (dimension: `nt`)
- **iy** (`int`) – observed data index

Overload 4:

set function that sets all standard deviation of a specific observable to the input value

Parameters

- **stdDev** (*float*) – standard deviation (dimension: scalar)
- **iy** (*int*) – observed data index

Return type *None*

setObservedEvents(*args) → *None*

Overload 1:

set function that copies observed event data from input to ExpData::observedEvents

Parameters **observedEvents** (*DoubleVector*) – observed data (dimension: nmaxevent x nztrue, row-major)

Overload 2:

set function that copies observed event data for specific event observable

Parameters

- **observedEvents** (*DoubleVector*) – observed data (dimension: nmaxevent)
- **iz** (*int*) – observed event data index

Return type *None*

setObservedEventsStdDev(*args) → *None*

Overload 1:

set function that copies data from input to ExpData::observedEventsStdDev

Parameters **observedEventsStdDev** (*DoubleVector*) – standard deviation of observed event data

Overload 2:

set function that sets all ExpData::observedDataStdDev to the input value

Parameters **stdDev** (*float*) – standard deviation (dimension: scalar)

Overload 3:

set function that copies standard deviation of observed data for specific observable

Parameters

- **observedEventsStdDev** ([DoubleVector](#)) – standard deviation of observed data (dimension: nmaxevent)
- **iz** ([int](#)) – observed data index

Overload 4:

set function that sets all standard deviation of a specific observable to the input value

Parameters

- **stdDev** ([float](#)) – standard deviation (dimension: scalar)
- **iz** ([int](#)) – observed data index

Return type [None](#)

setTimepoints(*ts*: [amici.amici.DoubleVector](#)) → [None](#)

Set function that copies data from input to ExpData::ts

Parameters **ts** ([amici.amici.DoubleVector](#)) – timepoints

Return type [None](#)

amici.amici.ExpDataPtr

class `amici.amici.ExpDataPtr(*args)`

Swig-Generated class that implements smart pointers to ExpData as objects.

Attributes

<code>fixedParameters</code>	Model constants
<code>fixedParametersPreequilibration</code>	Model constants for pre-equilibration
<code>fixedParametersPresimulation</code>	Model constants for pre-simulation
<code>id</code>	Arbitrary (not necessarily unique) identifier.
<code>parameters</code>	Model parameters
<code>plist</code>	Parameter indices w.r.t.
<code>pscale</code>	Parameter scales
<code>reinitialization_state_idxes_presim</code>	Indices of states to be reinitialized based on provided presimulation constants / fixed parameters.
<code>reinitialization_state_idxes_sim</code>	Indices of states to be reinitialized based on provided constants / fixed parameters.
<code>reinitializeFixedParameterInitialStates</code>	Flag indicating whether reinitialization of states depending on fixed parameters is activated
<code>sx0</code>	Initial state sensitivities
<code>t_presim</code>	Duration of pre-simulation.
<code>ts_</code>	Timepoints for which model state/outputs/.
<code>tstart_</code>	starting time
<code>x0</code>	Initial state

amici.amici.ExpDataPtrVector**class** amici.amici.ExpDataPtrVector(*args)

Swig-Generated class templating common python types including Iterable [[amici.amici.ExpData](#)] and `numpy.array` [[amici.amici.ExpData](#)] to facilitate interfacing with C++ bindings.

amici.amici.FixedParameterContext**class** amici.amici.FixedParameterContext(value)

An enumeration.

Attributes

simulation

preequilibration

presimulation

amici.amici.IntVector**class** amici.amici.IntVector(*args)

Swig-Generated class templating common python types including Iterable [[int](#)] and `numpy.array` [[int](#)] to facilitate interfacing with C++ bindings.

amici.amici.InternalSensitivityMethod**class** amici.amici.InternalSensitivityMethod(value)

An enumeration.

Attributes

simultaneous

staggered

staggered1

amici.amici.InterpolationType

class amici.amici.**InterpolationType**(*value*)
An enumeration.

Attributes

hermite

polynomial

amici.amici.LinearMultistepMethod

class amici.amici.**LinearMultistepMethod**(*value*)
An enumeration.

Attributes

adams

BDF

amici.amici.LinearSolver

class amici.amici.**LinearSolver**(*value*)
An enumeration.

Attributes

dense

band

LAPACKDense

LAPACKBand

diag

SPGMR

SPBCG

continues on next page

Table 14 – continued from previous page

SPTFQMR
KLU
SuperLUMT

amici.amici.Model

class amici.amici.**Model**(*args, **kwargs)

The Model class represents an AMICI ODE/DAE model.

The model can compute various model related quantities based on symbolically generated code.

__init__(*args, **kwargs)

Overload 1: Default ctor

Overload 2:

Constructor with model dimensions

Parameters

- **nx_rdata** (*int*) – Number of state variables
- **nxtrue_rdata** (*int*) – Number of state variables of the non-augmented model
- **nx_solver** (*int*) – Number of state variables with conservation laws applied
- **nxtrue_solver** (*int*) – Number of state variables of the non-augmented model with conservation laws applied
- **nx_solver_reinit** (*int*) – Number of state variables with conservation laws subject to reinitialization
- **np** (*int*) – Number of parameters
- **nk** (*int*) – Number of constants
- **ny** (*int*) – Number of observables
- **nytrue** (*int*) – Number of observables of the non-augmented model
- **nz** (*int*) – Number of event observables
- **nztrue** (*int*) – Number of event observables of the non-augmented model
- **ne** (*int*) – Number of events
- **nJ** (*int*) – Number of objective functions
- **nw** (*int*) – Number of repeating elements
- **ndwdx** (*int*) – Number of nonzero elements in the x derivative of the repeating elements
- **ndwdp** (*int*) – Number of nonzero elements in the p derivative of the repeating elements

- **ndwdw** (*int*) – Number of nonzero elements in the w derivative of the repeating elements
- **ndxdotdw** (*int*) – Number of nonzero elements in the w derivative of x_{dot}
- **ndJydy** (*IntVector*) – Number of nonzero elements in the y derivative of dJy (shape *nytrue*)
- **ndxrdatadxsolver** (*int*) – Number of nonzero elements in the x derivative of x_rdata
- **ndxrdatadtcl** (*int*) – Number of nonzero elements in the tcl derivative of x_rdata
- **ndtotal_cldx_rdata** (*int*) – Number of nonzero elements in the x_rdata derivative of $total_{cl}$
- **nnz** (*int*) – Number of nonzero elements in Jacobian
- **ubw** (*int*) – Upper matrix bandwidth in the Jacobian
- **lbw** (*int*) – Lower matrix bandwidth in the Jacobian

Methods Summary

<code>__init__(*args, **kwargs)</code>	<i>Overload 1:</i>
<code>clone()</code>	Clone this instance.
<code>fdsigmaydy(dsigmaydy, t, p, k, y)</code>	Model-specific implementation of fsigmay
<code>fdtotal_cldp(dttotal_cldp, x_rdata, p, k, ip)</code>	Compute $dtotal_{cl} / dp$
<code>fdtotal_cldx_rdata(dttotal_cldx_rdata, ...)</code>	Compute $dtotal_{cl} / dx_rdata$
<code>fdx_rdatadp(dx_rdatadp, x, tcl, p, k, ip)</code>	Compute dx_rdata / dp
<code>fdx_rdatadtcl(dx_rdatadtcl, x, tcl, p, k)</code>	Compute $dx_rdata / dtcl$
<code>fdx_rdatadx_solver(dx_rdatadx_solver, x, ...)</code>	Compute dx_rdata / dx_{solver}
<code>getAddSigmaResiduals()</code>	Checks whether residuals should be added to account for parameter dependent sigma.
<code>getAlwaysCheckFinite()</code>	Get setting of whether the result of every call to <i>Model::f*</i> should be checked for finiteness.
<code>getAmiciCommit()</code>	Returns the AMICI commit that was used to generate the model
<code>getAmiciVersion()</code>	Returns the AMICI version that was used to generate the model
<code>getExpressionIds()</code>	Get IDs of the expression.
<code>getExpressionNames()</code>	Get names of the expressions.
<code>getFixedParameterById(par_id)</code>	Get value of fixed parameter with the specified ID.
<code>getFixedParameterByName(par_name)</code>	Get value of fixed parameter with the specified name.
<code>getFixedParameterIds()</code>	Get IDs of the fixed model parameters.
<code>getFixedParameterNames()</code>	Get names of the fixed model parameters.
<code>getFixedParameters()</code>	Get values of fixed parameters.
<code>getInitialStateSensitivities()</code>	Get the initial states sensitivities.
<code>getInitialStates()</code>	Get the initial states.
<code>getMinimumSigmaResiduals()</code>	Gets the specified estimated lower boundary for σ_y .
<code>getName()</code>	Get the model name.
<code>getObservableIds()</code>	Get IDs of the observables.
<code>getObservableNames()</code>	Get names of the observables.
<code>getObservableScaling(iy)</code>	Get scaling type for observable
<code>getParameterById(par_id)</code>	Get value of first model parameter with the specified ID.

continues on next page

Table 15 – continued from previous page

<code>getParameterByName(par_name)</code>	Get value of first model parameter with the specified name.
<code>getParameterIds()</code>	Get IDs of the model parameters.
<code>getParameterList()</code>	Get the list of parameters for which sensitivities are computed.
<code>getParameterNames()</code>	Get names of the model parameters.
<code>getParameterScale()</code>	Get parameter scale for each parameter.
<code>getParameters()</code>	Get parameter vector.
<code>getReinitializationStateIdxs()</code>	Return indices of states to be reinitialized based on provided constants / fixed parameters
<code>getReinitializeFixedParameterInitialStates()</code>	Get whether initial states depending on fixed parameters are to be reinitialized after preequilibration and presimulation.
<code>getSolver()</code>	Retrieves the solver object
<code>getStateIds()</code>	Get IDs of the model states.
<code>getStateIdsSolver()</code>	Get IDs of the solver states.
<code>getStateIsNonNegative()</code>	Get flags indicating whether states should be treated as non-negative.
<code>getStateNames()</code>	Get names of the model states.
<code>getStateNamesSolver()</code>	Get names of the solver states.
<code>getSteadyStateSensitivityMode()</code>	Gets the mode how sensitivities are computed in the steadystate simulation.
<code>getTimepoint(it)</code>	Get simulation timepoint for time index <i>it</i> .
<code>getTimepoints()</code>	Get the timepoint vector.
<code>getUnscaledParameters()</code>	Get parameters with transformation according to parameter scale applied.
<code>hasCustomInitialStateSensitivities()</code>	Return whether custom initial state sensitivities have been set.
<code>hasCustomInitialStates()</code>	Return whether custom initial states have been set.
<code>hasExpressionIds()</code>	Report whether the model has expression IDs set.
<code>hasExpressionNames()</code>	Report whether the model has expression names set.
<code>hasFixedParameterIds()</code>	Report whether the model has fixed parameter IDs set.
<code>hasFixedParameterNames()</code>	Report whether the model has fixed parameter names set.
<code>hasObservableIds()</code>	Report whether the model has observable IDs set.
<code>hasObservableNames()</code>	Report whether the model has observable names set.
<code>hasParameterIds()</code>	Report whether the model has parameter IDs set.
<code>hasParameterNames()</code>	Report whether the model has parameter names set.
<code>hasQuadraticLLH()</code>	Checks whether the defined noise model is gaussian, i.e., the nllh is quadratic
<code>hasStateIds()</code>	Report whether the model has state IDs set.
<code>hasStateNames()</code>	Report whether the model has state names set.
<code>isFixedParameterStateReinitializationAllowed()</code>	Function indicating whether reinitialization of states depending on fixed parameters is permissible
<code>k()</code>	Get fixed parameters.
<code>nMaxEvent()</code>	Get maximum number of events that may occur for each type.
<code>ncl()</code>	Get number of conservation laws.
<code>nk()</code>	Get number of constants
<code>np()</code>	Get total number of model parameters.

continues on next page

Table 15 – continued from previous page

<code>nplist()</code>	Get number of parameters wrt to which sensitivities are computed.
<code>nt()</code>	Get number of timepoints.
<code>nx_reinit()</code>	Get number of solver states subject to reinitialization.
<code>plist(pos)</code>	Get entry in parameter list by index.
<code>requireSensitivitiesForAllParameters()</code>	Require computation of sensitivities for all parameters p $[0..np[$ in natural order.
<code>setAddSigmaResiduals(sigma_res)</code>	Specifies whether residuals should be added to account for parameter dependent sigma.
<code>setAllStatesNonNegative()</code>	Set flags indicating that all states should be treated as non-negative.
<code>setAlwaysCheckFinite(alwaysCheck)</code>	Set whether the result of every call to <code>Model::f*</code> should be checked for finiteness.
<code>setFixedParameterById(par_id, value)</code>	Set value of first fixed parameter with the specified ID.
<code>setFixedParameterByName(par_name, value)</code>	Set value of first fixed parameter with the specified name.
<code>setFixedParameters(k)</code>	Set values for constants.
<code>setFixedParametersByIdRegex(par_id_regex, value)</code>	Set values of all fixed parameters with the ID matching the specified regex.
<code>setFixedParametersByNameRegex(...)</code>	Set value of all fixed parameters with name matching the specified regex.
<code>setInitialStateSensitivities(sx0)</code>	Set the initial state sensitivities.
<code>setInitialStates(x0)</code>	Set the initial states.
<code>setMinimumSigmaResiduals(min_sigma)</code>	Sets the estimated lower boundary for σ_y .
<code>setNMaxEvent(nmaxevent)</code>	Set maximum number of events that may occur for each type.
<code>setParameterById(*args)</code>	<i>Overload 1:</i>
<code>setParameterByName(*args)</code>	<i>Overload 1:</i>
<code>setParameterList(plist)</code>	Set the list of parameters for which sensitivities are to be computed.
<code>setParameterScale(*args)</code>	rtype <code>None</code>
<code>setParameters(p)</code>	Set the parameter vector.
<code>setParametersByIdRegex(par_id_regex, value)</code>	Set all values of model parameters with IDs matching the specified regular expression.
<code>setParametersByNameRegex(par_name_regex, value)</code>	Set all values of all model parameters with names matching the specified regex.
<code>setReinitializationStateIdxs(idxs)</code>	Set indices of states to be reinitialized based on provided constants / fixed parameters
<code>setReinitializeFixedParameterInitialStates(flag)</code>	Set whether initial states depending on fixed parameters are to be reinitialized after preequilibration and presimulation.
<code>setStateIsNonNegative(stateIsNonNegative)</code>	Set flags indicating whether states should be treated as non-negative.
<code>setSteadyStateSensitivityMode(mode)</code>	Set the mode how sensitivities are computed in the steadystate simulation.
<code>setT0(t0)</code>	Set simulation start time.
<code>setTimepoints(ts)</code>	Set the timepoint vector.
<code>setUnscaledInitialStateSensitivities(sx0)</code>	Set the initial state sensitivities.

continues on next page

Table 15 – continued from previous page

<code>t0()</code>	Get simulation start time.
Attributes	
<code>app</code>	AMICI application context
<code>idlist</code>	Flag array for DAE equations
<code>lbw</code>	Lower bandwidth of the Jacobian
<code>nJ</code>	Dimension of the augmented objective function for 2nd order ASA
<code>ndJydy</code>	Number of nonzero elements in the y derivative of dJy (dimension $nytrue$)
<code>ndtotal_cldx_rdata</code>	Number of nonzero elements in the x_rdata derivative of $total_{cl}$
<code>ndwdp</code>	Number of nonzero elements in the p derivative of the repeating elements
<code>ndwdw</code>	Number of nonzero elements in the w derivative of the repeating elements
<code>ndwdx</code>	Number of nonzero elements in the x derivative of the repeating elements
<code>ndxdotdw</code>	Number of nonzero elements in the w derivative of $xdot$
<code>ndxrdatadtcl</code>	Number of nonzero elements in the tcl derivative of x_rdata
<code>ndxrdatadxsolver</code>	Number of nonzero elements in the x derivative of x_rdata
<code>ne</code>	Number of events
<code>nnz</code>	Number of nonzero entries in Jacobian
<code>nw</code>	Number of common expressions
<code>nx_rdata</code>	Number of states
<code>nx_solver</code>	Number of states with conservation laws applied
<code>nx_solver_reinit</code>	Number of solver states subject to reinitialization
<code>nxtrue_rdata</code>	Number of states in the unaugmented system
<code>nxtrue_solver</code>	Number of states in the unaugmented system with conservation laws applied
<code>ny</code>	Number of observables
<code>nytrue</code>	Number of observables in the unaugmented system
<code>nz</code>	Number of event outputs
<code>nztrue</code>	Number of event outputs in the unaugmented system
<code>o2mode</code>	Flag indicating whether for <code>amici::Solver::sensi_ == amici::SensitivityOrder::second</code> directional or full second order derivative will be computed
<code>pythonGenerated</code>	Flag indicating Matlab- or Python-based model generation
<code>ubw</code>	Upper bandwidth of the Jacobian

Methods

`__init__(*args, **kwargs)`

Overload 1: Default ctor

Overload 2:

Constructor with model dimensions

Parameters

- **nx_rdata** (*int*) – Number of state variables
- **nxtrue_rdata** (*int*) – Number of state variables of the non-augmented model
- **nx_solver** (*int*) – Number of state variables with conservation laws applied
- **nxtrue_solver** (*int*) – Number of state variables of the non-augmented model with conservation laws applied
- **nx_solver_reinit** (*int*) – Number of state variables with conservation laws subject to reinitialization
- **np** (*int*) – Number of parameters
- **nk** (*int*) – Number of constants
- **ny** (*int*) – Number of observables
- **nytrue** (*int*) – Number of observables of the non-augmented model
- **nz** (*int*) – Number of event observables
- **nztrue** (*int*) – Number of event observables of the non-augmented model
- **ne** (*int*) – Number of events
- **nJ** (*int*) – Number of objective functions
- **nw** (*int*) – Number of repeating elements
- **ndwdx** (*int*) – Number of nonzero elements in the x derivative of the repeating elements
- **ndwdp** (*int*) – Number of nonzero elements in the p derivative of the repeating elements
- **ndwdw** (*int*) – Number of nonzero elements in the w derivative of the repeating elements
- **ndxdotdw** (*int*) – Number of nonzero elements in the w derivative of $x\dot{d}ot$
- **ndJydy** (*IntVector*) – Number of nonzero elements in the y derivative of dJy (shape *nytrue*)
- **ndxrdatadxsolver** (*int*) – Number of nonzero elements in the x derivative of x_rdata
- **ndxrdatadtcl** (*int*) – Number of nonzero elements in the tcl derivative of x_rdata
- **ndtotal_cldx_rdata** (*int*) – Number of nonzero elements in the x_rdata derivative of $total_{cl}$
- **nnz** (*int*) – Number of nonzero elements in Jacobian

- **ubw** (*int*) – Upper matrix bandwidth in the Jacobian
- **lbw** (*int*) – Lower matrix bandwidth in the Jacobian

clone() → Iterable[*amici.amici.Model*]

Clone this instance.

Return type *amici.Model*

Returns The clone

fdsigmaydy(*dsigmaydy: Iterable[float], t: float, p: Iterable[float], k: Iterable[float], y: Iterable[float]*) → *None*

Model-specific implementation of fsigmay

Parameters

- **dsigmaydy** (*typing.Iterable[float]*) – partial derivative of standard deviation of measurements w.r.t. model outputs
- **t** (*float*) – current time
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **y** (*typing.Iterable[float]*) – model output at timepoint t

Return type *None*

fdtotal_cldp(*dtotal_cldp: Iterable[float], x_rdata: Iterable[float], p: Iterable[float], k: Iterable[float], ip: int*) → *None*

Compute dtotal_cl / dp

Parameters

- **dtotal_cldp** (*typing.Iterable[float]*) – dtotal_cl / dp
- **x_rdata** (*typing.Iterable[float]*) – State variables with conservation laws applied
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **ip** (*int*) – Sensitivity index

Return type *None*

fdtotal_cldx_rdata(*dtotal_cldx_rdata: Iterable[float], x_rdata: Iterable[float], p: Iterable[float], k: Iterable[float], tcl: Iterable[float]*) → *None*

Compute dtotal_cl / dx_rdata

Parameters

- **dtotal_cldx_rdata** (*typing.Iterable[float]*) – dtotal_cl / dx_rdata
- **x_rdata** (*typing.Iterable[float]*) – State variables with conservation laws applied
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **tcl** (*typing.Iterable[float]*) – Total abundances for conservation laws

Return type *None*

fdx_rdatadp(*dx_rdatadp: Iterable[float], x: Iterable[float], tcl: Iterable[float], p: Iterable[float], k: Iterable[float], ip: int*) → *None*

Compute dx_rdata / dp

Parameters

- **dx_rdatadp** (*typing.Iterable[float]*) – dx_rdata / dp
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **x** (*typing.Iterable[float]*) – State variables with conservation laws applied
- **tcl** (*typing.Iterable[float]*) – Total abundances for conservation laws
- **ip** (*int*) – Sensitivity index

Return type *None*

fdx_rdatadtcl(*dx_rdatadtcl: Iterable[float], x: Iterable[float], tcl: Iterable[float], p: Iterable[float], k: Iterable[float]*) → *None*

Compute $dx_rdata / dtcl$

Parameters

- **dx_rdatadtcl** (*typing.Iterable[float]*) – $dx_rdata / dtcl$
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **x** (*typing.Iterable[float]*) – State variables with conservation laws applied
- **tcl** (*typing.Iterable[float]*) – Total abundances for conservation laws

Return type *None*

fdx_rdatadx_solver(*dx_rdatadx_solver: Iterable[float], x: Iterable[float], tcl: Iterable[float], p: Iterable[float], k: Iterable[float]*) → *None*

Compute dx_rdata / dx_solver

Parameters

- **dx_rdatadx_solver** (*typing.Iterable[float]*) – dx_rdata / dx_solver
- **p** (*typing.Iterable[float]*) – parameter vector
- **k** (*typing.Iterable[float]*) – constant vector
- **x** (*typing.Iterable[float]*) – State variables with conservation laws applied
- **tcl** (*typing.Iterable[float]*) – Total abundances for conservation laws

Return type *None*

getAddSigmaResiduals() → *bool*

Checks whether residuals should be added to account for parameter dependent sigma.

Return type *boolean*

Returns *sigma_res*

getAlwaysCheckFinite() → *bool*

Get setting of whether the result of every call to *Model::f** should be checked for finiteness.

Return type *boolean*

Returns *that*

getAmiciCommit() → *str*

Returns the AMICI commit that was used to generate the model

Return type *str*

Returns AMICI commit string

getAmiciVersion() → *str*

Returns the AMICI version that was used to generate the model

Return type *str*

Returns AMICI version string

getExpressionIds() → *amici.amici.StringVector*

Get IDs of the expression.

Return type *StringVector*

Returns Expression IDs

getExpressionNames() → *amici.amici.StringVector*

Get names of the expressions.

Return type *StringVector*

Returns Expression names

getFixedParameterById(*par_id: str*) → *float*

Get value of fixed parameter with the specified ID.

Parameters *par_id* (*str*) – Parameter ID

Return type *float*

Returns Parameter value

getFixedParameterByName(*par_name: str*) → *float*

Get value of fixed parameter with the specified name.

If multiple parameters have the same name, the first parameter with matching name is returned.

Parameters *par_name* (*str*) – Parameter name

Return type *float*

Returns Parameter value

getFixedParameterIds() → *amici.amici.StringVector*

Get IDs of the fixed model parameters.

Return type *StringVector*

Returns Fixed parameter IDs

getFixedParameterNames() → *amici.amici.StringVector*

Get names of the fixed model parameters.

Return type *StringVector*

Returns Fixed parameter names

getFixedParameters() → *amici.amici.DoubleVector*

Get values of fixed parameters.

Return type *DoubleVector*

Returns Vector of fixed parameters with same ordering as in `Model::getFixedParameterIds`

getInitialStateSensitivities() → *amici.amici.DoubleVector*

Get the initial states sensitivities.

Return type *DoubleVector*

Returns vector of initial state sensitivities

getInitialStates() → *amici.amici.DoubleVector*

Get the initial states.

Return type *DoubleVector*

Returns Initial state vector

getMinimumSigmaResiduals() → *float*

Gets the specified estimated lower boundary for sigma_y.

Return type *float*

Returns lower boundary

getName() → *str*

Get the model name.

Return type *str*

Returns Model name

getObservableIds() → *amici.amici.StringVector*

Get IDs of the observables.

Return type *StringVector*

Returns Observable IDs

getObservableNames() → *amici.amici.StringVector*

Get names of the observables.

Return type *StringVector*

Returns Observable names

getObservableScaling(iy: int) → *amici.amici.ObservableScaling*

Get scaling type for observable

Parameters *iy* (*int*) – observable index

Return type *int*

Returns scaling type

getParameterById(par_id: str) → *float*

Get value of first model parameter with the specified ID.

Parameters *par_id* (*str*) – Parameter ID

Return type *float*

Returns Parameter value

getParameterByName(par_name: str) → *float*

Get value of first model parameter with the specified name.

Parameters *par_name* (*str*) – Parameter name

Return type *float*

Returns Parameter value

getParameterIds() → *amici.amici.StringVector*

Get IDs of the model parameters.

Return type *StringVector*

Returns Parameter IDs

getParameterList() → *amici.amici.IntVector*

Get the list of parameters for which sensitivities are computed.

Return type *IntVector*

Returns List of parameter indices

getParameterNames() → *amici.amici.StringVector*

Get names of the model parameters.

Return type *StringVector*

Returns The parameter names

getParameterScale() → *amici.amici.ParameterScalingVector*

Get parameter scale for each parameter.

Return type *ParameterScalingVector*

Returns Vector of parameter scales

getParameters() → *amici.amici.DoubleVector*

Get parameter vector.

Return type *DoubleVector*

Returns The user-set parameters (see also *Model::getUnscaledParameters*)

getReinitializationStateIdxs() → *amici.amici.IntVector*

Return indices of states to be reinitialized based on provided constants / fixed parameters

Return type *IntVector*

Returns Those indices.

getReinitializeFixedParameterInitialStates() → *bool*

Get whether initial states depending on fixedParameters are to be reinitialized after preequilibration and presimulation.

Return type *boolean*

Returns flag *true* / *false*

getSolver() → *amici.amici.Solver*

Retrieves the solver object

Return type *amici.Solver*

Returns The Solver instance

getStateIds() → *amici.amici.StringVector*

Get IDs of the model states.

Return type *StringVector*

Returns State IDs

getStateIdsSolver() → *amici.amici.StringVector*

Get IDs of the solver states.

Return type *StringVector*

Returns State IDs

getStateIsNonNegative() → *amici.amici.BoolVector*

Get flags indicating whether states should be treated as non-negative.

Return type *BoolVector*

Returns Vector of flags

getStateNames() → *amici.amici.StringVector*

Get names of the model states.

Return type *StringVector*

Returns State names

getStateNamesSolver() → *amici.amici.StringVector*

Get names of the solver states.

Return type *StringVector*

Returns State names

getSteadyStateSensitivityMode() → *amici.amici.SteadyStateSensitivityMode*

Gets the mode how sensitivities are computed in the steadystate simulation.

Return type *amici.SteadyStateSensitivityMode*

Returns Mode

getTimepoint(it: int) → float

Get simulation timepoint for time index *it*.

Parameters *it* (int) – Time index

Return type float

Returns Timepoint

getTimepoints() → *amici.amici.DoubleVector*

Get the timepoint vector.

Return type *DoubleVector*

Returns Timepoint vector

getUnscaledParameters() → *amici.amici.DoubleVector*

Get parameters with transformation according to parameter scale applied.

Return type *DoubleVector*

Returns Unscaled parameters

hasCustomInitialStateSensitivities() → bool

Return whether custom initial state sensitivities have been set.

Return type boolean

Returns *true* if has custom initial state sensitivities, otherwise *false*.

hasCustomInitialStates() → bool

Return whether custom initial states have been set.

Return type boolean

Returns *true* if has custom initial states, otherwise *false*

hasExpressionIds() → bool

Report whether the model has expression IDs set.

Return type boolean

Returns Boolean indicating whether expression ids were set. Also returns *true* if the number of corresponding variables is just zero.

hasExpressionNames() → bool

Report whether the model has expression names set.

Return type boolean

Returns Boolean indicating whether expression names were set. Also returns *true* if the number of corresponding variables is just zero.

hasFixedParameterIds() → bool

Report whether the model has fixed parameter IDs set.

Return type boolean

Returns Boolean indicating whether fixed parameter IDs were set. Also returns *true* if the number of corresponding variables is just zero.

hasFixedParameterNames() → bool

Report whether the model has fixed parameter names set.

Return type boolean

Returns Boolean indicating whether fixed parameter names were set. Also returns *true* if the number of corresponding variables is just zero.

hasObservableIds() → bool

Report whether the model has observable IDs set.

Return type boolean

Returns Boolean indicating whether observable ids were set. Also returns *true* if the number of corresponding variables is just zero.

hasObservableNames() → bool

Report whether the model has observable names set.

Return type boolean

Returns Boolean indicating whether observable names were set. Also returns *true* if the number of corresponding variables is just zero.

hasParameterIds() → bool

Report whether the model has parameter IDs set.

Return type boolean

Returns Boolean indicating whether parameter IDs were set. Also returns *true* if the number of corresponding variables is just zero.

hasParameterNames() → bool

Report whether the model has parameter names set.

Return type boolean

Returns Boolean indicating whether parameter names were set. Also returns *true* if the number of corresponding variables is just zero.

hasQuadraticLLH() → bool

Checks whether the defined noise model is gaussian, i.e., the nllh is quadratic

Return type boolean

Returns boolean flag

hasStateIds() → bool

Report whether the model has state IDs set.

Return type boolean

Returns Boolean indicating whether state IDs were set. Also returns *true* if the number of corresponding variables is just zero.

hasStateNames() → bool

Report whether the model has state names set.

Return type boolean

Returns Boolean indicating whether state names were set. Also returns *true* if the number of corresponding variables is just zero.

isFixedParameterStateReinitializationAllowed() → bool

Function indicating whether reinitialization of states depending on fixed parameters is permissible

Return type boolean

Returns flag indicating whether reinitialization of states depending on fixed parameters is permissible

k() → Iterable[float]

Get fixed parameters.

Return type float

Returns Pointer to constants array

nMaxEvent() → int

Get maximum number of events that may occur for each type.

Return type int

Returns Maximum number of events that may occur for each type

ncl() → int

Get number of conservation laws.

Return type int

Returns Number of conservation laws (i.e., difference between *nx_rdata* and *nx_solver*).

nk() → int

Get number of constants

Return type int

Returns Length of constant vector

np() → int

Get total number of model parameters.

Return type int

Returns Length of parameter vector

nplist() → int

Get number of parameters wrt to which sensitivities are computed.

Return type int

Returns Length of sensitivity index vector

nt() → *int*

Get number of timepoints.

Return type *int*

Returns Number of timepoints

nx_reinit() → *int*

Get number of solver states subject to reinitialization.

Return type *int*

Returns Model member *nx_solver_reinit*

plist(pos: *int*) → *int*

Get entry in parameter list by index.

Parameters **pos** (*int*) – Index in sensitivity parameter list

Return type *int*

Returns Index in parameter list

requireSensitivitiesForAllParameters() → *None*

Require computation of sensitivities for all parameters *p* [0..np[in natural order.

NOTE: Resets initial state sensitivities.

Return type *None*

setAddSigmaResiduals(sigma_res: *bool*) → *None*

Specifies whether residuals should be added to account for parameter dependent sigma.

If set to true, additional residuals of the form $\sqrt{\log(\sigma) + C}$ will be added. This enables least-squares optimization for variables with Gaussian noise assumption and parameter dependent standard deviation sigma. The constant *C* can be set via [setMinimumSigmaResiduals\(\)](#).

Parameters **sigma_res** (*bool*) – if true, additional residuals are added

Return type *None*

setAllStatesNonNegative() → *None*

Set flags indicating that all states should be treated as non-negative.

Return type *None*

setAlwaysCheckFinite(alwaysCheck: *bool*) → *None*

Set whether the result of every call to *Model::f** should be checked for finiteness.

Parameters **alwaysCheck** (*bool*) –

Return type *None*

setFixedParameterById(par_id: *str*, value: *float*) → *None*

Set value of first fixed parameter with the specified ID.

Parameters

- **par_id** (*str*) – Fixed parameter id
- **value** (*float*) – Fixed parameter value

Return type *None*

setFixedParameterByName(par_name: *str*, value: *float*) → *None*

Set value of first fixed parameter with the specified name.

Parameters

- **par_name** (*str*) – Fixed parameter ID
- **value** (*float*) – Fixed parameter value

Return type *None***setFixedParameters**(*k*: *amici.amici.DoubleVector*) → *None*

Set values for constants.

Parameters *k* (*amici.amici.DoubleVector*) – Vector of fixed parameters**Return type** *None***setFixedParametersByIdRegex**(*par_id_regex*: *str*, *value*: *float*) → *int*

Set values of all fixed parameters with the ID matching the specified regex.

Parameters

- **par_id_regex** (*str*) – Fixed parameter name regex
- **value** (*float*) – Fixed parameter value

Return type *int***Returns** Number of fixed parameter IDs that matched the regex**setFixedParametersByNameRegex**(*par_name_regex*: *str*, *value*: *float*) → *int*

Set value of all fixed parameters with name matching the specified regex.

Parameters

- **par_name_regex** (*str*) – Fixed parameter name regex
- **value** (*float*) – Fixed parameter value

Return type *int***Returns** Number of fixed parameter names that matched the regex**setInitialStateSensitivities**(*sx0*: *amici.amici.DoubleVector*) → *None*

Set the initial state sensitivities.

Parameters *sx0* (*amici.amici.DoubleVector*) – vector of initial state sensitivities with chainrule applied. This could be a slice of *ReturnData::sx* or *ReturnData::sx0***Return type** *None***setInitialStates**(*x0*: *amici.amici.DoubleVector*) → *None*

Set the initial states.

Parameters *x0* (*amici.amici.DoubleVector*) – Initial state vector**Return type** *None***setMinimumSigmaResiduals**(*min_sigma*: *float*) → *None*Sets the estimated lower boundary for *sigma_y*. When *setAddSigmaResiduals()* is activated, this lower boundary must ensure that $\log(\text{sigma}) + \text{min_sigma} > 0$.**Parameters** *min_sigma* (*float*) – lower boundary**Return type** *None***setMaxEvent**(*nmaxevent*: *int*) → *None*

Set maximum number of events that may occur for each type.

Parameters *nmaxevent* (*int*) – Maximum number of events that may occur for each type

Return type `None`

setParameterById(*args) → `None`

Overload 1:

Set model parameters according to the parameter IDs and mapped values.

Parameters

- **p** (`StringDoubleMap`) – Map of parameters IDs and values
- **ignoreErrors** (`boolean`, *optional*) – Ignore errors such as parameter IDs in p which are not model parameters

Overload 2:

Set value of first model parameter with the specified ID.

Parameters

- **par_id** (`str`) – Parameter ID
- **value** (`float`) – Parameter value

Return type `None`

setParameterByName(*args) → `None`

Overload 1:

Set value of first model parameter with the specified name.

Parameters

- **par_name** (`str`) – Parameter name
- **value** (`float`) – Parameter value

Overload 2:

Set model parameters according to the parameter name and mapped values.

Parameters

- **p** (`StringDoubleMap`) – Map of parameters names and values
- **ignoreErrors** (`boolean`, *optional*) – Ignore errors such as parameter names in p which are not model parameters

Overload 3:

Set model parameters according to the parameter name and mapped values.

Parameters

- **p** (`StringDoubleMap`) – Map of parameters names and values
- **ignoreErrors** – Ignore errors such as parameter names in p which are not model parameters

Return type `None`**setParameterList** (*plist*: `amici.amici.IntVector`) → `None`

Set the list of parameters for which sensitivities are to be computed.

NOTE: Resets initial state sensitivities.

Parameters **plist** (`amici.amici.IntVector`) – List of parameter indices**Return type** `None`**setParameterScale** (*args) → `None`**Return type** `None`**setParameters** (*p*: `amici.amici.DoubleVector`) → `None`

Set the parameter vector.

Parameters **p** (`amici.amici.DoubleVector`) – Vector of parameters**Return type** `None`**setParametersByIdRegex** (*par_id_regex*: `str`, *value*: `float`) → `int`

Set all values of model parameters with IDs matching the specified regular expression.

Parameters

- **par_id_regex** (`str`) – Parameter ID regex
- **value** (`float`) – Parameter value

Return type `int`**Returns** Number of parameter IDs that matched the regex**setParametersByNameRegex** (*par_name_regex*: `str`, *value*: `float`) → `int`

Set all values of all model parameters with names matching the specified regex.

Parameters

- **par_name_regex** (`str`) – Parameter name regex
- **value** (`float`) – Parameter value

Return type `int`**Returns** Number of fixed parameter names that matched the regex**setReinitializationStateIdxs** (*idxs*: `amici.amici.IntVector`) → `None`

Set indices of states to be reinitialized based on provided constants / fixed parameters

Parameters **idxs** (`amici.amici.IntVector`) – Array of state indices**Return type** `None`**setReinitializeFixedParameterInitialStates** (*flag*: `bool`) → `None`

Set whether initial states depending on fixed parameters are to be reinitialized after preequilibration and presimulation.

Parameters **flag** (`bool`) – Fixed parameters reinitialized?

Return type `None`

setStateIsNonNegative(*stateIsNonNegative*: `amici.amici.BoolVector`) → `None`

Set flags indicating whether states should be treated as non-negative.

Parameters **stateIsNonNegative** (`amici.amici.BoolVector`) – Vector of flags

Return type `None`

setSteadyStateSensitivityMode(*mode*: `amici.amici.SteadyStateSensitivityMode`) → `None`

Set the mode how sensitivities are computed in the steadystate simulation.

Parameters **mode** (`amici.amici.SteadyStateSensitivityMode`) – Steadystate sensitivity mode

Return type `None`

setT0(*t0*: `float`) → `None`

Set simulation start time.

Parameters **t0** (`float`) – Simulation start time

Return type `None`

setTimepoints(*ts*: `amici.amici.DoubleVector`) → `None`

Set the timepoint vector.

Parameters **ts** (`amici.amici.DoubleVector`) – New timepoint vector

Return type `None`

setUnscaledInitialStateSensitivities(*sx0*: `amici.amici.DoubleVector`) → `None`

Set the initial state sensitivities.

Parameters **sx0** (`amici.amici.DoubleVector`) – Vector of initial state sensitivities without chainrule applied. This could be the readin from a *model.sx0data* saved to HDF5.

Return type `None`

t0() → `float`

Get simulation start time.

Return type `float`

Returns Simulation start time

amici.amici.ModelDimensions

class `amici.amici.ModelDimensions(*args)`

Container for model dimensions.

Holds number of states, observables, etc.

__init__(*args)

Overload 1: Default ctor

Overload 2:

Constructor with model dimensions

Parameters

- **nx_rdata** (*int*) – Number of state variables
- **nxtrue_rdata** (*int*) – Number of state variables of the non-augmented model
- **nx_solver** (*int*) – Number of state variables with conservation laws applied
- **nxtrue_solver** (*int*) – Number of state variables of the non-augmented model with conservation laws applied
- **nx_solver_reinit** (*int*) – Number of state variables with conservation laws subject to reinitialization
- **np** (*int*) – Number of parameters
- **nk** (*int*) – Number of constants
- **ny** (*int*) – Number of observables
- **nytrue** (*int*) – Number of observables of the non-augmented model
- **nz** (*int*) – Number of event observables
- **nztrue** (*int*) – Number of event observables of the non-augmented model
- **ne** (*int*) – Number of events
- **nJ** (*int*) – Number of objective functions
- **nw** (*int*) – Number of repeating elements
- **ndwdx** (*int*) – Number of nonzero elements in the x derivative of the repeating elements
- **ndwdp** (*int*) – Number of nonzero elements in the p derivative of the repeating elements
- **ndwdw** (*int*) – Number of nonzero elements in the w derivative of the repeating elements
- **ndxdotdw** (*int*) – Number of nonzero elements in the w derivative of $x\dot{d}ot$
- **ndJydy** (*IntVector*) – Number of nonzero elements in the y derivative of dJy (shape *nytrue*)
- **ndxrdatadxsolver** (*int*) – Number of nonzero elements in the x derivative of x_rdata
- **ndxrdatadtcl** (*int*) – Number of nonzero elements in the tcl derivative of x_rdata
- **ndtotal_cldx_rdata** (*int*) – Number of nonzero elements in the x_rdata derivative of $total_{cl}$
- **nnz** (*int*) – Number of nonzero elements in Jacobian
- **ubw** (*int*) – Upper matrix bandwidth in the Jacobian
- **lbw** (*int*) – Lower matrix bandwidth in the Jacobian

Methods Summary

`__init__`(*args)

Overload 1:

Attributes

<code>lbw</code>	Lower bandwidth of the Jacobian
<code>nJ</code>	Dimension of the augmented objective function for 2nd order ASA
<code>ndJydy</code>	Number of nonzero elements in the y derivative of dJy (dimension <i>nytrue</i>)
<code>ndtotal_cldx_rdata</code>	Number of nonzero elements in the x_rdata derivative of $total_{cl}$
<code>ndwdp</code>	Number of nonzero elements in the p derivative of the repeating elements
<code>ndwdw</code>	Number of nonzero elements in the w derivative of the repeating elements
<code>ndwdx</code>	Number of nonzero elements in the x derivative of the repeating elements
<code>ndxdotdw</code>	Number of nonzero elements in the w derivative of $xdot$
<code>ndxrdatadtcl</code>	Number of nonzero elements in the tcl derivative of x_rdata
<code>ndxrdatadxsolver</code>	Number of nonzero elements in the x derivative of x_rdata
<code>ne</code>	Number of events
<code>nk</code>	Number of constants
<code>nnz</code>	Number of nonzero entries in Jacobian
<code>np</code>	Number of parameters
<code>nw</code>	Number of common expressions
<code>nx_rdata</code>	Number of states
<code>nx_solver</code>	Number of states with conservation laws applied
<code>nx_solver_reinit</code>	Number of solver states subject to reinitialization
<code>nxtrue_rdata</code>	Number of states in the unaugmented system
<code>nxtrue_solver</code>	Number of states in the unaugmented system with conservation laws applied
<code>ny</code>	Number of observables
<code>nytrue</code>	Number of observables in the unaugmented system
<code>nz</code>	Number of event outputs
<code>nztrue</code>	Number of event outputs in the unaugmented system
<code>ubw</code>	Upper bandwidth of the Jacobian

Methods

`__init__(*args)`

Overload 1: Default ctor

Overload 2:

Constructor with model dimensions

Parameters

- **nx_rdata** (*int*) – Number of state variables
- **nxtrue_rdata** (*int*) – Number of state variables of the non-augmented model
- **nx_solver** (*int*) – Number of state variables with conservation laws applied
- **nxtrue_solver** (*int*) – Number of state variables of the non-augmented model with conservation laws applied
- **nx_solver_reinit** (*int*) – Number of state variables with conservation laws subject to reinitialization
- **np** (*int*) – Number of parameters
- **nk** (*int*) – Number of constants
- **ny** (*int*) – Number of observables
- **nytrue** (*int*) – Number of observables of the non-augmented model
- **nz** (*int*) – Number of event observables
- **nztrue** (*int*) – Number of event observables of the non-augmented model
- **ne** (*int*) – Number of events
- **nJ** (*int*) – Number of objective functions
- **nw** (*int*) – Number of repeating elements
- **ndwdx** (*int*) – Number of nonzero elements in the x derivative of the repeating elements
- **ndwdp** (*int*) – Number of nonzero elements in the p derivative of the repeating elements
- **ndwdw** (*int*) – Number of nonzero elements in the w derivative of the repeating elements
- **ndxdotdw** (*int*) – Number of nonzero elements in the w derivative of $x\dot{d}ot$
- **ndJydy** (*IntVector*) – Number of nonzero elements in the y derivative of dJy (shape *nytrue*)
- **ndxrdatadxsolver** (*int*) – Number of nonzero elements in the x derivative of x_rdata
- **ndxrdatadtcl** (*int*) – Number of nonzero elements in the tcl derivative of x_rdata
- **ndtotal_cldx_rdata** (*int*) – Number of nonzero elements in the x_rdata derivative of $total_{cl}$
- **nnz** (*int*) – Number of nonzero elements in Jacobian

- **ubw** (*int*) – Upper matrix bandwidth in the Jacobian
- **lbw** (*int*) – Lower matrix bandwidth in the Jacobian

amici.amici.ModelPtr

class amici.amici.**ModelPtr**(*args)

Swig-Generated class that implements smart pointers to Model as objects.

Attributes

app	AMICI application context
idlist	Flag array for DAE equations
lbw	Lower bandwidth of the Jacobian
nJ	Dimension of the augmented objective function for 2nd order ASA
ndJydy	Number of nonzero elements in the y derivative of dJy (dimension ny_{true})
ndtotal_cldx_rdata	Number of nonzero elements in the x_rdata derivative of $total_{cl}$
ndwdp	Number of nonzero elements in the p derivative of the repeating elements
ndwdw	Number of nonzero elements in the w derivative of the repeating elements
ndwdx	Number of nonzero elements in the x derivative of the repeating elements
ndxdotdw	Number of nonzero elements in the w derivative of $xdot$
ndxrdatadtcl	Number of nonzero elements in the tcl derivative of x_rdata
ndxrdatadxsolver	Number of nonzero elements in the x derivative of x_rdata
ne	Number of events
nnz	Number of nonzero entries in Jacobian
nw	Number of common expressions
nx_rdata	Number of states
nx_solver	Number of states with conservation laws applied
nx_solver_reinit	Number of solver states subject to reinitialization
nxtrue_rdata	Number of states in the unaugmented system
nxtrue_solver	Number of states in the unaugmented system with conservation laws applied
ny	Number of observables
nytrue	Number of observables in the unaugmented system
nz	Number of event outputs
nztrue	Number of event outputs in the unaugmented system
o2mode	Flag indicating whether for <code>amici::Solver::sensi_ == amici::SensitivityOrder::second</code> directional or full second order derivative will be computed
pythonGenerated	Flag indicating Matlab- or Python-based model generation

continues on next page

Table 19 – continued from previous page

ubw	Upper bandwidth of the Jacobian
-----	---------------------------------

amici.amici.NewtonDampingFactorMode

class amici.amici.**NewtonDampingFactorMode**(*value*)
 An enumeration.

Attributes

off

on

amici.amici.NonlinearSolverIteration

class amici.amici.**NonlinearSolverIteration**(*value*)
 An enumeration.

Attributes

functional

fixedpoint

newton

amici.amici.ObservableScaling

class amici.amici.**ObservableScaling**(*value*)
 An enumeration.

Attributes

lin

log

log10

amici.amici.ParameterScaling

class amici.amici.**ParameterScaling**(*value*)
An enumeration.

Attributes

none

ln

log10

amici.amici.ParameterScalingVector

class amici.amici.**ParameterScalingVector**(*args)

amici.amici.RDataReporting

class amici.amici.**RDataReporting**(*value*)
An enumeration.

Attributes

full

residuals

likelihood

amici.amici.ReturnData

class amici.amici.**ReturnData**(*args)
Stores all data to be returned by `amici.amici.runAmiciSimulation()`.

NOTE: multi-dimensional arrays are stored in row-major order (C-style)

__init__(*args)

Overload 1:

Default constructor

Overload 2:

Constructor

Parameters

- **ts** ([DoubleVector](#)) – see amici::SimulationParameters::ts
- **model_dimensions** ([ModelDimensions](#)) – Model dimensions
- **nplist** ([int](#)) – see amici::ModelDimensions::nplist
- **nmaxevent** ([int](#)) – see amici::ModelDimensions::nmaxevent
- **nt** ([int](#)) – see amici::ModelDimensions::nt
- **newton_maxsteps** ([int](#)) – see amici::Solver::newton_maxsteps
- **pscale** ([ParameterScalingVector](#)) – see amici::SimulationParameters::pscale
- **o2mode** ([int](#)) – see amici::SimulationParameters::o2mode
- **sensi** ([amici.SensitivityOrder](#)) – see amici::Solver::sensi
- **sensi_meth** ([amici.SensitivityMethod](#)) – see amici::Solver::sensi_meth
- **rdrn** ([amici.RDataReporting](#)) – see amici::Solver::rdata_reporting
- **quadratic_llh** ([boolean](#)) – whether model defines a quadratic nllh and computing res, sres and FIM makes sense
- **sigma_res** ([boolean](#)) – indicates whether additional residuals are to be added for each sigma
- **sigma_offset** ([float](#)) – offset to ensure real-valuedness of sigma residuals

Overload 3:

constructor that uses information from model and solver to appropriately initialize fields

Parameters

- **solver** ([Solver](#)) – solver instance
- **model** ([Model](#)) – model instance

Methods Summary

[__init__](#)(*args)

Overload 1:

Attributes

FIM	fisher information matrix (shape $nplist \times nplist$, row-major)
J	Jacobian of differential equation right hand side (shape $nx \times nx$, row-major)
chi2	χ^2 value
cpu_time	computation time of forward solve [ms]
cpu_timeB	computation time of backward solve [ms]
cpu_time_total	total CPU time from entering runAmiciSimulation until exiting [ms]
id	Arbitrary (not necessarily unique) identifier.
lbw	Lower bandwidth of the Jacobian
llh	log-likelihood value
nJ	Dimension of the augmented objective function for 2nd order ASA
ndJydy	Number of nonzero elements in the y derivative of dJy (dimension $nytrue$)
ndtotal_cldx_rdata	Number of nonzero elements in the x_rdata derivative of $total_{cl}$
ndwdp	Number of nonzero elements in the p derivative of the repeating elements
ndwdw	Number of nonzero elements in the w derivative of the repeating elements
ndwdx	Number of nonzero elements in the x derivative of the repeating elements
ndxdotdw	Number of nonzero elements in the w derivative of $xdot$
ndxrdadatdtcl	Number of nonzero elements in the tcl derivative of x_rdata
ndxrdatadxsolver	Number of nonzero elements in the x derivative of x_rdata
ne	Number of events
newton_maxsteps	maximal number of newton iterations for steady state calculation
nk	Number of constants
nmaxevent	maximal number of occurring events (for every event type)
nnz	Number of nonzero entries in Jacobian
np	Number of parameters
nplist	number of parameter for which sensitivities were requested
nt	number of considered timepoints
numerrtestfails	number of error test failures forward problem (shape nt)
numerrtestfailsB	number of error test failures backward problem (shape nt)
numnonlinsolvconvfails	number of linear solver convergence failures forward problem (shape nt)
numnonlinsolvconvfailsB	number of linear solver convergence failures backward problem (shape nt)

continues on next page

Table 26 – continued from previous page

numrhsevals	number of right hand side evaluations forward problem (shape <i>nt</i>)
numrhsevalsB	number of right hand side evaluations backward problem (shape <i>nt</i>)
numsteps	number of integration steps forward problem (shape <i>nt</i>)
numstepsB	number of integration steps backward problem (shape <i>nt</i>)
nw	Number of common expressions
nx	number of states (alias <i>nx_rdata</i> , kept for backward compatibility)
nx_rdata	Number of states
nx_solver	Number of states with conservation laws applied
nx_solver_reinit	Number of solver states subject to reinitialization
nxtrue	number of states in the unaugmented system (alias <i>nxtrue_rdata</i> , kept for backward compatibility)
nxtrue_rdata	Number of states in the unaugmented system
nxtrue_solver	Number of states in the unaugmented system with conservation laws applied
ny	Number of observables
nytrue	Number of observables in the unaugmented system
nz	Number of event outputs
nztrue	Number of event outputs in the unaugmented system
o2mode	flag indicating whether second-order sensitivities were requested
order	employed order forward problem (shape <i>nt</i>)
posteq_cpu_time	computation time of the steady state solver [ms] (postequilibration)
posteq_cpu_timeB	computation time of the steady state solver of the backward problem [ms] (postequilibration)
posteq_numsteps	number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (shape 3) (postequilibration)
posteq_numstepsB	number of simulation steps for adjoint steady state problem (postequilibration) [== 0 if analytical solution worked, > 0 otherwise]
posteq_status	flags indicating success of steady state solver (postequilibration)
posteq_t	time when steadystate was reached via simulation (postequilibration)
posteq_wrms	weighted root-mean-square of the rhs when steadystate was reached (postequilibration)
preeq_cpu_time	computation time of the steady state solver [ms] (preequilibration)
preeq_cpu_timeB	computation time of the steady state solver of the backward problem [ms] (preequilibration)
preeq_numsteps	number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (length = 3)

continues on next page

Table 26 – continued from previous page

preeq_numstepsB	number of simulation steps for adjoint steady state problem (preequilibration) [== 0 if analytical solution worked, > 0 otherwise]
preeq_status	flags indicating success of steady state solver (preequilibration)
preeq_t	time when steadystate was reached via simulation (preequilibration)
preeq_wrms	weighted root-mean-square of the rhs when steadystate was reached (preequilibration)
pscale	scaling of parameterization
rdata_reporting	reporting mode
res	observable (shape $nt*ny$, row-major)
rz	event trigger output (shape $nmaxevent \times nz$, row-major)
s2llh	second-order parameter derivative of log-likelihood (shape $nJ-1 \times nplist$, row-major)
s2rz	second-order parameter derivative of event trigger output (shape $nmaxevent \times nztrue \times nplist \times nplist$, row-major)
sensi	sensitivity order
sensi_meth	sensitivity method
sigma_res	boolean indicating whether residuals for standard deviations have been added
sigmay	observable standard deviation (shape $nt \times ny$, row-major)
sigmaz	event output sigma standard deviation (shape $nmaxevent \times nz$, row-major)
sllh	parameter derivative of log-likelihood (shape $nplist$)
sres	parameter derivative of residual (shape $nt*ny \times nplist$, row-major)
srz	parameter derivative of event trigger output (shape $nmaxevent \times nplist \times nz$, row-major)
ssigmay	parameter derivative of observable standard deviation (shape $nt \times nplist \times ny$, row-major)
ssigmaz	parameter derivative of event output standard deviation (shape $nmaxevent \times nplist \times nz$, row-major)
status	status code
sx	parameter derivative of state (shape $nt \times nplist \times nx$, row-major)
sx0	initial sensitivities (shape $nplist \times nx$, row-major)
sx_ss	preequilibration sensitivities found by Newton solver (shape $nplist \times nx$, row-major)
sy	parameter derivative of observable (shape $nt \times nplist \times ny$, row-major)
sz	parameter derivative of event output (shape $nmaxevent \times nplist \times nz$, row-major)
ts	timepoints (shape nt)
ubw	Upper bandwidth of the Jacobian
w	w data from the model (recurring terms in <code>xdot</code> , for imported SBML models from python, this contains the flux vector) (shape $nt \times nw$, row major)

continues on next page

Table 26 – continued from previous page

x	state (shape $nt \times nx$, row-major)
x0	initial state (shape nx)
x_ss	preequilibration steady state found by Newton solver (shape nx)
xdot	time derivative (shape nx)
y	observable (shape $nt \times ny$, row-major)
z	event output (shape $nmaxevent \times nz$, row-major)

Methods

__init__(*args)

Overload 1:

Default constructor

Overload 2:

Constructor

Parameters

- **ts** ([DoubleVector](#)) – see amici::SimulationParameters::ts
- **model_dimensions** ([ModelDimensions](#)) – Model dimensions
- **nplist** (*int*) – see amici::ModelDimensions::nplist
- **nmaxevent** (*int*) – see amici::ModelDimensions::nmaxevent
- **nt** (*int*) – see amici::ModelDimensions::nt
- **newton_maxsteps** (*int*) – see amici::Solver::newton_maxsteps
- **pscale** ([ParameterScalingVector](#)) – see amici::SimulationParameters::pscale
- **o2mode** (*int*) – see amici::SimulationParameters::o2mode
- **sensi** ([amici.SensitivityOrder](#)) – see amici::Solver::sensi
- **sensi_meth** ([amici.SensitivityMethod](#)) – see amici::Solver::sensi_meth
- **rdrm** ([amici.RDataReporting](#)) – see amici::Solver::rdata_reporting
- **quadratic_llh** (*boolean*) – whether model defines a quadratic nllh and computing res, sres and FIM makes sense
- **sigma_res** (*boolean*) – indicates whether additional residuals are to be added for each sigma
- **sigma_offset** (*float*) – offset to ensure real-valuedness of sigma residuals

Overload 3:

constructor that uses information from model and solver to appropriately initialize fields

Parameters

- **solver** (*Solver*) – solver instance
- **model** (*Model*) – model instance

amici.amici.ReturnDataPtr

class amici.amici.ReturnDataPtr(*args)

Swig-Generated class that implements smart pointers to ReturnData as objects.

Attributes

FIM	fisher information matrix (shape $nplist \times nplist$, row-major)
J	Jacobian of differential equation right hand side (shape $nx \times nx$, row-major)
chi2	χ^2 value
cpu_time	computation time of forward solve [ms]
cpu_timeB	computation time of backward solve [ms]
cpu_time_total	total CPU time from entering runAmiciSimulation until exiting [ms]
id	Arbitrary (not necessarily unique) identifier.
lbw	Lower bandwidth of the Jacobian
llh	log-likelihood value
nJ	Dimension of the augmented objective function for 2nd order ASA
ndJydy	Number of nonzero elements in the y derivative of dJy (dimension $nytrue$)
ndtotal_cldx_rdata	Number of nonzero elements in the x_rdata derivative of $total_{cl}$
ndwdp	Number of nonzero elements in the p derivative of the repeating elements
ndwdw	Number of nonzero elements in the w derivative of the repeating elements
ndwdx	Number of nonzero elements in the x derivative of the repeating elements
ndxdotdw	Number of nonzero elements in the w derivative of x_{dot}
ndxrdatadtcl	Number of nonzero elements in the tcl derivative of x_rdata
ndxrdatadxsolver	Number of nonzero elements in the x derivative of x_rdata
ne	Number of events
newton_maxsteps	maximal number of newton iterations for steady state calculation
nk	Number of constants
nmaxevent	maximal number of occurring events (for every event type)

continues on next page

Table 27 – continued from previous page

<code>nnz</code>	Number of nonzero entries in Jacobian
<code>np</code>	Number of parameters
<code>nplist</code>	number of parameter for which sensitivities were requested
<code>nt</code>	number of considered timepoints
<code>numerrtestfails</code>	number of error test failures forward problem (shape <i>nt</i>)
<code>numerrtestfailsB</code>	number of error test failures backward problem (shape <i>nt</i>)
<code>numnonlinsolvconvfails</code>	number of linear solver convergence failures forward problem (shape <i>nt</i>)
<code>numnonlinsolvconvfailsB</code>	number of linear solver convergence failures backward problem (shape <i>nt</i>)
<code>numrhsevals</code>	number of right hand side evaluations forward problem (shape <i>nt</i>)
<code>numrhsevalsB</code>	number of right hand side evaluations backward problem (shape <i>nt</i>)
<code>numsteps</code>	number of integration steps forward problem (shape <i>nt</i>)
<code>numstepsB</code>	number of integration steps backward problem (shape <i>nt</i>)
<code>nw</code>	Number of common expressions
<code>nx</code>	number of states (alias <i>nx_rdata</i> , kept for backward compatibility)
<code>nx_rdata</code>	Number of states
<code>nx_solver</code>	Number of states with conservation laws applied
<code>nx_solver_reinit</code>	Number of solver states subject to reinitialization
<code>nxtrue</code>	number of states in the unaugmented system (alias <i>nxtrue_rdata</i> , kept for backward compatibility)
<code>nxtrue_rdata</code>	Number of states in the unaugmented system
<code>nxtrue_solver</code>	Number of states in the unaugmented system with conservation laws applied
<code>ny</code>	Number of observables
<code>nytrue</code>	Number of observables in the unaugmented system
<code>nz</code>	Number of event outputs
<code>nztrue</code>	Number of event outputs in the unaugmented system
<code>o2mode</code>	flag indicating whether second-order sensitivities were requested
<code>order</code>	employed order forward problem (shape <i>nt</i>)
<code>posteq_cpu_time</code>	computation time of the steady state solver [ms] (postequilibration)
<code>posteq_cpu_timeB</code>	computation time of the steady state solver of the backward problem [ms] (postequilibration)
<code>posteq_numsteps</code>	number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (shape 3) (postequilibration)
<code>posteq_numstepsB</code>	number of simulation steps for adjoint steady state problem (postequilibration) [== 0 if analytical solution worked, > 0 otherwise]
<code>posteq_status</code>	flags indicating success of steady state solver (postequilibration)

continues on next page

Table 27 – continued from previous page

posteq_t	time when steadystate was reached via simulation (postequilibration)
posteq_wrms	weighted root-mean-square of the rhs when steadystate was reached (postequilibration)
preeq_cpu_time	computation time of the steady state solver [ms] (preequilibration)
preeq_cpu_timeB	computation time of the steady state solver of the backward problem [ms] (preequilibration)
preeq_numsteps	number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (length = 3)
preeq_numstepsB	number of simulation steps for adjoint steady state problem (preequilibration) [== 0 if analytical solution worked, > 0 otherwise]
preeq_status	flags indicating success of steady state solver (preequilibration)
preeq_t	time when steadystate was reached via simulation (preequilibration)
preeq_wrms	weighted root-mean-square of the rhs when steadystate was reached (preequilibration)
pscale	scaling of parameterization
rdata_reporting	reporting mode
res	observable (shape $nt*ny$, row-major)
rz	event trigger output (shape $nmaxevent \times nz$, row-major)
s2llh	second-order parameter derivative of log-likelihood (shape $nJ-1 \times nplist$, row-major)
s2rz	second-order parameter derivative of event trigger output (shape $nmaxevent \times nztrue \times nplist \times nplist$, row-major)
sensi	sensitivity order
sensi_meth	sensitivity method
sigma_res	boolean indicating whether residuals for standard deviations have been added
sigmay	observable standard deviation (shape $nt \times ny$, row-major)
sigmaz	event output sigma standard deviation (shape $nmaxevent \times nz$, row-major)
sllh	parameter derivative of log-likelihood (shape $nplist$)
sres	parameter derivative of residual (shape $nt*ny \times nplist$, row-major)
srz	parameter derivative of event trigger output (shape $nmaxevent \times nplist \times nz$, row-major)
ssigmay	parameter derivative of observable standard deviation (shape $nt \times nplist \times ny$, row-major)
ssigmaz	parameter derivative of event output standard deviation (shape $nmaxevent \times nplist \times nz$, row-major)
status	status code
sx	parameter derivative of state (shape $nt \times nplist \times nx$, row-major)
sx0	initial sensitivities (shape $nplist \times nx$, row-major)

continues on next page

Table 27 – continued from previous page

<code>sx_ss</code>	preequilibration sensitivities found by Newton solver (shape <i>nplist</i> x <i>nx</i> , row-major)
<code>sy</code>	parameter derivative of observable (shape <i>nt</i> x <i>nplist</i> x <i>ny</i> , row-major)
<code>sz</code>	parameter derivative of event output (shape <i>nmax-event</i> x <i>nplist</i> x <i>nz</i> , row-major)
<code>ts</code>	timepoints (shape <i>nt</i>)
<code>ubw</code>	Upper bandwidth of the Jacobian
<code>w</code>	w data from the model (recurring terms in <code>xdot</code> , for imported SBML models from python, this contains the flux vector) (shape <i>nt</i> x <i>nw</i> , row major)
<code>x</code>	state (shape <i>nt</i> x <i>nx</i> , row-major)
<code>x0</code>	initial state (shape <i>nx</i>)
<code>x_ss</code>	preequilibration steady state found by Newton solver (shape <i>nx</i>)
<code>xdot</code>	time derivative (shape <i>nx</i>)
<code>y</code>	observable (shape <i>nt</i> x <i>ny</i> , row-major)
<code>z</code>	event output (shape <i>nmaxevent</i> x <i>nz</i> , row-major)

amici.amici.SecondOrderMode

class `amici.amici.SecondOrderMode(value)`
 An enumeration.

Attributes

 none

 full

 directional

amici.amici.SensitivityMethod

class `amici.amici.SensitivityMethod(value)`
 An enumeration.

Attributes

 none

 forward

 adjoint

amici.amici.SensitivityOrder

class amici.amici.**SensitivityOrder**(*value*)
An enumeration.

Attributes

none

first

second

amici.amici.SimulationParameters

class amici.amici.**SimulationParameters**(*args)
Container for various simulation parameters.

__init__(*args)
Overload 1:

Constructor

Parameters **timepoints** (**DoubleVector**) – Timepoints for which simulation results are requested

Overload 2:

Constructor

Parameters

- **fixedParameters** (**DoubleVector**) – Model constants
- **parameters** (**DoubleVector**) – Model parameters

Overload 3:

Constructor

Parameters

- **fixedParameters** (**DoubleVector**) – Model constants
- **parameters** (**DoubleVector**) – Model parameters
- **plist** (**IntVector**) – Model parameter indices w.r.t. which sensitivities are to be computed

Overload 4:

Constructor

Parameters

- **timepoints** (`DoubleVector`) – Timepoints for which simulation results are requested
- **fixedParameters** (`DoubleVector`) – Model constants
- **parameters** (`DoubleVector`) – Model parameters

Methods Summary

<code>__init__(*args)</code>	Overload 1:
<code>reinitializeAllFixedParameterDependentInitialStates()</code>	Self-initialization of all states based on model constants for all simulation phases.
<code>reinitializeAllFixedParameterDependentInitialStatesPresim()</code>	Self-initialization of all states based on model constants for presimulation (only meaningful if preequilibration is performed).
<code>reinitializeAllFixedParameterDependentInitialStatesSim()</code>	Self-initialization of all states based on model constants for the 'main' simulation (only meaningful if presimulation or preequilibration is performed).

Attributes

<code>fixedParameters</code>	Model constants
<code>fixedParametersPreequilibration</code>	Model constants for pre-equilibration
<code>fixedParametersPresimulation</code>	Model constants for pre-simulation
<code>parameters</code>	Model parameters
<code>plist</code>	Parameter indices w.r.t.
<code>pscale</code>	Parameter scales
<code>reinitialization_state_idxes_presim</code>	Indices of states to be reinitialized based on provided presimulation constants / fixed parameters.
<code>reinitialization_state_idxes_sim</code>	Indices of states to be reinitialized based on provided constants / fixed parameters.
<code>reinitializeFixedParameterInitialStates</code>	Flag indicating whether reinitialization of states depending on fixed parameters is activated
<code>sx0</code>	Initial state sensitivities
<code>t_presim</code>	Duration of pre-simulation.
<code>ts_</code>	Timepoints for which model state/outputs/.
<code>tstart_</code>	starting time
<code>x0</code>	Initial state

Methods

__init__(*args)

Overload 1:

Constructor

Parameters **timepoints** (**DoubleVector**) – Timepoints for which simulation results are requested

Overload 2:

Constructor

Parameters

- **fixedParameters** (**DoubleVector**) – Model constants
- **parameters** (**DoubleVector**) – Model parameters

Overload 3:

Constructor

Parameters

- **fixedParameters** (**DoubleVector**) – Model constants
- **parameters** (**DoubleVector**) – Model parameters
- **plist** (**IntVector**) – Model parameter indices w.r.t. which sensitivities are to be computed

Overload 4:

Constructor

Parameters

- **timepoints** (**DoubleVector**) – Timepoints for which simulation results are requested
- **fixedParameters** (**DoubleVector**) – Model constants
- **parameters** (**DoubleVector**) – Model parameters

reinitializeAllFixedParameterDependentInitialStates(*nx_rdata: int*) → **None**

Set reinitialization of all states based on model constants for all simulation phases.

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters **nx_rdata** (**int**) – Number of states (Model::nx_rdata)

Return type `None`

reinitializeAllFixedParameterDependentInitialStatesForPresimulation(*nx_rdata*: `int`) → `None`

Set reinitialization of all states based on model constants for presimulation (only meaningful if preequilibration is performed).

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters *nx_rdata* (`int`) – Number of states (Model::nx_rdata)

Return type `None`

reinitializeAllFixedParameterDependentInitialStatesForSimulation(*nx_rdata*: `int`) → `None`

Set reinitialization of all states based on model constants for the ‘main’ simulation (only meaningful if presimulation or preequilibration is performed).

Convenience function to populate *reinitialization_state_idxes_presim* and *reinitialization_state_idxes_sim*

Parameters *nx_rdata* (`int`) – Number of states (Model::nx_rdata)

Return type `None`

amici.amici.Solver

class amici.amici.Solver(*args, **kwargs)

The Solver class provides a generic interface to CVODES and IDAS solvers, individual realizations are realized in the CNodeSolver and the IDASolver class. All transient private/protected members (CVODES/IDAS memory, interface variables and status flags) are specified as mutable and not included in serialization or equality checks. No solver setting parameter should be marked mutable.

NOTE: Any changes in data members here must be propagated to copy ctor, equality operator, serialization functions in `serialization.h`, and `amici::hdf5::readSolverSettingsFromHDF5` in `hdf5.cpp`.

__init__(*args, **kwargs)

Methods Summary

<code>__init__(*args, **kwargs)</code>	
<code>clone()</code>	Clone this instance
<code>computingASA()</code>	check if ASA is being computed
<code>computingFSA()</code>	check if FSA is being computed
<code>getAbsoluteTolerance()</code>	Get the absolute tolerances for the forward problem
<code>getAbsoluteToleranceB()</code>	Returns the absolute tolerances for the backward problem for adjoint sensitivity analysis
<code>getAbsoluteToleranceFSA()</code>	Returns the absolute tolerances for the forward sensitivity problem
<code>getAbsoluteToleranceQuadratures()</code>	returns the absolute tolerance for the quadrature problem
<code>getAbsoluteToleranceSteadyState()</code>	returns the absolute tolerance for the steady state problem
<code>getAbsoluteToleranceSteadyStateSensi()</code>	returns the absolute tolerance for the sensitivities of the steady state problem
<code>getCpuTime()</code>	Reads out the CPU time needed for forward solve

continues on next page

Table 33 – continued from previous page

<code>getCpuTimeB()</code>	Reads out the CPU time needed for backward solve
<code>getInternalSensitivityMethod()</code>	returns the internal sensitivity method
<code>getInterpolationType()</code>	rtype amici.InterpolationType
<code>getLastOrder()</code>	Accessor order
<code>getLinearMultistepMethod()</code>	returns the linear system multistep method
<code>getLinearSolver()</code>	rtype amici.LinearSolver
<code>getMaxSteps()</code>	returns the maximum number of solver steps for the forward problem
<code>getMaxStepsBackwardProblem()</code>	returns the maximum number of solver steps for the backward problem
<code>getMaxTime()</code>	Returns the maximum time allowed for integration
<code>getNewtonDampingFactorLowerBound()</code>	Get a lower bound of the damping factor used in the Newton solver
<code>getNewtonDampingFactorMode()</code>	Get a state of the damping factor used in the Newton solver
<code>getNewtonMaxSteps()</code>	Get maximum number of allowed Newton steps for steady state computation
<code>getNewtonStepSteadyStateCheck()</code>	Returns how convergence checks for steadystate computation are performed.
<code>getNonlinearSolverIteration()</code>	returns the nonlinear system solution method
<code>getNumErrTestFails()</code>	Accessor netf
<code>getNumErrTestFailsB()</code>	Accessor netfB
<code>getNumNonlinSolvConvFails()</code>	Accessor nnlscf
<code>getNumNonlinSolvConvFailsB()</code>	Accessor nnlscfB
<code>getNumRhsEvals()</code>	Accessor nrhs
<code>getNumRhsEvalsB()</code>	Accessor nrhsB
<code>getNumSteps()</code>	Accessor ns
<code>getNumStepsB()</code>	Accessor nsB
<code>getRelativeTolerance()</code>	Get the relative tolerances for the forward problem
<code>getRelativeToleranceB()</code>	Returns the relative tolerances for the adjoint sensitivity problem
<code>getRelativeToleranceFSA()</code>	Returns the relative tolerances for the forward sensitivity problem
<code>getRelativeToleranceQuadratures()</code>	Returns the relative tolerance for the quadrature problem
<code>getRelativeToleranceSteadyState()</code>	returns the relative tolerance for the steady state problem
<code>getRelativeToleranceSteadyStateSensi()</code>	returns the relative tolerance for the sensitivities of the steady state problem
<code>getReturnDataReportingMode()</code>	returns the ReturnData reporting mode
<code>getSensiSteadyStateCheck()</code>	Returns how convergence checks for steadystate computation are performed.
<code>getSensitivityMethod()</code>	Return current sensitivity method
<code>getSensitivityMethodPreequilibration()</code>	Return current sensitivity method during preequilibration
<code>getSensitivityOrder()</code>	Get sensitivity order
<code>getStabilityLimitFlag()</code>	returns stability limit detection mode

continues on next page

Table 33 – continued from previous page

<code>getStateOrdering()</code>	Gets KLU / SuperLUMT state ordering mode
<code>gett()</code>	current solver timepoint
<code>nplist()</code>	number of parameters with which the solver was initialized
<code>nquad()</code>	number of quadratures with which the solver was initialized
<code>nx()</code>	number of states with which the solver was initialized
<code>setAbsoluteTolerance(atol)</code>	Sets the absolute tolerances for the forward problem
<code>setAbsoluteToleranceB(atol)</code>	Sets the absolute tolerances for the backward problem for adjoint sensitivity analysis
<code>setAbsoluteToleranceFSA(atol)</code>	Sets the absolute tolerances for the forward sensitivity problem
<code>setAbsoluteToleranceQuadratures(atol)</code>	sets the absolute tolerance for the quadrature problem
<code>setAbsoluteToleranceSteadyState(atol)</code>	sets the absolute tolerance for the steady state problem
<code>setAbsoluteToleranceSteadyStateSensi(atol)</code>	sets the absolute tolerance for the sensitivities of the steady state problem
<code>setInternalSensitivityMethod(ism)</code>	sets the internal sensitivity method
<code>setInterpolationType(interpType)</code>	sets the interpolation of the forward solution that is used for the backwards problem
<code>setLinearMultistepMethod(lmm)</code>	sets the linear system multistep method
<code>setLinearSolver(linsol)</code>	
type linsol amici.LinearSolver	
<code>setMaxSteps(maxsteps)</code>	sets the maximum number of solver steps for the forward problem
<code>setMaxStepsBackwardProblem(maxsteps)</code>	sets the maximum number of solver steps for the backward problem
<code>setMaxTime(maxtime)</code>	Set the maximum time allowed for integration
<code>setNewtonDampingFactorLowerBound(...)</code>	Set a lower bound of the damping factor in the Newton solver
<code>setNewtonDampingFactorMode(dampingFactorMode)</code>	Turn on/off a damping factor in the Newton method
<code>setNewtonMaxSteps(newton_maxsteps)</code>	Set maximum number of allowed Newton steps for steady state computation
<code>setNewtonStepSteadyStateCheck(flag)</code>	Sets how convergence checks for steadystate computation are performed.
<code>setNonlinearSolverIteration(iter)</code>	sets the nonlinear system solution method
<code>setRelativeTolerance(rtol)</code>	Sets the relative tolerances for the forward problem
<code>setRelativeToleranceB(rtol)</code>	Sets the relative tolerances for the adjoint sensitivity problem
<code>setRelativeToleranceFSA(rtol)</code>	Sets the relative tolerances for the forward sensitivity problem
<code>setRelativeToleranceQuadratures(rtol)</code>	sets the relative tolerance for the quadrature problem
<code>setRelativeToleranceSteadyState(rtol)</code>	sets the relative tolerance for the steady state problem
<code>setRelativeToleranceSteadyStateSensi(rtol)</code>	sets the relative tolerance for the sensitivities of the steady state problem
<code>setReturnDataReportingMode(rdrm)</code>	sets the ReturnData reporting mode
<code>setSensiSteadyStateCheck(flag)</code>	Sets for which variables convergence checks for steadystate computation are performed.
<code>setSensitivityMethod(sensi_meth)</code>	Set sensitivity method
<code>setSensitivityMethodPreequilibration(...)</code>	Set sensitivity method for preequilibration

continues on next page

Table 33 – continued from previous page

<code>setSensitivityOrder(sensi)</code>	Set the sensitivity order
<code>setStabilityLimitFlag(stdet)</code>	set stability limit detection mode
<code>setStateOrdering(ordering)</code>	Sets KLU / SuperLUMT state ordering mode
<code>startTimer()</code>	Start timer for tracking integration time
<code>switchForwardSensisOff()</code>	Disable forward sensitivity integration (used in steady state sim)
<code>timeExceeded()</code>	Check whether maximum integration time was exceeded

Attributes

<code>app</code>	AMICI context
------------------	---------------

Methods

`__init__(*args, **kwargs)`

`clone()` → Iterable[[*amici.amici.Solver*](#)]
Clone this instance

Return type [*amici.Solver*](#)

Returns The clone

`computingASA()` → bool
check if ASA is being computed

Return type boolean

Returns flag

`computingFSA()` → bool
check if FSA is being computed

Return type boolean

Returns flag

`getAbsoluteTolerance()` → float
Get the absolute tolerances for the forward problem

Same tolerance is used for the backward problem if not specified differently via `setAbsoluteToleranceASA`.

Return type float

Returns absolute tolerances

`getAbsoluteToleranceB()` → float
Returns the absolute tolerances for the backward problem for adjoint sensitivity analysis

Return type float

Returns absolute tolerances

`getAbsoluteToleranceFSA()` → float
Returns the absolute tolerances for the forward sensitivity problem

Return type float

Returns absolute tolerances

getAbsoluteToleranceQuadratures() → float
 returns the absolute tolerance for the quadrature problem
Return type float
Returns absolute tolerance

getAbsoluteToleranceSteadyState() → float
 returns the absolute tolerance for the steady state problem
Return type float
Returns absolute tolerance

getAbsoluteToleranceSteadyStateSensi() → float
 returns the absolute tolerance for the sensitivities of the steady state problem
Return type float
Returns absolute tolerance

getCpuTime() → float
 Reads out the CPU time needed for forward solve
Return type float
Returns cpu_time

getCpuTimeB() → float
 Reads out the CPU time needed for backward solve
Return type float
Returns cpu_timeB

getInternalSensitivityMethod() → *amici.amici.InternalSensitivityMethod*
 returns the internal sensitivity method
Return type *amici.InternalSensitivityMethod*
Returns internal sensitivity method

getInterpolationType() → *amici.amici.InterpolationType*
Return type *amici.InterpolationType*
Returns

getLastOrder() → *amici.amici.IntVector*
 Accessor order
Return type *IntVector*
Returns order

getLinearMultistepMethod() → *amici.amici.LinearMultistepMethod*
 returns the linear system multistep method
Return type *amici.LinearMultistepMethod*
Returns linear system multistep method

getLinearSolver() → *amici.amici.LinearSolver*
Return type *amici.LinearSolver*

Returns**getMaxSteps()** → *int*

returns the maximum number of solver steps for the forward problem

Return type *int***Returns** maximum number of solver steps**getMaxStepsBackwardProblem()** → *int*

returns the maximum number of solver steps for the backward problem

Return type *int***Returns** maximum number of solver steps**getMaxTime()** → *float*

Returns the maximum time allowed for integration

Return type *float***Returns** Time in seconds**getNewtonDampingFactorLowerBound()** → *float*

Get a lower bound of the damping factor used in the Newton solver

Return type *float***Returns****getNewtonDampingFactorMode()** → *amici.amici.NewtonDampingFactorMode*

Get a state of the damping factor used in the Newton solver

Return type *amici.NewtonDampingFactorMode***Returns****getNewtonMaxSteps()** → *int*

Get maximum number of allowed Newton steps for steady state computation

Return type *int***Returns****getNewtonStepSteadyStateCheck()** → *bool*

Returns how convergence checks for steadystate computation are performed.

Return type *boolean***Returns** boolean flag indicating newton step (true) or the right hand side (false)**getNonlinearSolverIteration()** → *amici.amici.NonlinearSolverIteration*

returns the nonlinear system solution method

Return type *amici.NonlinearSolverIteration***Returns****getNumErrTestFails()** → *amici.amici.IntVector*

Accessor netf

Return type *IntVector***Returns** netf**getNumErrTestFailsB()** → *amici.amici.IntVector*

Accessor netfB

Return type *IntVector*

Returns netfB

getNumNonlinSolvConvFails() → *amici.amici.IntVector*

Accessor nnlsf

Return type *IntVector*

Returns nnlsf

getNumNonlinSolvConvFailsB() → *amici.amici.IntVector*

Accessor nnlsfB

Return type *IntVector*

Returns nnlsfB

getNumRhsEvals() → *amici.amici.IntVector*

Accessor nrhs

Return type *IntVector*

Returns nrhs

getNumRhsEvalsB() → *amici.amici.IntVector*

Accessor nrhsB

Return type *IntVector*

Returns nrhsB

getNumSteps() → *amici.amici.IntVector*

Accessor ns

Return type *IntVector*

Returns ns

getNumStepsB() → *amici.amici.IntVector*

Accessor nsB

Return type *IntVector*

Returns nsB

getRelativeTolerance() → *float*

Get the relative tolerances for the forward problem

Same tolerance is used for the backward problem if not specified differently via setRelativeToleranceASA.

Return type *float*

Returns relative tolerances

getRelativeToleranceB() → *float*

Returns the relative tolerances for the adjoint sensitivity problem

Return type *float*

Returns relative tolerances

getRelativeToleranceFSA() → *float*

Returns the relative tolerances for the forward sensitivity problem

Return type *float*

Returns relative tolerances

getRelativeToleranceQuadratures() → `float`
Returns the relative tolerance for the quadrature problem

Return type `float`

Returns relative tolerance

getRelativeToleranceSteadyState() → `float`
returns the relative tolerance for the steady state problem

Return type `float`

Returns relative tolerance

getRelativeToleranceSteadyStateSensi() → `float`
returns the relative tolerance for the sensitivities of the steady state problem

Return type `float`

Returns relative tolerance

getReturnDataReportingMode() → `amici.amici.RDataReporting`
returns the ReturnData reporting mode

Return type `amici.RDataReporting`

Returns ReturnData reporting mode

getSensiSteadyStateCheck() → `bool`
Returns how convergence checks for steadystate computation are performed.

Return type `boolean`

Returns boolean flag indicating state and sensitivity equations (true) or only state variables (false).

getSensitivityMethod() → `amici.amici.SensitivityMethod`
Return current sensitivity method

Return type `amici.SensitivityMethod`

Returns method enum

getSensitivityMethodPreequilibration() → `amici.amici.SensitivityMethod`
Return current sensitivity method during preequilibration

Return type `amici.SensitivityMethod`

Returns method enum

getSensitivityOrder() → `amici.amici.SensitivityOrder`
Get sensitivity order

Return type `amici.SensitivityOrder`

Returns sensitivity order

getStabilityLimitFlag() → `bool`
returns stability limit detection mode

Return type `boolean`

Returns stldet can be false (deactivated) or true (activated)

getStateOrdering() → `int`
Gets KLU / SuperLUMT state ordering mode

Return type `int`

Returns State-ordering as integer according to `SUNLinSolKLU::StateOrdering` or `SUNLinSolSuperLUMT::StateOrdering` (which differ).

gett() → `float`

current solver timepoint

Return type `float`

Returns `t`

nplist() → `int`

number of parameters with which the solver was initialized

Return type `int`

Returns `sx.getLength()`

nquad() → `int`

number of quadratures with which the solver was initialized

Return type `int`

Returns `xQB.getLength()`

nx() → `int`

number of states with which the solver was initialized

Return type `int`

Returns `x.getLength()`

setAbsoluteTolerance(*atol: float*) → `None`

Sets the absolute tolerances for the forward problem

Same tolerance is used for the backward problem if not specified differently via `setAbsoluteToleranceASA`.

Parameters `atol (float)` – absolute tolerance (non-negative number)

Return type `None`

setAbsoluteToleranceB(*atol: float*) → `None`

Sets the absolute tolerances for the backward problem for adjoint sensitivity analysis

Parameters `atol (float)` – absolute tolerance (non-negative number)

Return type `None`

setAbsoluteToleranceFSA(*atol: float*) → `None`

Sets the absolute tolerances for the forward sensitivity problem

Parameters `atol (float)` – absolute tolerance (non-negative number)

Return type `None`

setAbsoluteToleranceQuadratures(*atol: float*) → `None`

sets the absolute tolerance for the quadrature problem

Parameters `atol (float)` – absolute tolerance (non-negative number)

Return type `None`

setAbsoluteToleranceSteadyState(*atol: float*) → `None`

sets the absolute tolerance for the steady state problem

Parameters `atol (float)` – absolute tolerance (non-negative number)

Return type `None`

setAbsoluteToleranceSteadyStateSensi(*atol*: *float*) → *None*

sets the absolute tolerance for the sensitivities of the steady state problem

Parameters *atol* (*float*) – absolute tolerance (non-negative number)

Return type *None*

setInternalSensitivityMethod(*ism*: *amici.amici.InternalSensitivityMethod*) → *None*

sets the internal sensitivity method

Parameters *ism* (*amici.amici.InternalSensitivityMethod*) – internal sensitivity method

Return type *None*

setInterpolationType(*interpType*: *amici.amici.InterpolationType*) → *None*

sets the interpolation of the forward solution that is used for the backwards problem

Parameters *interpType* (*amici.amici.InterpolationType*) – interpolation type

Return type *None*

setLinearMultistepMethod(*lmm*: *amici.amici.LinearMultistepMethod*) → *None*

sets the linear system multistep method

Parameters *lmm* (*amici.amici.LinearMultistepMethod*) – linear system multistep method

Return type *None*

setLinearSolver(*linsol*: *amici.amici.LinearSolver*) → *None*

Parameters *linsol* (*amici.amici.LinearSolver*) –

Return type *None*

setMaxSteps(*maxsteps*: *int*) → *None*

sets the maximum number of solver steps for the forward problem

Parameters *maxsteps* (*int*) – maximum number of solver steps (positive number)

Return type *None*

setMaxStepsBackwardProblem(*maxsteps*: *int*) → *None*

sets the maximum number of solver steps for the backward problem

Parameters *maxsteps* (*int*) – maximum number of solver steps (non-negative number)

Notes: default behaviour (100 times the value for the forward problem) can be restored by passing *maxsteps*=0

Return type *None*

setMaxTime(*maxtime*: *float*) → *None*

Set the maximum time allowed for integration

Parameters *maxtime* (*float*) – Time in seconds

Return type *None*

setNewtonDampingFactorLowerBound(*dampingFactorLowerBound*: *float*) → *None*

Set a lower bound of the damping factor in the Newton solver

Parameters *dampingFactorLowerBound* (*float*) –

Return type *None*

setNewtonDampingFactorMode(*dampingFactorMode*: `amici.amici.NewtonDampingFactorMode`) → `None`

Turn on/off a damping factor in the Newton method

Parameters `dampingFactorMode` (`amici.amici.NewtonDampingFactorMode`) –

Return type `None`

setNewtonMaxSteps(*newton_maxsteps*: `int`) → `None`

Set maximum number of allowed Newton steps for steady state computation

Parameters `newton_maxsteps` (`int`) –

Return type `None`

setNewtonStepSteadyStateCheck(*flag*: `bool`) → `None`

Sets how convergence checks for steadystate computation are performed.

Parameters `flag` (`bool`) – boolean flag to pick newton step (true) or the right hand side (false, default)

Return type `None`

setNonlinearSolverIteration(*iter*: `amici.amici.NonlinearSolverIteration`) → `None`

sets the nonlinear system solution method

Parameters `iter` (`amici.amici.NonlinearSolverIteration`) – nonlinear system solution method

Return type `None`

setRelativeTolerance(*rtol*: `float`) → `None`

Sets the relative tolerances for the forward problem

Same tolerance is used for the backward problem if not specified differently via `setRelativeToleranceASA`.

Parameters `rtol` (`float`) – relative tolerance (non-negative number)

Return type `None`

setRelativeToleranceB(*rtol*: `float`) → `None`

Sets the relative tolerances for the adjoint sensitivity problem

Parameters `rtol` (`float`) – relative tolerance (non-negative number)

Return type `None`

setRelativeToleranceFSA(*rtol*: `float`) → `None`

Sets the relative tolerances for the forward sensitivity problem

Parameters `rtol` (`float`) – relative tolerance (non-negative number)

Return type `None`

setRelativeToleranceQuadratures(*rtol*: `float`) → `None`

sets the relative tolerance for the quadrature problem

Parameters `rtol` (`float`) – relative tolerance (non-negative number)

Return type `None`

setRelativeToleranceSteadyState(*rtol*: `float`) → `None`

sets the relative tolerance for the steady state problem

Parameters `rtol` (`float`) – relative tolerance (non-negative number)

Return type `None`

setRelativeToleranceSteadyStateSensi(*rtol*: *float*) → *None*

sets the relative tolerance for the sensitivities of the steady state problem

Parameters *rtol* (*float*) – relative tolerance (non-negative number)

Return type *None*

setReturnDataReportingMode(*rdrm*: *amici.amici.RDataReporting*) → *None*

sets the ReturnData reporting mode

Parameters *rdrm* (*amici.amici.RDataReporting*) – ReturnData reporting mode

Return type *None*

setSensiSteadyStateCheck(*flag*: *bool*) → *None*

Sets for which variables convergence checks for steadystate computation are performed.

Parameters *flag* (*bool*) – boolean flag to pick state and sensitivity equations (true, default) or only state variables (false).

Return type *None*

setSensitivityMethod(*sensi_meth*: *amici.amici.SensitivityMethod*) → *None*

Set sensitivity method

Parameters *sensi_meth* (*amici.amici.SensitivityMethod*) –

Return type *None*

setSensitivityMethodPreequilibration(*sensi_meth_preeq*: *amici.amici.SensitivityMethod*) → *None*

Set sensitivity method for preequilibration

Parameters *sensi_meth_preeq* (*amici.amici.SensitivityMethod*) –

Return type *None*

setSensitivityOrder(*sensi*: *amici.amici.SensitivityOrder*) → *None*

Set the sensitivity order

Parameters *sensi* (*amici.amici.SensitivityOrder*) – sensitivity order

Return type *None*

setStabilityLimitFlag(*stldet*: *bool*) → *None*

set stability limit detection mode

Parameters *stldet* (*bool*) – can be false (deactivated) or true (activated)

Return type *None*

setStateOrdering(*ordering*: *int*) → *None*

Sets KLU / SuperLUMT state ordering mode

This only applies when *linsol* is set to *LinearSolver::KLU* or *LinearSolver::SuperLUMT*. Mind the difference between *SUNLinSolKLU::StateOrdering* and *SUNLinSolSuperLUMT::StateOrdering*.

Parameters *ordering* (*int*) – state ordering

Return type *None*

startTimer() → *None*

Start timer for tracking integration time

Return type *None*

switchForwardSensisOff() → *None*

Disable forward sensitivity integration (used in steady state sim)

Return type `None`

timeExceeded() → `bool`

Check whether maximum integration time was exceeded

Return type `boolean`

Returns True if the maximum integration time was exceeded, false otherwise.

amici.amici.SolverPtr

class `amici.amici.SolverPtr(*args)`

Swig-Generated class that implements smart pointers to Solver as objects.

Attributes

<code>app</code>	AMICI context
------------------	---------------

amici.amici.SteadyStateSensitivityMode

class `amici.amici.SteadyStateSensitivityMode(value)`

An enumeration.

Attributes

<code>newtonOnly</code>
<code>integrationOnly</code>
<code>integrateIfNewtonFails</code>

amici.amici.SteadyStateStatus

class `amici.amici.SteadyStateStatus(value)`

An enumeration.

Attributes

<code>failed_too_long_simulation</code>
<code>failed_damping</code>
<code>failed_factorization</code>
<code>failed_convergence</code>

continues on next page

Table 37 – continued from previous page

failed
not_run
success

amici.amici.SteadyStateStatusVector

```
class amici.amici.SteadyStateStatusVector(*args)
```

amici.amici.StringDoubleMap

```
class amici.amici.StringDoubleMap(*args)
```

Swig-Generated class templating Dict [str, float] to facilitate interfacing with C++ bindings.

amici.amici.StringVector

```
class amici.amici.StringVector(*args)
```

Swig-Generated class templating common python types including Iterable [str] and numpy.array [str] to facilitate interfacing with C++ bindings.

Functions Summary

<i>backtraceString</i> (maxFrames)	Returns the current backtrace as std::string
<i>compiledWithOpenMP</i> ()	AMICI extension was compiled with OpenMP?
<i>enum</i> (prefix)	
<i>getScaledParameter</i> (unscaledParameter, scaling)	Apply parameter scaling according to <i>scaling</i>
<i>getUnscaledParameter</i> (scaledParameter, scaling)	Remove parameter scaling according to <i>scaling</i>
<i>parameterScalingFromIntVector</i> (intVec)	Swig-Generated class, which, in contrast to other Vector classes, does not allow for simple interoperability with common Python types, but must be created using <i>amici.amici.parameterScalingFromIntVector()</i>
<i>runAmiciSimulation</i> (solver, edata, model[, ...])	Core integration routine.
<i>runAmiciSimulations</i> (solver, edatas, model, ...)	Same as runAmiciSimulation, but for multiple ExpData instances.
<i>scaleParameters</i> (bufferUnscaled, pscale, ...)	Apply parameter scaling according to <i>scaling</i>
<i>unscaleParameters</i> (bufferScaled, pscale, ...)	Remove parameter scaling according to the parameter scaling in pscale

Functions

`amici.amici.backtraceString(maxFrames: int) → str`

Returns the current backtrace as `std::string`

Parameters `maxFrames` (`int`) – Number of frames to include

Return type `str`

Returns Backtrace

`amici.amici.compiledWithOpenMP() → bool`

AMICI extension was compiled with OpenMP?

Return type `bool`

`amici.amici.enum(prefix)`

`amici.amici.getScaledParameter(unscaledParameter: float, scaling: amici.amici.ParameterScaling) → float`

Apply parameter scaling according to *scaling*

Parameters

- `unscaledParameter` (`float`) –
- `scaling` (`amici.amici.ParameterScaling`) – parameter scaling

Return type `float`

Returns Scaled parameter

`amici.amici.getUnscaledParameter(scaledParameter: float, scaling: amici.amici.ParameterScaling) → float`

Remove parameter scaling according to *scaling*

Parameters

- `scaledParameter` (`float`) – scaled parameter
- `scaling` (`amici.amici.ParameterScaling`) – parameter scaling

Return type `float`

Returns Unscaled parameter

`amici.amici.parameterScalingFromIntVector(intVec: amici.amici.IntVector) →
amici.amici.ParameterScalingVector`

Swig-Generated class, which, in contrast to other Vector classes, does not allow for simple interoperability with common Python types, but must be created using `amici.amici.parameterScalingFromIntVector()`

Return type `amici.amici.ParameterScalingVector`

`amici.amici.runAmiciSimulation(solver: amici.amici.Solver, edata: amici.amici.ExpData, model:
amici.amici.Model, rethrow: bool = False) → amici.amici.ReturnData`

Core integration routine. Initializes the solver and runs the forward and backward problem.

Parameters

- `solver` (`amici.amici.Solver`) – Solver instance
- `edata` (`amici.amici.ExpData`) – pointer to experimental data object
- `model` (`amici.amici.Model`) – model specification object
- `rethrow` (`bool`) – rethrow integration exceptions?

Return type `amici.ReturnData`

Returns rdata pointer to return data object

`amici.amici.runAmiciSimulations(solver: amici.amici.Solver, edatas: amici.amici.ExpDataPtrVector, model: amici.amici.Model, failfast: bool, num_threads: int) → Iterable[amici.amici.ReturnData]`

Same as `runAmiciSimulation`, but for multiple `ExpData` instances. When compiled with OpenMP support, this function runs multi-threaded.

Parameters

- **solver** (`amici.amici.Solver`) – Solver instance
- **edatas** (`amici.amici.ExpDataPtrVector`) – experimental data objects
- **model** (`amici.amici.Model`) – model specification object
- **failfast** (`bool`) – flag to allow early termination
- **num_threads** (`int`) – number of threads for parallel execution

Return type `Iterable[ReturnData]`

Returns vector of pointers to return data objects

`amici.amici.scaleParameters(bufferUnscaled: Iterable[float], pscale: Iterable[amici.amici.ParameterScaling], bufferScaled: Iterable[float]) → None`

Apply parameter scaling according to *scaling*

Parameters

- **bufferUnscaled** (`typing.Iterable[float]`) –
- **pscale** (`typing.Iterable[amici.amici.ParameterScaling]`) – parameter scaling
- **bufferScaled** (`typing.Iterable[float]`) – destination

Return type `None`

`amici.amici.unscaleParameters(bufferScaled: Iterable[float], pscale: Iterable[amici.amici.ParameterScaling], bufferUnscaled: Iterable[float]) → None`

Remove parameter scaling according to the parameter scaling in `pscale`

All vectors must be of same length.

Parameters

- **bufferScaled** (`typing.Iterable[float]`) – scaled parameters
- **pscale** (`typing.Iterable[amici.amici.ParameterScaling]`) – parameter scaling
- **bufferUnscaled** (`typing.Iterable[float]`) – unscaled parameters are written to the array

Return type `None`

10.4.3 amici.sbml_import

SBML Import

This module provides all necessary functionality to import a model specified in the [Systems Biology Markup Language \(SBML\)](#).

Classes

<i>SbmlImporter</i> (sbml_source[, ...])	Class to generate AMICI C++ files for a model provided in the Systems Biology Markup Language (SBML).
------------------------------------------	-------------------------------------------------------------------------------------------------------

amici.sbml_import.SbmlImporter

class amici.sbml_import.**SbmlImporter**(*sbml_source*, *show_sbml_warnings=False*, *from_file=True*)
 Class to generate AMICI C++ files for a model provided in the Systems Biology Markup Language (SBML).

Variables

- **show_sbml_warnings** – indicates whether libSBML warnings should be displayed
- **symbols** – dict carrying symbolic definitions
- **sbml_reader** – The libSBML sbml reader

Warning: Not storing this may result in a segfault.

- **sbml_doc** – document carrying the sbml definition

Warning: Not storing this may result in a segfault.

- **sbml** – SBML model to import
- **compartments** – dict of compartment ids and compartment volumes
- **stoichiometric_matrix** – stoichiometric matrix of the model
- **flux_vector** – reaction kinetic laws
- **flux_ids** – identifiers for elements of flux_vector
- **_local_symbols** – model symbols for sympy to consider during sympification see *locals* argument in `'sympy.sympify`
- **species_assignment_rules** – Assignment rules for species. Key is symbolic identifier and value is assignment value
- **compartment_assignment_rules** – Assignment rules for compartments. Key is symbolic identifier and value is assignment value
- **parameter_assignment_rules** – assignment rules for parameters, these parameters are not permissible for sensitivity analysis
- **initial_assignments** – initial assignments for parameters, these parameters are not permissible for sensitivity analysis
- **sbml_parser_settings** – sets behaviour of SBML Formula parsing

__init__(*sbml_source*, *show_sbml_warnings=False*, *from_file=True*)
 Create a new Model instance.

Parameters

- **sbml_source** (`typing.Union[str, libsbml.Model]`) – Either a path to SBML file where the model is specified, or a model string as created by `sbml.sbmlWriter().writeSBMLToString()` or an instance of `libsbml.Model`.
- **show_sbml_warnings** (`bool`) – Indicates whether libSBML warnings should be displayed.
- **from_file** (`bool`) – Whether *sbml_source* is a file name (True, default), or an SBML string

Methods Summary

<code>__init__(sbml_source[, show_sbml_warnings, ...])</code>	Create a new Model instance.
<code>add_d_dt(d_dt, variable, variable0, name)</code>	Creates or modifies species, to implement rate rules for compartments and species, respectively.
<code>add_local_symbol(key, value)</code>	Add local symbols with some sanity checking for duplication which would indicate redefinition of internals, which SBML permits, but we don't.
<code>check_event_support()</code>	Check possible events in the model, as AMICI does currently not support
<code>check_support()</code>	Check whether all required SBML features are supported.
<code>is_assignment_rule_target(element)</code>	Checks if an element has a valid assignment rule in the specified model.
<code>is_rate_rule_target(element)</code>	Checks if an element has a valid assignment rule in the specified model.
<code>process_conservation_laws(ode_model)</code>	Find conservation laws in reactions and species.
<code>sbml2amici([model_name, output_dir, ...])</code>	Generate and compile AMICI C++ files for the model provided to the constructor.

Methods

`__init__(sbml_source, show_sbml_warnings=False, from_file=True)`

Create a new Model instance.

Parameters

- **sbml_source** (`typing.Union[str, libsbml.Model]`) – Either a path to SBML file where the model is specified, or a model string as created by `sbml.sbmlWriter().writeSBMLToString()` or an instance of `libsbml.Model`.
- **show_sbml_warnings** (`bool`) – Indicates whether libSBML warnings should be displayed.
- **from_file** (`bool`) – Whether *sbml_source* is a file name (True, default), or an SBML string

`add_d_dt(d_dt, variable, variable0, name)`

Creates or modifies species, to implement rate rules for compartments and species, respectively.

Parameters

- **d_dt** (`sympy.core.expr.Expr`) – The rate rule (or, right-hand side of an ODE).
- **variable** (`sympy.core.symbol.Symbol`) – The subject of the rate rule.

- **variable0** (`typing.Union[float, sympy.core.expr.Expr]`) – The initial value of the variable.
- **name** (`str`) – Species name, only applicable if this function generates a new species

Return type `None`

add_local_symbol (*key*, *value*)

Add local symbols with some sanity checking for duplication which would indicate redefinition of internals, which SBML permits, but we don't.

Parameters

- **key** (`str`) – local symbol key
- **value** (`sympy.core.expr.Expr`) – local symbol value

check_event_support ()

Check possible events in the model, as AMICI does currently not support

- delays in events
- priorities of events
- events fired at initial time

Furthermore, event triggers are optional (e.g., if an event is fired at initial time, no trigger function is necessary). In this case, warn that this event will have no effect.

Return type `None`

check_support ()

Check whether all required SBML features are supported. Also ensures that the SBML contains at least one reaction, or rate rule, or assignment rule, to produce change in the system over time.

Return type `None`

is_assignment_rule_target (*element*)

Checks if an element has a valid assignment rule in the specified model.

Parameters **element** (`libsbml.SBase`) – SBML variable

Return type `bool`

Returns boolean indicating truth of function name

is_rate_rule_target (*element*)

Checks if an element has a valid assignment rule in the specified model.

Parameters **element** (`libsbml.SBase`) – SBML variable

Return type `bool`

Returns boolean indicating truth of function name

process_conservation_laws (*ode_model*)

Find conservation laws in reactions and species.

Parameters **ode_model** – ODEModel object with basic definitions

Return type `None`

```
sbml2amici(model_name=None, output_dir=None, observables=None, constant_parameters=None,
            sigmas=None, noise_distributions=None, verbose=40, assume_pow_positivity=False,
            compiler=None, allow_reinit_fixpar_initcond=True, compile=True,
            compute_conservation_laws=True, simplify=<function SbmlImporter.<lambda>>,
            cache_simplify=False, log_as_log10=True, generate_sensitivity_code=True, **kwargs)
```

Generate and compile AMICI C++ files for the model provided to the constructor.

The resulting model can be imported as a regular Python module (if *compile=True*), or used from Matlab or C++ as described in the documentation of the respective AMICI interface.

Note that this generates model ODEs for changes in concentrations, not amounts unless the *hasOnlySubstanceUnits* attribute has been defined for a particular species.

Sensitivity analysis for local parameters is enabled by creating global parameters `_reactionId_{localParameterName}`.

Parameters

- **model_name** (`typing.Optional[str]`) – name of the model/model directory
- **output_dir** (`typing.Optional[str]`) – see `amici.ode_export.ODEExporter.set_paths()`
- **observables** (`typing.Optional[typing.Dict[str, typing.Dict[str, str]]]`) – dictionary(observableId: { 'name': observableName (optional), 'formula': formulaString }) to be added to the model
- **constant_parameters** (`typing.Optional[typing.Iterable[str]]`) – list of SBML Ids identifying constant parameters
- **sigmas** (`typing.Optional[typing.Dict[str, typing.Union[str, float]]]`) – dictionary(observableId: sigma value or (existing) parameter name)
- **noise_distributions** (`typing.Optional[typing.Dict[str, typing.Union[str, typing.Callable]]]`) – dictionary(observableId: noise type). If nothing is passed for some observable id, a normal model is assumed as default. Either pass a noise type identifier, or a callable generating a custom noise string.
- **verbose** (`typing.Union[int, bool]`) – verbosity level for logging, True/False default to logging.Error/logging.DEBUG
- **assume_pow_positivity** (`bool`) – if set to True, a special pow function is used to avoid problems with state variables that may become negative due to numerical errors
- **compiler** (`typing.Optional[str]`) – distutils/setuptools compiler selection to build the python extension
- **allow_reinit_fixpar_initcond** (`bool`) – see `amici.ode_export.ODEExporter`
- **compile** (`bool`) – If True, compile the generated Python package, if False, just generate code.
- **compute_conservation_laws** (`bool`) – if set to True, conservation laws are automatically computed and applied such that the state-jacobian of the ODE right-hand-side has full rank. This option should be set to True when using the Newton algorithm to compute steadystate sensitivities. Conservation laws for constant species are enabled by default. Support for conservation laws for non-constant species is experimental and may be enabled by setting an environment variable `AMICI_EXPERIMENTAL_SBML_NONCONST_CLS` to either `demartino` to use the algorithm proposed by De Martino et al. (2014) <https://doi.org/10.1371/journal.pone.0100750>, or to any other value to use the deterministic algorithm implemented in `conserved_moieties2.py`. In some cases, the `demartino` may

run for a very long time. This has been observed for example in the case of stoichiometric coefficients with many significant digits.

- **simplify** (`typing.Callable`) – see `ODEModel._simplify`
- **cache_simplify** (`bool`) – see `amici.ODEModel.__init__()`
- **log_as_log10** (`bool`) – If True, log in the SBML model will be parsed as `log10` (default), if False, log will be parsed as natural logarithm `ln`
- **generate_sensitivity_code** (`bool`) – If False, the code required for sensitivity computation will not be generated

Return type `None`

Functions Summary

<code>assignmentRules2observables</code> (<code>sbml_model</code> [, ...])	Turn assignment rules into observables.
<code>get_species_initial</code> (<code>species</code>)	Extract the initial concentration from a given species
<code>replace_logx</code> (<code>math_str</code>)	Replace <code>logX(.)</code> by <code>log(., X)</code> since sympy cannot parse the former

Functions

`amici.sbml_import.assignmentRules2observables`(`sbml_model`, `filter_function`=<function <lambda>>)
Turn assignment rules into observables.

Parameters

- **sbml_model** (`libsbml.Model`) – Model to operate on
- **filter_function** (`typing.Callable`) – Callback function taking assignment variable as input and returning True/False to indicate if the respective rule should be turned into an observable.

Returns A dictionary(`observableId`:{ 'name': observableName, 'formula': formulaString })

`amici.sbml_import.get_species_initial`(`species`)
Extract the initial concentration from a given species

Parameters **species** (`libsbml.Species`) – species index

Return type `sympy.core.expr.Expr`

Returns initial species concentration

`amici.sbml_import.replace_logx`(`math_str`)
Replace `logX(.)` by `log(., X)` since sympy cannot parse the former

Parameters **math_str** (`typing.Union[str, float, None]`) – string for sympification

Return type `typing.Union[str, float, None]`

Returns sympifiable string

10.4.4 amici.pysb_import

PySB Import

This module provides all necessary functionality to import a model specified in the `pysb.core.Model` format.

Functions Summary

<code>extract_monomers</code> (<code>complex_patterns</code>)	Constructs a list of monomer names contained in complex patterns.
<code>has_fixed_parameter_ic</code> (<code>specie</code> , <code>pysb_model</code> , ...)	Wrapper to interface <code>ode_export.ODEModel.state_has_fixed_parameter_initial_condition()</code> from a <code>pysb</code> <code>specie</code> / <code>model</code> arguments
<code>ode_model_from_pysb_importer</code> (<code>model</code> [, ...])	Creates an <code>amici.ODEModel</code> instance from a <code>pysb.Model</code> instance.
<code>pysb2amici</code> (<code>model</code> [, <code>output_dir</code> , <code>observables</code> , ...])	Generate AMICI C++ files for the provided model.
<code>pysb_model_from_path</code> (<code>pysb_model_file</code>)	Load a <code>pysb</code> model module and return the <code>pysb.Model</code> instance

Functions

`amici.pysb_import.extract_monomers`(*complex_patterns*)

Constructs a list of monomer names contained in complex patterns. Multiplicity of names corresponds to the stoichiometry in the complex.

Parameters `complex_patterns` (`typing.Union`[`pysb.core.ComplexPattern`, `typing.List`[`pysb.core.ComplexPattern`]]) – (list of) complex pattern(s)

Return type `typing.List`[`str`]

Returns list of monomer names

`amici.pysb_import.has_fixed_parameter_ic`(*specie*, *pysb_model*, *ode_model*)

Wrapper to interface `ode_export.ODEModel.state_has_fixed_parameter_initial_condition()` from a `pysb` `specie`/`model` arguments

Parameters

- **specie** (`pysb.core.ComplexPattern`) – `pysb` species
- **pysb_model** (`pysb.core.Model`) – `pysb` model
- **ode_model** (`amici.ode_export.ODEModel`) – ODE model

Return type `bool`

Returns False if the species does not have an initial condition at all. Otherwise the return value of `ode_export.ODEModel.state_has_fixed_parameter_initial_condition()`

`amici.pysb_import.ode_model_from_pysb_importer`(*model*, *constant_parameters*=None, *observables*=None, *sigmas*=None, *noise_distributions*=None, *compute_conservation_laws*=True, *simplify*=<function powsimp>, *cache_simplify*=False, *verbose*=False)

Creates an `amici.ODEModel` instance from a `pysb.Model` instance.

Parameters

- **model** (`pysb.core.Model`) – see `amici.pysb_import.pysb2amici()`
- **constant_parameters** (`typing.Optional[typing.List[str]]`) – see `amici.pysb_import.pysb2amici()`
- **observables** (`typing.Optional[typing.List[str]]`) – see `amici.pysb_import.pysb2amici()`
- **sigmas** (`typing.Optional[typing.Dict[str, str]]`) – dict with names of observable Expressions as keys and names of sigma Expressions as value sigma
- **noise_distributions** (`typing.Optional[typing.Dict[str, typing.Union[str, typing.Callable]]]`) – see `amici.pysb_import.pysb2amici()`
- **compute_conservation_laws** (`bool`) – see `amici.pysb_import.pysb2amici()`
- **simplify** (`typing.Callable`) – see `amici.ODEModel._simplify`
- **cache_simplify** (`bool`) – see `amici.ODEModel.__init__()` Note that there are possible issues with PySB models: <https://github.com/AMICI-dev/AMICI/pull/1672>
- **verbose** (`typing.Union[int, bool]`) – verbosity level for logging, True/False default to `logging.DEBUG/logging.ERROR`

Return type `amici.ode_export.ODEModel`

Returns New ODEModel instance according to `pysbModel`

```
amici.pysb_import.pysb2amici(model, output_dir=None, observables=None, constant_parameters=None,
                             sigmas=None, noise_distributions=None, verbose=False,
                             assume_pow_positivity=False, compiler=None,
                             compute_conservation_laws=True, compile=True, simplify=<function
                             <lambda>>, cache_simplify=False, generate_sensitivity_code=True)
```

Generate AMICI C++ files for the provided model.

Warning: PySB models with Compartments

When importing a PySB model with `pysb.Compartments`, BioNetGen scales reaction fluxes with the compartment size. Instead of using the respective symbols, the compartment size Parameter or Expression is evaluated when generating equations. This may lead to unexpected results if the compartment size parameter is changed for AMICI simulations.

Parameters

- **model** (`pysb.core.Model`) – `pysb.Model.name` will determine the name of the generated module
- **output_dir** (`typing.Optional[str]`) – see `amici.ode_export.ODEExporter.set_paths()`
- **observables** (`typing.Optional[typing.List[str]]`) – list of `pysb.core.Expression` or `pysb.core.Observable` names in the provided model that should be mapped to observables
- **sigmas** (`typing.Optional[typing.Dict[str, str]]`) – dict of `pysb.core.Expression` names that should be mapped to sigmas
- **noise_distributions** (`typing.Optional[typing.Dict[str, typing.Union[str, typing.Callable]]]`) – dict with names of observable Expressions as keys and a noise

type identifier, or a callable generating a custom noise formula string (see `amici.import_utils.noise_distribution_to_cost_function()`). If nothing is passed for some observable id, a normal model is assumed as default.

- **constant_parameters** (`typing.Optional[typing.List[str]]`) – list of `pysb.core.Parameter` names that should be mapped as fixed parameters
- **verbose** (`typing.Union[int, bool]`) – verbosity level for logging, True/False default to `logging.DEBUG/logging.ERROR`
- **assume_pow_positivity** (`bool`) – if set to True, a special pow function is used to avoid problems with state variables that may become negative due to numerical errors
- **compiler** (`typing.Optional[str]`) – distutils/setuptools compiler selection to build the python extension
- **compute_conservation_laws** (`bool`) – if set to True, conservation laws are automatically computed and applied such that the state-jacobian of the ODE right-hand-side has full rank. This option should be set to True when using the Newton algorithm to compute steadystates
- **compile** (`bool`) – If True, build the python module for the generated model. If false, just generate the source code.
- **simplify** (`typing.Callable`) – see `amici.ODEModel._simplify`
- **cache_simplify** (`bool`) – see `amici.ODEModel.__init__()` Note that there are possible issues with PySB models: <https://github.com/AMICI-dev/AMICI/pull/1672>
- **generate_sensitivity_code** (`bool`) – if set to False, code for sensitivity computation will not be generated

`amici.pysb_import.pysb_model_from_path(pysb_model_file)`

Load a pysb model module and return the `pysb.Model` instance

Parameters `pysb_model_file` (`str`) – Full or relative path to the PySB model module

Return type `pysb.core.Model`

Returns The pysb Model instance

10.4.5 amici.bngl_import

BNGL Import

This module provides all necessary functionality to import a model specified in the *BNGL* format.

Functions Summary

<code>bngl2amici(bngl_model, *args, **kwargs)</code>	Generate AMICI C++ files for the provided model.
------------------------------------------------------	--------------------------------------------------

Functions

`amici.bngl_import.bngl2amici(bngl_model, *args, **kwargs)`

Generate AMICI C++ files for the provided model.

Parameters

- **bngl_model** (`str`) – bngl model file, model name will determine the name of the generated module
- **args** – see `amici.pysb_import.pysb2amici()` for additional arguments
- **kwargs** – see `amici.pysb_import.pysb2amici()` for additional arguments

Return type `None`

10.4.6 amici.petab_import

PEtab Import

Import a model in the petab (<https://github.com/PEtab-dev/PEtab>) format into AMICI.

Functions Summary

<code>constant_species_to_parameters(sbml_model)</code>	Convert constant species in the SBML model to constant parameters.
<code>get_fixed_parameters(sbml_model[, ...])</code>	Determine, set and return fixed model parameters.
<code>get_observation_model(observable_df)</code>	Get observables, sigmas, and noise distributions from PETA tab observation table in a format suitable for <code>amici.sbml_import.SbmlImporter.sbml2amici()</code> .
<code>import_model(sbml_model[, condition_table, ...])</code>	Create AMICI model from PETA tab problem
<code>import_model_sbml(sbml_model[, ...])</code>	Create AMICI model from PETA tab problem
<code>import_petab_problem(petab_problem[, ...])</code>	Import model from petab problem.
<code>main()</code>	Command line interface to import a model in the PETA tab (https://github.com/PEtab-dev/PEtab/) format into AMICI.
<code>petab_noise_distributions_to_amici(observable_df)</code>	Map from the petab to the amici format of noise distribution identifiers.
<code>petab_scale_to_amici_scale(scale_str)</code>	Convert PETA tab parameter scaling string to AMICI scaling integer
<code>show_model_info(sbml_model)</code>	Log some model quantities
<code>species_to_parameters(species_ids, sbml_model)</code>	Turn a SBML species into parameters and replace species references inside the model instance.

Functions

`amici.petab_import.constant_species_to_parameters(sbml_model)`

Convert constant species in the SBML model to constant parameters.

This can be used e.g. for setting up models with condition-specific constant species for PETab, since there it is not possible to specify constant species in the condition table.

Parameters `sbml_model` (`libsbml.Model`) – SBML Model

Return type `typing.List[str]`

Returns List of IDs of SBML species that have been turned into constants

`amici.petab_import.get_fixed_parameters(sbml_model, condition_df=None,
 const_species_to_parameters=False)`

Determine, set and return fixed model parameters.

Parameters specified in *condition_df* are turned into constants. Only global SBML parameters are considered. Local parameters are ignored.

Parameters

- **condition_df** (`typing.Optional[pandas.core.frame.DataFrame]`) – PETab condition table. If provided, the respective parameters will be turned into AMICI constant parameters.
- **sbml_model** (`libsbml.Model`) – `libsbml.Model` instance
- **const_species_to_parameters** (`bool`) – If *True*, species which are marked constant within the SBML model will be turned into constant parameters *within* the given *sbml_model*.

Return type `typing.List[str]`

Returns List of IDs of parameters which are to be considered constant.

`amici.petab_import.get_observation_model(observable_df)`

Get observables, sigmas, and noise distributions from PETab observation table in a format suitable for [amici.sbml_import.SbmlImporter.sbml2amici\(\)](#).

Parameters `observable_df` (`pandas.core.frame.DataFrame`) – PETab observables table

Return type `typing.Tuple[typing.Dict[str, typing.Dict[str, str]], typing.Dict[str, str], typing.Dict[str, typing.Union[str, float]]]`

Returns Tuple of dicts with observables, noise distributions, and sigmas.

`amici.petab_import.import_model(sbml_model, condition_table=None, observable_table=None,
 measurement_table=None, model_name=None, model_output_dir=None,
 verbose=True, allow_reinit_fixpar_initcond=True, **kwargs)`

Create AMICI model from PETab problem

Parameters

- **sbml_model** (`typing.Union[str, libsbml.Model]`) – PETab SBML model or SBML file name.
- **condition_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab condition table. If provided, parameters from there will be turned into AMICI constant parameters (i.e. parameters w.r.t. which no sensitivities will be computed).
- **observable_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab observable table.

- **measurement_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab measurement table.
- **model_name** (`typing.Optional[str]`) – Name of the generated model. If model file name was provided, this defaults to the file name without extension, otherwise the SBML model ID will be used.
- **model_output_dir** (`typing.Optional[str]`) – Directory to write the model code to. Will be created if doesn't exist. Defaults to current directory.
- **verbose** (`typing.Union[bool, int, None]`) – Print/log extra information.
- **allow_reinit_fixpar_initcond** (`bool`) – See [amici.ode_export.ODEExporter](#). Must be enabled if initial states are to be reset after preequilibration.
- **kwargs** – Additional keyword arguments to be passed to [amici.sbml_import.SbmlImporter.sbml2amici\(\)](#).

Return type [amici.sbml_import.SbmlImporter](#)

Returns The created [amici.sbml_import.SbmlImporter](#) instance.

```
amici.petab_import.import_model_sbml(sbml_model, condition_table=None, observable_table=None,
                                     measurement_table=None, model_name=None,
                                     model_output_dir=None, verbose=True,
                                     allow_reinit_fixpar_initcond=True, **kwargs)
```

Create AMICI model from PETab problem

Parameters

- **sbml_model** (`typing.Union[str, libsbml.Model]`) – PETab SBML model or SBML file name.
- **condition_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab condition table. If provided, parameters from there will be turned into AMICI constant parameters (i.e. parameters w.r.t. which no sensitivities will be computed).
- **observable_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab observable table.
- **measurement_table** (`typing.Union[str, pandas.core.frame.DataFrame, None]`) – PETab measurement table.
- **model_name** (`typing.Optional[str]`) – Name of the generated model. If model file name was provided, this defaults to the file name without extension, otherwise the SBML model ID will be used.
- **model_output_dir** (`typing.Optional[str]`) – Directory to write the model code to. Will be created if doesn't exist. Defaults to current directory.
- **verbose** (`typing.Union[bool, int, None]`) – Print/log extra information.
- **allow_reinit_fixpar_initcond** (`bool`) – See [amici.ode_export.ODEExporter](#). Must be enabled if initial states are to be reset after preequilibration.
- **kwargs** – Additional keyword arguments to be passed to [amici.sbml_import.SbmlImporter.sbml2amici\(\)](#).

Return type [amici.sbml_import.SbmlImporter](#)

Returns The created [amici.sbml_import.SbmlImporter](#) instance.

```
amici.petab_import.import_petab_problem(petab_problem, model_output_dir=None, model_name=None,  
                                         force_compile=False, **kwargs)
```

Import model from petab problem.

Parameters

- **petab_problem** (`petab.problem.Problem`) – A petab problem containing all relevant information on the model.
- **model_output_dir** (`typing.Optional[str]`) – Directory to write the model code to. Will be created if doesn't exist. Defaults to current directory.
- **model_name** (`typing.Optional[str]`) – Name of the generated model. If model file name was provided, this defaults to the file name without extension, otherwise the SBML model ID will be used.
- **force_compile** (`bool`) – Whether to compile the model even if the target folder is not empty, or the model exists already.
- **kwargs** – Additional keyword arguments to be passed to `amici.sbml_import.SbmlImporter.sbml2amici()`.

Return type `amici.amici.Model`

Returns The imported model.

```
amici.petab_import.main()
```

Command line interface to import a model in the PETab (<https://github.com/PETab-dev/PETab/>) format into AMICI.

```
amici.petab_import.petab_noise_distributions_to_amici(observable_df)
```

Map from the petab to the amici format of noise distribution identifiers.

Parameters **observable_df** (`pandas.core.frame.DataFrame`) – PETab observable table

Return type `typing.Dict[str, str]`

Returns Dictionary of observable_id => AMICI noise-distributions

```
amici.petab_import.petab_scale_to_amici_scale(scale_str)
```

Convert PETab parameter scaling string to AMICI scaling integer

Return type `int`

```
amici.petab_import.show_model_info(sbml_model)
```

Log some model quantities

```
amici.petab_import.species_to_parameters(species_ids, sbml_model)
```

Turn a SBML species into parameters and replace species references inside the model instance.

Parameters

- **species_ids** (`typing.List[str]`) – List of SBML species ID to convert to parameters with the same ID as the replaced species.
- **sbml_model** (`libsbml.Model`) – SBML model to modify

Return type `typing.List[str]`

Returns List of IDs of species which have been converted to parameters

10.4.7 amici.petab_import_pysb

PySB-PEtab Import

Import a model in the PySB-adapted petab (<https://github.com/PEtab-dev/PEtab>) format into AMICI.

Classes

<code>PysbPetabProblem([pysb_model])</code>	Representation of a PySB-model-based PETA problem
---------------------------------------------	---------------------------------------------------

amici.petab_import_pysb.PysbPetabProblem

class amici.petab_import_pysb.**PysbPetabProblem**(*pysb_model=None, *args, **kwargs*)

Representation of a PySB-model-based PETA problem

This class extends `petab.Problem` with a PySB model. The model is augmented with the observation model based on the PETA observable table. For now, a dummy SBML model is created which allows used the existing SBML-PEtab API.

Variables `pysb_model` – PySB model instance from of this PETA problem.

`__init__`(*pysb_model=None, *args, **kwargs*)

Constructor

Parameters

- **pysb_model** (`typing.Optional[pysb.core.Model]`) – PySB model instance for this PETA problem
- **args** – See `petab.Problem.__init__()`
- **kwargs** – See `petab.Problem.__init__()`

Methods Summary

<code>__init__([pysb_model])</code>	Constructor
<code>create_parameter_df(*args, **kwargs)</code>	Create a new PETA parameter table
<code>from_combine(filename)</code>	Read PETA COMBINE archive (http://co.mbine.org/documents/archive).
<code>from_files([condition_file, ...])</code>	Factory method to load model and tables from files.
<code>from_folder(folder[, model_name])</code>	Factory method to use the standard folder structure and file names, i.e.
<code>from_yaml(yaml_config[, flatten])</code>	Factory method to load model and tables as specified by YAML file.
<code>get_lb([free, fixed, scaled])</code>	Generic function to get lower parameter bounds.
<code>get_model_parameters()</code>	See <code>petab.sbml.get_model_parameters()</code>
<code>get_noise_distributions()</code>	See <code>petab.get_noise_distributions()</code> .
<code>get_observable_ids()</code>	Returns dictionary of observable ids.
<code>get_observables([remove])</code>	Returns dictionary of observables definitions.
<code>get_optimization_parameter_scales()</code>	Return list of optimization parameter scaling strings.
<code>get_optimization_parameters()</code>	Return list of optimization parameter IDs.
<code>get_optimization_to_simulation_parameter_mapping()</code>	See <code>petab.get_optimization_to_simulation_parameter_mapping()</code>

continues on next page

Table 46 – continued from previous page

<code>get_sigmas([remove])</code>	Return dictionary of observableId => sigma as defined in the SBML model.
<code>get_simulation_conditions_from_measurement_df()</code>	See <code>petab.get_simulation_conditions</code>
<code>get_ub([free, fixed, scaled])</code>	Generic function to get upper parameter bounds.
<code>get_x_ids([free, fixed])</code>	Generic function to get parameter ids.
<code>get_x_nominal([free, fixed, scaled])</code>	Generic function to get parameter nominal values.
<code>sample_parameter_startpoints([n_starts])</code>	Create starting points for optimization
<code>scale_parameters(x_dict)</code>	Scale parameter values.
<code>to_files([sbml_file, condition_file, ...])</code>	Write PETab tables to files for this problem
<code>to_files_generic(prefix_path)</code>	Save a PETab problem to generic file names.
<code>unscale_parameters(x_dict)</code>	Unscale parameter values.

Attributes

<code>lb</code>	Parameter table lower bounds.
<code>lb_scaled</code>	Parameter table lower bounds with applied parameter scaling
<code>ub</code>	Parameter table upper bounds
<code>ub_scaled</code>	Parameter table upper bounds with applied parameter scaling
<code>x_fixed_ids</code>	Parameter table parameter IDs, for fixed parameters.
<code>x_fixed_indices</code>	Parameter table non-estimated parameter indices.
<code>x_free_ids</code>	Parameter table parameter IDs, for free parameters.
<code>x_free_indices</code>	Parameter table estimated parameter indices.
<code>x_ids</code>	Parameter table parameter IDs
<code>x_nominal</code>	Parameter table nominal values
<code>x_nominal_fixed</code>	Parameter table nominal values, for fixed parameters.
<code>x_nominal_fixed_scaled</code>	Parameter table nominal values with applied parameter scaling, for fixed parameters.
<code>x_nominal_free</code>	Parameter table nominal values, for free parameters.
<code>x_nominal_free_scaled</code>	Parameter table nominal values with applied parameter scaling, for free parameters.
<code>x_nominal_scaled</code>	Parameter table nominal values with applied parameter scaling

Methods

`__init__(pysb_model=None, *args, **kwargs)`
 Constructor

Parameters

- **pysb_model** (`typing.Optional[pysb.core.Model]`) – PySB model instance for this PETab problem
- **args** – See `petab.Problem.__init__()`
- **kwargs** – See `petab.Problem.__init__()`

`create_parameter_df(*args, **kwargs)`
 Create a new PETab parameter table

See `create_parameter_df()`.

static from_combine(*filename*)

Read PETab COMBINE archive (<http://co.mbine.org/documents/archive>).

See also `petab.create_combine_archive()`.

Parameters **filename** (`typing.Union[pathlib.Path, str]`) – Path to the PETab-COMBINE archive

Return type `petab.problem.Problem`

Returns A `petab.Problem` instance.

static from_files(*condition_file=None, measurement_file=None, parameter_file=None, visualization_files=None, observable_files=None, pysb_model_file=None, flatten=False*)

Factory method to load model and tables from files.

Parameters

- **condition_file** (`typing.Optional[str]`) – PETab condition table
- **measurement_file** (`typing.Union[str, typing.Iterable[str], None]`) – PETab measurement table
- **parameter_file** (`typing.Union[str, typing.List[str], None]`) – PETab parameter table
- **visualization_files** (`typing.Union[str, typing.Iterable[str], None]`) – PETab visualization tables
- **observable_files** (`typing.Union[str, typing.Iterable[str], None]`) – PETab observables tables
- **pysb_model_file** (`typing.Optional[str]`) – PySB model file
- **flatten** (`bool`) – Flatten the petab problem

Return type `amici.petab_import_pysb.PysbPetabProblem`

Returns Petab Problem

static from_folder(*folder, model_name=None*)

Factory method to use the standard folder structure and file names, i.e.

```
${model_name}/
+-- experimentalCondition_${model_name}.tsv
+-- measurementData_${model_name}.tsv
+-- model_${model_name}.xml
+-- parameters_${model_name}.tsv
```

Parameters

- **folder** (`str`) – Path to the directory in which the files are located.
- **model_name** (`typing.Optional[str]`) – If specified, overrides the model component in the file names. Defaults to the last component of `folder`.

Return type `petab.problem.Problem`

static from_yaml(*yaml_config, flatten=False*)

Factory method to load model and tables as specified by YAML file.

NOTE: The PySB model is currently expected in the YAML file under `sbml_files`.

Parameters

- **yaml_config** (`typing.Union[typing.Dict, str]`) – PETab configuration as dictionary or YAML file name
- **flatten** (`bool`) – Flatten the petab problem

Return type `amici.petab_import_pysb.PysbPetabProblem`

Returns Petab Problem

get_lb(*free=True, fixed=True, scaled=False*)

Generic function to get lower parameter bounds.

Parameters

- **free** (`bool`) – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** (`bool`) – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** (`bool`) – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns

Return type The lower parameter bounds.

get_model_parameters()

See `petab.sbml.get_model_parameters()`

get_noise_distributions()

See `petab.get_noise_distributions()`.

get_observable_ids()

Returns dictionary of observable ids.

get_observables(*remove=False*)

Returns dictionary of observables definitions.

See `petab.assignment_rules_to_dict()` for details.

get_optimization_parameter_scales()

Return list of optimization parameter scaling strings.

See `petab.parameters.get_optimization_parameters()`.

get_optimization_parameters()

Return list of optimization parameter IDs.

See `petab.parameters.get_optimization_parameters()`.

get_optimization_to_simulation_parameter_mapping(*warn_unmapped=True,*

scaled_parameters=False, al-

low_timepoint_specific_numeric_noise_parameters=False)

See `get_simulation_to_optimization_parameter_mapping`.

get_sigmas(*remove=False*)

Return dictionary of observableId => sigma as defined in the SBML model.

This does not include parameter mappings defined in the measurement table.

get_simulation_conditions_from_measurement_df()

See `petab.get_simulation_conditions`

get_ub(*free=True, fixed=True, scaled=False*)

Generic function to get upper parameter bounds.

Parameters

- **free** (*bool*) – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** (*bool*) – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** (*bool*) – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns

Return type The upper parameter bounds.

get_x_ids(*free=True, fixed=True*)

Generic function to get parameter ids.

Parameters

- **free** (*bool*) – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** (*bool*) – Whether to return fixed parameters, i.e. parameters not to estimate.

Returns

Return type The parameter IDs.

get_x_nominal(*free=True, fixed=True, scaled=False*)

Generic function to get parameter nominal values.

Parameters

- **free** (*bool*) – Whether to return free parameters, i.e. parameters to estimate.
- **fixed** (*bool*) – Whether to return fixed parameters, i.e. parameters not to estimate.
- **scaled** (*bool*) – Whether to scale the values according to the parameter scale, or return them on linear scale.

Returns

Return type The parameter nominal values.

sample_parameter_startpoints(*n_starts=100*)

Create starting points for optimization

See `petab.sample_parameter_startpoints()`.

scale_parameters(*x_dict*)

Scale parameter values.

Parameters **x_dict** (*typing.Dict[str, float]*) – Keys are parameter IDs in the PETab problem, values are unscaled parameter values.

Returns

Return type The scaled parameter values.

to_files(*sbml_file=None, condition_file=None, measurement_file=None, parameter_file=None, visualization_file=None, observable_file=None, yaml_file=None, prefix_path=None, relative_paths=True*)

Write PETab tables to files for this problem

Writes PETab files for those entities for which a destination was passed.

NOTE: If this instance was created from multiple measurement or visualization tables, they will be merged and written to a single file.

Parameters

- **sbml_file** (`typing.Union[None, str, pathlib.Path]`) – SBML model destination
- **condition_file** (`typing.Union[None, str, pathlib.Path]`) – Condition table destination
- **measurement_file** (`typing.Union[None, str, pathlib.Path]`) – Measurement table destination
- **parameter_file** (`typing.Union[None, str, pathlib.Path]`) – Parameter table destination
- **visualization_file** (`typing.Union[None, str, pathlib.Path]`) – Visualization table destination
- **observable_file** (`typing.Union[None, str, pathlib.Path]`) – Observables table destination
- **yaml_file** (`typing.Union[None, str, pathlib.Path]`) – YAML file destination
- **prefix_path** (`typing.Union[None, str, pathlib.Path]`) – Specify a prefix to all paths, to avoid specifying the prefix for all paths individually. NB: the prefix is added to paths before *relative_paths* is handled.
- **relative_paths** (`bool`) – whether all paths in the YAML file should be relative to the location of the YAML file. If *False*, then paths are left unchanged.

Raises `ValueError` – If a destination was provided for a non-existing entity.

Return type `None`

to_files_generic(*prefix_path*)

Save a PETab problem to generic file names.

The PETab problem YAML file is always created. PETab data files are only created if the PETab problem contains corresponding data (e.g. a PETab visualization TSV file is only created if the PETab problem has one).

Parameters **prefix_path** (`typing.Union[str, pathlib.Path]`) – Specify a prefix to all paths, to avoid specifying the prefix for all paths individually. NB: the prefix is added to paths before *relative_paths* is handled downstream in *petab.yaml.create_problem_yaml*.

Return type `str`

Returns The path to the PETab problem YAML file.

unscale_parameters(*x_dict*)

Unscale parameter values.

Parameters **x_dict** (`typing.Dict[str, float]`) – Keys are parameter IDs in the PETab problem, values are scaled parameter values.

Returns

Return type The unscaled parameter values.

Functions Summary

<code>create_dummy_sbml(pysb_model[, observable_ids])</code>	Create SBML dummy model for to use PySB models with PETab.
<code>import_model_pysb(petab_problem[, ...])</code>	Create AMICI model from PySB-PETab problem

Functions

`amici.petab_import_pysb.create_dummy_sbml(pysb_model, observable_ids=None)`

Create SBML dummy model for to use PySB models with PETab.

Model must at least contain PETab problem parameter and noise parameters for observables.

Parameters

- **pysb_model** (`pysb.core.Model`) – PySB model
- **observable_ids** (`typing.Optional[typing.Iterable[str]]`) – Observable IDs

Return type `typing.Tuple[libsbml.Model, libsbml.SBMLDocument]`

Returns A dummy SBML model and document.

`amici.petab_import_pysb.import_model_pysb(petab_problem, model_output_dir=None, verbose=True, **kwargs)`

Create AMICI model from PySB-PETab problem

Parameters

- **petab_problem** (`amici.petab_import_pysb.PysbPetabProblem`) – PySB PETab problem
- **model_output_dir** (`typing.Optional[str]`) – Directory to write the model code to. Will be created if doesn't exist. Defaults to current directory.
- **verbose** (`typing.Union[bool, int, None]`) – Print/log extra information.
- **kwargs** – Additional keyword arguments to be passed to `amici.pysb_import.pysb2amici()`.

Return type `None`

10.4.8 amici.petab_objective

PETab Objective

Functionality related to running simulations or evaluating the objective function as defined by a PETab problem

Functions Summary

<code>create_edata_for_condition(condition, ...)</code>	Get <i>amici.amici.ExpData</i> for the given PETab condition.
<code>create_edatas(amici_model, petab_problem[, ...])</code>	Create list of <i>amici.amici.ExpData</i> objects for PETab problem.
<code>create_parameter_mapping(petab_problem, ...)</code>	Generate AMICI specific parameter mapping.
<code>create_parameter_mapping_for_condition(...)</code>	Generate AMICI specific parameter mapping for condition.
<code>create_parameterized_edatas(amici_model, ...)</code>	Create list of <code>:class:amici.ExpData</code> objects with parameters filled in.
<code>rdatas_to_measurement_df(rdatas, model, ...)</code>	Create a measurement dataframe in the PETab format from the passed <i>rdatas</i> and own information.
<code>rdatas_to_simulation_df(rdatas, model, ...)</code>	Create a PETab simulation dataframe from <i>amici.ReturnDatas</i> .
<code>simulate_petab(petab_problem, amici_model[, ...])</code>	Simulate PETab model.
<code>subset_dict(full, *args)</code>	Get subset of dictionary based on provided keys

Functions

`amici.petab_objective.create_edata_for_condition(condition, measurement_df, amici_model, petab_problem, observable_ids)`

Get *amici.amici.ExpData* for the given PETab condition.

Sets timepoints, observed data and sigmas.

Parameters

- **condition** (`typing.Union[typing.Dict, pandas.core.series.Series]`) – pandas.DataFrame row with preequilibrationConditionId and simulationConditionId.
- **measurement_df** (`pandas.core.frame.DataFrame`) – pandas.DataFrame with measurements for the given condition.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI model
- **petab_problem** (`petab.problem.Problem`) – Underlying PETab problem
- **observable_ids** (`typing.List[str]`) – List of observable IDs

Return type `amici.swig_wrappers.ExpData`

Returns ExpData instance.

`amici.petab_objective.create_edatas(amici_model, petab_problem, simulation_conditions=None)`

Create list of *amici.amici.ExpData* objects for PETab problem.

Parameters

- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI model.
- **petab_problem** (`petab.problem.Problem`) – Underlying PETab problem.
- **simulation_conditions** (`typing.Union[pandas.core.frame.DataFrame, typing.Dict, None]`) – Result of *petab.get_simulation_conditions*. Can be provided to save time if this has been obtained before.

Return type `typing.List[amici.swig_wrappers.ExpData]`

Returns List with one `amici.amici.ExpData` per simulation condition, with filled in timepoints and data.

`amici.petab_objective.create_parameter_mapping(petab_problem, simulation_conditions, scaled_parameters, amici_model)`

Generate AMICI specific parameter mapping.

Parameters

- **petab_problem** (`petab.problem.Problem`) – PETab problem
- **simulation_conditions** (`typing.Union[pandas.core.frame.DataFrame, typing.Dict]`) – Result of `petab.get_simulation_conditions`. Can be provided to save time if this has been obtained before.
- **scaled_parameters** (`bool`) – If True, problem_parameters are assumed to be on the scale provided in the PETab parameter table and will be unscaled. If False, they are assumed to be in linear scale.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AM-ICI model.

Return type `amici.parameter_mapping.ParameterMapping`

Returns List of the parameter mappings.

`amici.petab_objective.create_parameter_mapping_for_condition(parameter_mapping_for_condition, condition, petab_problem, amici_model)`

Generate AMICI specific parameter mapping for condition.

Parameters

- **parameter_mapping_for_condition** (`typing.Tuple[typing.Dict[str, typing.Union[str, numbers.Number]], typing.Dict[str, typing.Union[str, numbers.Number]], typing.Dict[str, str], typing.Dict[str, str]]`) – Preliminary parameter mapping for condition.
- **condition** (`typing.Union[pandas.core.series.Series, typing.Dict]`) – `pandas.DataFrame` row with `preequilibrationConditionId` and `simulationConditionId`.
- **petab_problem** (`petab.problem.Problem`) – Underlying PETab problem.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AM-ICI model.

Return type `amici.parameter_mapping.ParameterMappingForCondition`

Returns The parameter and parameter scale mappings, for fixed preequilibration, fixed simulation, and variable simulation parameters, and then the respective scalings.

`amici.petab_objective.create_parameterized_edatas(amici_model, petab_problem, problem_parameters, scaled_parameters=False, parameter_mapping=None, simulation_conditions=None)`

Create list of `:class:amici.ExpData` objects with parameters filled in.

Parameters

- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AM-ICI Model assumed to be compatible with `petab_problem`.

- **petab_problem** (`petab.problem.Problem`) – PETab problem to work on.
- **problem_parameters** (`typing.Dict[str, numbers.Number]`) – Run simulation with these parameters. If None, PETab *nominalValues* will be used). To be provided as dict, mapping PETab problem parameters to SBML IDs.
- **scaled_parameters** (`bool`) – If True, problem_parameters are assumed to be on the scale provided in the PETab parameter table and will be unscaled. If False, they are assumed to be in linear scale.
- **parameter_mapping** (`typing.Optional[amici.parameter_mapping.ParameterMapping]`) – Optional precomputed PETab parameter mapping for efficiency, as generated by *create_parameter_mapping*.
- **simulation_conditions** (`typing.Union[pandas.core.frame.DataFrame, typing.Dict, None]`) – Result of *petab.get_simulation_conditions*. Can be provided to save time if this has been obtained before.

Return type `typing.List[amici.swig_wrappers.ExpData]`

Returns List with one `amici.amici.ExpData` per simulation condition, with filled in timepoints, data and parameters.

`amici.petab_objective.rdatas_to_measurement_df(rdatas, model, measurement_df)`

Create a measurement dataframe in the PETab format from the passed *rdatas* and own information.

Parameters

- **rdatas** (`typing.Sequence[amici.amici.ReturnData]`) – A sequence of rdatas with the ordering of *petab.get_simulation_conditions*.
- **model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI model used to generate *rdatas*.
- **measurement_df** (`pandas.core.frame.DataFrame`) – PETab measurement table used to generate *rdatas*.

Return type `pandas.core.frame.DataFrame`

Returns A dataframe built from the rdatas in the format of *measurement_df*.

`amici.petab_objective.rdatas_to_simulation_df(rdatas, model, measurement_df)`

Create a PETab simulation dataframe from `amici.ReturnDatas`.

See *rdatas_to_measurement_df* for details, only that model outputs will appear in column “simulation” instead of “measurement”.

Return type `pandas.core.frame.DataFrame`

`amici.petab_objective.simulate_petab(petab_problem, amici_model, solver=None, problem_parameters=None, simulation_conditions=None, edatas=None, parameter_mapping=None, scaled_parameters=False, log_level=30, num_threads=1, failfast=True)`

Simulate PETab model.

Parameters

- **petab_problem** (`petab.problem.Problem`) – PETab problem to work on.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI Model assumed to be compatible with *petab_problem*.

- **solver** (`typing.Optional[amici.amici.Solver]`) – An AMICI solver. Will use default options if None.
- **problem_parameters** (`typing.Optional[typing.Dict[str, float]]`) – Run simulation with these parameters. If None, PETab *nominalValues* will be used). To be provided as dict, mapping PETab problem parameters to SBML IDs.
- **simulation_conditions** (`typing.Union[pandas.core.frame.DataFrame, typing.Dict, None]`) – Result of `petab.get_simulation_conditions`. Can be provided to save time if this has been obtained before. Not required if *edatas* and *parameter_mapping* are provided.
- **edatas** (`typing.Optional[typing.List[typing.Union[amici.swig_wrappers.ExpData, amici.amici.ExpDataPtr]]]`) – Experimental data. Parameters are inserted in-place for simulation.
- **parameter_mapping** (`typing.Optional[amici.parameter_mapping.ParameterMapping]`) – Optional precomputed PETab parameter mapping for efficiency, as generated by `create_parameter_mapping`.
- **scaled_parameters** (`typing.Optional[bool]`) – If True, problem_parameters are assumed to be on the scale provided in the PETab parameter table and will be unscaled. If False, they are assumed to be in linear scale.
- **log_level** (`int`) – Log level, see `amici.logging` module.
- **num_threads** (`int`) – Number of threads to use for simulating multiple conditions (only used if compiled with OpenMP).
- **failfast** (`bool`) – Returns as soon as an integration failure is encountered, skipping any remaining simulations.

Return type `typing.Dict[str, typing.Any]`

Returns

Dictionary of

- cost function value (LLH),
- cost function sensitivity w.r.t. parameters (SLLH), (**NOTE:** Sensitivities are computed for the scaled parameters)
- list of *ReturnData* (RDATAS),

corresponding to the different simulation conditions. For ordering of simulation conditions, see `petab.Problem.get_simulation_conditions_from_measurement_df()`.

`amici.petab_objective.subset_dict(full, *args)`

Get subset of dictionary based on provided keys

Parameters

- **full** (`typing.Dict[typing.Any, typing.Any]`) – Dictionary to subset
- **args** (`typing.Collection[typing.Any]`) – Collections of keys to be contained in the different subsets

Return type `typing.Iterator[typing.Dict[typing.Any, typing.Any]]`

Returns subsetted dictionary

10.4.9 amici.petab_simulate

PEtab Simulate

Functionality related to the use of AMICI for simulation with PÉtab's Simulator class.

Use cases:

- generate data for use with PÉtab's plotting methods
- generate synthetic data

Classes

<code>PetabSimulator(*args[, amici_model])</code>	Implementation of the PÉtab <i>Simulator</i> class that uses AMICI.
---------------------------------------------------	---------------------------------------------------------------------

amici.petab_simulate.PetabSimulator

class amici.petab_simulate.PetabSimulator(*args, amici_model=None, **kwargs)

Implementation of the PÉtab *Simulator* class that uses AMICI.

__init__(*args, amici_model=None, **kwargs)

Initialize the simulator.

Initialize the simulator with sufficient information to perform a simulation. If no working directory is specified, a temporary one is created.

Parameters

- **petab_problem** – A PÉtab problem.
- **working_dir** – All simulator-specific output files will be saved here. This directory and its contents may be modified and deleted, and should be considered ephemeral.

Methods Summary

<code>__init__(*args[, amici_model])</code>	Initialize the simulator.
<code>add_noise(simulation_df[, noise_scaling_factor])</code>	Add noise to simulated data.
<code>remove_working_dir([force])</code>	Remove the simulator working directory, and all files within.
<code>simulate([noise, noise_scaling_factor])</code>	Simulate a PÉtab problem, optionally with noise.
<code>simulate_without_noise(**kwargs)</code>	See <code>petab.simulate.Simulator.simulate()</code> docstring.

Methods

__init__(*args, amici_model=None, **kwargs)

Initialize the simulator.

Initialize the simulator with sufficient information to perform a simulation. If no working directory is specified, a temporary one is created.

Parameters

- **petab_problem** – A PETab problem.
- **working_dir** – All simulator-specific output files will be saved here. This directory and its contents may be modified and deleted, and should be considered ephemeral.

add_noise(simulation_df, noise_scaling_factor=1, **kwargs)

Add noise to simulated data.

Parameters

- **simulation_df** (`pandas.core.frame.DataFrame`) – A PETab measurements table that contains simulated data.
- **noise_scaling_factor** (`float`) – A multiplier of the scale of the noise distribution.
- ****kwargs** – Additional keyword arguments are passed to *sample_noise*.

Return type `pandas.core.frame.DataFrame`

Returns Simulated data with noise, as a PETab measurements table.

remove_working_dir(force=False, **kwargs)

Remove the simulator working directory, and all files within.

See the `__init__` method arguments.

Parameters

- **force** (`bool`) – If True, the working directory is removed regardless of whether it is a temporary directory.
- ****kwargs** – Additional keyword arguments are passed to *shutil.rmtree*.

Return type `None`

simulate(noise=False, noise_scaling_factor=1, **kwargs)

Simulate a PETab problem, optionally with noise.

Parameters

- **noise** (`bool`) – If True, noise is added to simulated data.
- **noise_scaling_factor** (`float`) – A multiplier of the scale of the noise distribution.
- ****kwargs** – Additional keyword arguments are passed to *simulate_without_noise*.

Return type `pandas.core.frame.DataFrame`

Returns Simulated data, as a PETab measurements table.

simulate_without_noise(**kwargs)

See `petab.simulate.Simulator.simulate()` docstring.

Additional keyword arguments can be supplied to specify arguments for the AMICI PETab import, simulate, and export methods. See the docstrings for the respective methods for argument options: - `amici.petab_import.import_petab_problem()`, and - `amici.petab_objective.simulate_petab()`.

Note that some arguments are expected to have already been specified in the Simulator constructor (including the PETab problem).

Return type `pandas.core.frame.DataFrame`

Functions Summary

<code>subset_call</code> (method, kwargs)	Helper function to call a method with the intersection of arguments in the method signature and the supplied arguments.
-------------------------------------------	-------------------------------------------------------------------------------------------------------------------------

Functions

`amici.petab_simulate.subset_call`(method, kwargs)

Helper function to call a method with the intersection of arguments in the method signature and the supplied arguments.

Parameters

- **method** (`typing.Callable`) – The method to be called.
- **kwargs** (`dict`) – The argument superset as a dictionary, similar to `**kwargs` in method signatures.

Returns The output of *method*, called with the applicable arguments in *kwargs*.

10.4.10 amici.import_utils

Miscellaneous functions related to model import, independent of any specific model format

Classes

<code>ObservableTransformation</code> (value)	Different modes of observable transformation.
-----------------------------------------------	-----------------------------------------------

`amici.import_utils.ObservableTransformation`

class `amici.import_utils.ObservableTransformation`(value)
Different modes of observable transformation.

Attributes

LOG10

LOG

LIN

Functions Summary

<code>cast_to_sym(value, input_name)</code>	Typecasts the value to <code>sympy.Float</code> if possible, and ensures the value is a symbolic expression.
<code>generate_flux_symbol(reaction_index[, name])</code>	Generate identifier symbol for a reaction flux.
<code>generate_measurement_symbol(observable_id)</code>	Generates the appropriate measurement symbol for the provided observable
<code>grouper(iterable, n[, fillvalue])</code>	Collect data into fixed-length chunks or blocks
<code>noise_distribution_to_cost_function(...)</code>	Parse noise distribution string to a cost function definition amici can work with.
<code>noise_distribution_to_observable_transformation(...)</code>	Parse noise distribution string and extract observable transformation
<code>smart_subs(element, old, new)</code>	Optimized substitution that checks whether anything needs to be done first
<code>smart_subs_dict(sym, subs[, field, reverse])</code>	Substitutes expressions completely flattening them out.
<code>strip_pysb(symbol)</code>	Strips pysb info from a <code>pysb.Component</code> object
<code>symbol_with_assumptions(name)</code>	Central function to create symbols with consistent, canonical assumptions
<code>toposort_symbols(symbols[, field])</code>	Topologically sort symbol definitions according to their interdependency

Functions

`amici.import_utils.cast_to_sym(value, input_name)`

Typecasts the value to `sympy.Float` if possible, and ensures the value is a symbolic expression.

Parameters

- **value** (`typing.Union[typing.SupportsFloat, sympy.core.expr.Expr, sympy.logic.boolalg.BooleanAtom]`) – value to be cast
- **input_name** (`str`) – name of input variable

Return type `sympy.core.expr.Expr`

Returns typecast value

`amici.import_utils.generate_flux_symbol(reaction_index, name=None)`

Generate identifier symbol for a reaction flux. This function will always return the same unique python object for a given entity.

Parameters

- **reaction_index** (`int`) – index of the reaction to which the flux corresponds
- **name** (`typing.Optional[str]`) – an optional identifier of the reaction to which the flux corresponds

Return type `sympy.core.symbol.Symbol`

Returns identifier symbol

`amici.import_utils.generate_measurement_symbol(observable_id)`

Generates the appropriate measurement symbol for the provided observable

Parameters **observable_id** (`typing.Union[str, sympy.core.symbol.Symbol]`) – symbol (or string representation) of the observable

Returns symbol for the corresponding measurement

`amici.import_utils.grouper(iterable, n, fillvalue=None)`

Collect data into fixed-length chunks or blocks

`grouper('ABCDEFGF', 3, 'x') -> ABC DEF Gxx`

Parameters

- **iterable** (`typing.Iterable`) – any iterable
- **n** (`int`) – chunk length
- **fillvalue** (`typing.Optional[typing.Any]`) – padding for last chunk if length < n

Return type `typing.Iterable[typing.Tuple[typing.Any]]`

Returns `itertools.zip_longest` of requested chunks

`amici.import_utils.noise_distribution_to_cost_function(noise_distribution)`

Parse noise distribution string to a cost function definition amici can work with.

The noise distributions listed in the following are supported. m denotes the measurement, y the simulation, and σ a distribution scale parameter (currently, AMICI only supports a single distribution parameter).

- *'normal'*, *'lin-normal'*: A normal distribution:

$$\pi(m|y, \sigma) = \frac{1}{\sqrt{2\pi}\sigma} \exp\left(-\frac{(m-y)^2}{2\sigma^2}\right)$$

- *'log-normal'*: A log-normal distribution (i.e. $\log(m)$ is normally distributed):

$$\pi(m|y, \sigma) = \frac{1}{\sqrt{2\pi}\sigma m} \exp\left(-\frac{(\log m - \log y)^2}{2\sigma^2}\right)$$

- *'log10-normal'*: A log10-normal distribution (i.e. $\log_{10}(m)$ is normally distributed):

$$\pi(m|y, \sigma) = \frac{1}{\sqrt{2\pi}\sigma m \log(10)} \exp\left(-\frac{(\log_{10} m - \log_{10} y)^2}{2\sigma^2}\right)$$

- *'laplace'*, *'lin-laplace'*: A laplace distribution:

$$\pi(m|y, \sigma) = \frac{1}{2\sigma} \exp\left(-\frac{|m-y|}{\sigma}\right)$$

- *'log-laplace'*: A log-Laplace distribution (i.e. $\log(m)$ is Laplace distributed):

$$\pi(m|y, \sigma) = \frac{1}{2\sigma m} \exp\left(-\frac{|\log m - \log y|}{\sigma}\right)$$

- *'log10-laplace'*: A log10-Laplace distribution (i.e. $\log_{10}(m)$ is Laplace distributed):

$$\pi(m|y, \sigma) = \frac{1}{2\sigma m \log(10)} \exp\left(-\frac{|\log_{10} m - \log_{10} y|}{\sigma}\right)$$

- *'binomial'*, *'lin-binomial'*: A (continuation of a discrete) binomial distribution, parameterized via the success probability $p = \sigma$:

$$\pi(m|y, \sigma) = \text{Heaviside}(y-m) \cdot \frac{\Gamma(y+1)}{\Gamma(m+1)\Gamma(y-m+1)} \sigma^m (1-\sigma)^{(y-m)}$$

- ‘negative-binomial’, ‘lin-negative-binomial’: A (continuation of a discrete) negative binomial distribution, with $mean = y$, parameterized via success probability p :

$$\pi(m|y, \sigma) = \frac{\Gamma(m+r)}{\Gamma(m+1)\Gamma(r)} (1-\sigma)^m \sigma^r$$

where

$$r = \frac{1-\sigma}{\sigma} y$$

The distributions above are for a single data point. For a collection $D = \{m_i\}_i$ of data points and corresponding simulations $Y = \{y_i\}_i$ and noise parameters $\Sigma = \{\sigma_i\}_i$, AMICI assumes independence, i.e. the full distributions is

$$\pi(D|Y, \Sigma) = \prod_i \pi(m_i|y_i, \sigma_i)$$

AMICI uses the logarithm $\log(\pi(m|y, \sigma))$.

In addition to the above mentioned distributions, it is also possible to pass a function taking a symbol string and returning a log-distribution string with variables ‘{str_symbol}’, ‘m{str_symbol}’, ‘sigma{str_symbol}’ for y , m , σ , respectively.

Parameters `noise_distribution` (`typing.Union[str, typing.Callable]`) – An identifier specifying a noise model. Possible values are

{‘normal’, ‘lin-normal’, ‘log-normal’, ‘log10-normal’, ‘laplace’, ‘lin-laplace’, ‘log-laplace’, ‘log10-laplace’, ‘binomial’, ‘lin-binomial’, ‘negative-binomial’, ‘lin-negative-binomial’, <Callable>}

For the meaning of the values see above.

Return type `typing.Callable[[str], str]`

Returns A function that takes a `strSymbol` and then creates a cost function string (negative log-likelihood) from it, which can be sympified.

`amici.import_utils.noise_distribution_to_observable_transformation(noise_distribution)`

Parse noise distribution string and extract observable transformation

Parameters `noise_distribution` (`typing.Union[str, typing.Callable]`) – see `noise_distribution_to_cost_function()`

Return type `amici.import_utils.ObservableTransformation`

Returns observable transformation

`amici.import_utils.smart_subs(element, old, new)`

Optimized substitution that checks whether anything needs to be done first

Parameters

- `element` (`sympy.core.expr.Expr`) – substitution target
- `old` (`sympy.core.symbol.Symbol`) – to be substituted
- `new` (`sympy.core.expr.Expr`) – substitution value

Return type `sympy.core.expr.Expr`

Returns substituted expression

`amici.import_utils.smart_subs_dict(sym, subs, field=None, reverse=True)`

Substitutes expressions completely flattening them out. Requires sorting of expressions with `toposort`.

Parameters

- **sym** (`sympy.core.expr.Expr`) – Symbolic expression in which expressions will be substituted
- **subs** (`typing.Dict[sympy.core.symbol.Symbol, typing.Union[typing.Dict[str, sympy.core.expr.Expr], sympy.core.expr.Expr]]`) – Substitutions
- **field** (`typing.Optional[str]`) – Field of substitution expressions in `subs.values()`, if applicable
- **reverse** (`bool`) – Whether ordering in `subs` should be reversed. Note that substitution requires the reverse order of what is required for evaluation.

Return type `sympy.core.expr.Expr`**Returns** Substituted symbolic expression`amici.import_utils.strip_pysb(symbol)`Strips pysb info from a `pysb.Component` object**Parameters** **symbol** (`sympy.core.basic.Basic`) – symbolic expression**Return type** `sympy.core.basic.Basic`**Returns** stripped expression`amici.import_utils.symbol_with_assumptions(name)`

Central function to create symbols with consistent, canonical assumptions

Parameters **name** (`str`) – name of the symbol**Returns** symbol with canonical assumptions`amici.import_utils.toposort_symbols(symbols, field=None)`

Topologically sort symbol definitions according to their interdependency

Parameters

- **symbols** (`typing.Dict[sympy.core.symbol.Symbol, typing.Union[typing.Dict[str, sympy.core.expr.Expr], sympy.core.expr.Expr]]`) – symbol definitions
- **field** (`typing.Optional[str]`) – field of definition.values() that is used to compute interdependency

Return type `typing.Dict[sympy.core.symbol.Symbol, typing.Union[typing.Dict[str, sympy.core.expr.Expr], sympy.core.expr.Expr]]`**Returns** ordered symbol definitions

10.4.11 amici.ode_export

C++ Export

This module provides all necessary functionality specify an ODE model and generate executable C++ simulation code. The user generally won't have to directly call any function from this module as this will be done by `amici.pysb_import.pysb2amici()`, `amici.sbml_import.SbmlImporter.sbml2amici()` and `amici.petab_import.import_model()`.

Classes

<code>ODEExporter(ode_model[, outdir, verbose, ...])</code>	The ODEExporter class generates AMICI C++ files for ODE model as defined in symbolic expressions.
<code>ODEModel([verbose, simplify, cache_simplify])</code>	Defines an Ordinary Differential Equation as set of ModelQuantities.
<code>TemplateAmici(template)</code>	Template format used in AMICI (see <code>string.Template</code> for more details).

amici.ode_export.ODEExporter

```
class amici.ode_export.ODEExporter(ode_model, outdir=None, verbose=False,
                                   assume_pow_positivity=False, compiler=None,
                                   allow_reinit_fixpar_initcond=True, generate_sensitivity_code=True,
                                   model_name='model')
```

The ODEExporter class generates AMICI C++ files for ODE model as defined in symbolic expressions.

Variables

- **model** – ODE definition
- **verbose** – more verbose output if True
- **assume_pow_positivity** – if set to true, a special pow function is used to avoid problems with state variables that may become negative due to numerical errors
- **compiler** – distutils/setuptools compiler selection to build the Python extension
- **functions** – carries C++ function signatures and other specifications
- **model_name** – name of the model that will be used for compilation
- **model_path** – path to the generated model specific files
- **model_swig_path** – path to the generated swig files
- **allow_reinit_fixpar_initcond** – indicates whether reinitialization of initial states depending on fixedParameters is allowed for this model
- **_build_hints** – If the given model uses special functions, this set contains hints for model building.
- **generate_sensitivity_code** – Specifies whether code for sensitivity computation is to be generated

```
__init__(ode_model, outdir=None, verbose=False, assume_pow_positivity=False, compiler=None,
          allow_reinit_fixpar_initcond=True, generate_sensitivity_code=True, model_name='model')
```

Generate AMICI C++ files for the ODE provided to the constructor.

Parameters

- **ode_model** (`amici.ode_export.ODEModel`) – ODE definition
- **outdir** (`typing.Optional[str]`) – see `amici.ode_export.ODEExporter.set_paths()`
- **verbose** (`typing.Union[bool, int, None]`) – verbosity level for logging, True/False default to `logging.Error/logging.DEBUG`

- **assume_pow_positivity** (`typing.Optional[bool]`) – if set to true, a special pow function is used to avoid problems with state variables that may become negative due to numerical errors
- **compiler** (`typing.Optional[str]`) – distutils/setuptools compiler selection to build the python extension
- **allow_reinit_fixpar_initcond** (`typing.Optional[bool]`) – see [`amici.ode_export.ODEExporter`](#)
- **generate_sensitivity_code** (`typing.Optional[bool]`) – specifies whether code required for sensitivity computation will be generated
- **model_name** (`typing.Optional[str]`) – name of the model to be used during code generation

Methods Summary

<code>__init__(ode_model[, outdir, verbose, ...])</code>	Generate AMICI C++ files for the ODE provided to the constructor.
<code>compile_model()</code>	Compiles the generated code it into a simulatable module
<code>generate_model_code()</code>	Generates the native C++ code for the loaded model and a Matlab script that can be run to compile a mex file from the C++ code
<code>set_name(model_name)</code>	Sets the model name
<code>set_paths([output_dir])</code>	Set output paths for the model and create if necessary

Methods

`__init__(ode_model, outdir=None, verbose=False, assume_pow_positivity=False, compiler=None, allow_reinit_fixpar_initcond=True, generate_sensitivity_code=True, model_name='model')`
Generate AMICI C++ files for the ODE provided to the constructor.

Parameters

- **ode_model** ([`amici.ode_export.ODEModel`](#)) – ODE definition
- **outdir** (`typing.Optional[str]`) – see [`amici.ode_export.ODEExporter.set_paths\(\)`](#)
- **verbose** (`typing.Union[bool, int, None]`) – verbosity level for logging, True/False default to logging.Error/logging.DEBUG
- **assume_pow_positivity** (`typing.Optional[bool]`) – if set to true, a special pow function is used to avoid problems with state variables that may become negative due to numerical errors
- **compiler** (`typing.Optional[str]`) – distutils/setuptools compiler selection to build the python extension
- **allow_reinit_fixpar_initcond** (`typing.Optional[bool]`) – see [`amici.ode_export.ODEExporter`](#)
- **generate_sensitivity_code** (`typing.Optional[bool]`) – specifies whether code required for sensitivity computation will be generated

- **model_name** (`typing.Optional[str]`) – name of the model to be used during code generation

compile_model()

Compiles the generated code it into a simulatable module

Return type `None`

generate_model_code()

Generates the native C++ code for the loaded model and a Matlab script that can be run to compile a mex file from the C++ code

Return type `None`

set_name(model_name)

Sets the model name

Parameters **model_name** (`str`) – name of the model (may only contain upper and lower case letters, digits and underscores, and must not start with a digit)

Return type `None`

set_paths(output_dir=None)

Set output paths for the model and create if necessary

Parameters **output_dir** (`typing.Optional[str]`) – relative or absolute path where the generated model code is to be placed. If `None`, this will default to `amici-{self.model_name}` in the current working directory. will be created if it does not exist.

Return type `None`

amici.ode_export.ODEModel

class `amici.ode_export.ODEModel(verbose=False, simplify=<function powsimp>, cache_simplify=False)`

Defines an Ordinary Differential Equation as set of ModelQuantities. This class provides general purpose interfaces to compute arbitrary symbolic derivatives that are necessary for model simulation or sensitivity computation.

Variables

- **_states** – list of state variables
- **_observables** – list of observables
- **_sigmayes** – list of sigmayes
- **_parameters** – list of parameters
- **_loglikelihoods** – list of loglikelihoods
- **_expressions** – list of expressions instances
- **_conservationlaws** – list of conservation laws
- **_symboldim_funs** – define functions that compute model dimensions, these are functions as the underlying symbolic expressions have not been populated at compile time
- **_eqs** – carries symbolic formulas of the symbolic variables of the model
- **_sparseeqs** – carries linear list of all symbolic formulas for sparsified variables
- **_vals** – carries numeric values of symbolic identifiers of the symbolic variables of the model
- **_names** – carries names of symbolic identifiers of the symbolic variables of the model

- **_syms** – carries symbolic identifiers of the symbolic variables of the model
- **_strippedsyms** – carries symbolic identifiers that were stripped of additional class information
- **_sparsesyms** – carries linear list of all symbolic identifiers for sparsified variables
- **_colptrs** – carries column pointers for sparsified variables. See `SUNMatrixContent_Sparse` definition in `sunmatrix/sunmatrix_sparse.h`
- **_rowvals** – carries row values for sparsified variables. See `SUNMatrixContent_Sparse` definition in `sunmatrix/sunmatrix_sparse.h`
- **_equation_prototype** – defines the attribute from which an equation should be generated via list comprehension (see `ODEModel._generate_equation()`)
- **_variable_prototype** – defines the attribute from which a variable should be generated via list comprehension (see `ODEModel._generate_symbol()`)
- **_value_prototype** – defines the attribute from which a value should be generated via list comprehension (see `ODEModel._generate_value()`)
- **_total_derivative_prototypes** – defines how a total derivative equation is computed for an equation, key defines the name and values should be arguments for `ODEModel.totalDerivative()`
- **_lock_total_derivative** – add chainvariables to this set when computing total derivative from a partial derivative call to enforce a partial derivative in the next recursion. prevents infinite recursion
- **_simplify** – If not None, this function will be used to simplify symbolic derivative expressions. Receives sympy expressions as only argument. To apply multiple simplifications, wrap them in a lambda expression.
- **_x0_fixedParameters_idx** – Index list of subset of states for which `x0_fixedParameters` was computed
- **_w_recursion_depth** – recursion depth in w, quantified as nilpotency of `dwdw`
- **_has_quadratic_nllh** – whether all observables have a gaussian noise model, i.e. whether res and FIM make sense.
- **_code_printer** – Code printer to generate C++ code

__init__(*verbose=False, simplify=<function powsimp>, cache_simplify=False*)

Create a new `ODEModel` instance.

Parameters

- **verbose** (`typing.Union[bool, int, None]`) – verbosity level for logging, True/False default to `logging.DEBUG/logging.ERROR`
- **simplify** (`typing.Optional[typing.Callable]`) – see `ODEModel._simplify()`
- **cache_simplify** (`bool`) – Whether to cache calls to the `simplify` method. Can e.g. decrease import times for models with events.

Methods Summary

<code>__init__([verbose, simplify, cache_simplify])</code>	Create a new ODEModel instance.
<code>add_component(component[, insert_first])</code>	Adds a new ModelQuantity to the model.
<code>add_conservation_law(state, total_abundance, ...)</code>	Adds a new conservation law to the model.
<code>colptrs(name)</code>	Returns (and constructs if necessary) the column pointers for a sparsified symbolic variable.
<code>conservation_law_has_multispecies(tcl)</code>	Checks whether a conservation law has multiple species or it just defines one constant species
<code>eq(name)</code>	Returns (and constructs if necessary) the formulas for a symbolic entity.
<code>free_symbols()</code>	Returns list of free symbols that appear in ODE RHS and initial conditions.
<code>generate_basic_variables(*[, from_sbml])</code>	Generates the symbolic identifiers for all variables in <code>ODEModel._variable_prototype</code>
<code>get_appearance_counts(idxs)</code>	Counts how often a state appears in the time derivative of another state and expressions for a subset of states
<code>get_conservation_laws()</code>	Returns a list of states with conservation law set
<code>get_observable_transformations()</code>	List of observable transformations
<code>get_solver_indices()</code>	Returns a mapping that maps rdata species indices to solver indices
<code>import_from_sbml_importer(si[, compute_cls])</code>	Imports a model specification from a <code>amici.sbml_import.SbmlImporter</code> instance.
<code>name(name)</code>	Returns (and constructs if necessary) the names of a symbolic variable
<code>num_cons_law()</code>	Number of conservation laws.
<code>num_const()</code>	Number of Constants.
<code>num_events()</code>	Number of Events.
<code>num_expr()</code>	Number of Expressions.
<code>num_obs()</code>	Number of Observables.
<code>num_par()</code>	Number of Parameters.
<code>num_state_reinits()</code>	Number of solver states which would be reinitialized after preequilibration
<code>num_states_rdata()</code>	Number of states.
<code>num_states_solver()</code>	Number of states after applying conservation laws.
<code>parse_events()</code>	This function checks the right-hand side for roots of Heaviside functions or events, collects the roots, removes redundant roots, and replaces the formulae of the found roots by identifiers of AMICI's Heaviside function implementation in the right-hand side
<code>rowvals(name)</code>	Returns (and constructs if necessary) the row values for a sparsified symbolic variable.
<code>sparseseq(name)</code>	Returns (and constructs if necessary) the sparsified formulas for a sparsified symbolic variable.
<code>sparsesym(name[, force_generate])</code>	Returns (and constructs if necessary) the sparsified identifiers for a sparsified symbolic variable.
<code>state_has_conservation_law(ix)</code>	Checks whether the state at specified index has a conservation law set

continues on next page

Table 58 – continued from previous page

<code>state_has_fixed_parameter_initial_condition(ix)</code>	Checks whether the state at specified index has a fixed parameter initial condition
<code>state_is_constant(ix)</code>	Checks whether the temporal derivative of the state is zero
<code>sym(name[, stripped])</code>	Returns (and constructs if necessary) the identifiers for a symbolic entity.
<code>sym_names()</code>	Returns a list of names of generated symbolic variables
<code>sym_or_eq(name, varname)</code>	Returns symbols or equations depending on whether a given variable appears in the function signature or not.
<code>val(name)</code>	Returns (and constructs if necessary) the numeric values of a symbolic entity

Methods

`__init__`(*verbose=False, simplify=<function powsimp>, cache_simplify=False*)
Create a new ODEModel instance.

Parameters

- **verbose** (`typing.Union[bool, int, None]`) – verbosity level for logging, True/False default to logging.DEBUG/logging.ERROR
- **simplify** (`typing.Optional[typing.Callable]`) – see `ODEModel._simplify()`
- **cache_simplify** (`bool`) – Whether to cache calls to the simplify method. Can e.g. decrease import times for models with events.

`add_component`(*component, insert_first=False*)
Adds a new ModelQuantity to the model.

Parameters

- **component** (`amici.ode_model.ModelQuantity`) – model quantity to be added
- **insert_first** (`typing.Optional[bool]`) – whether to add quantity first or last, relevant when components may refer to other components of the same type.

Return type `None`

`add_conservation_law`(*state, total_abundance, state_expr, abundance_expr*)
Adds a new conservation law to the model. A conservation law is defined by the conserved quantity $T = \sum_i (a_i * x_i)$, where a_i are coefficients and x_i are different state variables.

Parameters

- **state** (`sympy.core.symbol.Symbol`) – symbolic identifier of the state that should be replaced by the conservation law (x_j)
- **total_abundance** (`sympy.core.symbol.Symbol`) – symbolic identifier of the total abundance (T/a_j)
- **state_expr** (`sympy.core.expr.Expr`) – symbolic algebraic formula that replaces the state. This is used to compute the numeric value of **state** during simulations. $x_j = T/a_j - \sum_{ij} (a_i * x_i)/a_j$

- **abundance_expr** (`sympy.core.expr.Expr`) – symbolic algebraic formula that computes the value of the conserved quantity. This is used to update the numeric value for `total_abundance` after (re-)initialization. $T/a_j = \sum_{ij}(a_i * x_i)/a_j + x_j$

Return type `None`

colptrs(*name*)

Returns (and constructs if necessary) the column pointers for a sparsified symbolic variable.

Parameters **name** (`str`) – name of the symbolic variable

Return type `typing.Union[typing.List[sympy.core.numbers.Number], typing.List[typing.List[sympy.core.numbers.Number]]]`

Returns list containing the column pointers

conservation_law_has_multispecies(*tcl*)

Checks whether a conservation law has multiple species or it just defines one constant species

Parameters **tcl** (`amici.ode_model.ConservationLaw`) – conservation law

Return type `bool`

Returns boolean indicating if conservation_law is not None

eq(*name*)

Returns (and constructs if necessary) the formulas for a symbolic entity.

Parameters **name** (`str`) – name of the symbolic variable

Return type `sympy.matrices.dense.MutableDenseMatrix`

Returns matrix of symbolic formulas

free_symbols()

Returns list of free symbols that appear in ODE RHS and initial conditions.

Return type `typing.Set[sympy.core.basic.Basic]`

generate_basic_variables(**, from_sbml=False*)

Generates the symbolic identifiers for all variables in `ODEModel._variable_prototype`

Parameters **from_sbml** (`bool`) – whether the model is generated from SBML

Return type `None`

get_appearance_counts(*idxs*)

Counts how often a state appears in the time derivative of another state and expressions for a subset of states

Parameters **idxs** (`typing.List[int]`) – list of state indices for which counts are to be computed

Return type `typing.List[int]`

Returns list of counts for the states ordered according to the provided indices

get_conservation_laws()

Returns a list of states with conservation law set

Return type `typing.List[typing.Tuple[sympy.core.symbol.Symbol, sympy.core.basic.Basic]]`

Returns list of state identifiers

get_observable_transformations()

List of observable transformations

Return type `typing.List[amici.import_utils.ObservableTransformation]`

Returns list of transformations

get_solver_indices()

Returns a mapping that maps rdata species indices to solver indices

Return type `typing.Dict[int, int]`

Returns dictionary mapping rdata species indices to solver indices

import_from_sbml_importer(*si*, *compute_cls=True*)

Imports a model specification from a `amici.sbml_import.SbmlImporter` instance.

Parameters

- **si** (`amici.sbml_import.SbmlImporter`) – imported SBML model
- **compute_cls** (`typing.Optional[bool]`) – whether to compute conservation laws

Return type `None`

name(*name*)

Returns (and constructs if necessary) the names of a symbolic variable

Parameters **name** (`str`) – name of the symbolic variable

Return type `typing.List[str]`

Returns list of names

num_cons_law()

Number of conservation laws.

Return type `int`

Returns number of conservation laws

num_const()

Number of Constants.

Return type `int`

Returns number of constant symbols

num_events()

Number of Events.

Return type `int`

Returns number of event symbols (length of the root vector in AMICI)

num_expr()

Number of Expressions.

Return type `int`

Returns number of expression symbols

num_obs()

Number of Observables.

Return type `int`

Returns number of observable symbols

num_par()

Number of Parameters.

Return type `int`

Returns number of parameter symbols

num_state_reinits()

Number of solver states which would be reinitialized after preequilibration

Return type `int`

Returns number of state variable symbols with reinitialization

num_states_rdata()

Number of states.

Return type `int`

Returns number of state variable symbols

num_states_solver()

Number of states after applying conservation laws.

Return type `int`

Returns number of state variable symbols

parse_events()

This function checks the right-hand side for roots of Heaviside functions or events, collects the roots, removes redundant roots, and replaces the formulae of the found roots by identifiers of AMICI's Heaviside function implementation in the right-hand side

Return type `None`

rowvals(name)

Returns (and constructs if necessary) the row values for a sparsified symbolic variable.

Parameters **name** (`str`) – name of the symbolic variable

Return type `typing.Union[typing.List[sympy.core.numbers.Number], typing.List[typing.List[sympy.core.numbers.Number]]]`

Returns list containing the row values

sparseeq(name)

Returns (and constructs if necessary) the sparsified formulas for a sparsified symbolic variable.

Parameters **name** – name of the symbolic variable

Return type `sympy.matrices.dense.MutableDenseMatrix`

Returns linearized matrix containing the symbolic formulas

sparsesym(name, force_generate=True)

Returns (and constructs if necessary) the sparsified identifiers for a sparsified symbolic variable.

Parameters

- **name** (`str`) – name of the symbolic variable
- **force_generate** (`bool`) – whether the symbols should be generated if not available

Return type `typing.List[str]`

Returns linearized Matrix containing the symbolic identifiers

state_has_conservation_law(ix)

Checks whether the state at specified index has a conservation law set

Parameters **ix** (`int`) – state index

Return type `bool`

Returns boolean indicating if `conservation_law` is not `None`

`state_has_fixed_parameter_initial_condition(ix)`

Checks whether the state at specified index has a fixed parameter initial condition

Parameters `ix (int)` – state index

Return type `bool`

Returns boolean indicating if any of the initial condition free variables is contained in the model constants

`state_is_constant(ix)`

Checks whether the temporal derivative of the state is zero

Parameters `ix (int)` – state index

Return type `bool`

Returns boolean indicating if constant over time

`sym(name, stripped=False)`

Returns (and constructs if necessary) the identifiers for a symbolic entity.

Parameters

- **name** (`str`) – name of the symbolic variable
- **stripped** (`typing.Optional[bool]`) – should additional class information be stripped from the symbolic variables (default=False)

Return type `sympy.matrices.dense.MutableDenseMatrix`

Returns matrix of symbolic identifiers

`sym_names()`

Returns a list of names of generated symbolic variables

Return type `typing.List[str]`

Returns list of names

`sym_or_eq(name, varname)`

Returns symbols or equations depending on whether a given variable appears in the function signature or not.

Parameters

- **name** (`str`) – name of function for which the signature should be checked
- **varname** (`str`) – name of the variable which should be contained in the function signature

Return type `sympy.matrices.dense.MutableDenseMatrix`

Returns the variable symbols if the variable is part of the signature and the variable equations otherwise.

`val(name)`

Returns (and constructs if necessary) the numeric values of a symbolic entity

Parameters **name** (`str`) – name of the symbolic variable

Return type `typing.List[float]`

Returns list containing the numeric values

amici.ode_export.TemplateAmici

class amici.ode_export.**TemplateAmici**(*template*)
 Template format used in AMICI (see [string.Template](#) for more details).

Variables **delimiter** – delimiter that identifies template variables

__init__(*template*)

Methods Summary

[*__init__*](#)(*template*)

[*safe_substitute*](#)([*mapping*])

[*substitute*](#)([*mapping*])

Attributes

braceidpattern

delimiter

flags

idpattern

pattern

Methods

__init__(*template*)

safe_substitute(*mapping*={}, /, ***kws*)

substitute(*mapping*={}, /, ***kws*)

Functions Summary

<i>apply_template</i> (<i>source_file</i> , <i>target_file</i> , ...)	Load source file, apply template substitution as provided in <i>templateData</i> and save as <i>targetFile</i> .
<i>get_function_extern_declaration</i> (<i>fun</i> , <i>name</i>)	Constructs the extern function declaration for a given function
<i>get_model_override_implementation</i> (<i>fun</i> , <i>name</i>)	Constructs <code>amici::Model::*</code> override implementation for a given function
<i>get_sunindex_extern_declaration</i> (<i>fun</i> , <i>name</i> , ...)	Constructs the function declaration for an index function of a given function

continues on next page

Table 61 – continued from previous page

<code>get_sunindex_override_implementation(fun, ...)</code>	Constructs the <code>amici::Model</code> function implementation for an index function of a given function
<code>is_valid_identififier(x)</code>	Check whether x is a valid identifier for conditions, parameters, observables.
<code>remove_typedefs(signature)</code>	Strips typedef info from a function signature
<code>smart_is_zero_matrix(x)</code>	A faster implementation of sympy's <code>is_zero_matrix</code>
<code>smart_jacobian(eq, sym_var)</code>	Wrapper around symbolic jacobian with some additional checks that reduce computation time for large matrices
<code>smart_multiply(x, y)</code>	Wrapper around symbolic multiplication with some additional checks that reduce computation time for large matrices
<code>var_in_function_signature(name, varname)</code>	Checks if the values for a symbolic variable is passed in the signature of a function

Functions

`amici.ode_export.apply_template(source_file, target_file, template_data)`

Load source file, apply template substitution as provided in `templateData` and save as `targetFile`.

Parameters

- **source_file** (`str`) – relative or absolute path to template file
- **target_file** (`str`) – relative or absolute path to output file
- **template_data** (`typing.Dict[str, str]`) – template keywords to substitute (key is template variable without `TemplateAmici.delimiter`)

Return type

`None`

`amici.ode_export.get_function_extern_declaration(fun, name)`

Constructs the extern function declaration for a given function

Parameters

- **fun** (`str`) – function name
- **name** (`str`) – model name

Return type

`str`

Returns C++ function definition string

`amici.ode_export.get_model_override_implementation(fun, name, nobody=False)`

Constructs `amici::Model::*` override implementation for a given function

Parameters

- **fun** (`str`) – function name
- **name** (`str`) – model name
- **nobody** (`bool`) – whether the function has a nontrivial implementation

Return type

`str`

Returns C++ function implementation string

`amici.ode_export.get_sunindex_extern_declaration(fun, name, indextype)`

Constructs the function declaration for an index function of a given function

Parameters

- **fun** (*str*) – function name
- **name** (*str*) – model name
- **indextype** (*str*) – index function {'colptrs', 'rowvals'}

Return type *str*

Returns C++ function declaration string

`amici.ode_export.get_sunindex_override_implementation(fun, name, indextype, nobody=False)`
Constructs the amici::Model function implementation for an index function of a given function

Parameters

- **fun** (*str*) – function name
- **name** (*str*) – model name
- **indextype** (*str*) – index function {'colptrs', 'rowvals'}
- **nobody** (*bool*) – whether the corresponding function has a nontrivial implementation

Return type *str*

Returns C++ function implementation string

`amici.ode_export.is_valid_identifier(x)`

Check whether *x* is a valid identifier for conditions, parameters, observables... . Identifiers may only contain upper and lower case letters, digits and underscores, and must not start with a digit.

Parameters *x* (*str*) – string to check

Return type *bool*

Returns True if valid, False otherwise

`amici.ode_export.remove_typedefs(signature)`

Strips typedef info from a function signature

Parameters **signature** (*str*) – function signature

Return type *str*

Returns string that can be used to construct function calls with the same variable names and ordering as in the function signature

`amici.ode_export.smart_is_zero_matrix(x)`

A faster implementation of sympy's `is_zero_matrix`

Avoids repeated indexer type checks and double iteration to distinguish False/None. Found to be about 100x faster for large matrices.

Parameters *x* (`typing.Union[sympy.matrices.dense.MutableDenseMatrix, sympy.matrices.sparse.MutableSparseMatrix]`) – Matrix to check

Return type *bool*

`amici.ode_export.smart_jacobian(eq, sym_var)`

Wrapper around symbolic jacobian with some additional checks that reduce computation time for large matrices

Parameters

- **eq** (`sympy.matrices.dense.MutableDenseMatrix`) – equation
- **sym_var** (`sympy.matrices.dense.MutableDenseMatrix`) – differentiation variable

Return type `sympy.matrices.sparse.MutableSparseMatrix`

Returns jacobian of eq wrt sym_var

`amici.ode_export.smart_multiply(x, y)`

Wrapper around symbolic multiplication with some additional checks that reduce computation time for large matrices

Parameters

- **x** (`typing.Union[sympy.matrices.dense.MutableDenseMatrix, sympy.matrices.sparse.MutableSparseMatrix]`) – educt 1
- **y** (`sympy.matrices.dense.MutableDenseMatrix`) – educt 2

Return type `typing.Union[sympy.matrices.dense.MutableDenseMatrix, sympy.matrices.sparse.MutableSparseMatrix]`

Returns product

`amici.ode_export.var_in_function_signature(name, varname)`

Checks if the values for a symbolic variable is passed in the signature of a function

Parameters

- **name** (`str`) – name of the function
- **varname** (`str`) – name of the symbolic variable

Return type `bool`

Returns boolean indicating whether the variable occurs in the function signature

10.4.12 amici.ode_model

Objects for AMICI's internal ODE model representation

Classes

<i>ConservationLaw</i> (identifier, name, value)	A conservation law defines the absolute the total amount of a (weighted) sum of states
<i>Constant</i> (identifier, name, value)	A Constant is a fixed variable in the model with respect to which sensitivities cannot be computed, abbreviated by k.
<i>Event</i> (identifier, name, value, state_update, ...)	An Event defines either a SBML event or a root of the argument of a Heaviside function.
<i>Expression</i> (identifier, name, value)	An Expression is a recurring elements in symbolic formulas.
<i>LogLikelihood</i> (identifier, name, value)	A LogLikelihood defines the distance between measurements and experiments for a particular observable.
<i>ModelQuantity</i> (identifier, name, value)	Base class for model components
<i>Observable</i> (identifier, name, value[, ...])	An Observable links model simulations to experimental measurements, abbreviated by y.
<i>Parameter</i> (identifier, name, value)	A Parameter is a free variable in the model with respect to which sensitivities may be computed, abbreviated by p.

continues on next page

Table 62 – continued from previous page

<i>SigmaY</i> (identifier, name, value)	A Standard Deviation SigmaY rescales the distance between simulations and measurements when computing residuals or objective functions, abbreviated by <i>sigmay</i> .
<i>State</i> (identifier, name, init, dt)	A State variable defines an entity that evolves with time according to the provided time derivative, abbreviated by <i>x</i> .

amici.ode_model.ConservationLaw

class amici.ode_model.**ConservationLaw**(*identifier, name, value*)

A conservation law defines the absolute the total amount of a (weighted) sum of states

__init__(*identifier, name, value*)

Create a new ConservationLaw instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the ConservationLaw
- **name** (`str`) – individual name of the ConservationLaw (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula (sum of states)

Methods Summary

__init__ (identifier, name, value)	Create a new ConservationLaw instance.
get_id ()	ModelQuantity identifier
get_name ()	ModelQuantity name
get_val ()	ModelQuantity value
set_val (val)	Set ModelQuantity value

Methods

__init__(*identifier, name, value*)

Create a new ConservationLaw instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the ConservationLaw
- **name** (`str`) – individual name of the ConservationLaw (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula (sum of states)

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

get_name()

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`**Returns** value of the ModelQuantity**set_val(val)**

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.Constant

class `amici.ode_model.Constant(identifier, name, value)`

A Constant is a fixed variable in the model with respect to which sensitivities cannot be computed, abbreviated by k.

__init__(*identifier, name, value*)

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Constant
- **name** (`str`) – individual name of the Constant (does not need to be unique)
- **value** (`numbers.Number`) – numeric value

Methods Summary

<code>__init__(identifier, name, value)</code>	Create a new Expression instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

__init__(*identifier, name, value*)

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Constant
- **name** (`str`) – individual name of the Constant (does not need to be unique)
- **value** (`numbers.Number`) – numeric value

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`**Returns** identifier of the ModelQuantity**get_name()**

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

set_val(val)

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.Event

class `amici.ode_model.Event(identifier, name, value, state_update, event_observable)`

An Event defines either a SBML event or a root of the argument of a Heaviside function. The Heaviside functions will be tracked via the vector `h` during simulation and are needed to inform the ODE solver about a discontinuity in either the right-hand side or the states themselves, causing a reinitialization of the solver.

__init__(identifier, name, value, state_update, event_observable)

Create a new Event instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Event
- **name** (`str`) – individual name of the Event (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula for the root / trigger function
- **state_update** (`typing.Optional[sympy.core.expr.Expr]`) – formula for the bolus function (None for Heaviside functions, zero vector for events without bolus)
- **event_observable** (`typing.Optional[sympy.core.expr.Expr]`) – formula a potential observable linked to the event (None for Heaviside functions, empty events without observable)

Methods Summary

<code>__init__(identifier, name, value, ...)</code>	Create a new Event instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

__init__(*identifier, name, value, state_update, event_observable*)

Create a new Event instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Event
- **name** (`str`) – individual name of the Event (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula for the root / trigger function
- **state_update** (`typing.Optional[sympy.core.expr.Expr]`) – formula for the bolus function (None for Heaviside functions, zero vector for events without bolus)
- **event_observable** (`typing.Optional[sympy.core.expr.Expr]`) – formula a potential observable linked to the event (None for Heaviside functions, empty events without observable)

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

get_name()

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

set_val(*val*)

Set ModelQuantity value

Returns value of the ModelQuantity

`amici.ode_model.Expression`

class `amici.ode_model.Expression`(*identifier, name, value*)

An Expression is a recurring elements in symbolic formulas. Specifying this may yield more compact expression which may lead to substantially shorter model compilation times, but may also reduce model simulation time. Abbreviated by `w`.

__init__(*identifier, name, value*)

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Expression
- **name** (`str`) – individual name of the Expression (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

Methods Summary

<code>__init__(identifier, name, value)</code>	Create a new Expression instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

`__init__(identifier, name, value)`

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Expression
- **name** (`str`) – individual name of the Expression (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

`get_id()`

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

`get_name()`

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

`get_val()`

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

`set_val(val)`

Set ModelQuantity value

Returns value of the ModelQuantity

`amici.ode_model.LogLikelihood`

class `amici.ode_model.LogLikelihood(identifier, name, value)`

A LogLikelihood defines the distance between measurements and experiments for a particular observable. The final LogLikelihood value in the simulation will be the sum of all specified LogLikelihood instances evaluated at all timepoints, abbreviated by Jy.

`__init__(identifier, name, value)`

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the LogLikelihood

- **name** (`str`) – individual name of the LogLikelihood (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

Methods Summary

<code>__init__(identifier, name, value)</code>	Create a new Expression instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

`__init__(identifier, name, value)`

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the LogLikelihood
- **name** (`str`) – individual name of the LogLikelihood (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

`get_id()`

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

`get_name()`

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

`get_val()`

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

`set_val(val)`

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.ModelQuantity

class amici.ode_model.**ModelQuantity**(*identifier, name, value*)

Base class for model components

__init__(*identifier, name, value*)

Create a new ModelQuantity instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the quantity
- **name** (`str`) – individual name of the quantity (does not need to be unique)
- **value** (`typing.Union[typing.SupportsFloat, numbers.Number, sympy.core.expr.Expr]`) – either formula, numeric value or initial value

Methods Summary

<code>__init__</code> (<i>identifier, name, value</i>)	Create a new ModelQuantity instance.
<code>get_id</code> ()	ModelQuantity identifier
<code>get_name</code> ()	ModelQuantity name
<code>get_val</code> ()	ModelQuantity value
<code>set_val</code> (<i>val</i>)	Set ModelQuantity value

Methods

__init__(*identifier, name, value*)

Create a new ModelQuantity instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the quantity
- **name** (`str`) – individual name of the quantity (does not need to be unique)
- **value** (`typing.Union[typing.SupportsFloat, numbers.Number, sympy.core.expr.Expr]`) – either formula, numeric value or initial value

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

get_name()

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

set_val(*val*)

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.Observable

class amici.ode_model.Observable(*identifier*, *name*, *value*, *measurement_symbol*=None, *transformation*='lin')

An Observable links model simulations to experimental measurements, abbreviated by y.

Variables

- **_measurement_symbol** – sympy symbol used in the objective function to represent measurements to this observable
- **trafo** – observable transformation, only applies when evaluating objective function or residuals

__init__(*identifier*, *name*, *value*, *measurement_symbol*=None, *transformation*='lin')

Create a new Observable instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Observable
- **name** (`str`) – individual name of the Observable (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula
- **transformation** (`typing.Optional[amici.import_utils.ObservableTransformation]`) – observable transformation, only applies when evaluating objective function or residuals

Methods Summary

<code>__init__</code> (<i>identifier</i> , <i>name</i> , <i>value</i> [, ...])	Create a new Observable instance.
<code>get_id</code> ()	ModelQuantity identifier
<code>get_measurement_symbol</code> ()	rtype <code>sympy.core.symbol.Symbol</code>
<code>get_name</code> ()	ModelQuantity name
<code>get_val</code> ()	ModelQuantity value
<code>set_val</code> (<i>val</i>)	Set ModelQuantity value

Methods

__init__(*identifier*, *name*, *value*, *measurement_symbol*=None, *transformation*='lin')

Create a new Observable instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Observable
- **name** (`str`) – individual name of the Observable (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

- **transformation** (`typing.Optional[amici.import_utils.ObservableTransformation]`) – observable transformation, only applies when evaluating objective function or residuals

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

get_measurement_symbol()

Return type `sympy.core.symbol.Symbol`

get_name()

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

set_val(val)

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.Parameter

class `amici.ode_model.Parameter(identifier, name, value)`

A Parameter is a free variable in the model with respect to which sensitivities may be computed, abbreviated by p.

__init__(identifier, name, value)

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Parameter
- **name** (`str`) – individual name of the Parameter (does not need to be unique)
- **value** (`numbers.Number`) – numeric value

Methods Summary

<code>__init__(identifier, name, value)</code>	Create a new Expression instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

`__init__(identifier, name, value)`

Create a new Expression instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Parameter
- **name** (`str`) – individual name of the Parameter (does not need to be unique)
- **value** (`numbers.Number`) – numeric value

`get_id()`

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

`get_name()`

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

`get_val()`

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

`set_val(val)`

Set ModelQuantity value

Returns value of the ModelQuantity

`amici.ode_model.SigmaY`

class `amici.ode_model.SigmaY(identifier, name, value)`

A Standard Deviation SigmaY rescales the distance between simulations and measurements when computing residuals or objective functions, abbreviated by `sigmay`.

`__init__(identifier, name, value)`

Create a new Standard Deviation instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Standard Deviation

- **name** (`str`) – individual name of the Standard Deviation (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

Methods Summary

<code>__init__(identifier, name, value)</code>	Create a new Standard Deviation instance.
<code>get_id()</code>	ModelQuantity identifier
<code>get_name()</code>	ModelQuantity name
<code>get_val()</code>	ModelQuantity value
<code>set_val(val)</code>	Set ModelQuantity value

Methods

`__init__(identifier, name, value)`

Create a new Standard Deviation instance.

Parameters

- **identifier** (`sympy.core.symbol.Symbol`) – unique identifier of the Standard Deviation
- **name** (`str`) – individual name of the Standard Deviation (does not need to be unique)
- **value** (`sympy.core.expr.Expr`) – formula

`get_id()`

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

`get_name()`

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

`get_val()`

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

`set_val(val)`

Set ModelQuantity value

Returns value of the ModelQuantity

amici.ode_model.State

class amici.ode_model.State(*identifier, name, init, dt*)

A State variable defines an entity that evolves with time according to the provided time derivative, abbreviated by *x*.

Variables

- **_conservation_law** – algebraic formula that allows computation of this state according to a conservation law
- **_dt** – algebraic formula that defines the temporal derivative of this state

__init__(*identifier, name, init, dt*)

Create a new State instance. Extends *ModelQuantity.__init__()* by *dt*

Parameters

- **identifier** (*sympy.core.symbol.Symbol*) – unique identifier of the state
- **name** (*str*) – individual name of the state (does not need to be unique)
- **init** (*sympy.core.expr.Expr*) – initial value
- **dt** (*sympy.core.expr.Expr*) – time derivative

Methods Summary

<i>__init__</i> (<i>identifier, name, init, dt</i>)	Create a new State instance.
<i>get_dt</i> ()	Gets the time derivative
<i>get_free_symbols</i> ()	Gets the set of free symbols in time derivative and initial conditions
<i>get_id</i> ()	ModelQuantity identifier
<i>get_name</i> ()	ModelQuantity name
<i>get_val</i> ()	ModelQuantity value
<i>set_conservation_law</i> (<i>law</i>)	Sets the conservation law of a state.
<i>set_dt</i> (<i>dt</i>)	Sets the time derivative
<i>set_val</i> (<i>val</i>)	Set ModelQuantity value

Methods

__init__(*identifier, name, init, dt*)

Create a new State instance. Extends *ModelQuantity.__init__()* by *dt*

Parameters

- **identifier** (*sympy.core.symbol.Symbol*) – unique identifier of the state
- **name** (*str*) – individual name of the state (does not need to be unique)
- **init** (*sympy.core.expr.Expr*) – initial value
- **dt** (*sympy.core.expr.Expr*) – time derivative

get_dt()

Gets the time derivative

Return type *sympy.core.expr.Expr*

Returns time derivative

get_free_symbols()

Gets the set of free symbols in time derivative and initial conditions

Return type `typing.Set[sympy.core.symbol.Symbol]`

Returns free symbols

get_id()

ModelQuantity identifier

Return type `sympy.core.symbol.Symbol`

Returns identifier of the ModelQuantity

get_name()

ModelQuantity name

Return type `str`

Returns name of the ModelQuantity

get_val()

ModelQuantity value

Return type `sympy.core.expr.Expr`

Returns value of the ModelQuantity

set_conservation_law(*law*)

Sets the conservation law of a state.

If a conservation law is set, the respective state will be replaced by an algebraic formula according to the respective conservation law.

Parameters **law** (`sympy.core.expr.Expr`) – linear sum of states that if added to this state remain constant over time

Return type `None`

set_dt(*dt*)

Sets the time derivative

Parameters **dt** (`sympy.core.expr.Expr`) – time derivative

Return type `None`

set_val(*val*)

Set ModelQuantity value

Returns value of the ModelQuantity

10.4.13 amici.plotting

Plotting

Plotting related functions

Functions Summary

<code>plotObservableTrajectories(rdata[, ...])</code>	Plot observable trajectories
<code>plotStateTrajectories(rdata[, ...])</code>	Plot state trajectories

Functions

`amici.plotting.plotObservableTrajectories(rdata, observable_indices=None, ax=None, model=None)`
Plot observable trajectories

Parameters

- **rdata** (`amici.numpy.ReturnDataView`) – AMICI simulation results as returned by `amici.amici.runAmiciSimulation()`
- **observable_indices** (`typing.Optional[typing.Iterable[int]]`) – Indices of observables for which trajectories are to be plotted
- **ax** (`typing.Optional[matplotlib.axes._axes.Axes]`) – matplotlib Axes instance to plot into
- **model** (`typing.Optional[amici.amici.Model]`) – amici model instance

Return type `None`

`amici.plotting.plotStateTrajectories(rdata, state_indices=None, ax=None, model=None)`
Plot state trajectories

Parameters

- **rdata** (`amici.numpy.ReturnDataView`) – AMICI simulation results as returned by `amici.amici.runAmiciSimulation()`
- **state_indices** (`typing.Optional[typing.Iterable[int]]`) – Indices of states for which trajectories are to be plotted
- **ax** (`typing.Optional[matplotlib.axes._axes.Axes]`) – matplotlib Axes instance to plot into
- **model** (`typing.Optional[amici.amici.Model]`) – amici model instance

Return type `None`

10.4.14 amici.pandas

Pandas Wrappers

This module contains convenience wrappers that allow for easy interconversion between C++ objects from `amici` and pandas DataFrames

Functions Summary

<code>constructEdataFromDataFrame(df, model, condition)</code>	Constructs an ExpData instance according to the provided Model and DataFrame.
<code>getDataObservablesAsDataFrame(model, edata_list)</code>	Write Observables from experimental data as DataFrame.
<code>getEdataFromDataFrame(model, df[, by_id])</code>	Constructs a ExpData instances according to the provided Model and DataFrame.
<code>getResidualsAsDataFrame(model, edata_list, ...)</code>	Convert a list of ReturnData and ExpData to pandas DataFrame with residuals.
<code>getSimulationObservablesAsDataFrame(model, ...)</code>	Write Observables from simulation results as DataFrame.
<code>getSimulationStatesAsDataFrame(model, ...[, ...])</code>	Get model state according to lists of ReturnData and ExpData.
<code>get_expressions_as_dataframe(model, ...[, by_id])</code>	Get values of model expressions from lists of ReturnData as DataFrame.

Functions

`amici.pandas.constructEdataFromDataFrame(df, model, condition, by_id=False)`

Constructs an ExpData instance according to the provided Model and DataFrame.

Parameters

- **df** (`pandas.core.frame.DataFrame`) – `pd.DataFrame` with Observable Names/Ids as columns. Standard deviations may be specified by appending ‘_std’ as suffix.
- **model** (`typing.Union[amici.amici.ModelPtr, amici.amici.Model]`) – Model instance.
- **condition** (`pandas.core.series.Series`) – `pd.Series` with FixedParameter Names/Ids as columns. Preequilibration conditions may be specified by appending ‘_preeq’ as suffix. Presimulation conditions may be specified by appending ‘_presim’ as suffix.
- **by_id** (`typing.Optional[bool]`) – Indicate whether in the arguments, column headers are based on ids or names. This should correspond to the way *df* and *condition* was created in the first place.

Return type `amici.amici.ExpData`

Returns ExpData instance.

`amici.pandas.getDataObservablesAsDataFrame(model, edata_list, by_id=False)`

Write Observables from experimental data as DataFrame.

Parameters

- **model** (`typing.Union[amici.amici.ModelPtr, amici.amici.Model]`) – Model instance.
- **edata_list** (`typing.Union[typing.List[amici.amici.ExpData], typing.List[amici.amici.ExpDataPtr], amici.amici.ExpData, amici.amici.ExpDataPtr]`) – list of ExpData instances with experimental data. May also be a single ExpData instance.
- **by_id** (`typing.Optional[bool]`) – If True, uses observable ids as column names in the generated DataFrame, otherwise the possibly more descriptive observable names are used.

Return type `pandas.core.frame.DataFrame`

Returns pandas DataFrame with conditions/timepoints as rows and observables as columns.

`amici.pandas.getEdataFromDataFrame(model, df, by_id=False)`

Constructs a ExpData instances according to the provided Model and DataFrame.

Parameters

- **df** (`pandas.core.frame.DataFrame`) – dataframe with Observable Names/Ids, FixedParameter Names/Ids and time as columns. Standard deviations may be specified by appending ‘_std’ as suffix. Preequilibration fixedParameters may be specified by appending ‘_preeq’ as suffix. Presimulation fixedParameters may be specified by appending ‘_presim’ as suffix. Presimulation time may be specified as ‘t_presim’ column.
- **model** (`typing.Union[amici.amici.ModelPtr, amici.amici.Model]`) – Model instance.
- **by_id** (`typing.Optional[bool]`) – Whether the column names in *df* are based on ids or names, corresponding to how the dataframe was created in the first place.

Return type `typing.List[amici.amici.ExpData]`

Returns list of ExpData instances.

`amici.pandas.getResidualsAsDataFrame(model, edata_list, rdata_list, by_id=False)`

Convert a list of ReturnData and ExpData to pandas DataFrame with residuals.

Parameters

- **model** (`amici.amici.Model`) – Model instance.
- **edata_list** (`typing.Union[typing.List[amici.amici.ExpData], typing.List[amici.amici.ExpDataPtr], amici.amici.ExpData, amici.amici.ExpDataPtr]`) – list of ExpData instances with experimental data. May also be a single ExpData instance.
- **rdata_list** (`typing.Union[typing.List[amici.numpy.ReturnDataView], amici.numpy.ReturnDataView]`) – list of ReturnData instances corresponding to ExpData. May also be a single ReturnData instance.
- **by_id** (`typing.Optional[bool]`) – bool, optional (default = False) If True, ids are used as identifiers, otherwise the possibly more descriptive names.

Return type `pandas.core.frame.DataFrame`

Returns pandas DataFrame with conditions and residuals.

`amici.pandas.getSimulationObservablesAsDataFrame(model, edata_list, rdata_list, by_id=False)`

Write Observables from simulation results as DataFrame.

Parameters

- **model** (`amici.amici.Model`) – Model instance.
- **edata_list** (`typing.Union[typing.List[amici.amici.ExpData], typing.List[amici.amici.ExpDataPtr], amici.amici.ExpData, amici.amici.ExpDataPtr]`) – list of ExpData instances with experimental data. May also be a single ExpData instance.
- **rdata_list** (`typing.Union[typing.List[amici.numpy.ReturnDataView], amici.numpy.ReturnDataView]`) – list of ReturnData instances corresponding to ExpData. May also be a single ReturnData instance.

- **by_id** (`typing.Optional[bool]`) – If True, ids are used as identifiers, otherwise the possibly more descriptive names.

Return type `pandas.core.frame.DataFrame`

Returns pandas DataFrame with conditions/timepoints as rows and observables as columns.

`amici.pandas.getSimulationStatesAsDataFrame(model, edata_list, rdata_list, by_id=False)`

Get model state according to lists of ReturnData and ExpData.

Parameters

- **model** (`amici.amici.Model`) – Model instance.
- **edata_list** (`typing.Union[typing.List[amici.amici.ExpData], typing.List[amici.amici.ExpDataPtr], amici.amici.ExpData, amici.amici.ExpDataPtr]`) – list of ExpData instances with experimental data. May also be a single ExpData instance.
- **rdata_list** (`typing.Union[typing.List[amici.numpy.ReturnDataView], amici.numpy.ReturnDataView]`) – list of ReturnData instances corresponding to ExpData. May also be a single ReturnData instance.
- **by_id** (`typing.Optional[bool]`) – If True, ids are used as identifiers, otherwise the possibly more descriptive names.

Return type `pandas.core.frame.DataFrame`

Returns pandas DataFrame with conditions/timepoints as rows and state variables as columns.

`amici.pandas.get_expressions_as_dataframe(model, edata_list, rdata_list, by_id=False)`

Get values of model expressions from lists of ReturnData as DataFrame.

Parameters

- **model** (`amici.amici.Model`) – Model instance.
- **edata_list** (`typing.Union[typing.List[amici.amici.ExpData], typing.List[amici.amici.ExpDataPtr], amici.amici.ExpData, amici.amici.ExpDataPtr]`) – list of ExpData instances with experimental data. May also be a single ExpData instance.
- **rdata_list** (`typing.Union[typing.List[amici.numpy.ReturnDataView], amici.numpy.ReturnDataView]`) – list of ReturnData instances corresponding to ExpData. May also be a single ReturnData instance.
- **by_id** (`typing.Optional[bool]`) – If True, ids are used as identifiers, otherwise the possibly more descriptive names.

Return type `pandas.core.frame.DataFrame`

Returns pandas DataFrame with conditions/timepoints as rows and model expressions as columns.

10.4.15 amici.logging

Logging

This module provides custom logging functionality for other amici modules

Functions Summary

<code>get_logger([logger_name, log_level])</code>	Returns (if extistant) or creates an AMICI logger
<code>log_execution_time(description, logger)</code>	Parameterized function decorator that enables automatic execution time tracking
<code>set_log_level(logger, log_level)</code>	rtype None

Functions

`amici.logging.get_logger(logger_name='amici', log_level=None, **kwargs)`

Returns (if extistant) or creates an AMICI logger

If the AMICI base logger has already been set up, this method will return it or any of its descendant loggers without overriding the settings - i.e. any values supplied as kwargs will be ignored.

Parameters

- **logger_name** (`typing.Optional[str]`) – Get a logger for a specific namespace, typically `__name__` for code outside of classes or `self.__module__` inside a class
- **log_level** (`typing.Optional[int]`) – Override the default or preset log level for the requested logger. None or False uses the default or preset value. True evaluates to logging.DEBUG. Any integer is used directly.
- **console_output** – Set up a default console log handler if True (default). Only used when the AMICI logger hasn't been set up yet.
- **file_output** – Supply a filename to copy all log output to that file, or set to False to disable (default). Only used when the AMICI logger hasn't been set up yet.
- **capture_warnings** – Capture warnings from Python's warnings module if True (default). Only used when the AMICI logger hasn't been set up yet..

Return type `logging.Logger`

Returns A logging.Logger object with the requested name

`amici.logging.log_execution_time(description, logger)`

Parameterized function decorator that enables automatic execution time tracking

Parameters

- **description** (`str`) – Description of what the decorated function does
- **logger** (`logging.Logger`) – Logger to which execution timing will be printed

Return type `typing.Callable`

`amici.logging.set_log_level(logger, log_level)`

Return type `None`

10.4.16 amici.gradient_check

Finite Difference Check

This module provides functions to automatically check correctness of amici computed sensitivities using finite difference approximations

Functions Summary

<code>check_derivatives(model, solver[, edata, ...])</code>	Finite differences check for likelihood gradient.
<code>check_finite_difference(x0, model, solver, ...)</code>	Checks the computed sensitivity based derivatives against a finite difference approximation.

Functions

`amici.gradient_check.check_derivatives(model, solver, edata=None, atol=0.0001, rtol=0.0001, epsilon=0.001, check_least_squares=True, skip_zero_pars=False)`

Finite differences check for likelihood gradient.

Parameters

- **model** (`amici.amici.Model`) – amici model
- **solver** (`amici.amici.Solver`) – amici solver
- **edata** (`typing.Optional[amici.swig_wrappers.ExpData]`) – exp data
- **atol** (`typing.Optional[float]`) – absolute tolerance for comparison
- **rtol** (`typing.Optional[float]`) – relative tolerance for comparison
- **epsilon** (`typing.Optional[float]`) – finite difference step-size
- **check_least_squares** (`bool`) – whether to check least squares related values.
- **skip_zero_pars** (`bool`) – whether to perform FD checks for parameters that are zero

Return type `None`

`amici.gradient_check.check_finite_difference(x0, model, solver, edata, ip, fields, atol=0.0001, rtol=0.0001, epsilon=0.001)`

Checks the computed sensitivity based derivatives against a finite difference approximation.

Parameters

- **x0** (`typing.Sequence[float]`) – parameter value at which to check finite difference approximation
- **model** (`amici.amici.Model`) – amici model
- **solver** (`amici.amici.Solver`) – amici solver
- **edata** (`amici.swig_wrappers.ExpData`) – exp data
- **ip** (`int`) – parameter index

- **fields** (`typing.List[str]`) – rdata fields for which to check the gradient
- **atol** (`typing.Optional[float]`) – absolute tolerance for comparison
- **rtol** (`typing.Optional[float]`) – relative tolerance for comparison
- **epsilon** (`typing.Optional[float]`) – finite difference step-size

Return type `None`

10.4.17 amici.parameter_mapping

Parameter mapping

When performing parameter inference, often parameters need to be mapped from simulation to estimation parameters, and parameters can differ between conditions. This can be handled using the *ParameterMapping*.

Note: While the parameter mapping can be used directly with AMICI, it was developed for usage together with PETab, for which the whole workflow of generating the mapping is automatized.

Classes

<code>ParameterMapping([parameter_mappings])</code>	Parameter mapping for multiple conditions.
<code>ParameterMappingForCondition([map_sim_var, ...])</code>	Parameter mapping for condition.

amici.parameter_mapping.ParameterMapping

class `amici.parameter_mapping.ParameterMapping`(*parameter_mappings=None*)

Parameter mapping for multiple conditions.

This can be used like a list of *ParameterMappingForConditions*.

Parameters `parameter_mappings` (`typing.Optional[typing.List[amici.parameter_mapping.ParameterMappingForCondition]]`) – List of parameter mappings for specific conditions.

__init__(*parameter_mappings=None*)

Methods Summary

<code>__init__([parameter_mappings])</code>	
<code>append(parameter_mapping_for_condition)</code> <code>count(value)</code>	Append a condition specific parameter mapping.
<code>index(value, [start, [stop]])</code>	Raises <code>ValueError</code> if the value is not present.

Methods

`__init__`(*parameter_mappings=None*)

`append`(*parameter_mapping_for_condition*)
Append a condition specific parameter mapping.

`count`(*value*) → integer -- return number of occurrences of value

`index`(*value*[, *start*[, *stop*]]) → integer -- return first index of value.
Raises `ValueError` if the value is not present.

Supporting start and stop arguments is optional, but recommended.

`amici.parameter_mapping.ParameterMappingForCondition`

`class amici.parameter_mapping.ParameterMappingForCondition`(*map_sim_var=None*,
scale_map_sim_var=None,
map_preeq_fix=None,
scale_map_preeq_fix=None,
map_sim_fix=None,
scale_map_sim_fix=None)

Parameter mapping for condition.

Contains mappings for free parameters, fixed parameters, and fixed preequilibration parameters, both for parameters and scales.

In the scale mappings, for each simulation parameter the scale on which the value is passed (and potentially gradients are to be returned) is given. In the parameter mappings, for each simulation parameter a corresponding optimization parameter (or a numeric value) is given.

If a mapping is not passed, the parameter mappings are assumed to be empty, and if a scale mapping is not passed, all scales are set to linear.

Parameters

- **`map_sim_var`** (`typing.Optional[typing.Dict[str, typing.Union[str, numbers.Number]]]`) – Mapping for free simulation parameters.
- **`scale_map_sim_var`** (`typing.Optional[typing.Dict[str, str]]`) – Scales for free simulation parameters.
- **`map_preeq_fix`** (`typing.Optional[typing.Dict[str, typing.Union[str, numbers.Number]]]`) – Mapping for fixed preequilibration parameters.
- **`scale_map_preeq_fix`** (`typing.Optional[typing.Dict[str, str]]`) – Scales for fixed preequilibration parameters.
- **`map_sim_fix`** (`typing.Optional[typing.Dict[str, typing.Union[str, numbers.Number]]]`) – Mapping for fixed simulation parameters.
- **`scale_map_sim_fix`** (`typing.Optional[typing.Dict[str, str]]`) – Scales for fixed simulation parameters.

`__init__`(*map_sim_var=None*, *scale_map_sim_var=None*, *map_preeq_fix=None*,
scale_map_preeq_fix=None, *map_sim_fix=None*, *scale_map_sim_fix=None*)

Methods Summary

```
__init__([map_sim_var, scale_map_sim_var, ...])
```

Methods

```
__init__(map_sim_var=None, scale_map_sim_var=None, map_preeq_fix=None,
         scale_map_preeq_fix=None, map_sim_fix=None, scale_map_sim_fix=None)
```

Functions Summary

<code>amici_to_petab_scale(amici_scale)</code>	Convert amici scale id to petab scale id.
<code>fill_in_parameters(edatas, ...)</code>	Fill fixed and dynamic parameters into the edatas (in-place).
<code>fill_in_parameters_for_condition(edata, ...)</code>	Fill fixed and dynamic parameters into the edata for condition (in-place).
<code>petab_to_amici_scale(petab_scale)</code>	Convert petab scale id to amici scale id.
<code>scale_parameter(value, petab_scale)</code>	Bring parameter from linear scale to target scale.
<code>scale_parameters_dict(value_dict, ...)</code>	Bring parameters from linear scale to target scale.
<code>unscale_parameter(value, petab_scale)</code>	Bring parameter from scale to linear scale.
<code>unscale_parameters_dict(value_dict, ...)</code>	Bring parameters from target scale to linear scale.

Functions

`amici.parameter_mapping.amici_to_petab_scale(amici_scale)`
Convert amici scale id to petab scale id.

Return type `str`

`amici.parameter_mapping.fill_in_parameters(edatas, problem_parameters, scaled_parameters, parameter_mapping, amici_model)`
Fill fixed and dynamic parameters into the edatas (in-place).

Parameters

- **edatas** (`typing.List[amici.swig_wrappers.ExpData]`) – List of experimental datas `amici.amici.ExpData` with everything except parameters filled.
- **problem_parameters** (`typing.Dict[str, numbers.Number]`) – Problem parameters as `parameterId=>value` dict. Only parameters included here will be set. Remaining parameters will be used as currently set in `amici_model`.
- **scaled_parameters** (`bool`) – If True, `problem_parameters` are assumed to be on the scale provided in the parameter mapping. If False, they are assumed to be in linear scale.
- **parameter_mapping** (`amici.parameter_mapping.ParameterMapping`) – Parameter mapping for all conditions.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI model.

Return type `None`

`amici.parameter_mapping.fill_in_parameters_for_condition(edata, problem_parameters,
scaled_parameters, parameter_mapping,
amici_model)`

Fill fixed and dynamic parameters into the edata for condition (in-place).

Parameters

- **edata** (`amici.swig_wrappers.ExpData`) – Experimental data object to fill parameters into.
- **problem_parameters** (`typing.Dict[str, numbers.Number]`) – Problem parameters as parameterId=>value dict. Only parameters included here will be set. Remaining parameters will be used as already set in *amici_model* and *edata*.
- **scaled_parameters** (`bool`) – If True, problem_parameters are assumed to be on the scale provided in the parameter mapping. If False, they are assumed to be in linear scale.
- **parameter_mapping** (`amici.parameter_mapping.ParameterMappingForCondition`) – Parameter mapping for current condition.
- **amici_model** (`typing.Union[amici.amici.Model, amici.amici.ModelPtr]`) – AMICI model

Return type `None`

`amici.parameter_mapping.petab_to_amici_scale(petab_scale)`

Convert petab scale id to amici scale id.

Return type `int`

`amici.parameter_mapping.scale_parameter(value, petab_scale)`

Bring parameter from linear scale to target scale.

Parameters

- **value** (`numbers.Number`) – Value to scale
- **petab_scale** (`str`) – Target scale of value

Return type `numbers.Number`

Returns value on target scale

`amici.parameter_mapping.scale_parameters_dict(value_dict, petab_scale_dict)`

Bring parameters from linear scale to target scale.

Bring values in *value_dict* from linear scale to the scale provided in *petab_scale_dict* (in-place). Both arguments are expected to have the same length and matching keys.

Parameters

- **value_dict** (`typing.Dict[typing.Any, numbers.Number]`) – Values to scale
- **petab_scale_dict** (`typing.Dict[typing.Any, str]`) – Target scales of values

Return type `None`

`amici.parameter_mapping.unscale_parameter(value, petab_scale)`

Bring parameter from scale to linear scale.

Parameters

- **value** (`numbers.Number`) – Value to scale
- **petab_scale** (`str`) – Target scale of value

Return type `numbers.Number`

Returns value on linear scale

`amici.parameter_mapping.unscale_parameters_dict(value_dict, petab_scale_dict)`

Bring parameters from target scale to linear scale.

Bring values in `value_dict` from linear scale to the scale provided in `petab_scale_dict` (in-place). Both arguments are expected to have the same length and matching keys.

Parameters

- **value_dict** (`typing.Dict[typing.Any, numbers.Number]`) – Values to scale
- **petab_scale_dict** (`typing.Dict[typing.Any, str]`) – Target scales of values

Return type `None`

10.4.18 amici.conservated_quantities_demartino

Functions Summary

<code>compute_moiety_conservation_laws(...[, ...])</code>	Compute moiety conservation laws.
-----------------------------------------------------------	-----------------------------------

Functions

`amici.conservated_quantities_demartino.compute_moiety_conservation_laws(stoichiometric_list, num_species, num_reactions, max_num_monte_carlo=20, rng_seed=False, species_names=None)`

Compute moiety conservation laws.

According to the algorithm proposed by De Martino et al. (2014) <https://doi.org/10.1371/journal.pone.0100750>

Parameters

- **stoichiometric_list** (`typing.Sequence[float]`) – the stoichiometric matrix as a list (species x reactions, column-major ordering)
- **num_species** (`int`) – total number of species in the reaction network
- **num_reactions** (`int`) – total number of reactions in the reaction network
- **max_num_monte_carlo** (`int`) – maximum number of MonteCarlo steps before changing to relaxation
- **rng_seed** (`typing.Union[None, bool, int]`) – Seed for the random number generator. If `False`, the RNG will not be re-initialized. Other values will be passed to `random.seed()`.
- **species_names** (`typing.Optional[typing.Sequence[str]]`) – Species names. Optional and only used for logging.

Return type `typing.Tuple[typing.List[typing.List[int]], typing.List[typing.List[float]]]`

Returns Integer MCLs as list of lists of indices of involved species and list of lists of corresponding coefficients.

10.4.19 amici.conservated_quantities_rref

Find conserved quantities deterministically

Functions Summary

<code>nullspace_by_rref(mat)</code>	Compute basis of the nullspace of <code>mat</code> based on the reduced row echelon form
<code>pivots(mat)</code>	Get indices of pivot columns in <code>mat</code> , assumed to be in reduced row echelon form
<code>rref(mat[, round_ndigits])</code>	Bring matrix <code>mat</code> to reduced row echelon form

Functions

`amici.conservated_quantities_rref.nullspace_by_rref(mat)`

Compute basis of the nullspace of `mat` based on the reduced row echelon form

Return type `numpy.array`

`amici.conservated_quantities_rref.pivots(mat)`

Get indices of pivot columns in `mat`, assumed to be in reduced row echelon form

Return type `typing.List[int]`

`amici.conservated_quantities_rref.rref(mat, round_ndigits=None)`

Bring matrix `mat` to reduced row echelon form

see https://en.wikipedia.org/wiki/Row_echelon_form

Parameters

- **mat** (`numpy.array`) – Numpy float matrix to operate on (will be copied)
- **round_ndigits** (`typing.Union[typing.Literal[False], int, None]`) – Number of digits to round intermediary results to, or `False` to disable rounding completely. Helps to avoid numerical artifacts.

Return type `numpy.array`

Returns `mat` in rref form.

C++ INTERFACE

11.1 Building the C++ library

The following section describes building the AMICI C++ library:

Note: The AMICI C++ interface only supports simulation of models imported using the *Python interface* and *Matlab interface*. It cannot be used for model import itself.

Prerequisites:

- CBLAS compatible BLAS library
- HDF5 libraries (currently mandatory, see <https://github.com/AMICI-dev/AMICI/issues/1252>)
- a C++14 compatible compiler
- a C compiler
- Optional: boost for serialization

To use AMICI from C++, run the

```
./scripts/buildSuiteSparse.sh  
./scripts/buildSundials.sh  
./scripts/buildAmici.sh
```

script to build the AMICI library.

Note: On some systems, the CMake executable may be named something other than `cmake`. In this case, set the `CMAKE` environment variable to the correct name (e.g. `export CMAKE=cmake3`, in case you have CMake available as `cmake3`).

The static library can then be linked from

```
./build/libamici.a
```

In CMake-based packages, amici can be linked via

```
find_package(Amici)
```

For further usage, consult the AMICI *C++ interface documentation*.

11.1.1 Supported CBLAS libraries

The C++ interfaces require a system installation of a CBLAS-compatible *Basic Linear Algebra Subprograms* (BLAS) library. AMICI has been tested with various implementations such as Accelerate, Intel MKL, cblas, openblas and atlas.

11.1.2 Optional SuperLU_MT support

To build AMICI with SuperLU_MT support, run

```
./scripts/buildSuperLUMT.sh
./scripts/buildSundials.sh
cd build/
cmake -DSUNDIALS_SUPERLUMT_ENABLE=ON ..
make
```

11.2 Using AMICI's C++ interface

The various import functions in of the *Python interface* and *Matlab interface* translate models defined in different formats into C++ code. These generated model libraries, together with the AMICI base library can be used in any C++ application for model simulation and sensitivity analysis. This section will give a short overview over the generated files and provide a brief introduction of how this code can be included in other applications. Further details are available in the *C++ API reference*.

11.2.1 AMICI-generated C++ model files

After importing a model using either the *Python interface* or the *Matlab interface*, the specified output directory contains (among others) C++ code for the various model functions.

The content of a model source directory looks something like this (given *MODEL_NAME=model_steadystate*):

```
CMakeLists.txt
main.cpp
model_steadystate_deltaqB.cpp
model_steadystate_deltaqB.h
[... many more files model_steadystate_*.cpp|h|md5|o ]
wrapfunctions.cpp
wrapfunctions.h
model_steadystate.h
```

These files provide the implementation of a model-specific subclass of `amici::Model`. The `CMakeLists.txt` file can be used to build the model library using `CMake`. `main.cpp` contains a simple scaffold for running a model simulation from C++. See next section for more details on these files.

11.2.2 Running a model simulation

AMICI's public API is mostly available through `amici/amici.h`. This is the only header file that needs to be included for basic usage. All functions there are declared within the *amici namespace*. Additionally, `amici/hdf5.h` and `amici/serialization.h` may be handy for specific use cases. The former provides some functions for reading and writing *HDF5* files, latter for serialization (requires *Boost*). All model-specific functions are defined in the namespace `model_${modelname}`.

The main function for running an AMICI simulation is `amici::runAmiciSimulation()`. This function requires

- an instance of a `amici::Model` subclass as generated during model import. For the example `model_steadystate` the respective class is provided as `Model_model_steadystate` in `model_steadystate.h` in output directory for the given model.
- a `amici::Solver` instance. This solver instance needs to match the requirements of the model and can be obtained from `amici::AbstractModel::getSolver()`.
- optionally an `amici::ExpData` instance, which contains any experimental data (e.g. measurements, noise model parameters or model inputs) to evaluate residuals or an objective function.

This function returns a `amici::ReturnData` object, which contains all simulation results.

For running simulations for multiple experimental conditions (multiple `amici::ExpData` instances), `amici::runAmiciSimulations()` provides an alternative entry point. If AMICI (and your application) have been compiled with OpenMP support (see installation guide), this allows for running those simulations in parallel.

A scaffold for a standalone simulation program is automatically generated during model import in `main.cpp` in the model output directory. This program shows how to use the above-mentioned classes, how to obtain the simulation results, and may provide a starting point for your own simulation code.

Working with multiple or anonymous models

AMICI model import generates a `amici::Model` subclass for the specific model, based on the name used during import. On the one hand, this allows you to use multiple models with different names within a single application. On the other hand, this requires you to know the name of the model, which can be inconvenient in some cases.

When working with a single model, the `wrapfunctions.h` file generated during model import can be used to avoid specifying model names explicitly. It defines a function `amici::generic_model::getModel()`, that returns an instance of the model class by a generic name.

Note: Including multiple `wrapfunctions.h` files from different models in a single application is not possible. When using multiple models, explicit names have to be used or the different model libraries need to be loaded dynamically at runtime.

11.2.3 Compiling and linking

To run AMICI simulations from within your C++ application, you need to compile and link the following libraries:

- model library
- AMICI base library
- SUNDIALS libraries
- SuiteSparse libraries
- CBLAS-compatible BLAS

- optionally HDF5 (C, HL, and CXX components) set CMake option `ENABLE_HDF5` to OFF to build without HDF5-support
- optionally OpenMP (for parallel simulation of multiple conditions, see `amici::runAmiciSimulations()`)
- optionally boost (only when using serialization of AMICI object)

The simplest and recommended way is using the provide CMake files which take care of all these dependencies.

Considering the simple case, that you want to simulate one specific model in your CMake-based C++ application, you can copy or move the generated model directory containing the `CMakeLists.txt` file to your application directory, add `add_subdirectory(yourModelDirectory)` to your project's `CMakeLists.txt` file and build your project using CMake as usual.

11.2.4 Parameter estimation for AMICI models in high-performance computing environments

To perform parameter estimation for large or otherwise computationally demanding AMICI models from C++ in a high-performance computing environment, you may find the [parPE library](#) helpful. parPE allows for the private or shared memory parallel evaluation of a cost function requiring multiple simulations of the same model with different inputs. It provides interfaces to different optimizers, such as Ipopt.

11.3 AMICI C++ API

AMICI C++ library functions

11.3.1 Class Hierarchy

11.3.2 File Hierarchy

11.3.3 Full API

Namespaces

Namespace amici

Contents

- *Namespaces*
- *Classes*
- *Enums*
- *Functions*
- *Typedefs*
- *Variables*

Namespaces

- Namespace *amici::hdf5*

Classes

- Struct *ModelDimensions*
- Struct *ModelState*
- Struct *ModelStateDerived*
- Struct *SimulationState*
- Class *AbstractModel*
- Class *AmiciApplication*
- Class *AmiException*
- Class *AmiVector*
- Class *AmiVectorArray*
- Class *BackwardProblem*
- Class *ConditionContext*
- Class *ContextManager*
- Class *CvodeException*
- Class *CVodeSolver*
- Class *ExpData*
- Class *FinalStateStorer*
- Class *ForwardProblem*
- Class *IDAException*
- Class *IDASolver*
- Class *IntegrationFailure*
- Class *IntegrationFailureB*
- Class *Model*
- Class *Model_DAE*
- Class *Model_ODE*
- Class *ModelContext*
- Class *NewtonFailure*
- Class *NewtonSolver*
- Class *NewtonSolverDense*
- Class *NewtonSolverSparse*
- Class *ReturnData*
- Class *SetupFailure*

- *Class SimulationParameters*
- *Class Solver*
- *Class SteadystateProblem*
- *Class SUNLinSolBand*
- *Class SUNLinSolDense*
- *Class SUNLinSolKLU*
- *Class SUNLinSolPCG*
- *Class SUNLinSolSPBCGS*
- *Class SUNLinSolSPFGMR*
- *Class SUNLinSolSPGMR*
- *Class SUNLinSolSPTFQMR*
- *Class SUNLinSolWrapper*
- *Class SUNMatrixWrapper*
- *Class SUNNonLinSolFixedPoint*
- *Class SUNNonLinSolNewton*
- *Class SUNNonLinSolWrapper*

Enums

- *Enum BLASLayout*
- *Enum BLASTranspose*
- *Enum FixedParameterContext*
- *Enum InternalSensitivityMethod*
- *Enum InterpolationType*
- *Enum LinearMultistepMethod*
- *Enum LinearSolver*
- *Enum NewtonDampingFactorMode*
- *Enum NonlinearSolverIteration*
- *Enum ObservableScaling*
- *Enum ParameterScaling*
- *Enum RDataReporting*
- *Enum SecondOrderMode*
- *Enum SensitivityMethod*
- *Enum SensitivityOrder*
- *Enum SteadyStateContext*
- *Enum SteadyStateSensitivityMode*
- *Enum SteadyStateStatus*

Functions

- Function `amici::amici_daxpy`
- Function `amici::amici_dgemm`
- Function `amici::amici_dgemv`
- Function `amici::backtraceString`
- Template Function `amici::checkBufferSize`
- Function `amici::checkSigmaPositivity(realtype sigma, const char *sigmaName)`
- Function `amici::checkSigmaPositivity(std::vector<realtype> const &sigmaVector, const char *vectorName)`
- Template Function `amici::deserializeFromChar`
- Template Function `amici::deserializeFromString`
- Function `amici::dotProd`
- Function `amici::getScaledParameter`
- Function `amici::getUnscaledParameter`
- Function `amici::linearSum`
- Function `amici::N_VGetArrayPointerConst`
- Function `amici::operator==(const Model &a, const Model &b)`
- Function `amici::operator==(const ModelDimensions &a, const ModelDimensions &b)`
- Function `amici::operator==(const SimulationParameters &a, const SimulationParameters &b)`
- Function `amici::operator==(const Solver &a, const Solver &b)`
- Function `amici::printErrMsgIdAndTxt`
- Function `amici::printfToString`
- Function `amici::printWarnMsgIdAndTxt`
- Function `amici::regexErrorToString`
- Function `amici::runAmiciSimulation`
- Function `amici::runAmiciSimulations`
- Function `amici::scaleParameters`
- Template Function `amici::serializeToChar`
- Template Function `amici::serializeToStdVec`
- Template Function `amici::serializeToString`
- Template Function `amici::slice(const std::vector<T> &data, int index, unsigned size)`
- Template Function `amici::slice(std::vector<T> &data, int index, unsigned size)`
- Function `amici::unscaleParameters`
- Function `amici::wrapErrHandlerFn`
- Template Function `amici::writeSlice(const std::vector<T> &s, std::vector<T> &b)`
- Template Function `amici::writeSlice(const gsl::span<const T> slice, gsl::span<T> buffer)`
- Function `amici::writeSlice(const AmiVector &s, gsl::span<realtype> b)`

- *Template Function amici::writeSlice(const std::vector<T> &s, gsl::span<T> b)*

Typedefs

- *Typedef amici::const_N_Vector*
- *Typedef amici::outputFunctionType*
- *Typedef amici::realtype*

Variables

- *Variable amici::AMICI_CONV_FAILURE*
- *Variable amici::AMICI_DAMPING_FACTOR_ERROR*
- *Variable amici::AMICI_DATA_RETURN*
- *Variable amici::AMICI_ERR_FAILURE*
- *Variable amici::AMICI_ERROR*
- *Variable amici::AMICI_ILL_INPUT*
- *Variable amici::AMICI_MAX_TIME_EXCEEDED*
- *Variable amici::AMICI_NO_STEADY_STATE*
- *Variable amici::AMICI_NORMAL*
- *Variable amici::AMICI_NOT_IMPLEMENTED*
- *Variable amici::AMICI_ONE_STEP*
- *Variable amici::AMICI_ONEOUTPUT*
- *Variable amici::AMICI_PREEQUILIBRATE*
- *Variable amici::AMICI_RECOVERABLE_ERROR*
- *Variable amici::AMICI_RHSFUNC_FAIL*
- *Variable amici::AMICI_ROOT_RETURN*
- *Variable amici::AMICI_SINGULAR_JACOBIAN*
- *Variable amici::AMICI_SUCCESS*
- *Variable amici::AMICI_TOO_MUCH_ACC*
- *Variable amici::AMICI_TOO_MUCH_WORK*
- *Variable amici::AMICI_UNRECOVERABLE_ERROR*
- *Variable amici::defaultContext*
- *Variable amici::pi*

Namespace amici::hdf5

Contents

- *Functions*

Functions

- *Function amici::hdf5::attributeExists(H5::H5File const &file, const std::string &optionsObject, const std::string &attributeName)*
- *Function amici::hdf5::attributeExists(H5::H5Object const &object, const std::string &attributeName)*
- *Function amici::hdf5::createAndWriteDouble1DDataset*
- *Function amici::hdf5::createAndWriteDouble2DDataset*
- *Function amici::hdf5::createAndWriteDouble3DDataset*
- *Function amici::hdf5::createAndWriteInt1DDataset*
- *Function amici::hdf5::createAndWriteInt2DDataset*
- *Function amici::hdf5::createGroup*
- *Function amici::hdf5::createOrOpenForWriting*
- *Function amici::hdf5::getDoubleDataset1D*
- *Function amici::hdf5::getDoubleDataset2D*
- *Function amici::hdf5::getDoubleDataset3D*
- *Function amici::hdf5::getDoubleScalarAttribute*
- *Function amici::hdf5::getIntDataset1D*
- *Function amici::hdf5::getIntScalarAttribute*
- *Function amici::hdf5::getStringAttribute*
- *Function amici::hdf5::locationExists(std::string const &filename, std::string const &location)*
- *Function amici::hdf5::locationExists(H5::H5File const &file, std::string const &location)*
- *Function amici::hdf5::readModelDataFromHDF5(std::string const &hdf5file, Model &model, std::string const &datasetPath)*
- *Function amici::hdf5::readModelDataFromHDF5(H5::H5File const &file, Model &model, std::string const &datasetPath)*
- *Function amici::hdf5::readSimulationExpData*
- *Function amici::hdf5::readSolverSettingsFromHDF5(const H5::H5File &file, Solver &solver, std::string const &datasetPath)*
- *Function amici::hdf5::readSolverSettingsFromHDF5(std::string const &hdf5file, Solver &solver, std::string const &datasetPath)*
- *Function amici::hdf5::writeReturnData(const ReturnData &rdata, H5::H5File const &file, const std::string &hdf5Location)*

- Function `amici::hdf5::writeReturnData(const ReturnData &rdata, std::string const &hdf5Filename, const std::string &hdf5Location)`
- Function `amici::hdf5::writeReturnDataDiagnosis`
- Function `amici::hdf5::writeSimulationExpData`
- Function `amici::hdf5::writeSolverSettingsToHDF5(Solver const &solver, std::string const &hdf5Filename, std::string const &hdf5Location)`
- Function `amici::hdf5::writeSolverSettingsToHDF5(Solver const &solver, H5::H5File const &file, std::string const &hdf5Location)`

Namespace boost

Contents

- *Namespaces*

Namespaces

- *Namespace `boost::serialization`*

Namespace `boost::serialization`

Contents

- *Functions*

Functions

- *Template Function `boost::serialization::archiveVector`*
- *Template Function `boost::serialization::serialize(Archive &ar, amici::ReturnData &r, unsigned int version)`*
- *Template Function `boost::serialization::serialize(Archive &ar, amici::Solver &s, unsigned int version)`*
- *Template Function `boost::serialization::serialize(Archive &ar, amici::CNodeSolver &s, unsigned int version)`*
- *Template Function `boost::serialization::serialize(Archive &ar, amici::IDASolver &s, unsigned int version)`*
- *Template Function `boost::serialization::serialize(Archive &ar, amici::Model &m, unsigned int version)`*

Namespace gsl

Contents

- *Functions*

Functions

- *Function* `gsl::make_span(SUNMatrix m)`
- *Function* `gsl::make_span(N_Vector nv)`

Namespace std

STL namespace.

Classes and Structs

Struct ModelDimensions

- Defined in file `include_amici_model_dimensions.h`

Inheritance Relationships

Derived Types

- `public amici::Model` (*Class Model*)
- `public amici::ReturnData` (*Class ReturnData*)

Struct Documentation

`struct amici::ModelDimensions`

Container for model dimensions.

Holds number of states, observables, etc.

Subclassed by *amici::Model*, *amici::ReturnData*

Public Functions

ModelDimensions() = default

Default ctor

```
inline ModelDimensions(const int nx_rdata, const int nxtrue_rdata, const int nx_solver, const int
                        nxtrue_solver, const int nx_solver_reinit, const int np, const int nk, const int ny,
                        const int nytrue, const int nz, const int nztrue, const int ne, const int nJ, const int nw,
                        const int ndwdx, const int ndwdp, const int ndwdw, const int ndxdotdw,
                        std::vector<int> ndJydy, const int ndxrdatadxsolver, const int ndxrdatadtcl, const int
                        ndtotal_cldx_rdata, const int nnz, const int ubw, const int lbw)
```

Constructor with model dimensions.

Parameters

- **nx_rdata** – Number of state variables
- **nxtrue_rdata** – Number of state variables of the non-augmented model
- **nx_solver** – Number of state variables with conservation laws applied
- **nxtrue_solver** – Number of state variables of the non-augmented model with conservation laws applied
- **nx_solver_reinit** – Number of state variables with conservation laws subject to reinitialization
- **np** – Number of parameters
- **nk** – Number of constants
- **ny** – Number of observables
- **nytrue** – Number of observables of the non-augmented model
- **nz** – Number of event observables
- **nztrue** – Number of event observables of the non-augmented model
- **ne** – Number of events
- **nJ** – Number of objective functions
- **nw** – Number of repeating elements
- **ndwdx** – Number of nonzero elements in the \mathbf{x} derivative of the repeating elements
- **ndwdp** – Number of nonzero elements in the \mathbf{p} derivative of the repeating elements
- **ndwdw** – Number of nonzero elements in the \mathbf{w} derivative of the repeating elements
- **ndxdotdw** – Number of nonzero elements in the \mathbf{w} derivative of \mathbf{x} derivative
- **ndJydy** – Number of nonzero elements in the \mathbf{y} derivative of dJy (shape **nytrue**)
- **ndxrdatadxsolver** – Number of nonzero elements in the \mathbf{x} derivative of \mathbf{x}_r data
- **ndxrdatadtcl** – Number of nonzero elements in the \mathbf{tcl} derivative of \mathbf{x}_r data
- **ndtotal_cldx_rdata** – Number of nonzero elements in the \mathbf{x}_r data derivative of $\mathbf{total}_c l$
- **nnz** – Number of nonzero elements in Jacobian
- **ubw** – Upper matrix bandwidth in the Jacobian
- **lbw** – Lower matrix bandwidth in the Jacobian

Public Members

int **nx_rdata** = {0}
Number of states

int **nxtrue_rdata** = {0}
Number of states in the unaugmented system

int **nx_solver** = {0}
Number of states with conservation laws applied

int **nxtrue_solver** = {0}
Number of states in the unaugmented system with conservation laws applied

int **nx_solver_reinit** = {0}
Number of solver states subject to reinitialization

int **np** = {0}
Number of parameters

int **nk** = {0}
Number of constants

int **ny** = {0}
Number of observables

int **nytrue** = {0}
Number of observables in the unaugmented system

int **nz** = {0}
Number of event outputs

int **nztrue** = {0}
Number of event outputs in the unaugmented system

int **ne** = {0}
Number of events

int **nw** = {0}
Number of common expressions

int **ndwdx** = {0}
Number of nonzero elements in the **x** derivative of the repeating elements

int **ndwdp** = {0}
Number of nonzero elements in the **p** derivative of the repeating elements

int **ndwdw** = {0}
Number of nonzero elements in the **w** derivative of the repeating elements

int **ndxdotdw** = {0}
Number of nonzero elements in the w derivative of x_{dot}

std::vector<int> **ndJydy**
Number of nonzero elements in the y derivative of dJy (dimension `nytrue`)

int **ndxrdatadxsolver** = {0}
Number of nonzero elements in the x derivative of x_rdata

int **ndxrdatadtcl** = {0}
Number of nonzero elements in the tcl derivative of x_rdata

int **ndtotal_cldx_rdata** = {0}
Number of nonzero elements in the x_rdata derivative of $total_{cl}$

int **nnz** = {0}
Number of nonzero entries in Jacobian

int **nJ** = {0}
Dimension of the augmented objective function for 2nd order ASA

int **ubw** = {0}
Upper bandwidth of the Jacobian

int **lbw** = {0}
Lower bandwidth of the Jacobian

Struct ModelState

- Defined in file `_include_amici_model_state.h`

Struct Documentation

struct amici::ModelState
Exchange format to store and transfer the state of the model at a specific timepoint.
This is designed to only encompass the minimal number of attributes that need to be transferred.

Public Members

std::vector<realtype> **h**
Flag indicating whether a certain Heaviside function should be active or not (dimension: `ne`)

std::vector<realtype> **total_cl**
Total abundances for conservation laws (dimension: `nx_rdata` - `nx_solver`)

```
std::vector<realtype> stotal_cl
    Sensitivities of total abundances for conservation laws (dimension: (nx_rdata-nx_solver) x np, row-
    major)

std::vector<realtype> unscaledParameters
    Unscaled parameters (dimension: np)

std::vector<realtype> fixedParameters
    Constants (dimension: nk)

std::vector<int> plist
    Indexes of parameters wrt to which sensitivities are computed (dimension: nplist)
```

Struct ModelStateDerived

- Defined in file_include_amici_model_state.h

Struct Documentation

```
struct amici::ModelStateDerived
    Storage for amici::Model quantities computed based on amici::ModelState for a specific timepoint.
    Serves as workspace for a model simulation to avoid repeated reallocation.
```

Public Functions

ModelStateDerived() = default

```
explicit ModelStateDerived(ModelDimensions const &dim)
    Constructor from model dimensions.

    Parameters dim – Model dimensions
```

Public Members

```
SUNMatrixWrapper J_
    Sparse Jacobian (dimension: amici::Model::nnz)

SUNMatrixWrapper JB_
    Sparse Backwards Jacobian (dimension: amici::Model::nnz)

SUNMatrixWrapper dxdotdw_
    Sparse dxdotdw temporary storage (dimension: ndxdotdw)

SUNMatrixWrapper dwdx_
    Sparse dwdx temporary storage (dimension: ndwdx)
```

SUNMatrixWrapper **dwdp_**

Sparse dwdp temporary storage (dimension: ndwdp)

SUNMatrixWrapper **M_**

Dense Mass matrix (dimension: nx_solver x nx_solver)

SUNMatrixWrapper **dxdotdp_full**

Temporary storage of dxdotdp_full data across functions (Python only) (dimension: nplist x nx_solver, nnz: dynamic, type CSC_MAT)

SUNMatrixWrapper **dxdotdp_explicit**

Temporary storage of dxdotdp_explicit data across functions (Python only) (dimension: nplist x nx_solver, nnz: ndxdotdp_explicit, type CSC_MAT)

SUNMatrixWrapper **dxdotdp_implicit**

Temporary storage of dxdotdp_implicit data across functions, Python-only (dimension: nplist x nx_solver, nnz: dynamic, type CSC_MAT)

SUNMatrixWrapper **dxdotdx_explicit**

Temporary storage of dxdotdx_explicit data across functions (Python only) (dimension: nplist x nx_solver, nnz: nxdotdotdx_explicit, type CSC_MAT)

SUNMatrixWrapper **dxdotdx_implicit**

Temporary storage of dxdotdx_implicit data across functions, Python-only (dimension: nplist x nx_solver, nnz: dynamic, type CSC_MAT)

SUNMatrixWrapper **dx_rdatadx_solver**

Temporary storage for dx_rdatadx_solver (dimension: nx_rdata x nx_solver, nnz: ndxrdatadx_solver, type: CSC_MAT)

SUNMatrixWrapper **dx_rdatadtcl**

Temporary storage for dx_rdatadtcl (dimension: nx_rdata x ncl, nnz: ndxrdatadtclr, type: CSC_MAT)

SUNMatrixWrapper **dtotal_cldx_rdata**

Temporary storage for dtotal_cldx_rdata (dimension: ncl x nx_rdata, nnz: ndtotal_cldx_rdata, type: CSC_MAT)

AmiVectorArray **dxdotdp** = {0, 0}

Temporary storage of dxdotdp data across functions, Matlab only (dimension: nplist x nx_solver , row-major)

`std::vector<SUNMatrixWrapper>` **dJydy_**

Sparse observable derivative of data likelihood, only used if `pythonGenerated == true` (dimension nytrue, nJ x ny, row-major)

`std::vector<realtype>` **dJydy_matlab_**

Observable derivative of data likelihood, only used if `pythonGenerated == false` (dimension nJ x ny x nytrue , row-major)

`std::vector<realtype> dJydsigma_`
 Observable sigma derivative of data likelihood (dimension nJ x ny x nytrue, row-major)

`std::vector<realtype> dJydx_`
 State derivative of data likelihood (dimension nJ x nx_solver, row-major)

`std::vector<realtype> dJydp_`
 Parameter derivative of data likelihood for current timepoint (dimension: nJ x nplist, row-major)

`std::vector<realtype> dJzdz_`
 event output derivative of event likelihood (dimension nJ x nz x nztrue, row-major)

`std::vector<realtype> dJzdsigma_`
 event sigma derivative of event likelihood (dimension nJ x nz x nztrue, row-major)

`std::vector<realtype> dJrzdz_`
 event output derivative of event likelihood at final timepoint (dimension nJ x nz x nztrue, row-major)

`std::vector<realtype> dJrzdsigma_`
 event sigma derivative of event likelihood at final timepoint (dimension nJ x nz x nztrue, row-major)

`std::vector<realtype> dJzdx_`
 state derivative of event likelihood (dimension nJ x nx_solver, row-major)

`std::vector<realtype> dJzdp_`
 parameter derivative of event likelihood for current timepoint (dimension: nJ x nplist x, row-major)

`std::vector<realtype> dzdx_`
 state derivative of event output (dimension: nz x nx_solver, row-major)

`std::vector<realtype> dzdp_`
 parameter derivative of event output (dimension: nz x nplist, row-major)

`std::vector<realtype> drzdx_`
 state derivative of event regularization variable (dimension: nz x nx_solver, row-major)

`std::vector<realtype> drzdp_`
 parameter derivative of event regularization variable (dimension: nz x nplist, row-major)

`std::vector<realtype> dydp_`
 parameter derivative of observable (dimension: ny x nplist, row-major)

`std::vector<realtype> dydx_`
 state derivative of time-resolved observable (dimension: nx_solver x ny, row-major)

`std::vector<realtype> w_`
 temporary storage of w data across functions (dimension: nw)

`std::vector<realtype> sx_`
 temporary storage for flattened sx, (dimension: nx_solver x nplist, row-major)

`std::vector<realtype> x_rdata_`
temporary storage for `x_rdata` (dimension: `nx_rdata`)

`std::vector<realtype> sx_rdata_`
temporary storage for `sx_rdata` slice (dimension: `nx_rdata`)

`std::vector<realtype> y_`
temporary storage for time-resolved observable (dimension: `ny`)

`std::vector<realtype> sigmay_`
data standard deviation for current timepoint (dimension: `ny`)

`std::vector<realtype> dsigmaydp_`
temporary storage for parameter derivative of data standard deviation, (dimension: `ny` x `nplist`, row-major)

`std::vector<realtype> dsigmaydy_`
temporary storage for observable derivative of data standard deviation, (dimension: `ny` x `ny`, row-major)

`std::vector<realtype> z_`
temporary storage for event-resolved observable (dimension: `nz`)

`std::vector<realtype> rz_`
temporary storage for event regularization (dimension: `nz`)

`std::vector<realtype> sigmaz_`
temporary storage for event standard deviation (dimension: `nz`)

`std::vector<realtype> dsigmazdp_`
temporary storage for parameter derivative of event standard deviation, (dimension: `nz` x `nplist`, row-major)

`std::vector<realtype> deltax_`
temporary storage for change in `x` after event (dimension: `nx_solver`)

`std::vector<realtype> deltasx_`
temporary storage for change in `sx` after event (dimension: `nx_solver` x `nplist`, row-major)

`std::vector<realtype> deltaxB_`
temporary storage for change in `xB` after event (dimension: `nx_solver`)

`std::vector<realtype> deltaqB_`
temporary storage for change in `qB` after event (dimension: `nJ` x `nplist`, row-major)

AmiVector `x_pos_tmp_ = {0}`
temporary storage of positified state variables according to `stateIsNonNegative` (dimension: `nx_solver`)

Struct `SimulationState`

- Defined in `file_include_amici_forwardproblem.h`

Struct Documentation

struct `amici::SimulationState`

implements an exchange format to store and transfer the state of a simulation at a specific timepoint.

Public Members

realtype **t**
timepoint

AmiVector **x**
state variables

AmiVector **dx**
state variables

AmiVectorArray **sx**
state variable sensitivity

ModelState **state**
state of the model that was used for simulation

Class `AbstractModel`

- Defined in `file_include_amici_abstract_model.h`

Inheritance Relationships

Derived Type

- public `amici::Model` (*Class Model*)

Class Documentation

class `amici::AbstractModel`

Abstract base class of *amici::Model* defining functions that need to be implemented in an AMICI model.

Some functions have empty default implementations or throw. This class shall not have any data members.

Subclassed by *amici::Model*

Public Functions

virtual **~AbstractModel**() = default

virtual std::unique_ptr<*Solver*> **getSolver**() = 0

Retrieves the solver object.

Returns The *Solver* instance

virtual void **froot**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx, gsl::span<*realtype*> root) = 0

Root function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **root** – array to which values of the root function will be written

virtual void **fxdot**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx, *AmiVector* &xdot) = 0

Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – array to which values of the residual function will be written

virtual void **fsxdot**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx, int ip, const *AmiVector* &sx, const *AmiVector* &sdx, *AmiVector* &sxdot) = 0

Sensitivity Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **ip** – parameter index
- **sx** – sensitivity state
- **sdx** – time derivative of sensitivity state (DAE only)
- **sxdot** – array to which values of the sensitivity residual function will be written

virtual void **fxBdot_ss**(const *realtype* t, const *AmiVector* &xB, const *AmiVector* &dxB, *AmiVector* &xBdot) = 0

Residual function backward when running in steady state mode.

Parameters

- **t** – time
- **xB** – adjoint state
- **dxB** – time derivative of state (DAE only)

- **xBdot** – array to which values of the residual function will be written

virtual void **fJSparseB_ss**(SUNMatrix JB) = 0

Sparse Jacobian function backward, steady state case.

Parameters JB – sparse matrix to which values of the Jacobian will be written

virtual void **writeSteadystateJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot) = 0

Computes the sparse backward Jacobian for steadystate integration and writes it to the model member.

Parameters

- **t** – timepoint
- **cj** – scalar in Jacobian
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint state right hand side

virtual void **fJ**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) = 0

Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – dense matrix to which values of the jacobian will be written

virtual void **fJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) = 0

Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

virtual void **fJSparse**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) = 0

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – sparse matrix to which values of the Jacobian will be written

virtual void **fJSparseB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) = 0

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

virtual void **fJDiag**(const *realtype* t, *AmiVector* &Jdiag, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx) = 0

Diagonal Jacobian function.

Parameters

- **t** – time
- **Jdiag** – array to which the diagonal of the Jacobian will be written
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)

virtual void **fdxdotdp**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx) = 0

Model-specific sparse implementation of explicit parameter derivative of right hand side.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)

virtual void **fJv**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, const *AmiVector* &v, *AmiVector* &nJv, *realtype* cj) = 0

Jacobian multiply function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **v** – multiplication vector (unused)
- **nJv** – array to which result of multiplication will be written
- **cj** – scaling factor (inverse of timestep, DAE only)

virtual std::string **getAmiciVersion**() const

Returns the AMICI version that was used to generate the model.

Returns AMICI version string

virtual std::string **getAmiciCommit**() const

Returns the AMICI commit that was used to generate the model.

Returns AMICI commit string

virtual void **fx0**(*realtype* *x0, const *realtype* t, const *realtype* *p, const *realtype* *k)

Model-specific implementation of fx0.

Parameters

- **x0** – initial state
- **t** – initial time
- **p** – parameter vector
- **k** – constant vector

virtual bool **isFixedParameterStateReinitializationAllowed**() const

Function indicating whether reinitialization of states depending on fixed parameters is permissible.

Returns flag indicating whether reinitialization of states depending on fixed parameters is permissible

virtual void **fx0_fixedParameters**(*realtype* *x0, const *realtype* t, const *realtype* *p, const *realtype* *k, gsl::span<const int> reinitialization_state_idx)

Model-specific implementation of fx0_fixedParameters.

Parameters

- **x0** – initial state
- **t** – initial time
- **p** – parameter vector
- **k** – constant vector
- **reinitialization_state_idx** – Indices of states to be reinitialized based on provided constants / fixed parameters.

```
virtual void fsx0_fixedParameters(realtype *sx0, const realtype t, const realtype *x0, const realtype *p,  
                                const realtype *k, int ip, gsl::span<const int>  
                                reinitialization_state_idxs)
```

Model-specific implementation of fsx0_fixedParameters.

Parameters

- **sx0** – initial state sensitivities
- **t** – initial time
- **x0** – initial state
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index
- **reinitialization_state_idxs** – Indices of states to be reinitialized based on provided constants / fixed parameters.

```
virtual void fsx0(realtype *sx0, const realtype t, const realtype *x0, const realtype *p, const realtype *k, int  
                  ip)
```

Model-specific implementation of fsx0.

Parameters

- **sx0** – initial state sensitivities
- **t** – initial time
- **x0** – initial state
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index

```
virtual void fdx0(AmiVector &x0, AmiVector &dx0)
```

Initial value for time derivative of states (only necessary for DAEs)

Parameters

- **x0** – Vector with the initial states
- **dx0** – Vector to which the initial derivative states will be written (only DAE)

```
virtual void fstau(realtype *stau, const realtype t, const realtype *x, const realtype *p, const realtype *k,  
                  const realtype *h, const realtype *tcl, const realtype *sx, int ip, int ie)
```

Model-specific implementation of fstau.

Parameters

- **stau** – total derivative of event timepoint
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **tcl** – total abundances for conservation laws

- **sx** – current state sensitivity
- **ip** – sensitivity index
- **ie** – event index

virtual void **fy**(*realtype* *y, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w)

Model-specific implementation of fy.

Parameters

- **y** – model output at current timepoint
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector

virtual void **fdydp**(*realtype* *dydp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, const *realtype* *w, const *realtype* *dwdp)

Model-specific implementation of fdydp (MATLAB-only)

Parameters

- **dydp** – partial derivative of observables y w.r.t. model parameters p
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested
- **w** – repeating elements vector
- **dwdp** – Recurring terms in xdot, parameter derivative

virtual void **fdydp**(*realtype* *dydp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, const *realtype* *w, const *realtype* *tcl, const *realtype* *dtcldp)

Model-specific implementation of fdydp (Python)

Parameters

- **dydp** – partial derivative of observables y w.r.t. model parameters p
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested

- **w** – repeating elements vector
- **tc1** – total abundances for conservation laws
- **dtcldp** – Sensitivities of total abundances for conservation laws

virtual void **fdydx**(*realtype* *dydx, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, const *realtype* *w, const *realtype* *dwdx)

Model-specific implementation of fdydx.

Parameters

- **dydx** – partial derivative of observables y w.r.t. model states x
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector
- **dwdx** – Recurring terms in xdot, state derivative

virtual void **fz**(*realtype* *z, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h)

Model-specific implementation of fz.

Parameters

- **z** – value of event output
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fsz**(*realtype* *sz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, const *realtype* *sx, int ip)

Model-specific implementation of fsz.

Parameters

- **sz** – Sensitivity of rz, total derivative
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **sx** – current state sensitivity

- **ip** – sensitivity index

virtual void **frz**(*realtype* *rz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of frz.

Parameters

- **rz** – value of root function at current timepoint (non-output events not included)
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fsrz**(*realtype* *srz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *sx, int ip)

Model-specific implementation of fsrz.

Parameters

- **srz** – Sensitivity of rz, total derivative
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **sx** – current state sensitivity
- **h** – Heaviside vector
- **ip** – sensitivity index

virtual void **fdzdp**(*realtype* *dzdp, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip)

Model-specific implementation of fdzdp.

Parameters

- **dzdp** – partial derivative of event-resolved output z w.r.t. model parameters p
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested

virtual void **fdzdx**(*realtype* *dzdx, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of fdzdx.

Parameters

- **dzdx** – partial derivative of event-resolved output z w.r.t. model states x
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fdrzdp**(*realtype* *drzdp, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip)

Model-specific implementation of fdrzdp.

Parameters

- **drzdp** – partial derivative of root output rz w.r.t. model parameters p
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested

virtual void **fdrzdx**(*realtype* *drzdx, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of fdrzdx.

Parameters

- **drzdx** – partial derivative of root output rz w.r.t. model states x
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fdeltax**(*realtype* *deltax, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ie, const *realtype* *xdot, const *realtype* *xdot_old)

Model-specific implementation of fdeltax.

Parameters

- **deltax** – state update

- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side

```
virtual void fdeltasx(realtype *deltasx, const realtype t, const realtype *x, const realtype *p, const realtype
                    *k, const realtype *h, const realtype *w, int ip, int ie, const realtype *xdot, const
                    realtype *xdot_old, const realtype *sx, const realtype *stau, const realtype *tcl)
```

Model-specific implementation of fdeltasx.

Parameters

- **deltasx** – sensitivity update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector
- **ip** – sensitivity index
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **sx** – state sensitivity
- **stau** – event-time sensitivity
- **tcl** – total abundances for conservation laws

```
virtual void fdeltaxB(realtype *deltaxB, const realtype t, const realtype *x, const realtype *p, const realtype
                    *k, const realtype *h, int ie, const realtype *xdot, const realtype *xdot_old, const
                    realtype *xB)
```

Model-specific implementation of fdeltaxB.

Parameters

- **deltaxB** – adjoint state update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **xB** – current adjoint state

virtual void **fdeltaqB**(*realtype* *deltaqB, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, int ie, const *realtype* *xdot, const *realtype* *xdot_old, const *realtype* *xB)

Model-specific implementation of fdeltaqB.

Parameters

- **deltaqB** – sensitivity update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – sensitivity index
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **xB** – adjoint state

virtual void **fsgmay**(*realtype* *sgmay, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y)

Model-specific implementation of fsgmay.

Parameters

- **sgmay** – standard deviation of measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint t

virtual void **fdsigmaydp**(*realtype* *dsigmaydp, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y, int ip)

Model-specific implementation of fdsigmaydp.

Parameters

- **dsigmaydp** – partial derivative of standard deviation of measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint t

- **ip** – sensitivity index

virtual void **fdsigmaydy**(*realtype* *dsigmaydy, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y)

Model-specific implementation of fsigmay.

Parameters

- **dsigmaydy** – partial derivative of standard deviation of measurements w.r.t. model outputs
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint t

virtual void **fsigmaz**(*realtype* *sigmaz, const *realtype* t, const *realtype* *p, const *realtype* *k)

Model-specific implementation of fsigmaz.

Parameters

- **sigmaz** – standard deviation of event measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector

virtual void **fdsigmazdp**(*realtype* *dsigmazdp, const *realtype* t, const *realtype* *p, const *realtype* *k, int ip)

Model-specific implementation of fsigmaz.

Parameters

- **dsigmazdp** – partial derivative of standard deviation of event measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index

virtual void **fJy**(*realtype* *nllh, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fJy.

Parameters

- **nllh** – negative log-likelihood for measurements y
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint
- **sigmay** – measurement standard deviation at timepoint
- **my** – measurements at timepoint

virtual void **fJz**(*realtype* *nllh, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fJz.

Parameters

- **nllh** – negative log-likelihood for event measurements z
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurements at timepoint

virtual void **fJrz**(*realtype* *nllh, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz)

Model-specific implementation of fJrz.

Parameters

- **nllh** – regularization for event measurements z
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fdJydy**(*realtype* *dJydy, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fdJydy.

Parameters

- **dJydy** – partial derivative of time-resolved measurement negative log-likelihood J_y
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint
- **sigmay** – measurement standard deviation at timepoint
- **my** – measurement at timepoint

virtual void **fdJydy_colptrs**(*SUNMatrixWrapper* &dJydy, int index)

Model-specific implementation of fdJydy colptrs.

Parameters

- **dJydy** – sparse matrix to which colptrs will be written
- **index** – ytrue index

virtual void **fdJydy_rowvals**(*SUNMatrixWrapper* &dJydy, int index)

Model-specific implementation of fdJydy rowvals.

Parameters

- **dJydy** – sparse matrix to which rowvals will be written

- **index** – ytrue index

virtual void **fdJydsigma**(*realtype* *dJydsigma, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fdJydsigma.

Parameters

- **dJydsigma** – Sensitivity of time-resolved measurement negative log-likelihood Jy w.r.t. standard deviation sigmay
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint
- **sigmay** – measurement standard deviation at timepoint
- **my** – measurement at timepoint

virtual void **fdJzdz**(*realtype* *dJzdz, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fdJzdz.

Parameters

- **dJzdz** – partial derivative of event measurement negative log-likelihood Jz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurement at timepoint

virtual void **fdJzdsigma**(*realtype* *dJzdsigma, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fdJzdsigma.

Parameters

- **dJzdsigma** – Sensitivity of event measurement negative log-likelihood Jz w.r.t. standard deviation sigmaz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurement at timepoint

virtual void **fdJrzdz**(*realtype* *dJrzdz, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *rz, const *realtype* *sigmaz)

Model-specific implementation of fdJrzdz.

Parameters

- **dJrzd** – partial derivative of event penalization Jrz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **rz** – model root output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fdJrzdsigma**(*realtype* *dJrzdsigma, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *rz, const *realtype* *sigmaz)

Model-specific implementation of fdJrzdsigma.

Parameters

- **dJrzdsigma** – Sensitivity of event penalization Jrz w.r.t. standard deviation sigma
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **rz** – model root output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fw**(*realtype* *w, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *tcl)

Model-specific implementation of fw.

Parameters

- **w** – Recurring terms in xdot
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **tcl** – total abundances for conservation laws

virtual void **fdwdp**(*realtype* *dwdp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl, const *realtype* *stcl)

Model-specific sparse implementation of dwdp.

Parameters

- **dwdp** – Recurring terms in xdot, parameter derivative
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector

- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws
- **stcl** – sensitivities of total abundances for conservation laws

virtual void **fdwdp_colptrs**(*SUNMatrixWrapper* &dwdp)

Model-specific implementation for dwdp, column pointers.

Parameters **dwdp** – sparse matrix to which colptrs will be written

virtual void **fdwdp_rowvals**(*SUNMatrixWrapper* &dwdp)

Model-specific implementation for dwdp, row values.

Parameters **dwdp** – sparse matrix to which rowvals will be written

virtual void **fdwdp**(*realtype* *dwdp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, const *realtype* *w, const *realtype* *tcl, const *realtype* *stcl, int ip)

Model-specific sensitivity implementation of dwdp.

Parameters

- **dwdp** – Recurring terms in xdot, parameter derivative
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws
- **stcl** – sensitivities of total abundances for conservation laws
- **ip** – sensitivity parameter index

virtual void **fdwdx**(*realtype* *dwdx, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, const *realtype* *w, const *realtype* *tcl)

Model-specific implementation of dwdx, data part.

Parameters

- **dwdx** – Recurring terms in xdot, state derivative
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws

virtual void **fdwdx_colptrs**(*SUNMatrixWrapper* &dwdx)

Model-specific implementation for dwdx, column pointers.

Parameters **dwdx** – sparse matrix to which colptrs will be written

virtual void **fdwdx_rowvals**(*SUNMatrixWrapper* &dwdx)

Model-specific implementation for dwdx, row values.

Parameters **dwdx** – sparse matrix to which rowvals will be written

virtual void **fdwdw**(*realtype* *dwdw, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl)

Model-specific implementation of fdwdw, no w chainrule (Py)

Parameters

- **dwdw** – partial derivative w wrt w
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – Total abundances for conservation laws

virtual void **fdwdw_colptrs**(*SUNMatrixWrapper* &dwdw)

Model-specific implementation of fdwdw, colptrs part.

Parameters **dwdw** – sparse matrix to which colptrs will be written

virtual void **fdwdw_rowvals**(*SUNMatrixWrapper* &dwdw)

Model-specific implementation of fdwdw, rowvals part.

Parameters **dwdw** – sparse matrix to which rowvals will be written

virtual void **fdx_rdatadx_solver**(*realtype* *dx_rdatadx_solver, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k)

Compute dx_rdata / dx_solver.

Parameters

- **dx_rdatadx_solver** – dx_rdata / dx_solver
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws

virtual void **fdx_rdatadx_solver_colptrs**(*SUNMatrixWrapper* &dx_rdatadx_solver)

Model-specific implementation of fdx_rdatadx_solver, colptrs part.

Parameters **dx_rdatadx_solver** – sparse matrix to which colptrs will be written

virtual void **fdx_rdatadx_solver_rowvals**(*SUNMatrixWrapper* &dx_rdatadx_solver)

Model-specific implementation of fdx_rdatadx_solver, rowvals part.

Parameters **dx_rdatadx_solver** – sparse matrix to which rowvals will be written

virtual void **fdx_rdatadp**(*realtype* *dx_rdatadp, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k, const int ip)

Compute dx_rdata / dp.

Parameters

- **dx_rdatadp** – dx_rdata / dp
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws
- **ip** – Sensitivity index

virtual void **fdx_rdatadtcl**(*realtype* *dx_rdatadtcl, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k)

Compute $dx_rdata / dtcl$.

Parameters

- **dx_rdatadtcl** – $dx_rdata / dtcl$
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws

virtual void **fdx_rdatadtcl_colptrs**(*SUNMatrixWrapper* &dx_rdatadtcl)

Model-specific implementation of `fdx_rdatadtcl`, `colptrs` part.

Parameters **dx_rdatadtcl** – sparse matrix to which `colptrs` will be written

virtual void **fdx_rdatadtcl_rowvals**(*SUNMatrixWrapper* &dx_rdatadtcl)

Model-specific implementation of `fdx_rdatadtcl`, `rowvals` part.

Parameters **dx_rdatadtcl** – sparse matrix to which `rowvals` will be written

virtual void **fdtotal_cldp**(*realtype* *dtotal_cldp, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k, const int ip)

Compute $dtotal_cl / dp$.

Parameters

- **dtotal_cldp** – $dtotal_cl / dp$
- **x_rdata** – State variables with conservation laws applied
- **p** – parameter vector
- **k** – constant vector
- **ip** – Sensitivity index

virtual void **fdtotal_cldx_rdata**(*realtype* *dtotal_cldx_rdata, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k, const *realtype* *tcl)

Compute $dtotal_cl / dx_rdata$.

Parameters

- **dtotal_cldx_rdata** – $dtotal_cl / dx_rdata$
- **x_rdata** – State variables with conservation laws applied
- **p** – parameter vector
- **k** – constant vector
- **tcl** – Total abundances for conservation laws

virtual void **fdtotal_cldx_rdata_colptrs**(*SUNMatrixWrapper* &dtotal_cldx_rdata)
Model-specific implementation of fdtotal_cldx_rdata, colptrs part.

Parameters dtotal_cldx_rdata – sparse matrix to which colptrs will be written

virtual void **fdtotal_cldx_rdata_rowvals**(*SUNMatrixWrapper* &dtotal_cldx_rdata)
Model-specific implementation of fdtotal_cldx_rdata, rowvals part.

Parameters dtotal_cldx_rdata – sparse matrix to which rowvals will be written

Class AmiciApplication

- Defined in file_include_amici_amici.h

Class Documentation

class amici::AmiciApplication

Main class for making calls to AMICI.

This class is used to provide separate AMICI contexts, for example, for use in multi-threaded applications where different threads want to use AMICI with different settings, such custom logging functions.

NOTE: For this moment, the context object needs to be set manually to any *Model* and *Solver* object. If not set, they will use the default output channel.

Public Functions

AmiciApplication() = default

std::unique_ptr<*ReturnData*> **runAmiciSimulation**(*Solver* &solver, const *ExpData* *edata, *Model* &model,
bool rethrow = false)

Core integration routine. Initializes the solver and runs the forward and backward problem.

Parameters

- **solver** – *Solver* instance
- **edata** – pointer to experimental data object
- **model** – model specification object
- **rethrow** – rethrow integration exceptions?

Returns rdata pointer to return data object

std::vector<std::unique_ptr<*ReturnData*>> **runAmiciSimulations**(*Solver* const &solver, const
std::vector<*ExpData**> &edatas, *Model*
const &model, bool failfast, int
num_threads)

Same as runAmiciSimulation, but for multiple *ExpData* instances.

Parameters

- **solver** – *Solver* instance
- **edatas** – experimental data objects
- **model** – model specification object

- **failfast** – flag to allow early termination
- **num_threads** – number of threads for parallel execution

Returns vector of pointers to return data objects

void **warningF**(const char *identifier, const char *format, ...) const
printf interface to *warning()*

Parameters

- **identifier** – warning identifier
- **format** – string with warning message printf-style format
- ... – arguments to be formatted

void **errorF**(const char *identifier, const char *format, ...) const
printf interface to *error()*

Parameters

- **identifier** – warning identifier
- **format** – string with error message printf-style format
- ... – arguments to be formatted

int **checkFinite**(gsl::span<const *realtype*> array, const char *fun)
Checks the values in an array for NaNs and Infs.

Parameters

- **array** – array
- **fun** – name of calling function

Returns AMICI_RECOVERABLE_ERROR if a NaN/Inf value was found, AMICI_SUCCESS otherwise

Public Members

outputFunctionType **warning** = *printWarnMsgIdAndTxt*
Function to process warnings

outputFunctionType **error** = *printErrMsgIdAndTxt*
Function to process errors

Class AmiException

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- `public std::exception`

Derived Types

- `public amici::CvodeException` (*Class CvodeException*)
- `public amici::IDAException` (*Class IDAException*)
- `public amici::IntegrationFailure` (*Class IntegrationFailure*)
- `public amici::IntegrationFailureB` (*Class IntegrationFailureB*)
- `public amici::NewtonFailure` (*Class NewtonFailure*)
- `public amici::SetupFailure` (*Class SetupFailure*)

Class Documentation

class `amici::AmiException` : `public std::exception`
AMICI exception class.

Has a printf style interface to allow easy generation of error messages

Subclassed by `amici::CvodeException`, `amici::IDAException`, `amici::IntegrationFailure`, `amici::IntegrationFailureB`, `amici::NewtonFailure`, `amici::SetupFailure`

Public Functions

`AmiException()`

Constructor with printf style interface.

Parameters

- **`fmt`** – error message with printf format
- `...` – printf formatting variables

explicit `AmiException`(char const *fmt, ...)

Constructor with printf style interface.

Parameters

- **`fmt`** – error message with printf format
- `...` – printf formatting variables

const char ***`what()`** const noexcept override

Override of default error message function.

Returns msg error message

const char ***`getBacktrace()`** const

Returns the stored backtrace.

Returns trace backtrace

void **storeBacktrace**(int nMaxFrames)

Stores the current backtrace.

Parameters **nMaxFrames** – number of frames to go back in stacktrace

Protected Functions

void **storeMessage**(const char *fmt, va_list argptr)

Store the provided message.

Parameters

- **fmt** – error message with printf format
- **argptr** – pointer to variadic argument list

Class AmiVector

- Defined in file_include_amici_vector.h

Class Documentation

class amici::AmiVector

AmiVector class provides a generic interface to the NVector_Serial struct

Public Functions

AmiVector() = default

Default constructor.

inline explicit **AmiVector**(const long int length)

empty constructor

Creates an std::vector<realtype> and attaches the data pointer to a newly created N_Vector_Serial. Using N_VMake_Serial ensures that the N_Vector module does not try to deallocate the data vector when calling N_VDestroy_Serial

Parameters **length** – number of elements in vector

inline explicit **AmiVector**(std::vector<realtype> rvec)

constructor from std::vector,

Moves data from std::vector and constructs an nvec that points to the data

Parameters **rvec** – vector from which the data will be moved

inline explicit **AmiVector**(gsl::span<realtype> rvec)

constructor from gsl::span,

Copy data from gsl::span and constructs a vector

Parameters **rvec** – vector from which the data will be copied

inline **AmiVector**(const *AmiVector* &vold)

copy constructor

Parameters **vold** – vector from which the data will be copied

inline **AmiVector**(*AmiVector* &&other) noexcept
 move constructor

Parameters **other** – vector from which the data will be moved

~AmiVector()
 destructor

AmiVector &**operator**=(*AmiVector* const &other)
 copy assignment operator

Parameters **other** – right hand side

Returns left hand side

inline *AmiVector* &**operator***=(*AmiVector* const &multiplier)
 operator *= (element-wise multiplication)

Parameters **multiplier** – multiplier

Returns result

inline *AmiVector* &**operator**/=(*AmiVector* const &divisor)
 operator /= (element-wise division)

Parameters **divisor** – divisor

Returns result

inline auto **begin**()
 Returns an iterator that points to the first element of the vector.

Returns iterator that points to the first element

inline auto **end**()
 Returns an iterator that points to one element after the last element of the vector.

Returns iterator that points to one element after the last element

realtype ***data**()
 data accessor

Returns pointer to data array

const *realtype* ***data**() const
 const data accessor

Returns const pointer to data array

N_Vector **getNVector**()
 N_Vector accessor.

Returns N_Vector

const N_Vector **getNVector**() const
 N_Vector accessor.

Returns N_Vector

std::vector<*realtype*> const &**getVector**() const
 Vector accessor.

Returns Vector

int **getLength**() const
 returns the length of the vector

Returns length

void **zero**()

fills vector with zero values

void **minus**()

changes the sign of data elements

void **set**(*realtype* val)

sets all data elements to a specific value

Parameters **val** – value for data elements

realtype &**operator**[](int pos)

accessor to data elements of the vector

Parameters **pos** – index of element

Returns element

realtype &**at**(int pos)

accessor to data elements of the vector

Parameters **pos** – index of element

Returns element

const *realtype* &**at**(int pos) const

accessor to data elements of the vector

Parameters **pos** – index of element

Returns element

void **copy**(const *AmiVector* &other)

copies data from another *AmiVector*

Parameters **other** – data source

inline void **abs**()

Take absolute value (in-place)

Class *AmiVectorArray*

- Defined in file_include_amici_vector.h

Class Documentation

class amici::**AmiVectorArray**

AmiVectorArray class.

Provides a generic interface to arrays of NVector_Serial structs

Public Functions

AmiVectorArray() = default

Default constructor.

AmiVectorArray(long int length_inner, long int length_outer)

empty constructor

Creates an `std::vector<realtype>` and attaches the data pointer to a newly created `N_VectorArray` using `CloneVectorArrayEmpty` ensures that the `N_Vector` module does not try to deallocate the data vector when calling `N_VDestroyVectorArray_Serial`

Parameters

- **length_inner** – length of vectors
- **length_outer** – number of vectors

AmiVectorArray(const *AmiVectorArray* &vaold)

copy constructor

Parameters **vaold** – object to copy from

~AmiVectorArray() = default

AmiVectorArray &**operator=**(*AmiVectorArray* const &other)

copy assignment operator

Parameters **other** – right hand side

Returns left hand side

realtype ***data**(int pos)

accessor to data of *AmiVector* elements

Parameters **pos** – index of *AmiVector*

Returns pointer to data array

const *realtype* ***data**(int pos) const

const accessor to data of *AmiVector* elements

Parameters **pos** – index of *AmiVector*

Returns const pointer to data array

realtype &**at**(int ipos, int jpos)

accessor to elements of *AmiVector* elements

Parameters

- **ipos** – inner index in *AmiVector*
- **jpos** – outer index in *AmiVectorArray*

Returns element

const *realtype* &**at**(int ipos, int jpos) const

const accessor to elements of *AmiVector* elements

Parameters

- **ipos** – inner index in *AmiVector*
- **jpos** – outer index in *AmiVectorArray*

Returns element

`N_Vector *getNVectorArray()`
accessor to `NVectorArray`

Returns `N_VectorArray`

`N_Vector getNVector(int pos)`
accessor to `NVector` element

Parameters `pos` – index of corresponding *AmiVector*

Returns `N_Vector`

`const N_Vector getNVector(int pos) const`
const accessor to `NVector` element

Parameters `pos` – index of corresponding *AmiVector*

Returns `N_Vector`

`AmiVector &operator[] (int pos)`
accessor to *AmiVector* elements

Parameters `pos` – index of *AmiVector*

Returns *AmiVector*

`const AmiVector &operator[] (int pos) const`
const accessor to *AmiVector* elements

Parameters `pos` – index of *AmiVector*

Returns `const AmiVector`

`int getLength() const`
length of *AmiVectorArray*

Returns length

`void zero()`
set every *AmiVector* in *AmiVectorArray* to zero

`void flatten_to_vector(std::vector<realtype> &vec) const`
flattens the *AmiVectorArray* to a vector in row-major format

Parameters `vec` – vector into which the *AmiVectorArray* will be flattened. Must have length equal to number of elements.

`void copy(const AmiVectorArray &other)`
copies data from another *AmiVectorArray*

Parameters `other` – data source

Class BackwardProblem

- Defined in file `_include_amici_backwardproblem.h`

Class Documentation

class `amici::BackwardProblem`

class to solve backwards problems.

solves the backwards problem for adjoint sensitivity analysis and handles events and data-points

Public Functions

explicit **BackwardProblem**(const *ForwardProblem* &fwd, const *SteadystateProblem* *posteq)

Construct backward problem from forward problem.

Parameters

- **fwd** – pointer to corresponding forward problem
- **posteq** – pointer to postequilibration problem, can be nullptr

void **workBackwardProblem**()

Solve the backward problem.

If adjoint sensitivities are enabled this will also compute sensitivities. `workForwardProblem` must be called before this is function is called.

inline *realtype* **gett**() const

Accessor for current time t.

Returns t

inline int **getwhich**() const

Accessor for which.

Returns which

inline int ***getwhichptr**()

Accessor for pointer to which.

Returns which

inline std::vector<*realtype*> const &**getdJydx**() const

Accessor for dJydx.

Returns dJydx

inline *AmiVector* const &**getAdjointState**() const

Accessor for xB.

Returns xB

inline *AmiVector* const &**getAdjointQuadrature**() const

Accessor for xQB.

Returns xQB

Class ConditionContext

- Defined in file_include_amici_edata.h

Inheritance Relationships

Base Type

- public amici::ContextManager (*Class ContextManager*)

Class Documentation

class amici::ConditionContext : public amici::ContextManager

The *ConditionContext* class applies condition-specific *amici::Model* settings and restores them when going out of scope.

Public Functions

explicit ConditionContext(*Model* *model, const *ExpData* *edata = nullptr, *FixedParameterContext* fpc = *FixedParameterContext::simulation*)

Apply condition-specific settings from edata to model while keeping a backup of the original values.

Parameters

- **model** –
- **edata** –
- **fpc** – flag indicating which fixedParameter from edata to apply

ConditionContext &operator=(const *ConditionContext* &other) = delete

~ConditionContext()

void applyCondition(const *ExpData* *edata, *FixedParameterContext* fpc)

Apply condition-specific settings from edata to the constructor-supplied model, not changing the settings which were backed-up in the constructor call.

Parameters

- **edata** –
- **fpc** – flag indicating which fixedParameter from edata to apply

void restore()

Restore original settings on constructor-supplied *amici::Model*. Will be called during destruction. Explicit call is generally not necessary.

Class ContextManager

- Defined in file_include_amici_misc.h

Inheritance Relationships

Derived Types

- public amici::ConditionContext (*Class ConditionContext*)
- public amici::FinalStateStorer (*Class FinalStateStorer*)
- public amici::ModelContext (*Class ModelContext*)

Class Documentation

class amici::ContextManager

Generic implementation for a context manager, explicitly deletes copy and move operators for derived classes.

Subclassed by *amici::ConditionContext*, *amici::FinalStateStorer*, *amici::ModelContext*

Public Functions

ContextManager() = default

ContextManager(*ContextManager* &other) = delete

ContextManager(*ContextManager* &&other) = delete

Class CvodeException

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- public amici::AmiException (*Class AmiException*)

Class Documentation

class amici::CvodeException : public amici::AmiException
 cvode exception handler class

Public Functions

CvodeException(int error_code, const char *function)
 Constructor.

Parameters

- **error_code** – error code returned by cvode function
- **function** – cvode function name

Class CVodeSolver

- Defined in file_include_amici_solver_cvodes.h

Inheritance Relationships

Base Type

- public amici::Solver (*Class Solver*)

Class Documentation

class amici::CVodeSolver : public amici::Solver
 The *CVodeSolver* class is a wrapper around the SUNDIALS CVODES solver.

Public Functions

~CVodeSolver() override = default

virtual *Solver* ***clone**() const override
 Clone this instance.

Returns The clone

virtual void **reInit**(*realtype* t0, const *AmiVector* &yy0, const *AmiVector* &yp0) const override
 Reinitializes the states in the solver after an event occurrence.

Parameters

- **t0** – reinitialization timepoint
- **yy0** – initial state variables
- **yp0** – initial derivative state variables (DAE only)

virtual void **sensReInit**(const *AmiVectorArray* &yyS0, const *AmiVectorArray* &ypS0) const override
Reinitializes the state sensitivities in the solver after an event occurrence.

Parameters

- **yyS0** – new state sensitivity
- **ypS0** – new derivative state sensitivities (DAE only)

virtual void **sensToggleOff**() const override
Switches off computation of state sensitivities without deallocating the memory for sensitivities.

virtual void **reInitB**(int which, *realtype* tB0, const *AmiVector* &yyB0, const *AmiVector* &ypB0) const override
Reinitializes the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **tB0** – reinitialization timepoint
- **yyB0** – new adjoint state
- **ypB0** – new adjoint derivative state

virtual void **quadReInitB**(int which, const *AmiVector* &yQB0) const override
Reinitialize the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **yQB0** – new adjoint quadrature state

virtual int **solve**(*realtype* tout, int itask) const override
Solves the forward problem until a predefined timepoint.

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP

Returns status flag indicating success of execution

virtual int **solveF**(*realtype* tout, int itask, int *ncheckPtr) const override
Solves the forward problem until a predefined timepoint (adjoint only)

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP
- **ncheckPtr** – pointer to a number that counts the internal checkpoints

Returns status flag indicating success of execution

virtual void **solveB**(*realtype* tBout, int itaskB) const override
Solves the backward problem until a predefined timepoint (adjoint only)

Parameters

- **tBout** – timepoint until which simulation should be performed
- **itaskB** – task identifier, can be CV_NORMAL or CV_ONE_STEP

virtual void **getDky**(*realtype* t, int k) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getSensDky**(*realtype* t, int k) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getQuadDkyB**(*realtype* t, int k, int which) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getDkyB**(*realtype* t, int k, int which) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getRootInfo**(int *rootsfound) const override
getRootInfo extracts information which event occurred

Parameters **rootsfound** – array with flags indicating whether the respective event occurred

virtual void **setStopTime**(*realtype* tstop) const override
Sets a timepoint at which the simulation will be stopped.

Parameters **tstop** – timepoint until which simulation should be performed

virtual void **turnOffRootFinding**() const override
Disable rootfinding.

virtual const *Model* ***getModel**() const override
Accessor function to the model stored in the user data

Returns user data model

virtual void **setLinearSolver**() const override
Sets the linear solver for the forward problem.

virtual void **setLinearSolverB**(int which) const override
Sets the linear solver for the backward problem.

Parameters **which** – index of the backward problem

virtual void **setNonLinearSolver**() const override
Set the non-linear solver for the forward problem.

virtual void **setNonLinearSolverSens**() const override
Set the non-linear solver for sensitivities.

virtual void **setNonLinearSolverB**(int which) const override
Set the non-linear solver for the backward problem.

Parameters *which* – index of the backward problem

Solver() = default
Default constructor.

Solver(*AmiciApplication* *app)
Constructor.

Parameters *app* – AMICI application context

Solver(const *Solver* &other)
Solver copy constructor.

Parameters *other* –

Protected Functions

virtual void **calcIC**(*realtype* tout1) const override
Calculates consistent initial conditions, assumes initial states to be correct (DAE only)

Parameters *tout1* – next timepoint to be computed (sets timescale)

virtual void **calcICB**(int which, *realtype* tout1) const override
Calculates consistent initial conditions for the backwards problem, assumes initial states to be correct (DAE only)

Parameters

- *which* – identifier of the backwards problem
- *tout1* – next timepoint to be computed (sets timescale)

virtual void **getB**(int which) const override
extracts the adjoint state at the current timepoint from solver memory and writes it to the xB member variable

Parameters *which* – index of the backwards problem

virtual void **getSens**() const override
extracts the state sensitivity at the current timepoint from solver memory and writes it to the sx member variable

virtual void **getQuadB**(int which) const override
extracts the adjoint quadrature state at the current timepoint from solver memory and writes it to the xQB member variable

Parameters *which* – index of the backwards problem

virtual void **getQuad**(*realtype* &t) const override
extracts the quadrature at the current timepoint from solver memory and writes it to the xQ member variable

Parameters *t* – timepoint for quadrature extraction

virtual void **getQuadDky**(*realtype* t, int k) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **reInitPostProcessF**(*realtype* tnext) const override
 reInitPostProcessF postprocessing of the solver memory after a discontinuity in the forward problem

Parameters **tnext** – next timepoint (defines integration direction)

virtual void **reInitPostProcessB**(*realtype* tnext) const override
 reInitPostProcessB postprocessing of the solver memory after a discontinuity in the backward problem

Parameters **tnext** – next timepoint (defines integration direction)

void **reInitPostProcess**(void *cv_mem, *realtype* *t, *AmiVector* *yout, *realtype* tout) const
 Postprocessing of the solver memory after a discontinuity.

Parameters

- **cv_mem** – pointer to CVODES solver memory object
- **t** – pointer to integration time
- **yout** – new state vector
- **tout** – anticipated next integration timepoint.

virtual void **allocateSolver**() const override
 Create specifies solver method and initializes solver memory for the forward problem.

virtual void **setSStolerances**(double rtol, double atol) const override
 sets scalar relative and absolute tolerances for the forward problem

Parameters

- **rtol** – relative tolerances
- **atol** – absolute tolerances

virtual void **setSensSStolerances**(double rtol, const double *atol) const override
 activates sets scalar relative and absolute tolerances for the sensitivity variables

Parameters

- **rtol** – relative tolerances
- **atol** – array of absolute tolerances for every sensitivity variable

virtual void **setSensErrCon**(bool error_corr) const override
 SetSensErrCon specifies whether error control is also enforced for sensitivities for the forward problem

Parameters **error_corr** – activation flag

virtual void **setQuadErrConB**(int which, bool flag) const override
 Specifies whether error control is also enforced for the backward quadrature problem.

Parameters

- **which** – identifier of the backwards problem
- **flag** – activation flag

virtual void **setQuadErrCon**(bool flag) const override
 Specifies whether error control is also enforced for the forward quadrature problem.

Parameters **flag** – activation flag

virtual void **setErrHandlerFn**() const override
Attaches the error handler function (errMsgIdAndTxt) to the solver.

virtual void **setUserData**() const override
Attaches the user data to the forward problem.

virtual void **setUserDataB**(int which) const override
attaches the user data to the backward problem

Parameters **which** – identifier of the backwards problem

virtual void **setMaxNumSteps**(long int mxsteps) const override
specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters **mxsteps** – number of steps

virtual void **setStabLimDet**(int stldet) const override
activates stability limit detection for the forward problem

Parameters **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setStabLimDetB**(int which, int stldet) const override
activates stability limit detection for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setId**(const *Model* *model) const override
specify algebraic/differential components (DAE only)

Parameters **model** – model specification

virtual void **setSuppressAlg**(bool flag) const override
deactivates error control for algebraic components (DAE only)

Parameters **flag** – deactivation flag

void **resetState**(void *cv_mem, const *N_Vector* y0) const
resetState reset the CVODES solver to restart integration after a rhs discontinuity.

Parameters

- **cv_mem** – pointer to CVODES solver memory object
- **y0** – new state vector

virtual void **setSensParams**(const *realtypes* *p, const *realtypes* *pbar, const int *plist) const override
specifies the scaling and indexes for sensitivity computation

Parameters

- **p** – parameters
- **pbar** – parameter scaling constants
- **plist** – parameter index list

virtual void **adjInit**() const override
initializes the adjoint problem

virtual void **quadInit**(const *AmiVector* &xQ0) const override
initializes the quadratures

Parameters **xQ0** – vector with initial values for xQ

virtual void **allocateSolverB**(int *which) const override
Specifies solver method and initializes solver memory for the backward problem.

Parameters **which** – identifier of the backwards problem

virtual void **setSStolerancesB**(int which, *realtype* relTolB, *realtype* absTolB) const override
sets relative and absolute tolerances for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **relTolB** – relative tolerances
- **absTolB** – absolute tolerances

virtual void **quadSStolerancesB**(int which, *realtype* reltolQB, *realtype* abstolQB) const override
sets relative and absolute tolerances for the quadrature backward problem

Parameters

- **which** – identifier of the backwards problem
- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual void **quadSStolerances**(*realtype* reltolQ, *realtype* abstolQ) const override
sets relative and absolute tolerances for the quadrature problem

Parameters

- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual void **setMaxNumStepsB**(int which, long int mxstepsB) const override
specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters

- **which** – identifier of the backwards problem
- **mxstepsB** – number of steps

virtual void **diag**() const override
attaches a diagonal linear solver to the forward problem

virtual void **diagB**(int which) const override
attaches a diagonal linear solver to the backward problem

Parameters **which** – identifier of the backwards problem

virtual void **getNumSteps**(const void *ami_mem, long int *numsteps) const override
reports the number of solver steps

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numsteps** – output array

virtual void **getNumRhsEvals**(const void *ami_mem, long int *numrhsevals) const override
reports the number of right hand evaluations

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numrhsevals** – output array

virtual void **getNumErrTestFails**(const void *ami_mem, long int *numerrtestfails) const override
reports the number of local error test failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numerrtestfails** – output array

virtual void **getNumNonlinSolvConvFails**(const void *ami_mem, long int *numnonlinsolvconvfails) const override
reports the number of nonlinear convergence failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numnonlinsolvconvfails** – output array

virtual void **getLastOrder**(const void *ami_mem, int *order) const override
Reports the order of the integration method during the last internal step.

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **order** – output array

virtual void ***getAdjBmem**(void *ami_mem, int which) const override
Retrieves the solver memory instance for the backward problem.

Parameters

- **which** – identifier of the backwards problem
- **ami_mem** – pointer to the forward solver memory instance

Returns A (void *) pointer to the CVODES memory allocated for the backward problem.

virtual void **init**(*realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const override
Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **initSteadystate**(const *realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const override

Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **sensInit1**(const *AmiVectorArray* &sx0, const *AmiVectorArray* &sdx0) const override

Initializes the forward sensitivities.

Parameters

- **sx0** – initial states sensitivities
- **sdx0** – initial derivative states sensitivities

virtual void **binit**(int which, *realtype* tf, const *AmiVector* &xB0, const *AmiVector* &dxB0) const override

Initialize the adjoint states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **tf** – final timepoint
- **xB0** – initial adjoint state
- **dxB0** – initial adjoint derivative state

virtual void **qbinit**(int which, const *AmiVector* &xQB0) const override

Initialize the quadrature states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **xQB0** – initial adjoint quadrature state

virtual void **rootInit**(int ne) const override

Initializes the rootfinding for events.

Parameters **ne** – number of different events

virtual void **setDenseJacFn**() const override

Set the dense Jacobian function.

virtual void **setSparseJacFn**() const override

sets the sparse Jacobian function

virtual void **setBandJacFn**() const override

sets the banded Jacobian function

virtual void **setJacTimesVecFn**() const override

sets the Jacobian vector multiplication function

virtual void **setDenseJacFnB**(int which) const override

sets the dense Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFnB**(int which) const override
sets the sparse Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setBandJacFnB**(int which) const override
sets the banded Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setJacTimesVecFnB**(int which) const override
sets the Jacobian vector multiplication function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFn_ss**() const override
sets the sparse Jacobian function for backward steady state case

Friends

template<class **Archive**>

friend void **serialize**(*Archive* &ar, *CVodeSolver* &s, unsigned int)
Serialize *amici::CVodeSolver* to boost archive.

Parameters

- **ar** – Archive
- **s** – *Solver* instance to serialize

friend bool **operator==**(const *CVodeSolver* &a, const *CVodeSolver* &b)
Equality operator.

Parameters

- **a** –
- **b** –

Returns Whether a and b are equal

Class ExpData

- Defined in file_include_amici_edata.h

Inheritance Relationships

Base Type

- public *amici::SimulationParameters* (*Class SimulationParameters*)

Class Documentation

class amici::ExpData : public amici::SimulationParameters
ExpData carries all information about experimental or condition-specific data.

Public Functions

ExpData() = default
 default constructor

ExpData(const *ExpData*&) = default
 Copy constructor, needs to be declared to be generated in swig.

ExpData(int nytrue, int nztrue, int nmaxevent)
 constructor that only initializes dimensions

Parameters

- **nytrue** – Number of observables
- **nztrue** – Number of event outputs
- **nmaxevent** – Maximal number of events to track

ExpData(int nytrue, int nztrue, int nmaxevent, std::vector<*realtype*> ts)
 constructor that initializes timepoints from vectors

Parameters

- **nytrue** – Number of observables
- **nztrue** – Number of event outputs
- **nmaxevent** – Maximal number of events to track
- **ts** – Timepoints (dimension: nt)

ExpData(int nytrue, int nztrue, int nmaxevent, std::vector<*realtype*> ts, std::vector<*realtype*> fixedParameters)
 constructor that initializes timepoints and fixed parameters from vectors

Parameters

- **nytrue** – Number of observables
- **nztrue** – Number of event outputs
- **nmaxevent** – Maximal number of events to track
- **ts** – Timepoints (dimension: nt)
- **fixedParameters** – *Model* constants (dimension: nk)

ExpData(int nytrue, int nztrue, int nmaxevent, std::vector<*realtype*> ts, std::vector<*realtype*> const &observedData, std::vector<*realtype*> const &observedDataStdDev, std::vector<*realtype*> const &observedEvents, std::vector<*realtype*> const &observedEventsStdDev)
 constructor that initializes timepoints and data from vectors

Parameters

- **nytrue** – Number of observables
- **nztrue** – Number of event outputs
- **nmaxevent** – Maximal number of events to track

- **ts** – Timepoints (dimension: nt)
- **observedData** – observed data (dimension: nt x nytrue, row-major)
- **observedDataStdDev** – standard deviation of observed data (dimension: nt x nytrue, row-major)
- **observedEvents** – observed events (dimension: nmaxevents x nztrue, row-major)
- **observedEventsStdDev** – standard deviation of observed events/roots (dimension: nmaxevents x nztrue, row-major)

explicit **ExpData**(const *Model* &model)
constructor that initializes with *Model*

Parameters *model* – pointer to model specification object

ExpData(const *ReturnData* &rdata, *realtype* sigma_y, *realtype* sigma_z)
constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** – return data pointer with stored simulation results
- **sigma_y** – scalar standard deviations for all observables
- **sigma_z** – scalar standard deviations for all event observables

ExpData(const *ReturnData* &rdata, std::vector<*realtype*> sigma_y, std::vector<*realtype*> sigma_z)
constructor that initializes with returnData, adds noise according to specified sigmas

Parameters

- **rdata** – return data pointer with stored simulation results
- **sigma_y** – vector of standard deviations for observables (dimension: nytrue or nt x nytrue, row-major)
- **sigma_z** – vector of standard deviations for event observables (dimension: nztrue or nmax-event x nztrue, row-major)

~ExpData() = default

int **nytrue()** const
number of observables of the non-augmented model

Returns number of observables of the non-augmented model

int **nztrue()** const
number of event observables of the non-augmented model

Returns number of event observables of the non-augmented model

int **nmaxevent()** const
maximal number of events to track

Returns maximal number of events to track

int **nt()** const
number of timepoints

Returns number of timepoints

void **setTimepoints**(const std::vector<*realtype*> &ts)
Set function that copies data from input to ExpData::ts.

Parameters **ts** – timepoints

`std::vector<realtype> const &getTimepoints() const`
 get function that copies data from ExpData::ts to output

Returns ExpData::ts

`realtype getTimepoint(int it) const`
 get function that returns timepoint at index

Parameters **it** – timepoint index

Returns timepoint timepoint at index

`void setObservedData(const std::vector<realtype> &observedData)`
 set function that copies data from input to ExpData::my

Parameters **observedData** – observed data (dimension: nt x nytrue, row-major)

`void setObservedData(const std::vector<realtype> &observedData, int iy)`
 set function that copies observed data for specific observable

Parameters

- **observedData** – observed data (dimension: nt)
- **iy** – observed data index

`bool isSetObservedData(int it, int iy) const`
 get function that checks whether data at specified indices has been set

Parameters

- **it** – time index
- **iy** – observable index

Returns boolean specifying if data was set

`std::vector<realtype> const &getObservedData() const`
 get function that copies data from ExpData::observedData to output

Returns observed data (dimension: nt x nytrue, row-major)

`const realtype *getObservedDataPtr(int it) const`
 get function that returns a pointer to observed data at index

Parameters **it** – timepoint index

Returns pointer to observed data at index (dimension: nytrue)

`void setObservedDataStdDev(const std::vector<realtype> &observedDataStdDev)`
 set function that copies data from input to ExpData::observedDataStdDev

Parameters **observedDataStdDev** – standard deviation of observed data (dimension: nt x nytrue, row-major)

`void setObservedDataStdDev(realtype stdDev)`
 set function that sets all ExpData::observedDataStdDev to the input value

Parameters **stdDev** – standard deviation (dimension: scalar)

`void setObservedDataStdDev(const std::vector<realtype> &observedDataStdDev, int iy)`
 set function that copies standard deviation of observed data for specific observable

Parameters

- **observedDataStdDev** – standard deviation of observed data (dimension: nt)

- **iy** – observed data index

void **setObservedDataStdDev**(*realtype* stdDev, int iy)

set function that sets all standard deviation of a specific observable to the input value

Parameters

- **stdDev** – standard deviation (dimension: scalar)
- **iy** – observed data index

bool **isSetObservedDataStdDev**(int it, int iy) const

get function that checks whether standard deviation of data at specified indices has been set

Parameters

- **it** – time index
- **iy** – observable index

Returns boolean specifying if standard deviation of data was set

std::vector<*realtype*> const &**getObservedDataStdDev**() const

get function that copies data from ExpData::observedDataStdDev to output

Returns standard deviation of observed data

const *realtype* ***getObservedDataStdDevPtr**(int it) const

get function that returns a pointer to standard deviation of observed data at index

Parameters **it** – timepoint index

Returns pointer to standard deviation of observed data at index

void **setObservedEvents**(const std::vector<*realtype*> &observedEvents)

set function that copies observed event data from input to ExpData::observedEvents

Parameters **observedEvents** – observed data (dimension: nmaxevent x nztrue, row-major)

void **setObservedEvents**(const std::vector<*realtype*> &observedEvents, int iz)

set function that copies observed event data for specific event observable

Parameters

- **observedEvents** – observed data (dimension: nmaxevent)
- **iz** – observed event data index

bool **isSetObservedEvents**(int ie, int iz) const

get function that checks whether event data at specified indices has been set

Parameters

- **ie** – event index
- **iz** – event observable index

Returns boolean specifying if data was set

std::vector<*realtype*> const &**getObservedEvents**() const

get function that copies data from ExpData::mz to output

Returns observed event data

const *realtype* ***getObservedEventsPtr**(int ie) const

get function that returns a pointer to observed data at ieth occurrence

Parameters **ie** – event occurrence

Returns pointer to observed event data at ieth occurrence

void **setObservedEventsStdDev**(const std::vector<*realtype*> &observedEventsStdDev)
set function that copies data from input to ExpData::observedEventsStdDev

Parameters **observedEventsStdDev** – standard deviation of observed event data

void **setObservedEventsStdDev**(*realtype* stdDev)
set function that sets all ExpData::observedDataStdDev to the input value

Parameters **stdDev** – standard deviation (dimension: scalar)

void **setObservedEventsStdDev**(const std::vector<*realtype*> &observedEventsStdDev, int iz)
set function that copies standard deviation of observed data for specific observable

Parameters

- **observedEventsStdDev** – standard deviation of observed data (dimension: nmaxevent)
- **iz** – observed data index

void **setObservedEventsStdDev**(*realtype* stdDev, int iz)
set function that sets all standard deviation of a specific observable to the input value

Parameters

- **stdDev** – standard deviation (dimension: scalar)
- **iz** – observed data index

bool **isSetObservedEventsStdDev**(int ie, int iz) const
get function that checks whether standard deviation of even data at specified indices has been set

Parameters

- **ie** – event index
- **iz** – event observable index

Returns boolean specifying if standard deviation of event data was set

std::vector<*realtype*> const &**getObservedEventsStdDev**() const
get function that copies data from ExpData::observedEventsStdDev to output

Returns standard deviation of observed event data

const *realtype* ***getObservedEventsStdDevPtr**(int ie) const
get function that returns a pointer to standard deviation of observed event data at ie-th occurrence

Parameters **ie** – event occurrence

Returns pointer to standard deviation of observed event data at ie-th occurrence

Public Members

std::string **id**
Arbitrary (not necessarily unique) identifier.

Protected Functions

void **applyDimensions**()
resizes `observedData`, `observedDataStdDev`, `observedEvents` and `observedEventsStdDev`

void **applyDataDimension**()
resizes `observedData` and `observedDataStdDev`

void **applyEventDimension**()
resizes `observedEvents` and `observedEventsStdDev`

void **checkDataDimension**(std::vector<*realtype*> const &input, const char *fieldname) const
checker for dimensions of input `observedData` or `observedDataStdDev`

Parameters

- **input** – vector input to be checked
- **fieldname** – name of the input

void **checkEventsDimension**(std::vector<*realtype*> const &input, const char *fieldname) const
checker for dimensions of input `observedEvents` or `observedEventsStdDev`

Parameters

- **input** – vector input to be checked
- **fieldname** – name of the input

Protected Attributes

int **nytrue_** = {0}
number of observables

int **nztrue_** = {0}
number of event observables

int **nmaxevent_** = {0}
maximal number of event occurrences

std::vector<*realtype*> **observed_data_**
observed data (dimension: `nt` x `nytrue`, row-major)

std::vector<*realtype*> **observed_data_std_dev_**
standard deviation of observed data (dimension: `nt` x `nytrue`, row-major)

std::vector<*realtype*> **observed_events_**
observed events (dimension: `nmaxevents` x `nztrue`, row-major)

std::vector<*realtype*> **observed_events_std_dev_**
standard deviation of observed events/roots (dimension: `nmaxevents` x `nztrue`, row-major)

Class FinalStateStorer

- Defined in file_include_amici_forwardproblem.h

Inheritance Relationships

Base Type

- public amici::ContextManager (*Class ContextManager*)

Class Documentation

class amici::FinalStateStorer : public amici::ContextManager
stores the stimulation state when it goes out of scope

Public Functions

inline explicit FinalStateStorer(ForwardProblem *fwd)
constructor, attaches problem pointer

Parameters fwd – problem from which the simulation state is to be stored

FinalStateStorer &operator=(const FinalStateStorer &other) = delete

inline ~FinalStateStorer()
destructor, stores simulation state

Class ForwardProblem

- Defined in file_include_amici_forwardproblem.h

Class Documentation

class amici::ForwardProblem
The ForwardProblem class groups all functions for solving the forward problem.

Public Functions

ForwardProblem(const ExpData *edata, Model *model, Solver *solver, const SteadystateProblem *preeq)
Constructor.

Parameters

- edata – pointer to ExpData instance
- model – pointer to Model instance
- solver – pointer to Solver instance

- **preeq** – preequilibration with which to initialize the forward problem, pass nullptr for no initialization

~ForwardProblem() = default

void **workForwardProblem()**

Solve the forward problem.

If forward sensitivities are enabled this will also compute sensitivities.

void **getAdjointUpdates**(*Model* &model, const *ExpData* &edata)
computes adjoint updates dJydx according to provided model and expdata

Parameters

- **model** – *Model* instance
- **edata** – experimental data

inline *realtype* **getTime()** const
Accessor for t.

Returns t

inline *AmiVector* const &**getState()** const
Accessor for x.

Returns x

inline *AmiVector* const &**getStateDerivative()** const
Accessor for dx.

Returns dx

inline *AmiVectorArray* const &**getStateSensitivity()** const
Accessor for sx.

Returns sx

inline std::vector<*AmiVector*> const &**getStatesAtDiscontinuities()** const
Accessor for x_disc.

Returns x_disc

inline std::vector<*AmiVector*> const &**getRHSAtDiscontinuities()** const
Accessor for xdot_disc.

Returns xdot_disc

inline std::vector<*AmiVector*> const &**getRHSBeforeDiscontinuities()** const
Accessor for xdot_old_disc.

Returns xdot_old_disc

inline std::vector<int> const &**getNumberOfRoots()** const
Accessor for nroots.

Returns nroots

inline std::vector<*realtype*> const &**getDiscontinuities()** const
Accessor for discs.

Returns discs

inline std::vector<std::vector<int>> const &**getRootIndexes()** const
Accessor for rootidx.

Returns rootidx

inline std::vector<*realtype*> const &getDJydx() const
 Accessor for dJydx.

Returns dJydx

inline std::vector<*realtype*> const &getDJzdx() const
 Accessor for dJzdx.

Returns dJzdx

inline *AmiVector* *getStatePointer()
 Accessor for pointer to x.

Returns &x

inline *AmiVector* *getStateDerivativePointer()
 Accessor for pointer to dx.

Returns &dx

inline *AmiVectorArray* *getStateSensitivityPointer()
 accessor for pointer to sx

Returns &sx

inline *AmiVectorArray* *getStateDerivativeSensitivityPointer()
 Accessor for pointer to sdx.

Returns &sdx

inline int getCurrentTimeIteration() const
 Accessor for it.

Returns it

inline *realtype* getFinalTime() const
 Returns final time point for which simulations are available.

Returns time point

inline int getEventCounter() const
 Returns maximal event index for which simulations are available.

Returns index

inline int getRootCounter() const
 Returns maximal event index for which the timepoint is available.

Returns index

inline const *SimulationState* &getSimulationStateTimepoint(int it) const
 Retrieves the carbon copy of the simulation state variables at the specified timepoint index.

Parameters *it* – timepoint index

Returns state

inline const *SimulationState* &getSimulationStateEvent(int iroot) const
 Retrieves the carbon copy of the simulation state variables at the specified event index.

Parameters *iroot* – event index

Returns *SimulationState*

inline const *SimulationState* &getInitialSimulationState() const

Retrieves the carbon copy of the simulation state variables at the initial timepoint.

Returns *SimulationState*

inline const *SimulationState* &getFinalSimulationState() const

Retrieves the carbon copy of the simulation state variables at the final timepoint (or when simulation failed)

Returns *SimulationState*

Public Members

Model ***model**

pointer to model instance

Solver ***solver**

pointer to solver instance

const *ExpData* ***edata**

pointer to experimental data instance

Class IDAException

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- public amici::AmiException (*Class AmiException*)

Class Documentation

class amici::IDAException : public amici::AmiException
ida exception handler class

Public Functions

IDAException(int error_code, const char *function)

Constructor.

Parameters

- **error_code** – error code returned by ida function
- **function** – ida function name

Class IDASolver

- Defined in file_include_amici_solver_idas.h

Inheritance Relationships

Base Type

- public amici::Solver (*Class Solver*)

Class Documentation

class amici::IDASolver : public amici::Solver

The *IDASolver* class is a wrapper around the SUNDIALS IDAS solver.

Public Functions

~IDASolver() override = default

virtual *Solver* ***clone()** const override

Clone this instance.

Returns The clone

virtual void **reInitPostProcessF**(*realtype* tnext) const override

reInitPostProcessF postprocessing of the solver memory after a discontinuity in the forward problem

Parameters *tnext* – next timepoint (defines integration direction)

virtual void **reInitPostProcessB**(*realtype* tnext) const override

reInitPostProcessB postprocessing of the solver memory after a discontinuity in the backward problem

Parameters *tnext* – next timepoint (defines integration direction)

virtual void **reInit**(*realtype* t0, const *AmiVector* &yy0, const *AmiVector* &yp0) const override

Reinitializes the states in the solver after an event occurrence.

Parameters

- **t0** – reinitialization timepoint
- **yy0** – initial state variables
- **yp0** – initial derivative state variables (DAE only)

virtual void **sensReInit**(const *AmiVectorArray* &yyS0, const *AmiVectorArray* &ypS0) const override

Reinitializes the state sensitivities in the solver after an event occurrence.

Parameters

- **yyS0** – new state sensitivity
- **ypS0** – new derivative state sensitivities (DAE only)

virtual void **sensToggleOff**() const override

Switches off computation of state sensitivities without deallocating the memory for sensitivities.

virtual void **reInitB**(int which, *realtype* tB0, const *AmiVector* &yyB0, const *AmiVector* &ypB0) const override

Reinitializes the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **tB0** – reinitialization timepoint
- **yyB0** – new adjoint state
- **ypB0** – new adjoint derivative state

virtual void **quadReInitB**(int which, const *AmiVector* &yQB0) const override

Reinitialize the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **yQB0** – new adjoint quadrature state

virtual void **quadStolerancesB**(int which, *realtype* reltolQB, *realtype* abstolQB) const override
sets relative and absolute tolerances for the quadrature backward problem

Parameters

- **which** – identifier of the backwards problem
- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual void **quadStolerances**(*realtype* reltolQ, *realtype* abstolQ) const override
sets relative and absolute tolerances for the quadrature problem

Parameters

- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual int **solve**(*realtype* tout, int itask) const override
Solves the forward problem until a predefined timepoint.

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP

Returns status flag indicating success of execution

virtual int **solveF**(*realtype* tout, int itask, int *ncheckPtr) const override
Solves the forward problem until a predefined timepoint (adjoint only)

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP
- **ncheckPtr** – pointer to a number that counts the internal checkpoints

Returns status flag indicating success of execution

virtual void **solveB**(*realtype* tBout, int itaskB) const override
Solves the backward problem until a predefined timepoint (adjoint only)

Parameters

- **tBout** – timepoint until which simulation should be performed
- **itaskB** – task identifier, can be CV_NORMAL or CV_ONE_STEP

virtual void **getRootInfo**(int *rootsfound) const override
 getRootInfo extracts information which event occurred

Parameters rootsfound – array with flags indicating whether the respective event occurred

virtual void **getDky**(*realtype* t, int k) const override
 interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getSens**() const override
 extracts the state sensitivity at the current timepoint from solver memory and writes it to the sx member variable

virtual void **getSensDky**(*realtype* t, int k) const override
 interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getB**(int which) const override
 extracts the adjoint state at the current timepoint from solver memory and writes it to the xB member variable

Parameters which – index of the backwards problem

virtual void **getDkyB**(*realtype* t, int k, int which) const override
 interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getQuadB**(int which) const override
 extracts the adjoint quadrature state at the current timepoint from solver memory and writes it to the xQB member variable

Parameters which – index of the backwards problem

virtual void **getQuadDkyB**(*realtype* t, int k, int which) const override
 interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getQuad**(*realtype* &t) const override
extracts the quadrature at the current timepoint from solver memory and writes it to the xQ member variable

Parameters **t** – timepoint for quadrature extraction

virtual void **getQuadDky**(*realtype* t, int k) const override
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **calcIC**(*realtype* tout1) const override
Calculates consistent initial conditions, assumes initial states to be correct (DAE only)

Parameters **tout1** – next timepoint to be computed (sets timescale)

virtual void **calcICB**(int which, *realtype* tout1) const override
Calculates consistent initial conditions for the backwards problem, assumes initial states to be correct (DAE only)

Parameters

- **which** – identifier of the backwards problem
- **tout1** – next timepoint to be computed (sets timescale)

virtual void **setStopTime**(*realtype* tstop) const override
Sets a timepoint at which the simulation will be stopped.

Parameters **tstop** – timepoint until which simulation should be performed

virtual void **turnOffRootFinding**() const override
Disable rootfinding.

virtual const *Model* ***getModel**() const override
Accessor function to the model stored in the user data

Returns user data model

virtual void **setLinearSolver**() const override
Sets the linear solver for the forward problem.

virtual void **setLinearSolverB**(int which) const override
Sets the linear solver for the backward problem.

Parameters **which** – index of the backward problem

virtual void **setNonLinearSolver**() const override
Set the non-linear solver for the forward problem.

virtual void **setNonLinearSolverSens**() const override
Set the non-linear solver for sensitivities.

virtual void **setNonLinearSolverB**(int which) const override
Set the non-linear solver for the backward problem.

Parameters **which** – index of the backward problem

Solver() = default
Default constructor.

Solver(*AmiciApplication* *app)
Constructor.

Parameters **app** – AMICI application context

Solver(const *Solver* &other)
Solver copy constructor.

Parameters **other** –

Protected Functions

void **reInitPostProcess**(void *ida_mem, *realtype* *t, *AmiVector* *yout, *AmiVector* *ypout, *realtype* tout)
 const

Postprocessing of the solver memory after a discontinuity.

Parameters

- **ida_mem** – pointer to IDAS solver memory object
- **t** – pointer to integration time
- **yout** – new state vector
- **ypout** – new state derivative vector
- **tout** – anticipated next integration timepoint.

virtual void **allocateSolver**() const override

Create specifies solver method and initializes solver memory for the forward problem.

virtual void **setSStolerances**(*realtype* rtol, *realtype* atol) const override
 sets scalar relative and absolute tolerances for the forward problem

Parameters

- **rtol** – relative tolerances
- **atol** – absolute tolerances

virtual void **setSensSStolerances**(*realtype* rtol, const *realtype* *atol) const override
 activates sets scalar relative and absolute tolerances for the sensitivity variables

Parameters

- **rtol** – relative tolerances
- **atol** – array of absolute tolerances for every sensitivity variable

virtual void **setSensErrCon**(bool error_corr) const override

SetSensErrCon specifies whether error control is also enforced for sensitivities for the forward problem

Parameters **error_corr** – activation flag

virtual void **setQuadErrConB**(int which, bool flag) const override

Specifies whether error control is also enforced for the backward quadrature problem.

Parameters

- **which** – identifier of the backwards problem
- **flag** – activation flag

virtual void **setQuadErrCon**(bool flag) const override

Specifies whether error control is also enforced for the forward quadrature problem.

Parameters **flag** – activation flag

virtual void **setErrHandlerFn**() const override
Attaches the error handler function (errMsgIdAndTxt) to the solver.

virtual void **setUserData**() const override
Attaches the user data to the forward problem.

virtual void **setUserDataB**(int which) const override
attaches the user data to the backward problem

Parameters **which** – identifier of the backwards problem

virtual void **setMaxNumSteps**(long int mxsteps) const override
specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters **mxsteps** – number of steps

virtual void **setStabLimDet**(int stldet) const override
activates stability limit detection for the forward problem

Parameters **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setStabLimDetB**(int which, int stldet) const override
activates stability limit detection for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setId**(const *Model* *model) const override
specify algebraic/differential components (DAE only)

Parameters **model** – model specification

virtual void **setSuppressAlg**(bool flag) const override
deactivates error control for algebraic components (DAE only)

Parameters **flag** – deactivation flag

void **resetState**(void *ida_mem, const *N_Vector* yy0, const *N_Vector* yp0) const
resetState reset the IDAS solver to restart integration after a rhs discontinuity.

Parameters

- **ida_mem** – pointer to IDAS solver memory object
- **yy0** – new state vector
- **yp0** – new state derivative vector

virtual void **setSensParams**(const *realtypes* *p, const *realtypes* *pbar, const int *plist) const override
specifies the scaling and indexes for sensitivity computation

Parameters

- **p** – parameters
- **pbar** – parameter scaling constants
- **plist** – parameter index list

virtual void **adjInit**() const override
initializes the adjoint problem

virtual void **quadInit**(const *AmiVector* &xQ0) const override
initializes the quadratures

Parameters **xQ0** – vector with initial values for xQ

virtual void **allocateSolverB**(int *which) const override
Specifies solver method and initializes solver memory for the backward problem.

Parameters **which** – identifier of the backwards problem

virtual void **setMaxNumStepsB**(int which, long int mxstepsB) const override
specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters

- **which** – identifier of the backwards problem
- **mxstepsB** – number of steps

virtual void **setSStolerancesB**(int which, *realt* relTolB, *realt* absTolB) const override
sets relative and absolute tolerances for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **relTolB** – relative tolerances
- **absTolB** – absolute tolerances

virtual void **diag**() const override
attaches a diagonal linear solver to the forward problem

virtual void **diagB**(int which) const override
attaches a diagonal linear solver to the backward problem

Parameters **which** – identifier of the backwards problem

virtual void **getNumSteps**(const void *ami_mem, long int *numsteps) const override
reports the number of solver steps

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numsteps** – output array

virtual void **getNumRhsEvals**(const void *ami_mem, long int *numrhsevals) const override
reports the number of right hand evaluations

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numrhsevals** – output array

virtual void **getNumErrTestFails**(const void *ami_mem, long int *numerrtestfails) const override
reports the number of local error test failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numerrtestfails** – output array

virtual void **getNumNonlinSolvConvFails**(const void *ami_mem, long int *numnonlinsolvconvfails) const override
reports the number of nonlinear convergence failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numnonlinsolvconvfails** – output array

virtual void **getLastOrder**(const void *ami_mem, int *order) const override
Reports the order of the integration method during the last internal step.

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **order** – output array

virtual void ***getAdjBmem**(void *ami_mem, int which) const override
Retrieves the solver memory instance for the backward problem.

Parameters

- **which** – identifier of the backwards problem
- **ami_mem** – pointer to the forward solver memory instance

Returns A (void *) pointer to the CVODES memory allocated for the backward problem.

virtual void **init**(*realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const override
Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **initSteadystate**(const *realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const override
Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **sensInit1**(const *AmiVectorArray* &sx0, const *AmiVectorArray* &sdx0) const override
Initializes the forward sensitivities.

Parameters

- **sx0** – initial states sensitivities
- **sdx0** – initial derivative states sensitivities

virtual void **binit**(int which, *realtype* tf, const *AmiVector* &xB0, const *AmiVector* &dxB0) const override
Initialize the adjoint states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **tf** – final timepoint
- **xB0** – initial adjoint state
- **dxB0** – initial adjoint derivative state

virtual void **qbinit**(int which, const *AmiVector* &xB0) const override
Initialize the quadrature states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **xB0** – initial adjoint quadrature state

virtual void **rootInit**(int ne) const override
Initializes the rootfinding for events.

Parameters **ne** – number of different events

virtual void **setDenseJacFn**() const override
Set the dense Jacobian function.

virtual void **setSparseJacFn**() const override
sets the sparse Jacobian function

virtual void **setBandJacFn**() const override
sets the banded Jacobian function

virtual void **setJacTimesVecFn**() const override
sets the Jacobian vector multiplication function

virtual void **setDenseJacFnB**(int which) const override
sets the dense Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFnB**(int which) const override
sets the sparse Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setBandJacFnB**(int which) const override
sets the banded Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setJacTimesVecFnB**(int which) const override
sets the Jacobian vector multiplication function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFn_ss**() const override
sets the sparse Jacobian function for backward steady state case

Class IntegrationFailure

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- `public amici::AmiException` (*Class AmiException*)

Class Documentation

`class amici::IntegrationFailure` : public `amici::AmiException`
Integration failure exception for the forward problem.

This exception should be thrown when an integration failure occurred for this exception we can assume that we can recover from the exception and return a solution struct to the user

Public Functions

IntegrationFailure(int code, *realtype* t)
Constructor.

Parameters

- **code** – error code returned by ccode/ida
- **t** – time of integration failure

Public Members

int **error_code**
error code returned by cvodes/idas

realtype **time**
time of integration failure

Class IntegrationFailureB

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- `public amici::AmiException` (*Class AmiException*)

Class Documentation

`class amici::IntegrationFailureB` : `public amici::AmiException`
Integration failure exception for the backward problem.

This exception should be thrown when an integration failure occurred for this exception we can assume that we can recover from the exception and return a solution struct to the user

Public Functions

IntegrationFailureB(int code, *realtype* t)
Constructor.

Parameters

- **code** – error code returned by ccode/ida
- **t** – time of integration failure

Public Members

int **error_code**
error code returned by ccode/ida

realtype **time**
time of integration failure

Class Model

- Defined in `file_include_amici_model.h`

Inheritance Relationships

Base Types

- `public amici::AbstractModel` (*Class AbstractModel*)
- `public amici::ModelDimensions` (*Struct ModelDimensions*)

Derived Types

- `public amici::Model_DAE` (*Class Model_DAE*)
- `public amici::Model_ODE` (*Class Model_ODE*)

Class Documentation

class `amici::Model` : public `amici::AbstractModel`, public `amici::ModelDimensions`

The *Model* class represents an AMICI ODE/DAE model.

The model can compute various model related quantities based on symbolically generated code.

Subclassed by *amici::Model_DAE*, *amici::Model_ODE*

Public Functions

Model() = default

Default constructor

Model(*ModelDimensions* const &model_dimensions, *SimulationParameters* simulation_parameters, *amici::SecondOrderMode* o2mode, std::vector<*amici::realtype*> idlist, std::vector<int> z2event, bool pythonGenerated = false, int ndxdotdp_explicit = 0, int ndxdotdx_explicit = 0, int w_recursion_depth = 0)

Constructor with model dimensions.

Parameters

- **model_dimensions** – *Model* dimensions
- **simulation_parameters** – Simulation parameters
- **o2mode** – Second order sensitivity mode
- **idlist** – Indexes indicating algebraic components (DAE only)
- **z2event** – Mapping of event outputs to events
- **pythonGenerated** – Flag indicating matlab or python wrapping
- **ndxdotdp_explicit** – Number of nonzero elements in `dxdotdp_explicit`
- **ndxdotdx_explicit** – Number of nonzero elements in `dxdotdx_explicit`
- **w_recursion_depth** – Recursion depth of fw

~Model() override = default

Destructor.

Model &**operator=**(*Model* const &other) = delete

Copy assignment is disabled until const members are removed.

Parameters **other** – Object to copy from

Returns

virtual *Model* ***clone**() const = 0

Clone this instance.

Returns The clone

void **initialize**(*AmiVector* &x, *AmiVector* &dx, *AmiVectorArray* &sx, *AmiVectorArray* &sdx, bool computeSensitivities)

Initialize model properties.

Parameters

- **x** – Reference to state variables
- **dx** – Reference to time derivative of states (DAE only)
- **sx** – Reference to state variable sensitivities
- **sdx** – Reference to time derivative of state sensitivities (DAE only)
- **computeSensitivities** – Flag indicating whether sensitivities are to be computed

void **initializeB**(*AmiVector* &xB, *AmiVector* &dxB, *AmiVector* &xQB, bool posteq) const

Initialize model properties.

Parameters

- **xB** – Adjoint state variables
- **dxB** – Time derivative of adjoint states (DAE only)
- **xQB** – Adjoint quadratures
- **posteq** – Flag indicating whether postequilibration was performed

void **initializeStates**(*AmiVector* &x)

Initialize initial states.

Parameters **x** – State vector to be initialized

void **initializeStateSensitivities**(*AmiVectorArray* &sx, const *AmiVector* &x)

Initialize initial state sensitivities.

Parameters

- **sx** – Reference to state variable sensitivities
- **x** – Reference to state variables

void **initHeaviside**(const *AmiVector* &x, const *AmiVector* &dx)

Initialize the Heaviside variables **h** at the initial time **t0**.

Heaviside variables activate/deactivate on event occurrences.

Parameters

- **x** – Reference to state variables
- **dx** – Reference to time derivative of states (DAE only)

int **nplist**() const

Get number of parameters wrt to which sensitivities are computed.

Returns Length of sensitivity index vector

int **np**() const

Get total number of model parameters.

Returns Length of parameter vector

int **nk**() const

Get number of constants.

Returns Length of constant vector

`int ncl()` const
Get number of conservation laws.
Returns Number of conservation laws (i.e., difference between `nx_rdata` and `nx_solver`).

`int nx_reinit()` const
Get number of solver states subject to reinitialization.
Returns *Model* member `nx_solver_reinit`

`const double *k()` const
Get fixed parameters.
Returns Pointer to constants array

`int nMaxEvent()` const
Get maximum number of events that may occur for each type.
Returns Maximum number of events that may occur for each type

`void setNMaxEvent(int nmaxevent)`
Set maximum number of events that may occur for each type.
Parameters `nmaxevent` – Maximum number of events that may occur for each type

`int nt()` const
Get number of timepoints.
Returns Number of timepoints

`std::vector<ParameterScaling> const &getParameterScale()` const
Get parameter scale for each parameter.
Returns Vector of parameter scales

`void setParameterScale(ParameterScaling pscale)`
Set parameter scale for each parameter.
NOTE: Resets initial state sensitivities.
Parameters `pscale` – Scalar parameter scale to be set for all parameters

`void setParameterScale(const std::vector<ParameterScaling> &pscaleVec)`
Set parameter scale for each parameter.
NOTE: Resets initial state sensitivities.
Parameters `pscaleVec` – Vector of parameter scales

`std::vector<realtype> const &getUnscaledParameters()` const
Get parameters with transformation according to parameter scale applied.
Returns Unscaled parameters

`std::vector<realtype> const &getParameters()` const
Get parameter vector.
Returns The user-set parameters (see also *Model::getUnscaledParameters*)

realtype `getParameterById(std::string const &par_id)` const
Get value of first model parameter with the specified ID.
Parameters `par_id` – Parameter ID
Returns Parameter value

realtype **getParameterByName**(std::string const &par_name) const

Get value of first model parameter with the specified name.

Parameters **par_name** – Parameter name

Returns Parameter value

void **setParameters**(std::vector<*realtype*> const &p)

Set the parameter vector.

Parameters **p** – Vector of parameters

void **setParameterById**(std::map<std::string, *realtype*> const &p, bool ignoreErrors = false)

Set model parameters according to the parameter IDs and mapped values.

Parameters

- **p** – Map of parameters IDs and values
- **ignoreErrors** – Ignore errors such as parameter IDs in p which are not model parameters

void **setParameterById**(std::string const &par_id, *realtype* value)

Set value of first model parameter with the specified ID.

Parameters

- **par_id** – Parameter ID
- **value** – Parameter value

int **setParametersByIdRegex**(std::string const &par_id_regex, *realtype* value)

Set all values of model parameters with IDs matching the specified regular expression.

Parameters

- **par_id_regex** – Parameter ID regex
- **value** – Parameter value

Returns Number of parameter IDs that matched the regex

void **setParameterByName**(std::string const &par_name, *realtype* value)

Set value of first model parameter with the specified name.

Parameters

- **par_name** – Parameter name
- **value** – Parameter value

void **setParameterByName**(std::map<std::string, *realtype*> const &p, bool ignoreErrors = false)

Set model parameters according to the parameter name and mapped values.

Parameters

- **p** – Map of parameters names and values
- **ignoreErrors** – Ignore errors such as parameter names in p which are not model parameters

int **setParametersByNameRegex**(std::string const &par_name_regex, *realtype* value)

Set all values of all model parameters with names matching the specified regex.

Parameters

- **par_name_regex** – Parameter name regex
- **value** – Parameter value

Returns Number of fixed parameter names that matched the regex

`std::vector<realtype> const &getFixedParameters()` const
Get values of fixed parameters.

Returns Vector of fixed parameters with same ordering as in *Model::getFixedParameterIds*

realtype `getFixedParameterById`(std::string const &par_id) const
Get value of fixed parameter with the specified ID.

Parameters `par_id` – Parameter ID

Returns Parameter value

realtype `getFixedParameterByName`(std::string const &par_name) const
Get value of fixed parameter with the specified name.

If multiple parameters have the same name, the first parameter with matching name is returned.

Parameters `par_name` – Parameter name

Returns Parameter value

void `setFixedParameters`(std::vector<*realtype*> const &k)
Set values for constants.

Parameters `k` – Vector of fixed parameters

void `setFixedParameterById`(std::string const &par_id, *realtype* value)
Set value of first fixed parameter with the specified ID.

Parameters

- `par_id` – Fixed parameter id
- `value` – Fixed parameter value

int `setFixedParametersByIdRegex`(std::string const &par_id_regex, *realtype* value)
Set values of all fixed parameters with the ID matching the specified regex.

Parameters

- `par_id_regex` – Fixed parameter name regex
- `value` – Fixed parameter value

Returns Number of fixed parameter IDs that matched the regex

void `setFixedParameterByName`(std::string const &par_name, *realtype* value)
Set value of first fixed parameter with the specified name.

Parameters

- `par_name` – Fixed parameter ID
- `value` – Fixed parameter value

int `setFixedParametersByNameRegex`(std::string const &par_name_regex, *realtype* value)
Set value of all fixed parameters with name matching the specified regex.

Parameters

- `par_name_regex` – Fixed parameter name regex
- `value` – Fixed parameter value

Returns Number of fixed parameter names that matched the regex

virtual std::string **getName()** const

Get the model name.

Returns *Model* name

virtual bool **hasParameterNames()** const

Report whether the model has parameter names set.

Returns Boolean indicating whether parameter names were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getParameterNames()** const

Get names of the model parameters.

Returns The parameter names

virtual bool **hasStateNames()** const

Report whether the model has state names set.

Returns Boolean indicating whether state names were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getStateNames()** const

Get names of the model states.

Returns State names

virtual std::vector<std::string> **getStateNamesSolver()** const

Get names of the solver states.

Returns State names

virtual bool **hasFixedParameterNames()** const

Report whether the model has fixed parameter names set.

Returns Boolean indicating whether fixed parameter names were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getFixedParameterNames()** const

Get names of the fixed model parameters.

Returns Fixed parameter names

virtual bool **hasObservableNames()** const

Report whether the model has observable names set.

Returns Boolean indicating whether observable names were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getObservableNames()** const

Get names of the observables.

Returns Observable names

virtual bool **hasExpressionNames()** const

Report whether the model has expression names set.

Returns Boolean indicating whether expression names were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getExpressionNames()** const

Get names of the expressions.

Returns Expression names

virtual bool **hasParameterIds()** const

Report whether the model has parameter IDs set.

Returns Boolean indicating whether parameter IDs were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getParameterIds()** const

Get IDs of the model parameters.

Returns Parameter IDs

virtual bool **hasStateIds()** const

Report whether the model has state IDs set.

Returns Boolean indicating whether state IDs were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getStateIds()** const

Get IDs of the model states.

Returns State IDs

virtual std::vector<std::string> **getStateIdsSolver()** const

Get IDs of the solver states.

Returns State IDs

virtual bool **hasFixedParameterIds()** const

Report whether the model has fixed parameter IDs set.

Returns Boolean indicating whether fixed parameter IDs were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getFixedParameterIds()** const

Get IDs of the fixed model parameters.

Returns Fixed parameter IDs

virtual bool **hasObservableIds()** const

Report whether the model has observable IDs set.

Returns Boolean indicating whether observable ids were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getObservableIds()** const

Get IDs of the observables.

Returns Observable IDs

virtual bool **hasExpressionIds()** const

Report whether the model has expression IDs set.

Returns Boolean indicating whether expression ids were set. Also returns `true` if the number of corresponding variables is just zero.

virtual std::vector<std::string> **getExpressionIds()** const

Get IDs of the expression.

Returns Expression IDs

virtual bool **hasQuadraticLLH()** const

Checks whether the defined noise model is gaussian, i.e., the nllh is quadratic.

Returns boolean flag

`std::vector<realtype> const &getTimepoints() const`

Get the timepoint vector.

Returns Timepoint vector

`realtype getTimepoint(int it) const`

Get simulation timepoint for time index `it`.

Parameters `it` – Time index

Returns Timepoint

`void setTimepoints(std::vector<realtype> const &ts)`

Set the timepoint vector.

Parameters `ts` – New timepoint vector

`double t0() const`

Get simulation start time.

Returns Simulation start time

`void setT0(double t0)`

Set simulation start time.

Parameters `t0` – Simulation start time

`std::vector<bool> const &getStateIsNonNegative() const`

Get flags indicating whether states should be treated as non-negative.

Returns Vector of flags

`void setStateIsNonNegative(std::vector<bool> const &stateIsNonNegative)`

Set flags indicating whether states should be treated as non-negative.

Parameters `stateIsNonNegative` – Vector of flags

`void setAllStatesNonNegative()`

Set flags indicating that all states should be treated as non-negative.

`inline ModelState const &getModelState() const`

Get the current model state.

Returns Current model state

`inline void setModelState(ModelState const &state)`

Set the current model state.

Parameters `state` – *Model* state

`inline void setMinimumSigmaResiduals(double min_sigma)`

Sets the estimated lower boundary for `sigma_y`. When `:meth:setAddSigmaResiduals` is activated, this lower boundary must ensure that $\log(\text{sigma}) + \text{min_sigma} > 0$.

Parameters `min_sigma` – lower boundary

`inline realtype getMinimumSigmaResiduals() const`

Gets the specified estimated lower boundary for `sigma_y`.

Returns lower boundary

`inline void setAddSigmaResiduals(bool sigma_res)`

Specifies whether residuals should be added to account for parameter dependent sigma.

If set to true, additional residuals of the form $\sqrt{\log(\sigma) + C}$ will be added. This enables least-squares optimization for variables with Gaussian noise assumption and parameter dependent standard deviation sigma. The constant C can be set via `:meth:setMinimumSigmaResiduals`.

Parameters `sigma_res` – if true, additional residuals are added

inline bool `getAddSigmaResiduals()` const

Checks whether residuals should be added to account for parameter dependent sigma.

Returns `sigma_res`

std::vector<int> const &`getParameterList()` const

Get the list of parameters for which sensitivities are computed.

Returns List of parameter indices

int `plist`(int pos) const

Get entry in parameter list by index.

Parameters `pos` – Index in sensitivity parameter list

Returns Index in parameter list

void `setParameterList`(std::vector<int> const &plist)

Set the list of parameters for which sensitivities are to be computed.

NOTE: Resets initial state sensitivities.

Parameters `plist` – List of parameter indices

std::vector<realtype> `getInitialStates()`

Get the initial states.

Returns Initial state vector

void `setInitialStates`(std::vector<realtype> const &x0)

Set the initial states.

Parameters `x0` – Initial state vector

bool `hasCustomInitialStates()` const

Return whether custom initial states have been set.

Returns true if has custom initial states, otherwise false

std::vector<realtype> `getInitialStateSensitivities()`

Get the initial states sensitivities.

Returns vector of initial state sensitivities

void `setInitialStateSensitivities`(std::vector<realtype> const &sx0)

Set the initial state sensitivities.

Parameters `sx0` – vector of initial state sensitivities with chainrule applied. This could be a slice of `ReturnData::sx` or `ReturnData::sx0`

bool `hasCustomInitialStateSensitivities()` const

Return whether custom initial state sensitivities have been set.

Returns true if has custom initial state sensitivities, otherwise false.

void `setUnscaledInitialStateSensitivities`(std::vector<realtype> const &sx0)

Set the initial state sensitivities.

Parameters `sx0` – Vector of initial state sensitivities without chainrule applied. This could be the readin from a `model.sx0data` saved to HDF5.

void **setSteadyStateSensitivityMode**(*SteadyStateSensitivityMode* mode)

Set the mode how sensitivities are computed in the steadystate simulation.

Parameters **mode** – Steadystate sensitivity mode

SteadyStateSensitivityMode **getSteadyStateSensitivityMode**() const

Gets the mode how sensitivities are computed in the steadystate simulation.

Returns Mode

void **setReinitializeFixedParameterInitialStates**(bool flag)

Set whether initial states depending on fixed parameters are to be reinitialized after preequilibration and presimulation.

Parameters **flag** – Fixed parameters reinitialized?

bool **getReinitializeFixedParameterInitialStates**() const

Get whether initial states depending on fixedParameters are to be reinitialized after preequilibration and presimulation.

Returns flag true / false

void **requireSensitivitiesForAllParameters**()

Require computation of sensitivities for all parameters p [0..np[in natural order.

NOTE: Resets initial state sensitivities.

void **getExpression**(gsl::span<*realtype*> w, const *realtype* t, const *AmiVector* &x)

Get time-resolved w.

Parameters

- **w** – Buffer (shape nw)
- **t** – Current timepoint
- **x** – Current state

void **getObservable**(gsl::span<*realtype*> y, const *realtype* t, const *AmiVector* &x)

Get time-resolved observables.

Parameters

- **y** – Buffer (shape ny)
- **t** – Current timepoint
- **x** – Current state

virtual *ObservableScaling* **getObservableScaling**(int iy) const

Get scaling type for observable.

Parameters **iy** – observable index

Returns scaling type

void **getObservableSensitivity**(gsl::span<*realtype*> sy, const *realtype* t, const *AmiVector* &x, const *AmiVectorArray* &sx)

Get sensitivity of time-resolved observables.

Total derivative $sy = dydx * sx + dydp$ (only for forward sensitivities).

Parameters

- **sy** – buffer (shape ny x nplist, row-major)
- **t** – Timepoint

- **x** – State variables
- **sx** – State sensitivities

void **getObservableSigma**(gsl::span<*realtype*> sigmay, const int it, const *ExpData* *edata)
Get time-resolved observable standard deviations.

Parameters

- **sigmay** – Buffer (shape ny)
- **it** – Timepoint index
- **edata** – Pointer to experimental data instance (optional, pass nullptr to ignore)

void **getObservableSigmaSensitivity**(gsl::span<*realtype*> ssigmay, gsl::span<const *realtype*> sy, const int it, const *ExpData* *edata)

Sensitivity of time-resolved observable standard deviation.

Total derivative (can be used with both adjoint and forward sensitivity).

Parameters

- **ssigmay** – Buffer (shape ny x nplist, row-major)
- **sy** – Sensitivity of time-resolved observables for current timepoint
- **it** – Timepoint index
- **edata** – Pointer to experimental data instance (optional, pass nullptr to ignore)

void **addObservableObjective**(*realtype* &Jy, const int it, const *AmiVector* &x, const *ExpData* &edata)
Add time-resolved measurement negative log-likelihood J_y .

Parameters

- **Jy** – Buffer (shape 1)
- **it** – Timepoint index
- **x** – State variables
- **edata** – Experimental data

void **addObservableObjectiveSensitivity**(std::vector<*realtype*> &s1lh, std::vector<*realtype*> &s2lh, const int it, const *AmiVector* &x, const *AmiVectorArray* &sx, const *ExpData* &edata)

Add sensitivity of time-resolved measurement negative log-likelihood J_y .

Parameters

- **s1lh** – First-order buffer (shape nplist)
- **s2lh** – Second-order buffer (shape nJ - 1 x nplist, row-major)
- **it** – Timepoint index
- **x** – State variables
- **sx** – State sensitivities
- **edata** – Experimental data

void **addPartialObservableObjectiveSensitivity**(std::vector<*realtype*> &s1lh, std::vector<*realtype*> &s2lh, const int it, const *AmiVector* &x, const *ExpData* &edata)

Add sensitivity of time-resolved measurement negative log-likelihood J_y .

Partial derivative (to be used with adjoint sensitivities).

Parameters

- **s1lh** – First order output buffer (shape `nplist`)
- **s2lh** – Second order output buffer (shape `nJ - 1 x nplist`, row-major)
- **it** – Timepoint index
- **x** – State variables
- **edata** – Experimental data

void **getAdjointStateObservableUpdate**(gsl::span<*realtype*> dJydx, const int it, const *AmiVector* &x, const *ExpData* &edata)

Get state sensitivity of the negative loglikelihood Jy , partial derivative (to be used with adjoint sensitivities).

Parameters

- **dJydx** – Output buffer (shape `nJ x nx_solver`, row-major)
- **it** – Timepoint index
- **x** – State variables
- **edata** – Experimental data instance

void **getEvent**(gsl::span<*realtype*> z, const int ie, const *realtype* t, const *AmiVector* &x)

Get event-resolved observables.

Parameters

- **z** – Output buffer (shape `nz`)
- **ie** – Event index
- **t** – Timepoint
- **x** – State variables

void **getEventSensitivity**(gsl::span<*realtype*> sz, const int ie, const *realtype* t, const *AmiVector* &x, const *AmiVectorArray* &sx)

Get sensitivities of event-resolved observables.

Total derivative (only forward sensitivities).

Parameters

- **sz** – Output buffer (shape `nz x nplist`, row-major)
- **ie** – Event index
- **t** – Timepoint
- **x** – State variables
- **sx** – State sensitivities

void **getUnobservedEventSensitivity**(gsl::span<*realtype*> sz, const int ie)

Get sensitivity of z at final timepoint.

Ignores sensitivity of timepoint. Total derivative.

Parameters

- **sz** – Output buffer (shape `nz x nplist`, row-major)

- **ie** – Event index

void **getEventRegularization**(gsl::span<*realtype*> rz, const int ie, const *realtype* t, const *AmiVector* &x)
Get regularization for event-resolved observables.

Parameters

- **rz** – Output buffer (shape nz)
- **ie** – Event index
- **t** – Timepoint
- **x** – State variables

void **getEventRegularizationSensitivity**(gsl::span<*realtype*> srz, const int ie, const *realtype* t, const *AmiVector* &x, const *AmiVectorArray* &sx)

Get sensitivities of regularization for event-resolved observables.

Total derivative. Only forward sensitivities.

Parameters

- **srz** – Output buffer (shape nz x nplist, row-major)
- **ie** – Event index
- **t** – Timepoint
- **x** – State variables
- **sx** – State sensitivities

void **getEventSigma**(gsl::span<*realtype*> sigmaz, const int ie, const int nroots, const *realtype* t, const *ExpData* *edata)

Get event-resolved observable standard deviations.

Parameters

- **sigmaz** – Output buffer (shape nz)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **edata** – Pointer to experimental data (optional, pass nullptr to ignore)

void **getEventSigmaSensitivity**(gsl::span<*realtype*> ssigmaz, const int ie, const int nroots, const *realtype* t, const *ExpData* *edata)

Get sensitivities of event-resolved observable standard deviations.

Total derivative (only forward sensitivities).

Parameters

- **ssigmaz** – Output buffer (shape nz x nplist, row-major)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **edata** – Pointer to experimental data (optional, pass nullptr to ignore)

void **addEventObjective**(*realtype* &Jz, const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Add event-resolved observable negative log-likelihood.

Parameters

- **Jz** – Output buffer (shape 1)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **x** – State variables
- **edata** – Experimental data

void **addEventObjectiveRegularization**(*realtype* &Jrz, const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Add event-resolved observable negative log-likelihood.

Parameters

- **Jrz** – Output buffer (shape 1)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **x** – State variables
- **edata** – Experimental data

void **addEventObjectiveSensitivity**(std::vector<*realtype*> &s1lh, std::vector<*realtype*> &s2lh, const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *AmiVectorArray* &sx, const *ExpData* &edata)

Add sensitivity of time-resolved measurement negative log-likelihood J_y .

Total derivative (to be used with forward sensitivities).

Parameters

- **s1lh** – First order buffer (shape nplist)
- **s2lh** – Second order buffer (shape nJ-1 x nplist, row-major)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **x** – State variables
- **sx** – State sensitivities
- **edata** – Experimental data

void **addPartialEventObjectiveSensitivity**(std::vector<*realtype*> &s1lh, std::vector<*realtype*> &s2lh, const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Add sensitivity of time-resolved measurement negative log-likelihood J_y .

Partial derivative (to be used with adjoint sensitivities).

Parameters

- **s1lh** – First order buffer (shape `nplist`)
- **s2lh** – Second order buffer (shape `(nJ-1) x nplist`, row-major)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **x** – State variables
- **edata** – Experimental data

void **getAdjointStateEventUpdate**(gsl::span<*realtype*> dJzdx, const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

State sensitivity of the negative loglikelihood Jz .

Partial derivative (to be used with adjoint sensitivities).

Parameters

- **dJzdx** – Output buffer (shape `nJ x nx_solver`, row-major)
- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Timepoint
- **x** – State variables
- **edata** – Experimental data

void **getEventTimeSensitivity**(std::vector<*realtype*> &stau, const *realtype* t, const int ie, const *AmiVector* &x, const *AmiVectorArray* &sx)

Sensitivity of event timepoint, total derivative.

Only forward sensitivities.

Parameters

- **stau** – Timepoint sensitivity (shape `nplist`)
- **t** – Timepoint
- **ie** – Event index
- **x** – State variables
- **sx** – State sensitivities

void **addStateEventUpdate**(*AmiVector* &x, const int ie, const *realtype* t, const *AmiVector* &xdot, const *AmiVector* &xdot_old)

Update state variables after event.

Parameters

- **x** – Current state (will be overwritten)
- **ie** – Event index
- **t** – Current timepoint
- **xdot** – Current residual function values
- **xdot_old** – Value of residual function before event

void **addStateSensitivityEventUpdate**(*AmiVectorArray* &sx, const int ie, const *realtype* t, const *AmiVector* &x_old, const *AmiVector* &xdot, const *AmiVector* &xdot_old, const std::vector<*realtype*> &stau)

Update state sensitivity after event.

Parameters

- **sx** – Current state sensitivity (will be overwritten)
- **ie** – Event index
- **t** – Current timepoint
- **x_old** – Current state
- **xdot** – Current residual function values
- **xdot_old** – Value of residual function before event
- **stau** – Timepoint sensitivity, to be computed with *Model::getEventTimeSensitivity*

void **addAdjointStateEventUpdate**(*AmiVector* &xB, const int ie, const *realtype* t, const *AmiVector* &x, const *AmiVector* &xdot, const *AmiVector* &xdot_old)

Update adjoint state after event.

Parameters

- **xB** – Current adjoint state (will be overwritten)
- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state
- **xdot** – Current residual function values
- **xdot_old** – Value of residual function before event

void **addAdjointQuadratureEventUpdate**(*AmiVector* xQB, const int ie, const *realtype* t, const *AmiVector* &x, const *AmiVector* &xB, const *AmiVector* &xdot, const *AmiVector* &xdot_old)

Update adjoint quadratures after event.

Parameters

- **xQB** – Current quadrature state (will be overwritten)
- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state
- **xB** – Current adjoint state
- **xdot** – Current residual function values
- **xdot_old** – Value of residual function before event

void **updateHeaviside**(const std::vector<int> &rootsfound)

Update the Heaviside variables **h** on event occurrences.

Parameters **rootsfound** – Provides the direction of the zero-crossing, so adding it will give the right update to the Heaviside variables (zero if no root was found)

void **updateHeavisideB**(const int *rootsfound)

Updates the Heaviside variables **h** on event occurrences in the backward problem.

Parameters **rootsfound** – Provides the direction of the zero-crossing, so adding it will give the right update to the Heaviside variables (zero if no root was found)

int **checkFinite**(gsl::span<const *realtype*> array, const char *fun) const

Check if the given array has only finite elements.

If not, try to give hints by which other fields this could be caused.

Parameters

- **array** – Array to check
- **fun** – Name of the function that generated the values (for more informative messages).

Returns amici::AMICI_RECOVERABLE_ERROR if a NaN/Inf value was found, amici::AMICI_SUCCESS otherwise

void **setAlwaysCheckFinite**(bool alwaysCheck)

Set whether the result of every call to `Model::f*` should be checked for finiteness.

Parameters **alwaysCheck** –

bool **getAlwaysCheckFinite**() const

Get setting of whether the result of every call to `Model::f*` should be checked for finiteness.

Returns that

void **fx0**(*AmiVector* &x)

Compute/get initial states.

Parameters **x** – Output buffer.

void **fx0_fixedParameters**(*AmiVector* &x)

Set only those initial states that are specified via fixed parameters.

Parameters **x** – Output buffer.

void **fsx0**(*AmiVectorArray* &sx, const *AmiVector* &x)

Compute/get initial value for initial state sensitivities.

Parameters

- **sx** – Output buffer for state sensitivities
- **x** – State variables

void **fsx0_fixedParameters**(*AmiVectorArray* &sx, const *AmiVector* &x)

Get only those initial states sensitivities that are affected from `amici::Model::fx0_fixedParameters`.

Parameters

- **sx** – Output buffer for state sensitivities
- **x** – State variables

virtual void **fsdx0**()

Compute sensitivity of derivative initial states sensitivities `sdx0`.

Only necessary for DAEs.

void **fx_rdata**(*AmiVector* &x_rdata, const *AmiVector* &x_solver)

Expand conservation law for states.

Parameters

- **x_rdata** – Output buffer for state variables with conservation laws expanded (stored in `amici::ReturnData`).

- **x_solver** – State variables with conservation laws applied (solver returns this)

void **fsx_rdata**(*AmiVectorArray* &sx_rdata, const *AmiVectorArray* &sx_solver, const *AmiVector* &x_solver)
Expand conservation law for state sensitivities.

Parameters

- **sx_rdata** – Output buffer for state variables sensitivities with conservation laws expanded (stored in *amici::ReturnData*).
- **sx_solver** – State variables sensitivities with conservation laws applied (solver returns this)
- **x_solver** – State variables with conservation laws applied (solver returns this)

void **setReinitializationStateIdxs**(const std::vector<int> &idxs)
Set indices of states to be reinitialized based on provided constants / fixed parameters.

Parameters **idxs** – Array of state indices

std::vector<int> const &**getReinitializationStateIdxs**() const
Return indices of states to be reinitialized based on provided constants / fixed parameters.

Returns Those indices.

const *AmiVectorArray* &**get_dxdotdp**() const
getter for dxdotdp (matlab generated)

Returns dxdotdp

const *SUNMatrixWrapper* &**get_dxdotdp_full**() const
getter for dxdotdp (python generated)

Returns dxdotdp

virtual void **fdeltaqB**(*realtype* *deltaqB, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, int ie, const *realtype* *xdot, const *realtype* *xdot_old, const *realtype* *xB)

Model-specific implementation of fdeltaqB.

Parameters

- **deltaqB** – sensitivity update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – sensitivity index
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **xB** – adjoint state

```
virtual void fdeltasx(realtype *deltasx, const realtype t, const realtype *x, const realtype *p, const realtype
                    *k, const realtype *h, const realtype *w, int ip, int ie, const realtype *xdot, const
                    realtype *xdot_old, const realtype *sx, const realtype *stau, const realtype *tcl)
```

Model-specific implementation of fdeltasx.

Parameters

- **deltasx** – sensitivity update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector
- **ip** – sensitivity index
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **sx** – state sensitivity
- **stau** – event-time sensitivity
- **tcl** – total abundances for conservation laws

```
virtual void fdeltax(realtype *deltax, const realtype t, const realtype *x, const realtype *p, const realtype *k,
                    const realtype *h, int ie, const realtype *xdot, const realtype *xdot_old)
```

Model-specific implementation of fdeltax.

Parameters

- **deltax** – state update
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side

```
virtual void fdeltaxB(realtype *deltaxB, const realtype t, const realtype *x, const realtype *p, const realtype
                    *k, const realtype *h, int ie, const realtype *xdot, const realtype *xdot_old, const
                    realtype *xB)
```

Model-specific implementation of fdeltaxB.

Parameters

- **deltaxB** – adjoint state update
- **t** – current time

- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ie** – event index
- **xdot** – new model right hand side
- **xdot_old** – previous model right hand side
- **xB** – current adjoint state

virtual void **fdJrzdsigma**(*realtype* *dJrzdsigma, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *rz, const *realtype* *sigmaz)

Model-specific implementation of fdJrzdsigma.

Parameters

- **dJrzdsigma** – Sensitivity of event penalization Jrz w.r.t. standard deviation sigmaz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **rz** – model root output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fdJrzdz**(*realtype* *dJrzdz, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *rz, const *realtype* *sigmaz)

Model-specific implementation of fdJrzdz.

Parameters

- **dJrzdz** – partial derivative of event penalization Jrz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **rz** – model root output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fdJydsigma**(*realtype* *dJydsigma, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fdJydsigma.

Parameters

- **dJydsigma** – Sensitivity of time-resolved measurement negative log-likelihood Jy w.r.t. standard deviation sigmay
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint

- **sigmay** – measurement standard deviation at timepoint
- **my** – measurement at timepoint

virtual void **fdJydy**(*realtype* *dJydy, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fdJydy.

Parameters

- **dJydy** – partial derivative of time-resolved measurement negative log-likelihood Jy
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint
- **sigmay** – measurement standard deviation at timepoint
- **my** – measurement at timepoint

virtual void **fdJydy_colptrs**(*SUNMatrixWrapper* &dJydy, int index)

Model-specific implementation of fdJydy colptrs.

Parameters

- **dJydy** – sparse matrix to which colptrs will be written
- **index** – ytrue index

virtual void **fdJydy_rowvals**(*SUNMatrixWrapper* &dJydy, int index)

Model-specific implementation of fdJydy rowvals.

Parameters

- **dJydy** – sparse matrix to which rowvals will be written
- **index** – ytrue index

virtual void **fdJzdsigma**(*realtype* *dJzdsigma, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fdJzdsigma.

Parameters

- **dJzdsigma** – Sensitivity of event measurement negative log-likelihood Jz w.r.t. standard deviation sigma_z
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurement at timepoint

virtual void **fdJzdz**(*realtype* *dJzdz, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fdJzdz.

Parameters

- **dJzdz** – partial derivative of event measurement negative log-likelihood Jz
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurement at timepoint

virtual void **fdrzdp**(*realtype* *drzdp, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip)

Model-specific implementation of fdrzdp.

Parameters

- **drzdp** – partial derivative of root output rz w.r.t. model parameters p
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested

virtual void **fdrzdx**(*realtype* *drzdx, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of fdrzdx.

Parameters

- **drzdx** – partial derivative of root output rz w.r.t. model states x
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fdsigmaydp**(*realtype* *dsigmaydp, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y, int ip)

Model-specific implementation of fdsigmaydp.

Parameters

- **dsigmaydp** – partial derivative of standard deviation of measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector

- **y** – model output at timepoint **t**
- **ip** – sensitivity index

virtual void **fdsigmaydy**(*realtype* *dsigmaydy, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y)

Model-specific implementation of fsigmay.

Parameters

- **dsigmaydy** – partial derivative of standard deviation of measurements w.r.t. model outputs
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint **t**

virtual void **fdsigmazdp**(*realtype* *dsigmazdp, const *realtype* t, const *realtype* *p, const *realtype* *k, int ip)

Model-specific implementation of fsigmaz.

Parameters

- **dsigmazdp** – partial derivative of standard deviation of event measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index

virtual void **fdwdp**(*realtype* *dwdp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl, const *realtype* *stcl)

Model-specific sparse implementation of dwdp.

Parameters

- **dwdp** – Recurring terms in xdot, parameter derivative
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws
- **stcl** – sensitivities of total abundances for conservation laws

virtual void **fdwdp**(*realtype* *dwdp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl, const *realtype* *stcl, int ip)

Model-specific sensitivity implementation of dwdp.

Parameters

- **dwdp** – Recurring terms in xdot, parameter derivative
- **t** – timepoint

- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws
- **stcl** – sensitivities of total abundances for conservation laws
- **ip** – sensitivity parameter index

virtual void **fdwdp_colptrs**(*SUNMatrixWrapper* &dwdp)

Model-specific implementation for dwdp, column pointers.

Parameters **dwdp** – sparse matrix to which colptrs will be written

virtual void **fdwdp_rowvals**(*SUNMatrixWrapper* &dwdp)

Model-specific implementation for dwdp, row values.

Parameters **dwdp** – sparse matrix to which rowvals will be written

virtual void **fdwdx**(*realtype* *dwdx, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl)

Model-specific implementation of dwdx, data part.

Parameters

- **dwdx** – Recurring terms in xdot, state derivative
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – total abundances for conservation laws

virtual void **fdwdx_colptrs**(*SUNMatrixWrapper* &dwdx)

Model-specific implementation for dwdx, column pointers.

Parameters **dwdx** – sparse matrix to which colptrs will be written

virtual void **fdwdx_rowvals**(*SUNMatrixWrapper* &dwdx)

Model-specific implementation for dwdx, row values.

Parameters **dwdx** – sparse matrix to which rowvals will be written

virtual void **fdwdw**(*realtype* *dwdw, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *tcl)

Model-specific implementation of fdwdw, no w chainrule (Py)

Parameters

- **dwdw** – partial derivative w wrt w
- **t** – timepoint
- **x** – Vector with the states

- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **tcl** – Total abundances for conservation laws

virtual void **fdwdw_colptrs**(*SUNMatrixWrapper* &dwdw)

Model-specific implementation of fdwdw, colptrs part.

Parameters **dwdw** – sparse matrix to which colptrs will be written

virtual void **fdwdw_rowvals**(*SUNMatrixWrapper* &dwdw)

Model-specific implementation of fdwdw, rowvals part.

Parameters **dwdw** – sparse matrix to which rowvals will be written

virtual void **fdydp**(*realtype* *dydp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, int ip, const *realtype* *w, const *realtype* *dwdp)

Model-specific implementation of fdydp (MATLAB-only)

Parameters

- **dydp** – partial derivative of observables y w.r.t. model parameters p
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested
- **w** – repeating elements vector
- **dwdp** – Recurring terms in xdot, parameter derivative

virtual void **fdydp**(*realtype* *dydp, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
const *realtype* *h, int ip, const *realtype* *w, const *realtype* *tcl, const *realtype* *dtcldp)

Model-specific implementation of fdydp (Python)

Parameters

- **dydp** – partial derivative of observables y w.r.t. model parameters p
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested
- **w** – repeating elements vector
- **tcl** – total abundances for conservation laws
- **dtcldp** – Sensitivities of total abundances for conservation laws

virtual void **fdydx**(*realtype* *dydx, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *dwdx)

Model-specific implementation of fdydx.

Parameters

- **dydx** – partial derivative of observables y w.r.t. model states x
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector
- **dwdx** – Recurring terms in xdot, state derivative

virtual void **fdzdp**(*realtype* *dzdp, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip)

Model-specific implementation of fdzdp.

Parameters

- **dzdp** – partial derivative of event-resolved output z w.r.t. model parameters p
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector
- **ip** – parameter index w.r.t. which the derivative is requested

virtual void **fdzdx**(*realtype* *dzdx, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of fdzdx.

Parameters

- **dzdx** – partial derivative of event-resolved output z w.r.t. model states x
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fJrz**(*realtype* *nllh, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz)

Model-specific implementation of fJrz.

Parameters

- **nllh** – regularization for event measurements z
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint

virtual void **fJy**(*realtype* *nllh, int iy, const *realtype* *p, const *realtype* *k, const *realtype* *y, const *realtype* *sigmay, const *realtype* *my)

Model-specific implementation of fJy.

Parameters

- **nllh** – negative log-likelihood for measurements y
- **iy** – output index
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint
- **sigmay** – measurement standard deviation at timepoint
- **my** – measurements at timepoint

virtual void **fJz**(*realtype* *nllh, int iz, const *realtype* *p, const *realtype* *k, const *realtype* *z, const *realtype* *sigmaz, const *realtype* *mz)

Model-specific implementation of fJz.

Parameters

- **nllh** – negative log-likelihood for event measurements z
- **iz** – event output index
- **p** – parameter vector
- **k** – constant vector
- **z** – model event output at timepoint
- **sigmaz** – event measurement standard deviation at timepoint
- **mz** – event measurements at timepoint

virtual void **frz**(*realtype* *rz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of frz.

Parameters

- **rz** – value of root function at current timepoint (non-output events not included)
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector

- **h** – Heaviside vector

virtual void **fsigmay**(*realtype* *sigmay, const *realtype* t, const *realtype* *p, const *realtype* *k, const *realtype* *y)

Model-specific implementation of fsigmay.

Parameters

- **sigmay** – standard deviation of measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector
- **y** – model output at timepoint t

virtual void **fsigmaz**(*realtype* *sigmaz, const *realtype* t, const *realtype* *p, const *realtype* *k)

Model-specific implementation of fsigmaz.

Parameters

- **sigmaz** – standard deviation of event measurements
- **t** – current time
- **p** – parameter vector
- **k** – constant vector

virtual void **fsrz**(*realtype* *srz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *sx, int ip)

Model-specific implementation of fsrz.

Parameters

- **srz** – Sensitivity of rz, total derivative
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **sx** – current state sensitivity
- **h** – Heaviside vector
- **ip** – sensitivity index

virtual void **fstau**(*realtype* *stau, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *tcl, const *realtype* *sx, int ip, int ie)

Model-specific implementation of fstau.

Parameters

- **stau** – total derivative of event timepoint
- **t** – current time
- **x** – current state
- **p** – parameter vector

- **k** – constant vector
- **h** – Heaviside vector
- **tc1** – total abundances for conservation laws
- **sx** – current state sensitivity
- **ip** – sensitivity index
- **ie** – event index

virtual void **fsx0**(*realtype* *sx0, const *realtype* t, const *realtype* *x0, const *realtype* *p, const *realtype* *k, int ip)

Model-specific implementation of fsx0.

Parameters

- **sx0** – initial state sensitivities
- **t** – initial time
- **x0** – initial state
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index

virtual void **fsx0_fixedParameters**(*realtype* *sx0, const *realtype* t, const *realtype* *x0, const *realtype* *p, const *realtype* *k, int ip, gsl::span<const int> reinitialization_state_idx)

Model-specific implementation of fsx0_fixedParameters.

Parameters

- **sx0** – initial state sensitivities
- **t** – initial time
- **x0** – initial state
- **p** – parameter vector
- **k** – constant vector
- **ip** – sensitivity index
- **reinitialization_state_idx** – Indices of states to be reinitialized based on provided constants / fixed parameters.

virtual void **fsz**(*realtype* *sz, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *sx, int ip)

Model-specific implementation of fsz.

Parameters

- **sz** – Sensitivity of rz, total derivative
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector

- **h** – Heaviside vector
- **sx** – current state sensitivity
- **ip** – sensitivity index

virtual void **fw**(*realtype* *w, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *tcl)

Model-specific implementation of fw.

Parameters

- **w** – Recurring terms in xdot
- **t** – timepoint
- **x** – vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **tcl** – total abundances for conservation laws

virtual void **fx0**(*realtype* *x0, const *realtype* t, const *realtype* *p, const *realtype* *k)

Model-specific implementation of fx0.

Parameters

- **x0** – initial state
- **t** – initial time
- **p** – parameter vector
- **k** – constant vector

virtual void **fx0_fixedParameters**(*realtype* *x0, const *realtype* t, const *realtype* *p, const *realtype* *k, gsl::span<const int> reinitialization_state_idx)

Model-specific implementation of fx0_fixedParameters.

Parameters

- **x0** – initial state
- **t** – initial time
- **p** – parameter vector
- **k** – constant vector
- **reinitialization_state_idx** – Indices of states to be reinitialized based on provided constants / fixed parameters.

virtual void **fy**(*realtype* *y, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w)

Model-specific implementation of fy.

Parameters

- **y** – model output at current timepoint
- **t** – current time
- **x** – current state
- **p** – parameter vector

- **k** – constant vector
- **h** – Heaviside vector
- **w** – repeating elements vector

virtual void **fz**(*realtype* *z, int ie, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h)

Model-specific implementation of fz.

Parameters

- **z** – value of event output
- **ie** – event index
- **t** – current time
- **x** – current state
- **p** – parameter vector
- **k** – constant vector
- **h** – Heaviside vector

virtual void **fdx_rdatadx_solver**(*realtype* *dx_rdatadx_solver, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k)

Compute dx_rdata / dx_solver.

Parameters

- **dx_rdatadx_solver** – dx_rdata / dx_solver
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws

virtual void **fdx_rdatadx_solver_colptrs**(*SUNMatrixWrapper* &dx_rdatadx_solver)

Model-specific implementation of fdx_rdatadx_solver, colptrs part.

Parameters dx_rdatadx_solver – sparse matrix to which colptrs will be written

virtual void **fdx_rdatadx_solver_rowvals**(*SUNMatrixWrapper* &dx_rdatadx_solver)

Model-specific implementation of fdx_rdatadx_solver, rowvals part.

Parameters dx_rdatadx_solver – sparse matrix to which rowvals will be written

virtual void **fdx_rdatadp**(*realtype* *dx_rdatadp, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k, const int ip)

Compute dx_rdata / dp.

Parameters

- **dx_rdatadp** – dx_rdata / dp
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws
- **ip** – Sensitivity index

virtual void **fdx_rdatadtcl**(*realtype* *dx_rdatadtcl, const *realtype* *x, const *realtype* *tcl, const *realtype* *p, const *realtype* *k)

Compute dx_rdata / dtcl.

Parameters

- **dx_rdatadtcl** – dx_rdata / dtcl
- **p** – parameter vector
- **k** – constant vector
- **x** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws

virtual void **fdx_rdatadtcl_colptrs**(*SUNMatrixWrapper* &dx_rdatadtcl)

Model-specific implementation of fdx_rdatadtcl, colptrs part.

Parameters dx_rdatadtcl – sparse matrix to which colptrs will be written

virtual void **fdx_rdatadtcl_rowvals**(*SUNMatrixWrapper* &dx_rdatadtcl)

Model-specific implementation of fdx_rdatadtcl, rowvals part.

Parameters dx_rdatadtcl – sparse matrix to which rowvals will be written

virtual void **fdtotal_cldx_rdata**(*realtype* *dtotal_cldx_rdata, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k, const *realtype* *tcl)

Compute dtotal_cl / dx_rdata.

Parameters

- **dtotal_cldx_rdata** – dtotal_cl / dx_rdata
- **x_rdata** – State variables with conservation laws applied
- **p** – parameter vector
- **k** – constant vector
- **tcl** – Total abundances for conservation laws

virtual void **fdtotal_cldx_rdata_colptrs**(*SUNMatrixWrapper* &dtotal_cldx_rdata)

Model-specific implementation of fdtotal_cldx_rdata, colptrs part.

Parameters dtotal_cldx_rdata – sparse matrix to which colptrs will be written

virtual void **fdtotal_cldx_rdata_rowvals**(*SUNMatrixWrapper* &dtotal_cldx_rdata)

Model-specific implementation of fdtotal_cldx_rdata, rowvals part.

Parameters dtotal_cldx_rdata – sparse matrix to which rowvals will be written

virtual void **fdtotal_cldp**(*realtype* *dtotal_cldp, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k, const int ip)

Compute dtotal_cl / dp.

Parameters

- **dtotal_cldp** – dtotal_cl / dp
- **x_rdata** – State variables with conservation laws applied
- **p** – parameter vector
- **k** – constant vector
- **ip** – Sensitivity index

Public Members

bool **pythonGenerated**

Flag indicating Matlab- or Python-based model generation

SecondOrderMode **o2mode** = {*SecondOrderMode::none*}

Flag indicating whether for `amici::Solver::sensi_ == amici::SensitivityOrder::second` directional or full second order derivative will be computed

std::vector<*realtype*> **idlist**

Flag array for DAE equations

AmiciApplication ***app** = &*defaultContext*

AMICI application context

Protected Functions

void **writeSliceEvent**(gsl::span<const *realtype*> slice, gsl::span<*realtype*> buffer, const int ie)

Write part of a slice to a buffer according to indices specified in `z2event`.

Parameters

- **slice** – Input data slice
- **buffer** – Output data slice
- **ie** – Event index

void **writeSensitivitySliceEvent**(gsl::span<const *realtype*> slice, gsl::span<*realtype*> buffer, const int ie)

Write part of a sensitivity slice to a buffer according to indices specified in `z2event`.

Parameters

- **slice** – source data slice
- **buffer** – output data slice
- **ie** – event index

void **writeLLHSensitivitySlice**(const std::vector<*realtype*> &dLLhdp, std::vector<*realtype*> &s1lh, std::vector<*realtype*> &s2llh)

Separate first and second order objective sensitivity information and write them into the respective buffers.

Parameters

- **dLLhdp** – Data with mangled first- and second-order information
- **s1lh** – First order buffer
- **s2llh** – Second order buffer

void **checkLLHBufferSize**(const std::vector<*realtype*> &s1lh, const std::vector<*realtype*> &s2llh) const

Verify that the provided buffers have the expected size.

Parameters

- **s1lh** – first order buffer
- **s2llh** – second order buffer

void **initializeVectors**()

Set the nplist-dependent vectors to their proper sizes.

void **fy**(*realtype* t, const *AmiVector* &x)

Compute observables / measurements.

Parameters

- **t** – Current timepoint
- **x** – Current state

void **fdydp**(*realtype* t, const *AmiVector* &x)

Compute partial derivative of observables y w.r.t. model parameters p .

Parameters

- **t** – Current timepoint
- **x** – Current state

void **fdydx**(*realtype* t, const *AmiVector* &x)

Compute partial derivative of observables y w.r.t. state variables x .

Parameters

- **t** – Current timepoint
- **x** – Current state

void **fsigmay**(int it, const *ExpData* *edata)

Compute standard deviation of measurements.

Parameters

- **it** – Timepoint index
- **edata** – Experimental data

void **fdsigmaydp**(int it, const *ExpData* *edata)

Compute partial derivative of standard deviation of measurements w.r.t. model parameters.

Parameters

- **it** – Timepoint index
- **edata** – pointer to *amici::ExpData* data instance holding sigma values

void **fdsigmaydy**(int it, const *ExpData* *edata)

Compute partial derivative of standard deviation of measurements w.r.t. model outputs.

Parameters

- **it** – Timepoint index
- **edata** – pointer to *amici::ExpData* data instance holding sigma values

void **fJy**(*realtype* &Jy, int it, const *AmiVector* &y, const *ExpData* &edata)

Compute negative log-likelihood of measurements y .

Parameters

- **Jy** – Variable to which llh will be added
- **it** – Timepoint index
- **y** – Simulated observable
- **edata** – Pointer to experimental data instance

void **fdJydy**(int it, const *AmiVector* &x, const *ExpData* &edata)

Compute partial derivative of time-resolved measurement negative log-likelihood J_y .

Parameters

- **it** – timepoint index
- **x** – state variables
- **edata** – Pointer to experimental data

void **fdJydsigma**(int it, const *AmiVector* &x, const *ExpData* &edata)

Sensitivity of time-resolved measurement negative log-likelihood J_y w.r.t. standard deviation sigma.

Parameters

- **it** – timepoint index
- **x** – state variables
- **edata** – pointer to experimental data instance

void **fdJydp**(const int it, const *AmiVector* &x, const *ExpData* &edata)

Compute sensitivity of time-resolved measurement negative log-likelihood J_y w.r.t. parameters for the given timepoint.

Parameters

- **it** – timepoint index
- **x** – state variables
- **edata** – pointer to experimental data instance

void **fdJydx**(const int it, const *AmiVector* &x, const *ExpData* &edata)

Sensitivity of time-resolved measurement negative log-likelihood J_y w.r.t. state variables.

Parameters

- **it** – Timepoint index
- **x** – State variables
- **edata** – Pointer to experimental data instance

void **fz**(int ie, *realtype* t, const *AmiVector* &x)

Compute event-resolved output.

Parameters

- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state

void **fdzdp**(int ie, *realtype* t, const *AmiVector* &x)

Compute partial derivative of event-resolved output z w.r.t. model parameters p

Parameters

- **ie** – event index
- **t** – current timepoint
- **x** – current state

void **fdzdx**(int ie, *realtype* t, const *AmiVector* &x)

Compute partial derivative of event-resolved output z w.r.t. model states x.

Parameters

- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state

void **frz**(int ie, *realtype* t, const *AmiVector* &x)

Compute event root function of events.

Equal to *Model::froot* but does not include non-output events.

Parameters

- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state

void **fdrzdp**(int ie, *realtype* t, const *AmiVector* &x)

Compute sensitivity of event-resolved root output w.r.t. model parameters p.

Parameters

- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state

void **fdrzdx**(int ie, *realtype* t, const *AmiVector* &x)

Compute sensitivity of event-resolved measurements *rz* w.r.t. model states **x**.

Parameters

- **ie** – Event index
- **t** – Current timepoint
- **x** – Current state

void **fsigmaz**(const int ie, const int nroots, const *realtype* t, const *ExpData* *edata)

Compute standard deviation of events.

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **edata** – Experimental data

void **fdsigmazdp**(int ie, int nroots, *realtype* t, const *ExpData* *edata)

Compute sensitivity of standard deviation of events measurements w.r.t. model parameters p.

Parameters

- **ie** – Event index
- **nroots** – Event occurrence
- **t** – Current timepoint
- **edata** – Pointer to experimental data instance

void **fJz**(*realtype* &Jz, int nroots, const *AmiVector* &z, const *ExpData* &edata)

Compute negative log-likelihood of event-resolved measurements \mathbf{z} .

Parameters

- **Jz** – Variable to which llh will be added
- **nroots** – Event index
- **z** – Simulated event
- **edata** – Experimental data

void **fdJzdz**(const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Compute partial derivative of event measurement negative log-likelihood Jz .

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **x** – State variables
- **edata** – Experimental data

void **fdJzdsigma**(const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Compute sensitivity of event measurement negative log-likelihood Jz w.r.t. standard deviation σ_{maz} .

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **x** – State variables
- **edata** – Pointer to experimental data instance

void **fdJzdp**(const int ie, const int nroots, *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Compute sensitivity of event-resolved measurement negative log-likelihood Jz w.r.t. parameters.

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **x** – State variables
- **edata** – Pointer to experimental data instance

void **fdJzdx**(const int ie, const int nroots, *realtype* t, const *AmiVector* &x, const *ExpData* &edata)

Compute sensitivity of event-resolved measurement negative log-likelihood Jz w.r.t. state variables.

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **x** – State variables

- **edata** – Experimental data

void **fJrz**(*realtype* &Jrz, int nroots, const *AmiVector* &rz, const *ExpData* &edata)
 Compute regularization of negative log-likelihood with roots of event-resolved measurements rz.

Parameters

- **Jrz** – Variable to which regularization will be added
- **nroots** – Event index
- **rz** – Regularization variable
- **edata** – Experimental data

void **fdJrzd**(const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)
 Compute partial derivative of event measurement negative log-likelihood J.

Parameters

- **ie** – Event index
- **nroots** – Event index
- **t** – Current timepoint
- **x** – State variables
- **edata** – Experimental data

void **fdJrzdsigma**(const int ie, const int nroots, const *realtype* t, const *AmiVector* &x, const *ExpData* &edata)
 Compute sensitivity of event measurement negative log-likelihood Jz w.r.t. standard deviation sigma_z.

Parameters

- **ie** – event index
- **nroots** – event index
- **t** – current timepoint
- **x** – state variables
- **edata** – pointer to experimental data instance

void **fw**(*realtype* t, const *realtype* *x)
 Compute recurring terms in xdot.

Parameters

- **t** – Timepoint
- **x** – Array with the states

void **fdwdp**(*realtype* t, const *realtype* *x)
 Compute parameter derivative for recurring terms in xdot.

Parameters

- **t** – Timepoint
- **x** – Array with the states

void **fdwdx**(*realtype* t, const *realtype* *x)
 Compute state derivative for recurring terms in xdot.

Parameters

- **t** – Timepoint

- **x** – Array with the states

void **fdwdw**(*realtype* t, const *realtype* *x)

Compute self derivative for recurring terms in xdot.

Parameters

- **t** – Timepoint
- **x** – Array with the states

virtual void **fx_rdata**(*realtype* *x_rdata, const *realtype* *x_solver, const *realtype* *tcl, const *realtype* *p, const *realtype* *k)

Compute fx_rdata.

To be implemented by derived class if applicable.

Parameters

- **x_rdata** – State variables with conservation laws expanded
- **x_solver** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws
- **p** – parameter vector
- **k** – constant vector

virtual void **fsx_rdata**(*realtype* *sx_rdata, const *realtype* *sx_solver, const *realtype* *stcl, const *realtype* *p, const *realtype* *k, const *realtype* *x_solver, const *realtype* *tcl, const int ip)

Compute fsx_solver.

To be implemented by derived class if applicable.

Parameters

- **sx_rdata** – State sensitivity variables with conservation laws expanded
- **sx_solver** – State sensitivity variables with conservation laws applied
- **stcl** – Sensitivities of total abundances for conservation laws
- **p** – parameter vector
- **k** – constant vector
- **x_solver** – State variables with conservation laws applied
- **tcl** – Total abundances for conservation laws
- **ip** – Sensitivity index

virtual void **fx_solver**(*realtype* *x_solver, const *realtype* *x_rdata)

Compute fx_solver.

To be implemented by derived class if applicable.

Parameters

- **x_solver** – State variables with conservation laws applied
- **x_rdata** – State variables with conservation laws expanded

virtual void **fsx_solver**(*realtype* *sx_solver, const *realtype* *sx_rdata)

Compute fsx_solver.

To be implemented by derived class if applicable.

Parameters

- **sx_rdata** – State sensitivity variables with conservation laws expanded
- **sx_solver** – State sensitivity variables with conservation laws applied

virtual void **ftotal_cl**(*realtype* *total_cl, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k)
 Compute ftotal_cl.

To be implemented by derived class if applicable.

Parameters

- **total_cl** – Total abundances of conservation laws
- **x_rdata** – State variables with conservation laws expanded
- **p** – parameter vector
- **k** – constant vector

virtual void **fstotal_cl**(*realtype* *stotal_cl, const *realtype* *sx_rdata, const int ip, const *realtype* *x_rdata, const *realtype* *p, const *realtype* *k, const *realtype* *tcl)
 Compute fstotal_cl.

To be implemented by derived class if applicable.

Parameters

- **stotal_cl** – Sensitivities for the total abundances of conservation laws
- **sx_rdata** – State sensitivity variables with conservation laws expanded
- **ip** – Sensitivity index
- **x_rdata** – State variables with conservation laws expanded
- **p** – parameter vector
- **k** – constant vector
- **tcl** – Total abundances for conservation laws

const_N_Vector **computeX_pos**(*const_N_Vector* x)

Compute non-negative state vector.

Compute non-negative state vector according to stateIsNonNegative. If anyStateNonNegative is set to false, i.e., all entries in stateIsNonNegative are false, this function directly returns x, otherwise all entries of x are copied in to amici::Model::x_pos_tmp_ and negative values are replaced by 0 where applicable.

Parameters **x** – State vector possibly containing negative values

Returns State vector with negative values replaced by 0 according to stateIsNonNegative

const *realtype* ***computeX_pos**(*AmiVector* const &x)

Compute non-negative state vector.

Compute non-negative state vector according to stateIsNonNegative. If anyStateNonNegative is set to false, i.e., all entries in stateIsNonNegative are false, this function directly returns x, otherwise all entries of x are copied in to amici::Model::x_pos_tmp_ and negative values are replaced by 0 where applicable.

Parameters **x** – State vector possibly containing negative values

Returns State vector with negative values replaced by 0 according to stateIsNonNegative

Protected Attributes

ModelState **state_**

All variables necessary for function evaluation

ModelStateDerived **derived_state_**

Storage for model quantities beyond *ModelState* for the current timepoint

`std::vector<int>` **z2event_**

index indicating to which event an event output belongs

`std::vector<realtype>` **x0data_**

state initialization (size `nx_solver`)

`std::vector<realtype>` **sx0data_**

sensitivity initialization (size `nx_rdata` x `nplist`, row-major)

`std::vector<bool>` **state_is_non_negative_**

vector of bools indicating whether state variables are to be assumed to be positive

`bool` **any_state_non_negative_** = {false}

boolean indicating whether any entry in `stateIsNonNegative` is `true`

`int` **nmaxevent_** = {10}

maximal number of events to track

SteadyStateSensitivityMode **steadystate_sensitivity_mode_** =

{*SteadyStateSensitivityMode::newtonOnly*}

flag indicating whether steadystate sensitivities are to be computed via FSA when `steadyStateSimulation` is used

`bool` **always_check_finite_** = {false}

Indicates whether the result of every call to `Model::f*` should be checked for finiteness

`bool` **sigma_res_** = {false}

indicates whether sigma residuals are to be added for every datapoint

realtype **min_sigma_** = {50.0}

offset to ensure positivity of sigma residuals, only has an effect when `sigma_res_` is `true`

Friends

`template<class` **Archive**`>`

`friend void` **serialize**(*Archive* &ar, *Model* &m, unsigned int version)

Serialize *Model* (see `boost::serialization::serialize`).

Parameters

- **ar** – Archive to serialize to
- **m** – Data to serialize
- **version** – Version number

friend bool **operator==**(const *Model* &a, const *Model* &b)
 Check equality of data members.

Parameters

- **a** – First model instance
- **b** – Second model instance

Returns Equality

Class *Model_DAE*

- Defined in file_include_amici_model_dae.h

Inheritance Relationships

Base Type

- public amici::Model (*Class Model*)

Class Documentation

class amici::Model_DAE : public amici::Model

The *Model* class represents an AMICI DAE model.

The model does not contain any data, but represents the state of the model at a specific time t. The states must not always be in sync, but may be updated asynchronously.

Public Functions

Model_DAE() = default
 default constructor

inline **Model_DAE**(const *ModelDimensions* &model_dimensions, *SimulationParameters*
 simulation_parameters, const *SecondOrderMode* o2mode, std::vector<realtype> const
 &idlist, std::vector<int> const &z2event, const bool pythonGenerated = false, const int
 ndxdotdp_explicit = 0)

Constructor with model dimensions.

Parameters

- **model_dimensions** – *Model* dimensions
- **simulation_parameters** – Simulation parameters
- **o2mode** – second order sensitivity mode
- **idlist** – indexes indicating algebraic components (DAE only)
- **z2event** – mapping of event outputs to events
- **pythonGenerated** – flag indicating matlab or python wrapping
- **ndxdotdp_explicit** – number of nonzero elements dxdotdp_explicit

virtual void **fJ**(*realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) override
Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – dense matrix to which values of the jacobian will be written

void **fJ**(*realtype* t, *realtype* cj, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xdot, SUNMatrix J)
Jacobian of xdot with respect to states x.

Parameters

- **t** – timepoint
- **cj** – scaling factor, inverse of the step size
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xdot** – Vector with the right hand side
- **J** – Matrix to which the Jacobian will be written

virtual void **fJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) override
Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

void **fJB**(*realtype* t, *realtype* cj, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xB, *const_N_Vector* dxB, SUNMatrix JB)
Jacobian of xBdot with respect to adjoint state xB.

Parameters

- **t** – timepoint
- **cj** – scaling factor, inverse of the step size
- **x** – Vector with the states

- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **JB** – Matrix to which the Jacobian will be written

virtual void **fJSparse**(*realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) override

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – sparse matrix to which values of the Jacobian will be written

void **fJSparse**(*realtype* t, *realtype* cj, *const_N_Vector* x, *const_N_Vector* dx, SUNMatrix J)
J in sparse form (for sparse solvers from the SuiteSparse Package)

Parameters

- **t** – timepoint
- **cj** – scalar in Jacobian (inverse stepsize)
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **J** – Matrix to which the Jacobian will be written

virtual void **fJSparseB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) override

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

void **fJSparseB**(*realtype* t, *realtype* cj, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xB, *const_N_Vector* dxB, SUNMatrix JB)

JB in sparse form (for sparse solvers from the SuiteSparse Package)

Parameters

- **t** – timepoint
- **cj** – scalar in Jacobian
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **JB** – Matrix to which the Jacobian will be written

virtual void **fJDiag**(*realtype* t, *AmiVector* &JDiag, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx)
override

Diagonal of the Jacobian (for preconditioning)

Parameters

- **t** – timepoint
- **JDiag** – Vector to which the Jacobian diagonal will be written
- **cj** – scaling factor, inverse of the step size
- **x** – Vector with the states
- **dx** – Vector with the derivative states

virtual void **fJv**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, const *AmiVector* &v, *AmiVector* &nJv, *realtype* cj) override

Jacobian multiply function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **v** – multiplication vector (unused)
- **nJv** – array to which result of multiplication will be written
- **cj** – scaling factor (inverse of timestep, DAE only)

void **fJv**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* v, *N_Vector* Jv, *realtype* cj)
Matrix vector product of J with a vector v (for iterative solvers)

Parameters

- **t** – timepoint
- **cj** – scaling factor, inverse of the step size
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **v** – Vector with which the Jacobian is multiplied
- **Jv** – Vector to which the Jacobian vector product will be written

void **fJvB**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xB, *const_N_Vector* dxB, *const_N_Vector* vB, *N_Vector* JvB, *realtype* cj)

Matrix vector product of JB with a vector v (for iterative solvers)

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **vB** – Vector with which the Jacobian is multiplied
- **JvB** – Vector to which the Jacobian vector product will be written
- **cj** – scalar in Jacobian (inverse stepsize)

virtual void **froot**(*realtype* t, *const AmiVector* &x, *const AmiVector* &dx, *gsl::span<realtype>* root) override
Root function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **root** – array to which values of the root function will be written

void **froot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *gsl::span<realtype>* root)

Event trigger function for events.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **root** – array with root function values

virtual void **fxdot**(*realtype* t, *const AmiVector* &x, *const AmiVector* &dx, *AmiVector* &xdot) override
Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – array to which values of the residual function will be written

void **fxdot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *N_Vector* xdot)

Residual function of the DAE.

Parameters

- **t** – timepoint
- **x** – Vector with the states

- **dx** – Vector with the derivative states
- **xdot** – Vector with the right hand side

void **fxBdot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xB, *const_N_Vector* dxB, *N_Vector* xBdot)

Right hand side of differential equation for adjoint state xB.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side

void **fqBdot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, *const_N_Vector* xB, *const_N_Vector* dxB, *N_Vector* qBdot)

Right hand side of integral equation for quadrature states qB.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **qBdot** – Vector with the adjoint quadrature right hand side

virtual void **fxBdot_ss**(const *realtype* t, const *AmiVector* &xB, const *AmiVector* &dxB, *AmiVector* &xBdot)
override

Residual function backward when running in steady state mode.

Parameters

- **t** – time
- **xB** – adjoint state
- **dxB** – time derivative of state (DAE only)
- **xBdot** – array to which values of the residual function will be written

void **fxBdot_ss**(*realtype* t, *const_N_Vector* xB, *const_N_Vector* dxB, *N_Vector* xBdot) const
Implementation of fxBdot for steady state case at the *N_Vector* level.

Parameters

- **t** – timepoint
- **xB** – Vector with the adjoint state
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side

void **fqBdot_ss**(*realtype* t, *const_N_Vector* xB, *const_N_Vector* dxB, *N_Vector* qBdot) const
Implementation of fqBdot for steady state at the *N_Vector* level.

Parameters

- **t** – timepoint
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **qBdot** – Vector with the adjoint quadrature right hand side

virtual void **fJSparseB_ss**(SUNMatrix JB) override
 Sparse Jacobian function backward, steady state case.

Parameters JB – sparse matrix to which values of the Jacobian will be written

virtual void **writeSteadystateJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot) override

Computes the sparse backward Jacobian for steadystate integration and writes it to the model member.

Parameters

- **t** – timepoint
- **cj** – scalar in Jacobian
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint state right hand side

void **fdxdotdp**(*realtype* t, const *const_N_Vector* x, const *const_N_Vector* dx)
 Sensitivity of dx/dt wrt model parameters p.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states

inline virtual void **fdxdotdp**(const *realtype* t, const *AmiVector* &x, const *AmiVector* &dx) override
 Model-specific sparse implementation of explicit parameter derivative of right hand side.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)

virtual void **fsxdot**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, int ip, const *AmiVector* &sx, const *AmiVector* &sdx, *AmiVector* &sxdot) override
 Sensitivity Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)

- **ip** – parameter index
- **sx** – sensitivity state
- **sdx** – time derivative of sensitivity state (DAE only)
- **sxdot** – array to which values of the sensitivity residual function will be written

void **fsxdot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* dx, int ip, *const_N_Vector* sx, *const_N_Vector* sdx, *N_Vector* sxdot)

Right hand side of differential equation for state sensitivities sx.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **ip** – parameter index
- **sx** – Vector with the state sensitivities
- **sdx** – Vector with the derivative state sensitivities
- **sxdot** – Vector with the sensitivity right hand side

void **fm**(*realtype* t, *const_N_Vector* x)

Mass matrix for DAE systems.

Parameters

- **t** – timepoint
- **x** – Vector with the states

virtual std::unique_ptr<*Solver*> **getSolver**() override

Retrieves the solver object.

Returns The *Solver* instance

Protected Functions

virtual void **fJSparse**(SUNMatrixContent_Sparse JSparse, *realtype* t, const *realtype* *x, const double *p, const double *k, const *realtype* *h, *realtype* cj, const *realtype* *dx, const *realtype* *w, const *realtype* *dwdx) = 0

Model specific implementation for fJSparse.

Parameters

- **JSparse** – Matrix to which the Jacobian will be written
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **cj** – scaling factor, inverse of the step size
- **dx** – Vector with the derivative states

- **w** – vector with helper variables
- **dwdx** – derivative of w wrt x

virtual void **froot**(*realtype* *root, *realtype* t, const *realtype* *x, const double *p, const double *k, const *realtype* *h, const *realtype* *dx)

Model specific implementation for froot.

Parameters

- **root** – values of the trigger function
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **dx** – Vector with the derivative states

virtual void **fxdot**(*realtype* *xdot, *realtype* t, const *realtype* *x, const double *p, const double *k, const *realtype* *h, const *realtype* *dx, const *realtype* *w) = 0

Model specific implementation for fxdot.

Parameters

- **xdot** – residual function
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **dx** – Vector with the derivative states

virtual void **fdxdotdp**(*realtype* *dxdotdp, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, const *realtype* *dx, const *realtype* *w, const *realtype* *dwdp)

Model specific implementation of fdxdotdp.

Parameters

- **dxdotdp** – partial derivative xdot wrt p
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **ip** – parameter index
- **dx** – Vector with the derivative states
- **w** – vector with helper variables

- **dwdp** – derivative of w wrt p

virtual void **fM**(*realtype* *M, const *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k)
Model specific implementation of fM.

Parameters

- **M** – mass matrix
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector

Class Model_ODE

- Defined in file_include_amici_model_ode.h

Inheritance Relationships

Base Type

- public amici::Model (*Class Model*)

Class Documentation

class amici::Model_ODE : public amici::Model

The *Model* class represents an AMICI ODE model.

The model does not contain any data, but represents the state of the model at a specific time t . The states must not always be in sync, but may be updated asynchronously.

Public Functions

Model_ODE() = default

default constructor

inline **Model_ODE**(*ModelDimensions* const &model_dimensions, *SimulationParameters*
simulation_parameters, const *SecondOrderMode* o2mode, std::vector<*realtype*> const
&idlist, std::vector<int> const &z2event, const bool pythonGenerated = false, const int
ndxdotdp_explicit = 0, const int ndxdotdx_explicit = 0, const int w_recursion_depth = 0)

Constructor with model dimensions.

Parameters

- **model_dimensions** – *Model* dimensions
- **simulation_parameters** – Simulation parameters
- **o2mode** – second order sensitivity mode
- **idlist** – indexes indicating algebraic components (DAE only)
- **z2event** – mapping of event outputs to events

- **pythonGenerated** – flag indicating matlab or python wrapping
- **ndxdotdp_explicit** – number of nonzero elements dxdotdp_explicit
- **ndxdotdx_explicit** – number of nonzero elements dxdotdx_explicit
- **w_recursion_depth** – Recursion depth of fw

virtual void **fJ**(*realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) override

Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – dense matrix to which values of the jacobian will be written

void **fJ**(*realtype* t, *const_N_Vector* x, *const_N_Vector* xdot, SUNMatrix J)

Implementation of fJ at the N_Vector level.

This function provides an interface to the model specific routines for the solver implementation as well as the *AmiVector* level implementation

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xdot** – Vector with the right hand side
- **J** – Matrix to which the Jacobian will be written

virtual void **fJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) override

Dense Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

void **fJB**(*realtype* t, *const_N_Vector* x, *const_N_Vector* xB, *const_N_Vector* xBdot, SUNMatrix JB)

Implementation of fJB at the N_Vector level, this function provides an interface to the model specific routines for the solver implementation.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xB** – Vector with the adjoint states
- **xBdot** – Vector with the adjoint right hand side
- **JB** – Matrix to which the Jacobian will be written

virtual void **fJSparse**(*realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, SUNMatrix J) override

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **J** – sparse matrix to which values of the Jacobian will be written

void **fJSparse**(*realtype* t, *const_N_Vector* x, SUNMatrix J)

Implementation of fJSparse at the N_Vector level, this function provides an interface to the model specific routines for the solver implementation as well as the *AmiVector* level implementation.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **J** – Matrix to which the Jacobian will be written

virtual void **fJSparseB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot, SUNMatrix JB) override

Sparse Jacobian function.

Parameters

- **t** – time
- **cj** – scaling factor (inverse of timestep, DAE only)
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint right hand side (unused)
- **JB** – dense matrix to which values of the jacobian will be written

void **fJSparseB**(*realtype* t, *const_N_Vector* x, *const_N_Vector* xB, *const_N_Vector* xBdot, SUNMatrix JB)

Implementation of fJSparseB at the N_Vector level, this function provides an interface to the model specific routines for the solver implementation.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xB** – Vector with the adjoint states
- **xBdot** – Vector with the adjoint right hand side
- **JB** – Matrix to which the Jacobian will be written

void **fJDiag**(*realtype* t, N_Vector JDiag, *const_N_Vector* x)

Implementation of fJDiag at the N_Vector level, this function provides an interface to the model specific routines for the solver implementation.

Parameters

- **t** – timepoint
- **JDiag** – Vector to which the Jacobian diagonal will be written
- **x** – Vector with the states

virtual void **fJDiag**(*realtype* t, *AmiVector* &JDiag, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx) override

Diagonal of the Jacobian (for preconditioning)

Parameters

- **t** – timepoint
- **JDiag** – Vector to which the Jacobian diagonal will be written
- **cj** – scaling factor, inverse of the step size
- **x** – Vector with the states
- **dx** – Vector with the derivative states

virtual void **fJv**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xdot, const *AmiVector* &v, *AmiVector* &nJv, *realtype* cj) override

Jacobian multiply function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – values of residual function (unused)
- **v** – multiplication vector (unused)
- **nJv** – array to which result of multiplication will be written
- **cj** – scaling factor (inverse of timestep, DAE only)

void **fJv**(*const_N_Vector* v, N_Vector Jv, *realtype* t, *const_N_Vector* x)

Implementation of fJv at the N_Vector level.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **v** – Vector with which the Jacobian is multiplied

- **Jv** – Vector to which the Jacobian vector product will be written

void **fJvB**(*const_N_Vector* vB, *N_Vector* JvB, *realtype* t, *const_N_Vector* x, *const_N_Vector* xB)
Implementation of fJvB at the *N_Vector* level.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xB** – Vector with the adjoint states
- **vB** – Vector with which the Jacobian is multiplied
- **JvB** – Vector to which the Jacobian vector product will be written

virtual void **froot**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, gsl::span<*realtype*> root) override
Root function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **root** – array to which values of the root function will be written

void **froot**(*realtype* t, *const_N_Vector* x, gsl::span<*realtype*> root)
Implementation of froot at the *N_Vector* level This function provides an interface to the model specific routines for the solver implementation as well as the *AmiVector* level implementation.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **root** – array with root function values

virtual void **fxdot**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, *AmiVector* &xdot) override
Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **xdot** – array to which values of the residual function will be written

void **fxdot**(*realtype* t, *const_N_Vector* x, *N_Vector* xdot)
Implementation of fxdot at the *N_Vector* level, this function provides an interface to the model specific routines for the solver implementation as well as the *AmiVector* level implementation.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xdot** – Vector with the right hand side

void **fxBdot**(*realtype* t, *N_Vector* x, *N_Vector* xB, *N_Vector* xBdot)
Implementation of fxBdot at the *N_Vector* level.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xB** – Vector with the adjoint states
- **xBdot** – Vector with the adjoint right hand side

void **fqBdot**(*realtype* t, *const_N_Vector* x, *const_N_Vector* xB, *N_Vector* qBdot)

Implementation of fqBdot at the *N_Vector* level.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **xB** – Vector with the adjoint states
- **qBdot** – Vector with the adjoint quadrature right hand side

virtual void **fxBdot_ss**(const *realtype* t, const *AmiVector* &xB, const *AmiVector*&, *AmiVector* &xBdot) override

Residual function backward when running in steady state mode.

Parameters

- **t** – time
- **xB** – adjoint state
- **dxB** – time derivative of state (DAE only)
- **xBdot** – array to which values of the residual function will be written

void **fxBdot_ss**(*realtype* t, *const_N_Vector* xB, *N_Vector* xBdot) const

Implementation of fxBdot for steady state at the *N_Vector* level.

Parameters

- **t** – timepoint
- **xB** – Vector with the states
- **xBdot** – Vector with the adjoint right hand side

void **fqBdot_ss**(*realtype* t, *N_Vector* xB, *N_Vector* qBdot) const

Implementation of fqBdot for steady state case at the *N_Vector* level.

Parameters

- **t** – timepoint
- **xB** – Vector with the adjoint states
- **qBdot** – Vector with the adjoint quadrature right hand side

virtual void **fJSparseB_ss**(*SUNMatrix* JB) override

Sparse Jacobian function backward, steady state case.

Parameters **JB** – sparse matrix to which values of the Jacobian will be written

virtual void **writeSteadystateJB**(const *realtype* t, *realtype* cj, const *AmiVector* &x, const *AmiVector* &dx, const *AmiVector* &xB, const *AmiVector* &dxB, const *AmiVector* &xBdot) override

Computes the sparse backward Jacobian for steadystate integration and writes it to the model member.

Parameters

- **t** – timepoint
- **cj** – scalar in Jacobian
- **x** – Vector with the states
- **dx** – Vector with the derivative states
- **xB** – Vector with the adjoint states
- **dxB** – Vector with the adjoint derivative states
- **xBdot** – Vector with the adjoint state right hand side

virtual void **fsxdot**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx, int ip, const *AmiVector* &sx, const *AmiVector* &sdx, *AmiVector* &sxdot) override

Sensitivity Residual function.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)
- **ip** – parameter index
- **sx** – sensitivity state
- **sdx** – time derivative of sensitivity state (DAE only)
- **sxdot** – array to which values of the sensitivity residual function will be written

void **fsxdot**(*realtype* t, *const_N_Vector* x, int ip, *const_N_Vector* sx, *N_Vector* sxdot)

Implementation of fsxdot at the *N_Vector* level.

Parameters

- **t** – timepoint
- **x** – Vector with the states
- **ip** – parameter index
- **sx** – Vector with the state sensitivities
- **sxdot** – Vector with the sensitivity right hand side

virtual std::unique_ptr<*Solver*> **getSolver**() override

Retrieves the solver object.

Returns The *Solver* instance

Protected Functions

virtual void **fJSparse**(SUNMatrixContent_Sparse JSparse, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *dwdx)

Model specific implementation for fJSparse (Matlab)

Parameters

- **JSparse** – Matrix to which the Jacobian will be written
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **dwdx** – derivative of w wrt x

virtual void **fJSparse**(*realtype* *JSparse, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w, const *realtype* *dwdx)

Model specific implementation for fJSparse, data only (Py)

Parameters

- **JSparse** – Matrix to which the Jacobian will be written
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables
- **dwdx** – derivative of w wrt x

virtual void **fJSparse_colptrs**(SUNMatrixWrapper &JSparse)

Model specific implementation for fJSparse, column pointers.

Parameters **JSparse** – sparse matrix to which colptrs will be written

virtual void **fJSparse_rowvals**(SUNMatrixWrapper &JSparse)

Model specific implementation for fJSparse, row values.

Parameters **JSparse** – sparse matrix to which rowvals will be written

virtual void **froot**(*realtype* *root, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *tcl)

Model specific implementation for froot.

Parameters

- **root** – values of the trigger function
- **t** – timepoint
- **x** – Vector with the states

- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **tc1** – total abundances for conservation laws

virtual void **fxdot**(*realtype* *xdot, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w) = 0

Model specific implementation for fxdot.

Parameters

- **xdot** – residual function
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables

virtual void **fdxdotdp**(*realtype* *dxdotdp, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, int ip, const *realtype* *w, const *realtype* *dwdp)

Model specific implementation of fdxdotdp, with w chainrule (Matlab)

Parameters

- **dxdotdp** – partial derivative xdot wrt p
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **ip** – parameter index
- **w** – vector with helper variables
- **dwdp** – derivative of w wrt p

virtual void **fdxdotdp_explicit**(*realtype* *dxdotdp_explicit, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k, const *realtype* *h, const *realtype* *w)

Model specific implementation of fdxdotdp_explicit, no w chainrule (Py)

Parameters

- **dxdotdp_explicit** – partial derivative xdot wrt p
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector

- **w** – vector with helper variables

virtual void **fdxdotdp_explicit_colptrs**(*SUNMatrixWrapper* &dxdotdp)
Model specific implementation of fdxdotdp_explicit, colptrs part.

Parameters **dxdotdp** – sparse matrix to which colptrs will be written

virtual void **fdxdotdp_explicit_rowvals**(*SUNMatrixWrapper* &dxdotdp)
Model specific implementation of fdxdotdp_explicit, rowvals part.

Parameters **dxdotdp** – sparse matrix to which rowvals will be written

virtual void **fdxdotdx_explicit**(*realtype* *dxdotdx_explicit, *realtype* t, const *realtype* *x, const *realtype* *p,
 const *realtype* *k, const *realtype* *h, const *realtype* *w)
Model specific implementation of fdxdotdx_explicit, no w chainrule (Py)

Parameters

- **dxdotdx_explicit** – partial derivative xdot wrt x
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – heavyside vector
- **w** – vector with helper variables

virtual void **fdxdotdx_explicit_colptrs**(*SUNMatrixWrapper* &dxdotdx)
Model specific implementation of fdxdotdx_explicit, colptrs part.

Parameters **dxdotdx** – sparse matrix to which colptrs will be written

virtual void **fdxdotdx_explicit_rowvals**(*SUNMatrixWrapper* &dxdotdx)
Model specific implementation of fdxdotdx_explicit, rowvals part.

Parameters **dxdotdx** – sparse matrix to which rowvals will be written

virtual void **fdxdotdw**(*realtype* *dxdotdw, *realtype* t, const *realtype* *x, const *realtype* *p, const *realtype* *k,
 const *realtype* *h, const *realtype* *w)
Model specific implementation of fdxdotdw, data part.

Parameters

- **dxdotdw** – partial derivative xdot wrt w
- **t** – timepoint
- **x** – Vector with the states
- **p** – parameter vector
- **k** – constants vector
- **h** – Heaviside vector
- **w** – vector with helper variables

virtual void **fdxdotdw_colptrs**(*SUNMatrixWrapper* &dxdotdw)
Model specific implementation of fdxdotdw, colptrs part.

Parameters **dxdotdw** – sparse matrix to which colptrs will be written

virtual void **fdxdotdw_rowvals**(*SUNMatrixWrapper* &dxdotdw)
Model specific implementation of fdxdotdw, rowvals part.

Parameters **dxdotdw** – sparse matrix to which rowvals will be written

void **fdxdotdw**(*realtype* t, *const_N_Vector* x)
 Sensitivity of dx/dt wrt model parameters w.

Parameters

- **t** – timepoint
- **x** – Vector with the states

void **fdxdotdp**(*realtype* t, *const_N_Vector* x)
 Explicit sensitivity of dx/dt wrt model parameters p

Parameters

- **t** – timepoint
- **x** – Vector with the states

virtual void **fdxdotdp**(*realtype* t, const *AmiVector* &x, const *AmiVector* &dx) override
 Model-specific sparse implementation of explicit parameter derivative of right hand side.

Parameters

- **t** – time
- **x** – state
- **dx** – time derivative of state (DAE only)

Class ModelContext

- Defined in file_include_amici_rdata.h

Inheritance Relationships

Base Type

- public amici::ContextManager (*Class ContextManager*)

Class Documentation

class amici::ModelContext : public amici::ContextManager

The *ModelContext* temporarily stores amici::Model::state and restores it when going out of scope.

Public Functions

explicit **ModelContext**(*Model* *model)
initialize backup of the original values.

Parameters *model* –

ModelContext &**operator**=(const *ModelContext* &other) = delete

~ModelContext()

void **restore**()

Restore original state on constructor-supplied *amici::Model*. Will be called during destruction. Explicit call is generally not necessary.

Class NewtonFailure

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- public *amici::AmiException* (*Class AmiException*)

Class Documentation

class *amici::NewtonFailure* : public *amici::AmiException*
Newton failure exception.

This exception should be thrown when the steady state computation failed to converge for this exception we can assume that we can recover from the exception and return a solution struct to the user

Public Functions

NewtonFailure(int code, const char *function)

Constructor, simply calls *AmiException* constructor.

Parameters

- **function** – name of the function in which the error occurred
- **code** – error code

Public Members

int **error_code**
error code returned by solver

Class NewtonSolver

- Defined in file `_include_amici_newton_solver.h`

Inheritance Relationships

Derived Types

- public `amici::NewtonSolverDense` (*Class NewtonSolverDense*)
- public `amici::NewtonSolverSparse` (*Class NewtonSolverSparse*)

Class Documentation

class `amici::NewtonSolver`

The *NewtonSolver* class sets up the linear solver for the Newton method.

Subclassed by *amici::NewtonSolverDense*, *amici::NewtonSolverSparse*

Public Functions

explicit **NewtonSolver**(const *Model* &model)

Initializes solver according to the dimensions in the provided model.

Parameters `model` – pointer to the model object

void **getStep**(*AmiVector* &delta, *Model* &model, const *SimulationState* &state)

Computes the solution of one Newton iteration.

Parameters

- **delta** – containing the RHS of the linear system, will be overwritten by solution to the linear system
- **model** – pointer to the model instance
- **state** – current simulation state

void **computeNewtonSensis**(*AmiVectorArray* &sx, *Model* &model, const *SimulationState* &state)

Computes steady state sensitivities.

Parameters

- **sx** – pointer to state variable sensitivities
- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **prepareLinearSystem**(*Model* &model, const *SimulationState* &state) = 0

Writes the Jacobian for the Newton iteration and passes it to the linear solver.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **prepareLinearSystemB**(*Model* &model, const *SimulationState* &state) = 0

Writes the Jacobian (JB) for the Newton iteration and passes it to the linear solver

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **solveLinearSystem**(*AmiVector* &rhs) = 0

Solves the linear system for the Newton step.

Parameters **rhs** – containing the RHS of the linear system, will be overwritten by solution to the linear system

virtual void **reinitialize**() = 0

Reinitialize the linear solver.

virtual bool **is_singular**(*Model* &model, const *SimulationState* &state) const = 0

Checks whether linear system is singular.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

Returns boolean indicating whether the linear system is singular (condition number < 1/machine precision)

virtual **~NewtonSolver**() = default

Public Static Functions

static std::unique_ptr<*NewtonSolver*> **getSolver**(const *Solver* &simulationSolver, const *Model* &model)

Factory method to create a *NewtonSolver* based on linsolType.

Parameters

- **simulationSolver** – solver with settings
- **model** – pointer to the model instance

Returns solver *NewtonSolver* according to the specified linsolType

Protected Attributes

AmiVector **xdot_**

dummy rhs, used as dummy argument when computing J and JB

AmiVector **x_**

dummy state, attached to linear solver

AmiVector **xB_**

dummy adjoint state, used as dummy argument when computing JB

AmiVector **dxB_**

dummy differential adjoint state, used as dummy argument when computing JB

Class `NewtonSolverDense`

- Defined in `file_include_amici_newton_solver.h`

Inheritance Relationships

Base Type

- `public amici::NewtonSolver` (*Class `NewtonSolver`*)

Class Documentation

`class amici::NewtonSolverDense : public amici::NewtonSolver`

The *NewtonSolverDense* provides access to the dense linear solver for the Newton method.

Public Functions

explicit **NewtonSolverDense**(const *Model* &model)

constructor for sparse solver

Parameters **model** – model instance that provides problem dimensions

NewtonSolverDense(const *NewtonSolverDense*&) = delete

NewtonSolverDense &**operator**=(const *NewtonSolverDense* &other) = delete

~NewtonSolverDense() override

virtual void **solveLinearSystem**(*AmiVector* &rhs) override

Solves the linear system for the Newton step.

Parameters **rhs** – containing the RHS of the linear system, will be overwritten by solution to the linear system

virtual void **prepareLinearSystem**(*Model* &model, const *SimulationState* &state) override

Writes the Jacobian for the Newton iteration and passes it to the linear solver.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **prepareLinearSystemB**(*Model* &model, const *SimulationState* &state) override

Writes the Jacobian (JB) for the Newton iteration and passes it to the linear solver

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **reinitialize()** override

Reinitialize the linear solver.

virtual bool **is_singular**(*Model* &model, const *SimulationState* &state) const override

Checks whether linear system is singular.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

Returns boolean indicating whether the linear system is singular (condition number < 1/machine precision)

Class NewtonSolverSparse

- Defined in file_include_amici_newton_solver.h

Inheritance Relationships**Base Type**

- public amici::NewtonSolver (*Class NewtonSolver*)

Class Documentation

class amici::NewtonSolverSparse : public amici::NewtonSolver

The *NewtonSolverSparse* provides access to the sparse linear solver for the Newton method.

Public Functions

explicit **NewtonSolverSparse**(const *Model* &model)

constructor for dense solver

Parameters **model** – model instance that provides problem dimensions

NewtonSolverSparse(const *NewtonSolverSparse*&) = delete

NewtonSolverSparse &**operator=**(const *NewtonSolverSparse* &other) = delete

~NewtonSolverSparse() override

virtual void **solveLinearSystem**(*AmiVector* &rhs) override

Solves the linear system for the Newton step.

Parameters **rhs** – containing the RHS of the linear system, will be overwritten by solution to the linear system

virtual void **prepareLinearSystem**(*Model* &model, const *SimulationState* &state) override

Writes the Jacobian for the Newton iteration and passes it to the linear solver.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual void **prepareLinearSystemB**(*Model* &model, const *SimulationState* &state) override

Writes the Jacobian (JB) for the Newton iteration and passes it to the linear solver

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

virtual bool **is_singular**(*Model* &model, const *SimulationState* &state) const override

Checks whether linear system is singular.

Parameters

- **model** – pointer to the model instance
- **state** – current simulation state

Returns boolean indicating whether the linear system is singular (condition number < 1/machine precision)

virtual void **reinitialize**() override

Reinitialize the linear solver.

Class ReturnData

- Defined in file_include_amici_rdata.h

Inheritance Relationships

Base Type

- public amici::ModelDimensions (*Struct ModelDimensions*)

Class Documentation

```
class amici::ReturnData : public amici::ModelDimensions
```

Stores all data to be returned by amici::runAmiciSimulation.

NOTE: multi-dimensional arrays are stored in row-major order (C-style)

Public Functions

ReturnData() = default

Default constructor.

ReturnData(std::vector<*realtype*> ts, *ModelDimensions* const &model_dimensions, int nplist, int nmaxevent, int nt, int newton_maxsteps, std::vector<*ParameterScaling*> pscale, *SecondOrderMode* o2mode, *SensitivityOrder* sensi, *SensitivityMethod* sensi_meth, *RDataReporting* rdrm, bool quadratic_llh, bool sigma_res, *realtype* sigma_offset)

Constructor.

Parameters

- **ts** – see amici::SimulationParameters::ts
- **model_dimensions** – *Model* dimensions
- **nplist** – see amici::ModelDimensions::nplist
- **nmaxevent** – see amici::ModelDimensions::nmaxevent
- **nt** – see amici::ModelDimensions::nt
- **newton_maxsteps** – see amici::Solver::newton_maxsteps
- **pscale** – see amici::SimulationParameters::pscale
- **o2mode** – see amici::SimulationParameters::o2mode
- **sensi** – see amici::Solver::sensi
- **sensi_meth** – see amici::Solver::sensi_meth
- **rdrm** – see amici::Solver::rdata_reporting
- **quadratic_llh** – whether model defines a quadratic nllh and computing res, sres and FIM makes sense
- **sigma_res** – indicates whether additional residuals are to be added for each sigma
- **sigma_offset** – offset to ensure real-valuedness of sigma residuals

ReturnData(*Solver* const &solver, const *Model* &model)

constructor that uses information from model and solver to appropriately initialize fields

Parameters

- **solver** – solver instance
- **model** – model instance

~ReturnData() = default

void **processSimulationObjects**(*SteadystateProblem* const *preeq, *ForwardProblem* const *fwd, *BackwardProblem* const *bwd, *SteadystateProblem* const *posteq, *Model* &model, *Solver* const &solver, *ExpData* const *edata)

constructor that uses information from model and solver to appropriately initialize fields

Parameters

- **preeq** – simulated preequilibration problem, pass nullptr to ignore
- **fwd** – simulated forward problem, pass nullptr to ignore
- **bwd** – simulated backward problem, pass nullptr to ignore

- **posteq** – simulated postequilibration problem, pass `nullptr` to ignore
- **model** – matching model instance
- **solver** – matching solver instance
- **edata** – matching experimental data

Public Members

`std::string id`

Arbitrary (not necessarily unique) identifier.

`std::vector<realtype> ts`

timepoints (shape `nt`)

`std::vector<realtype> xdot`

time derivative (shape `nx`)

`std::vector<realtype> J`

Jacobian of differential equation right hand side (shape `nx` x `nx`, row-major)

`std::vector<realtype> w`

w data from the model (recurring terms in `xdot`, for imported SBML models from python, this contains the flux vector) (shape `nt` x `nw`, row major)

`std::vector<realtype> z`

event output (shape `nmaxevent` x `nz`, row-major)

`std::vector<realtype> sigmaz`

event output sigma standard deviation (shape `nmaxevent` x `nz`, row-major)

`std::vector<realtype> sz`

parameter derivative of event output (shape `nmaxevent` x `nplist` x `nz`, row-major)

`std::vector<realtype> ssigmaz`

parameter derivative of event output standard deviation (shape `nmaxevent` x `nplist` x `nz`, row-major)

`std::vector<realtype> rz`

event trigger output (shape `nmaxevent` x `nz`, row-major)

`std::vector<realtype> srz`

parameter derivative of event trigger output (shape `nmaxevent` x `nplist` x `nz`, row-major)

`std::vector<realtype> s2rz`

second-order parameter derivative of event trigger output (shape `nmaxevent` x `nztrue` x `nplist` x `nplist`, row-major)

`std::vector<realtype> x`

state (shape `nt` x `nx`, row-major)

`std::vector<realtype> sx`
 parameter derivative of state (shape `nt x nplist x nx`, row-major)

`std::vector<realtype> y`
 observable (shape `nt x ny`, row-major)

`std::vector<realtype> sigmay`
 observable standard deviation (shape `nt x ny`, row-major)

`std::vector<realtype> sy`
 parameter derivative of observable (shape `nt x nplist x ny`, row-major)

`std::vector<realtype> ssigmay`
 parameter derivative of observable standard deviation (shape `nt x nplist x ny`, row-major)

`std::vector<realtype> res`
 observable (shape `nt*ny`, row-major)

`std::vector<realtype> sres`
 parameter derivative of residual (shape `nt*ny x nplist`, row-major)

`std::vector<realtype> FIM`
 fisher information matrix (shape `nplist x nplist`, row-major)

`std::vector<int> numsteps`
 number of integration steps forward problem (shape `nt`)

`std::vector<int> numstepsB`
 number of integration steps backward problem (shape `nt`)

`std::vector<int> numrhsevals`
 number of right hand side evaluations forward problem (shape `nt`)

`std::vector<int> numrhsevalsB`
 number of right hand side evaluations backward problem (shape `nt`)

`std::vector<int> numerrtestfails`
 number of error test failures forward problem (shape `nt`)

`std::vector<int> numerrtestfailsB`
 number of error test failures backward problem (shape `nt`)

`std::vector<int> numnonlinsolvconvfails`
 number of linear solver convergence failures forward problem (shape `nt`)

`std::vector<int> numnonlinsolvconvfailsB`
 number of linear solver convergence failures backward problem (shape `nt`)

`std::vector<int> order`
 employed order forward problem (shape `nt`)

double **cpu_time** = 0.0
computation time of forward solve [ms]

double **cpu_timeB** = 0.0
computation time of backward solve [ms]

double **cpu_time_total** = 0.0
total CPU time from entering runAmiciSimulation until exiting [ms]

std::vector<*SteadyStateStatus*> **preeq_status**
flags indicating success of steady state solver (preequilibration)

double **preeq_cpu_time** = 0.0
computation time of the steady state solver [ms] (preequilibration)

double **preeq_cpu_timeB** = 0.0
computation time of the steady state solver of the backward problem [ms] (preequilibration)

std::vector<*SteadyStateStatus*> **posteq_status**
flags indicating success of steady state solver (postequilibration)

double **posteq_cpu_time** = 0.0
computation time of the steady state solver [ms] (postequilibration)

double **posteq_cpu_timeB** = 0.0
computation time of the steady state solver of the backward problem [ms] (postequilibration)

std::vector<int> **preeq_numsteps**
number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (length = 3)

int **preeq_numstepsB** = 0
number of simulation steps for adjoint steady state problem (preequilibration) [== 0 if analytical solution worked, > 0 otherwise]

std::vector<int> **posteq_numsteps**
number of Newton steps for steady state problem (preequilibration) [newton, simulation, newton] (shape 3) (postequilibration)

int **posteq_numstepsB** = 0
number of simulation steps for adjoint steady state problem (postequilibration) [== 0 if analytical solution worked, > 0 otherwise]

realtype **preeq_t** = NAN
time when steadystate was reached via simulation (preequilibration)

realtype **preeq_wrms** = NAN
weighted root-mean-square of the rhs when steadystate was reached (preequilibration)

realtype **posteq_t** = NAN
time when steadystate was reached via simulation (postequilibration)

realtype **posteq_wrms** = NAN
 weighted root-mean-square of the rhs when steadystate was reached (postequilibration)

std::vector<*realtype*> **x0**
 initial state (shape **nx**)

std::vector<*realtype*> **x_ss**
 preequilibration steady state found by Newton solver (shape **nx**)

std::vector<*realtype*> **sx0**
 initial sensitivities (shape **nplist** x **nx**, row-major)

std::vector<*realtype*> **sx_ss**
 preequilibration sensitivities found by Newton solver (shape **nplist** x **nx**, row-major)

realtype **llh** = 0.0
 log-likelihood value

realtype **chi2** = 0.0
 χ^2 value

std::vector<*realtype*> **sllh**
 parameter derivative of log-likelihood (shape **nplist**)

std::vector<*realtype*> **s2llh**
 second-order parameter derivative of log-likelihood (shape **nJ-1** x **nplist**, row-major)

int **status** = 0
 status code

int **nx** = {0}
 number of states (alias **nx_rdata**, kept for backward compatibility)

int **nxtrue** = {0}
 number of states in the unaugmented system (alias **nxtrue_rdata**, kept for backward compatibility)

int **nplist** = {0}
 number of parameter for which sensitivities were requested

int **nmaxevent** = {0}
 maximal number of occurring events (for every event type)

int **nt** = {0}
 number of considered timepoints

int **newton_maxsteps** = {0}
 maximal number of newton iterations for steady state calculation

std::vector<*ParameterScaling*> **pscale**
 scaling of parameterization

SecondOrderMode **o2mode** = {*SecondOrderMode::none*}
flag indicating whether second-order sensitivities were requested

SensitivityOrder **sensi** = {*SensitivityOrder::none*}
sensitivity order

SensitivityMethod **sensi_meth** = {*SensitivityMethod::none*}
sensitivity method

RDataReporting **rdata_reporting** = {*RDataReporting::full*}
reporting mode

bool **sigma_res**
boolean indicating whether residuals for standard deviations have been added

Protected Functions

void **initializeLikelihoodReporting**(bool quadratic_llh)
initializes storage for likelihood reporting mode

Parameters **quadratic_llh** – whether model defines a quadratic nllh and computing res, sres and FIM makes sense.

void **initializeResidualReporting**(bool enable_res)
initializes storage for residual reporting mode

Parameters **enable_res** – whether residuals are to be computed

void **initializeFullReporting**(bool enable_fim)
initializes storage for full reporting mode

Parameters **enable_fim** – whether FIM Hessian approximation is to be computed

void **initializeObjectiveFunction**(bool enable_chi2)
initialize values for chi2 and llh and derivatives

Parameters **enable_chi2** – whether chi2 values are to be computed

void **processPreEquilibration**(*SteadystateProblem* const &preeq, *Model* &model)
extracts data from a preequilibration *SteadystateProblem*

Parameters

- **preeq** – *SteadystateProblem* for preequilibration
- **model** – *Model* instance to compute return values

void **processPostEquilibration**(*SteadystateProblem* const &posteq, *Model* &model, *ExpData* const *edata)
extracts data from a preequilibration *SteadystateProblem*

Parameters

- **posteq** – *SteadystateProblem* for postequilibration
- **model** – *Model* instance to compute return values
- **edata** – *ExpData* instance containing observable data

void **processForwardProblem**(*ForwardProblem* const &fwd, *Model* &model, *ExpData* const *edata)
extracts results from forward problem

Parameters

- **fwd** – forward problem
- **model** – model that was used for forward simulation
- **edata** – *ExpData* instance containing observable data

void **processBackwardProblem**(*ForwardProblem* const &fwd, *BackwardProblem* const &bwd, *SteadystateProblem* const *preeq, *Model* &model)
extracts results from backward problem

Parameters

- **fwd** – forward problem
- **bwd** – backward problem
- **preeq** – *SteadystateProblem* for preequilibration
- **model** – model that was used for forward/backward simulation

void **processSolver**(*Solver* const &solver)
extracts results from solver

Parameters **solver** – solver that was used for forward/backward simulation

template<class T>

inline void **storeJacobianAndDerivativeInReturnData**(T const &problem, *Model* &model)
Evaluates and stores the Jacobian and right hand side at final timepoint.

Parameters

- **problem** – forward problem or steadystate problem
- **model** – model that was used for forward/backward simulation

void **readSimulationState**(*SimulationState* const &state, *Model* &model)
sets member variables and model state according to provided simulation state

Parameters

- **state** – simulation state provided by Problem
- **model** – model that was used for forward/backward simulation

void **fres**(int it, *Model* &model, const *ExpData* &edata)
Residual function.

Parameters

- **it** – time index
- **model** – model that was used for forward/backward simulation
- **edata** – *ExpData* instance containing observable data

void **fchi2**(int it, const *ExpData* &edata)
Chi-squared function.

Parameters

- **it** – time index
- **edata** – *ExpData* instance containing observable data

void **fsres**(int it, *Model* &model, const *ExpData* &edata)
Residual sensitivity function.

Parameters

- **it** – time index
- **model** – model that was used for forward/backward simulation
- **edata** – *ExpData* instance containing observable data

void **ffim**(int it, *Model* &model, const *ExpData* &edata)
Fisher information matrix function.

Parameters

- **it** – time index
- **model** – model that was used for forward/backward simulation
- **edata** – *ExpData* instance containing observable data

void **invalidate**(int it_start)
Set likelihood, state variables, outputs and respective sensitivities to NaN (typically after integration failure)

Parameters **it_start** – time index at which to start invalidating

void **invalidateLLH**()
Set likelihood and chi2 to NaN (typically after integration failure)

void **invalidateSLLH**()
Set likelihood sensitivities to NaN (typically after integration failure)

void **applyChainRuleFactorToSimulationResults**(const *Model* &model)
applies the chain rule to account for parameter transformation in the sensitivities of simulation results

Parameters **model** – *Model* from which the *ReturnData* was obtained

inline bool **computingFSA**() const
Checks whether forward sensitivity analysis is performed.

Returns boolean indicator

void **getDataOutput**(int it, *Model* &model, *ExpData* const *edata)
Extracts output information for data-points, expects that x_solver_ and sx_solver_ were set appropriately.

Parameters

- **it** – timepoint index
- **model** – model that was used in forward solve
- **edata** – *ExpData* instance carrying experimental data

void **getDataSensisFSA**(int it, *Model* &model, *ExpData* const *edata)
Extracts data information for forward sensitivity analysis, expects that x_solver_ and sx_solver_ were set appropriately.

Parameters

- **it** – index of current timepoint
- **model** – model that was used in forward solve
- **edata** – *ExpData* instance carrying experimental data

void **getEventOutput**(*realtype* t, const std::vector<int> rootidx, *Model* &model, *ExpData* const *edata)
Extracts output information for events, expects that x_solver_ and sx_solver_ were set appropriately.

Parameters

- **t** – event timepoint
- **rootidx** – information about which roots fired (1 indicating fired, 0/-1 for not)
- **model** – model that was used in forward solve
- **edata** – *ExpData* instance carrying experimental data

void **getEventSensisFSA**(int ie, *realtype* t, *Model* &model, *ExpData* const *edata)

Extracts event information for forward sensitivity analysis, expects that `x_solver_` and `sx_solver_` were set appropriately.

Parameters

- **ie** – index of event type
- **t** – event timepoint
- **model** – model that was used in forward solve
- **edata** – *ExpData* instance carrying experimental data

void **handleSx0Backward**(const *Model* &model, *SteadystateProblem* const &preeq, std::vector<*realtype*> &llhS0, *AmiVector* &xQB) const

Updates contribution to likelihood from quadratures (xQB), if preequilibration was run in adjoint mode.

Parameters

- **model** – model that was used for forward/backward simulation
- **preeq** – *SteadystateProblem* for preequilibration
- **llhS0** – contribution to likelihood for initial state sensitivities of preequilibration
- **xQB** – vector with quadratures from adjoint computation

void **handleSx0Forward**(const *Model* &model, std::vector<*realtype*> &llhS0, *AmiVector* &xB) const

Updates contribution to likelihood for initial state sensitivities (llhS0), if no preequilibration was run or if forward sensitivities were used.

Parameters

- **model** – model that was used for forward/backward simulation
- **llhS0** – contribution to likelihood for initial state sensitivities
- **xB** – vector with final adjoint state (excluding conservation laws)

Protected Attributes

realtype **sigma_offset**

offset for sigma_residuals

realtype **t_**

timepoint for model evaluation

AmiVector **x_solver_**

partial state vector, excluding states eliminated from conservation laws

AmiVector **dx_solver_**

partial time derivative of state vector, excluding states eliminated from conservation laws

AmiVectorArray **sx_solver_**

partial sensitivity state vector array, excluding states eliminated from conservation laws

AmiVector **x_rdata_**

full state vector, including states eliminated from conservation laws

AmiVectorArray **sx_rdata_**

full sensitivity state vector array, including states eliminated from conservation laws

std::vector<int> **nroots_**

array of number of found roots for a certain event type (shape ne)

Friends

template<class **Archive**>

friend void **serialize**(*Archive* &ar, *ReturnData* &r, unsigned int version)

Serialize *ReturnData* (see boost::serialization::serialize)

Parameters

- **ar** – Archive to serialize to
- **r** – Data to serialize
- **version** – Version number

Class SetupFailure

- Defined in file_include_amici_exception.h

Inheritance Relationships

Base Type

- public amici::AmiException (*Class AmiException*)

Class Documentation

class amici::SetupFailure : public amici::AmiException

Setup failure exception.

This exception should be thrown when the solver setup failed for this exception we can assume that we cannot recover from the exception and an error will be thrown

Public Functions

explicit **SetupFailure**(char const *fmt, ...)
 Constructor with printf style interface.

Parameters

- **fmt** – error message with printf format
- ... – printf formatting variables

Class SimulationParameters

- Defined in file_include_amici_simulation_parameters.h

Inheritance Relationships

Derived Type

- public amici::ExpData (*Class ExpData*)

Class Documentation

class amici::**SimulationParameters**
 Container for various simulation parameters.
 Subclassed by *amici::ExpData*

Public Functions

SimulationParameters() = default

inline explicit **SimulationParameters**(std::vector<*realtype*> timepoints)
 Constructor.

Parameters **timepoints** – Timepoints for which simulation results are requested

inline **SimulationParameters**(std::vector<*realtype*> fixedParameters, std::vector<*realtype*> parameters)
 Constructor.

Parameters

- **fixedParameters** – *Model* constants
- **parameters** – *Model* parameters

inline **SimulationParameters**(std::vector<*realtype*> fixedParameters, std::vector<*realtype*> parameters,
 std::vector<int> plist)
 Constructor.

Parameters

- **fixedParameters** – *Model* constants
- **parameters** – *Model* parameters

- **plist** – *Model* parameter indices w.r.t. which sensitivities are to be computed

inline **SimulationParameters**(std::vector<*realtype*> timepoints, std::vector<*realtype*> fixedParameters, std::vector<*realtype*> parameters)

Constructor.

Parameters

- **timepoints** – Timepoints for which simulation results are requested
- **fixedParameters** – *Model* constants
- **parameters** – *Model* parameters

void **reinitializeAllFixedParameterDependentInitialStatesForPresimulation**(int nx_rdata)

Set reinitialization of all states based on model constants for presimulation (only meaningful if preequilibration is performed).

Convenience function to populate `reinitialization_state_idxes_presim` and `reinitialization_state_idxes_sim`

Parameters `nx_rdata` – Number of states (*Model::nx_rdata*)

void **reinitializeAllFixedParameterDependentInitialStatesForSimulation**(int nx_rdata)

Set reinitialization of all states based on model constants for the ‘main’ simulation (only meaningful if presimulation or preequilibration is performed).

Convenience function to populate `reinitialization_state_idxes_presim` and `reinitialization_state_idxes_sim`

Parameters `nx_rdata` – Number of states (*Model::nx_rdata*)

void **reinitializeAllFixedParameterDependentInitialStates**(int nx_rdata)

Set reinitialization of all states based on model constants for all simulation phases.

Convenience function to populate `reinitialization_state_idxes_presim` and `reinitialization_state_idxes_sim`

Parameters `nx_rdata` – Number of states (*Model::nx_rdata*)

Public Members

std::vector<*realtype*> **fixedParameters**

Model constants.

Vector of size *Model::nk()* or empty

std::vector<*realtype*> **fixedParametersPreequilibration**

Model constants for pre-equilibration.

Vector of size *Model::nk()* or empty.

std::vector<*realtype*> **fixedParametersPresimulation**

Model constants for pre-simulation.

Vector of size *Model::nk()* or empty.

std::vector<*realtype*> **parameters**

Model parameters.

Vector of size *Model::np()* or empty with parameter scaled according to `SimulationParameter::pscale`.

`std::vector<realtype> x0`

Initial state.

Vector of size `Model::nx()` or empty

`std::vector<realtype> sx0`

Initial state sensitivities.

Dimensions: `Model::nx() * Model::nplist()`, `Model::nx() * ExpData::plist.size()`, if `ExpData::plist` is not empty, or empty

`std::vector<ParameterScaling> pscale`

Parameter scales.

Vector of parameter scale of size `Model::np()`, indicating how/if each parameter is to be scaled.

`std::vector<int> plist`

Parameter indices w.r.t. which to compute sensitivities.

`realtype tstart_ = {0.0}`

starting time

`realtype t_presim = {0.0}`

Duration of pre-simulation.

If this is > 0 , presimulation will be performed from $(\text{model} \rightarrow t_0 - t_{\text{presim}})$ to $\text{model} \rightarrow t_0$ using the fixed-Parameters in `fixedParametersPresimulation`

`std::vector<realtype> ts_`

Timepoints for which model state/outputs/... are requested.

Vector of timepoints.

`bool reinitializeFixedParameterInitialStates = {false}`

Flag indicating whether reinitialization of states depending on fixed parameters is activated.

`std::vector<int> reinitialization_state_idxes_presim`

Indices of states to be reinitialized based on provided presimulation constants / fixed parameters.

`std::vector<int> reinitialization_state_idxes_sim`

Indices of states to be reinitialized based on provided constants / fixed parameters.

Class Solver

- Defined in `file_include_amici_solver.h`

Inheritance Relationships

Derived Types

- `public amici::CVodeSolver` (*Class CVodeSolver*)
- `public amici::IDASolver` (*Class IDASolver*)

Class Documentation

class `amici::Solver`

The *Solver* class provides a generic interface to CVODES and IDAS solvers, individual realizations are realized in the *CVodeSolver* and the *IDASolver* class. All transient private/protected members (CVODES/IDAS memory, interface variables and status flags) are specified as mutable and not included in serialization or equality checks. No solver setting parameter should be marked mutable.

NOTE: Any changes in data members here must be propagated to copy ctor, equality operator, serialization functions in `serialization.h`, and `amici::hdf5::readSolverSettingsFromHDF5` in `hdf5.cpp`.

Subclassed by *amici::CVodeSolver*, *amici::IDASolver*

Public Types

using `user_data_type` = `std::pair<Model*, Solver const*>`
Type of what is passed to Sundials solvers as `user_data`

Public Functions

`Solver()` = default

Default constructor.

`Solver(AmiciApplication *app)`

Constructor.

Parameters `app` – AMICI application context

`Solver(const Solver &other)`

Solver copy constructor.

Parameters `other` –

virtual `~Solver()` = default

virtual `Solver *clone()` const = 0

Clone this instance.

Returns The clone

int `run(realtype tout)` const

runs a forward simulation until the specified timepoint

Parameters `tout` – next timepoint

Returns status flag

int **step**(*realtype* tout) const
makes a single step in the simulation

Parameters tout – next timepoint

Returns status flag

void **runB**(*realtype* tout) const
runs a backward simulation until the specified timepoint

Parameters tout – next timepoint

void **setup**(*realtype* t0, *Model* *model, const *AmiVector* &x0, const *AmiVector* &dx0, const *AmiVectorArray* &sx0, const *AmiVectorArray* &sdx0) const

Initializes the ami memory object and applies specified options.

Parameters

- **t0** – initial timepoint
- **model** – pointer to the model instance
- **x0** – initial states
- **dx0** – initial derivative states
- **sx0** – initial state sensitivities
- **sdx0** – initial derivative state sensitivities

void **setupB**(int *which, *realtype* tf, *Model* *model, const *AmiVector* &xB0, const *AmiVector* &dxB0, const *AmiVector* &xQB0) const

Initializes the AMI memory object for the backwards problem.

Parameters

- **which** – index of the backward problem, will be set by this routine
- **tf** – final timepoint (initial timepoint for the bwd problem)
- **model** – pointer to the model instance
- **xB0** – initial adjoint states
- **dxB0** – initial adjoint derivative states
- **xQB0** – initial adjoint quadratures

void **setupSteadystate**(const *realtype* t0, *Model* *model, const *AmiVector* &x0, const *AmiVector* &dx0, const *AmiVector* &xB0, const *AmiVector* &dxB0, const *AmiVector* &xQ0) const

Initializes the ami memory for quadrature computation.

Parameters

- **t0** – initial timepoint
- **model** – pointer to the model instance
- **x0** – initial states
- **dx0** – initial derivative states
- **xB0** – initial adjoint states
- **dxB0** – initial derivative adjoint states
- **xQ0** – initial quadrature vector

void **updateAndReinitStatesAndSensitivities**(*Model* *model) const

Reinitializes state and respective sensitivities (if necessary) according to changes in fixedParameters.

Parameters *model* – pointer to the model instance

virtual void **getRootInfo**(int *rootsfound) const = 0

getRootInfo extracts information which event occurred

Parameters *rootsfound* – array with flags indicating whether the respective event occurred

virtual void **calcIC**(*realtype* tout1) const = 0

Calculates consistent initial conditions, assumes initial states to be correct (DAE only)

Parameters *tout1* – next timepoint to be computed (sets timescale)

virtual void **calcICB**(int which, *realtype* tout1) const = 0

Calculates consistent initial conditions for the backwards problem, assumes initial states to be correct (DAE only)

Parameters

- **which** – identifier of the backwards problem
- **tout1** – next timepoint to be computed (sets timescale)

virtual void **solveB**(*realtype* tBout, int itaskB) const = 0

Solves the backward problem until a predefined timepoint (adjoint only)

Parameters

- **tBout** – timepoint until which simulation should be performed
- **itaskB** – task identifier, can be CV_NORMAL or CV_ONE_STEP

virtual void **turnOffRootFinding**() const = 0

Disable rootfinding.

SensitivityMethod **getSensitivityMethod**() const

Return current sensitivity method.

Returns method enum

void **setSensitivityMethod**(*SensitivityMethod* sensi_meth)

Set sensitivity method.

Parameters *sensi_meth* –

SensitivityMethod **getSensitivityMethodPreequilibration**() const

Return current sensitivity method during preequilibration.

Returns method enum

void **setSensitivityMethodPreequilibration**(*SensitivityMethod* sensi_meth_preeq)

Set sensitivity method for preequilibration.

Parameters *sensi_meth_preeq* –

void **switchForwardSensisOff**() const

Disable forward sensitivity integration (used in steady state sim)

int **getNewtonMaxSteps**() const

Get maximum number of allowed Newton steps for steady state computation.

Returns

void **setNewtonMaxSteps**(int newton_maxsteps)

Set maximum number of allowed Newton steps for steady state computation.

Parameters **newton_maxsteps** –

NewtonDampingFactorMode **getNewtonDampingFactorMode()** const
Get a state of the damping factor used in the Newton solver.

Returns

void **setNewtonDampingFactorMode**(*NewtonDampingFactorMode* dampingFactorMode)
Turn on/off a damping factor in the Newton method.

Parameters **dampingFactorMode** –

double **getNewtonDampingFactorLowerBound()** const
Get a lower bound of the damping factor used in the Newton solver.

Returns

void **setNewtonDampingFactorLowerBound**(double dampingFactorLowerBound)
Set a lower bound of the damping factor in the Newton solver.

Parameters **dampingFactorLowerBound** –

SensitivityOrder **getSensitivityOrder()** const
Get sensitivity order.

Returns sensitivity order

void **setSensitivityOrder**(*SensitivityOrder* sensi)
Set the sensitivity order.

Parameters **sensi** – sensitivity order

double **getRelativeTolerance()** const
Get the relative tolerances for the forward problem.

Same tolerance is used for the backward problem if not specified differently via setRelativeToleranceASA.

Returns relative tolerances

void **setRelativeTolerance**(double rtol)
Sets the relative tolerances for the forward problem.

Same tolerance is used for the backward problem if not specified differently via setRelativeToleranceASA.

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteTolerance()** const
Get the absolute tolerances for the forward problem.

Same tolerance is used for the backward problem if not specified differently via setAbsoluteToleranceASA.

Returns absolute tolerances

void **setAbsoluteTolerance**(double atol)
Sets the absolute tolerances for the forward problem.

Same tolerance is used for the backward problem if not specified differently via setAbsoluteToleranceASA.

Parameters **atol** – absolute tolerance (non-negative number)

double **getRelativeToleranceFSA()** const
Returns the relative tolerances for the forward sensitivity problem.

Returns relative tolerances

void **setRelativeToleranceFSA**(double rtol)
Sets the relative tolerances for the forward sensitivity problem.

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteToleranceFSA()** const

Returns the absolute tolerances for the forward sensitivity problem.

Returns absolute tolerances

void **setAbsoluteToleranceFSA**(double atol)

Sets the absolute tolerances for the forward sensitivity problem.

Parameters **atol** – absolute tolerance (non-negative number)

double **getRelativeToleranceB()** const

Returns the relative tolerances for the adjoint sensitivity problem.

Returns relative tolerances

void **setRelativeToleranceB**(double rtol)

Sets the relative tolerances for the adjoint sensitivity problem.

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteToleranceB()** const

Returns the absolute tolerances for the backward problem for adjoint sensitivity analysis.

Returns absolute tolerances

void **setAbsoluteToleranceB**(double atol)

Sets the absolute tolerances for the backward problem for adjoint sensitivity analysis.

Parameters **atol** – absolute tolerance (non-negative number)

double **getRelativeToleranceQuadratures()** const

Returns the relative tolerance for the quadrature problem.

Returns relative tolerance

void **setRelativeToleranceQuadratures**(double rtol)

sets the relative tolerance for the quadrature problem

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteToleranceQuadratures()** const

returns the absolute tolerance for the quadrature problem

Returns absolute tolerance

void **setAbsoluteToleranceQuadratures**(double atol)

sets the absolute tolerance for the quadrature problem

Parameters **atol** – absolute tolerance (non-negative number)

double **getRelativeToleranceSteadyState()** const

returns the relative tolerance for the steady state problem

Returns relative tolerance

void **setRelativeToleranceSteadyState**(double rtol)

sets the relative tolerance for the steady state problem

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteToleranceSteadyState()** const

returns the absolute tolerance for the steady state problem

Returns absolute tolerance

void **setAbsoluteToleranceSteadyState**(double atol)
 sets the absolute tolerance for the steady state problem

Parameters **atol** – absolute tolerance (non-negative number)

double **getRelativeToleranceSteadyStateSensi**() const
 returns the relative tolerance for the sensitivities of the steady state problem

Returns relative tolerance

void **setRelativeToleranceSteadyStateSensi**(double rtol)
 sets the relative tolerance for the sensitivities of the steady state problem

Parameters **rtol** – relative tolerance (non-negative number)

double **getAbsoluteToleranceSteadyStateSensi**() const
 returns the absolute tolerance for the sensitivities of the steady state problem

Returns absolute tolerance

void **setAbsoluteToleranceSteadyStateSensi**(double atol)
 sets the absolute tolerance for the sensitivities of the steady state problem

Parameters **atol** – absolute tolerance (non-negative number)

long int **getMaxSteps**() const
 returns the maximum number of solver steps for the forward problem

Returns maximum number of solver steps

void **setMaxSteps**(long int maxsteps)
 sets the maximum number of solver steps for the forward problem

Parameters **maxsteps** – maximum number of solver steps (positive number)

double **getMaxTime**() const
 Returns the maximum time allowed for integration.

Returns Time in seconds

void **setMaxTime**(double maxtime)
 Set the maximum time allowed for integration.

Parameters **maxtime** – Time in seconds

void **startTimer**() const
 Start timer for tracking integration time.

bool **timeExceeded**() const
 Check whether maximum integration time was exceeded.

Returns True if the maximum integration time was exceeded, false otherwise.

long int **getMaxStepsBackwardProblem**() const
 returns the maximum number of solver steps for the backward problem

Returns maximum number of solver steps

void **setMaxStepsBackwardProblem**(long int maxsteps)
 sets the maximum number of solver steps for the backward problem

Note: default behaviour (100 times the value for the forward problem) can be restored by passing maxsteps=0

Parameters **maxsteps** – maximum number of solver steps (non-negative number)

LinearMultistepMethod **getLinearMultistepMethod()** const
returns the linear system multistep method

Returns linear system multistep method

void **setLinearMultistepMethod**(*LinearMultistepMethod* lmm)
sets the linear system multistep method

Parameters **lmm** – linear system multistep method

NonlinearSolverIteration **getNonlinearSolverIteration()** const
returns the nonlinear system solution method

Returns

void **setNonlinearSolverIteration**(*NonlinearSolverIteration* iter)
sets the nonlinear system solution method

Parameters **iter** – nonlinear system solution method

InterpolationType **getInterpolationType()** const
getInterpolationType

Returns

void **setInterpolationType**(*InterpolationType* interpType)
sets the interpolation of the forward solution that is used for the backwards problem

Parameters **interpType** – interpolation type

int **getStateOrdering()** const
Gets KLU / SuperLUMT state ordering mode.

Returns State-ordering as integer according to *SUNLinSolKLU::StateOrdering* or *SUNLinSolSuperLUMT::StateOrdering* (which differ).

void **setStateOrdering**(int ordering)
Sets KLU / SuperLUMT state ordering mode.

This only applies when linsol is set to *LinearSolver::KLU* or *LinearSolver::SuperLUMT*. Mind the difference between *SUNLinSolKLU::StateOrdering* and *SUNLinSolSuperLUMT::StateOrdering*.

Parameters **ordering** – state ordering

bool **getStabilityLimitFlag()** const
returns stability limit detection mode

Returns stldet can be false (deactivated) or true (activated)

void **setStabilityLimitFlag**(bool stldet)
set stability limit detection mode

Parameters **stldet** – can be false (deactivated) or true (activated)

LinearSolver **getLinearSolver()** const
getLinearSolver

Returns

void **setLinearSolver**(*LinearSolver* linsol)
setLinearSolver

Parameters **linsol** –

InternalSensitivityMethod **getInternalSensitivityMethod()** const
returns the internal sensitivity method

Returns internal sensitivity method

void **setInternalSensitivityMethod**(*InternalSensitivityMethod* ism)
sets the internal sensitivity method

Parameters **ism** – internal sensitivity method

RDataReporting **getReturnDataReportingMode()** const
returns the *ReturnData* reporting mode

Returns *ReturnData* reporting mode

void **setReturnDataReportingMode**(*RDataReporting* rdrm)
sets the *ReturnData* reporting mode

Parameters **rdrm** – *ReturnData* reporting mode

void **writeSolution**(*realtype* *t, *AmiVector* &x, *AmiVector* &dx, *AmiVectorArray* &sx, *AmiVector* &xQ)
const
write solution from forward simulation

Parameters

- **t** – time
- **x** – state
- **dx** – derivative state
- **sx** – state sensitivity
- **xQ** – quadrature

void **writeSolutionB**(*realtype* *t, *AmiVector* &xB, *AmiVector* &dxB, *AmiVector* &xQB, int which) const
write solution from backward simulation

Parameters

- **t** – time
- **xB** – adjoint state
- **dxB** – adjoint derivative state
- **xQB** – adjoint quadrature
- **which** – index of adjoint problem

const *AmiVector* &**getState**(*realtype* t) const
Access state solution at time t.

Parameters **t** – time

Returns x or interpolated solution dky

const *AmiVector* &**getDerivativeState**(*realtype* t) const
Access derivative state solution at time t.

Parameters **t** – time

Returns dx or interpolated solution dky

const *AmiVectorArray* &**getStateSensitivity**(*realtype* t) const
Access state sensitivity solution at time t.

Parameters **t** – time

Returns (interpolated) solution **sx**

const *AmiVector* &**getAdjointState**(int which, *realtype* t) const
Access adjoint solution at time t.

Parameters

- **which** – adjoint problem index
- **t** – time

Returns (interpolated) solution **xB**

const *AmiVector* &**getAdjointDerivativeState**(int which, *realtype* t) const
Access adjoint derivative solution at time t.

Parameters

- **which** – adjoint problem index
- **t** – time

Returns (interpolated) solution **dxB**

const *AmiVector* &**getAdjointQuadrature**(int which, *realtype* t) const
Access adjoint quadrature solution at time t.

Parameters

- **which** – adjoint problem index
- **t** – time

Returns (interpolated) solution **xQB**

const *AmiVector* &**getQuadrature**(*realtype* t) const
Access quadrature solution at time t.

Parameters **t** – time

Returns (interpolated) solution **xQ**

virtual void **reInit**(*realtype* t0, const *AmiVector* &yy0, const *AmiVector* &yp0) const = 0
Reinitializes the states in the solver after an event occurrence.

Parameters

- **t0** – reinitialization timepoint
- **yy0** – initial state variables
- **yp0** – initial derivative state variables (DAE only)

virtual void **sensReInit**(const *AmiVectorArray* &yyS0, const *AmiVectorArray* &ypS0) const = 0
Reinitializes the state sensitivities in the solver after an event occurrence.

Parameters

- **yyS0** – new state sensitivity
- **ypS0** – new derivative state sensitivities (DAE only)

virtual void **sensToggleOff**() const = 0
Switches off computation of state sensitivities without deallocating the memory for sensitivities.

virtual void **reInitB**(int which, *realtype* tB0, const *AmiVector* &yyB0, const *AmiVector* &ypB0) const = 0
Reinitializes the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **tB0** – reinitialization timepoint
- **yyB0** – new adjoint state
- **ypB0** – new adjoint derivative state

virtual void **quadReInitB**(int which, const *AmiVector* &yQB0) const = 0
 Reinitialize the adjoint states after an event occurrence.

Parameters

- **which** – identifier of the backwards problem
- **yQB0** – new adjoint quadrature state

realtype **gett**() const
 current solver timepoint

Returns t

realtype **getCpuTime**() const
 Reads out the CPU time needed for forward solve.

Returns cpu_time

realtype **getCpuTimeB**() const
 Reads out the CPU time needed for backward solve.

Returns cpu_timeB

int **nx**() const
 number of states with which the solver was initialized

Returns x.getLength()

int **nplist**() const
 number of parameters with which the solver was initialized

Returns sx.getLength()

int **nquad**() const
 number of quadratures with which the solver was initialized

Returns xQB.getLength()

inline bool **computingFSA**() const
 check if FSA is being computed

Returns flag

inline bool **computingASA**() const
 check if ASA is being computed

Returns flag

void **resetDiagnosis**() const
 Resets vectors containing diagnosis information.

void **storeDiagnosis**() const
 Stores diagnosis information from solver memory block for forward problem.

void **storeDiagnosisB**(int which) const
 Stores diagnosis information from solver memory block for backward problem.

Parameters **which** – identifier of the backwards problem

inline std::vector<int> const &**getNumSteps**() const
Accessor ns.

Returns ns

inline std::vector<int> const &**getNumStepsB**() const
Accessor nsB.

Returns nsB

inline std::vector<int> const &**getNumRhsEvals**() const
Accessor nrhs.

Returns nrhs

inline std::vector<int> const &**getNumRhsEvalsB**() const
Accessor nrhsB.

Returns nrhsB

inline std::vector<int> const &**getNumErrTestFails**() const
Accessor netf.

Returns netf

inline std::vector<int> const &**getNumErrTestFailsB**() const
Accessor netfB.

Returns netfB

inline std::vector<int> const &**getNumNonlinSolvConvFails**() const
Accessor nnlscf.

Returns nnlscf

inline std::vector<int> const &**getNumNonlinSolvConvFailsB**() const
Accessor nnlscfB.

Returns nnlscfB

inline std::vector<int> const &**getLastOrder**() const
Accessor order.

Returns order

inline bool **getNewtonStepSteadyStateCheck**() const
Returns how convergence checks for steadystate computation are performed.

Returns boolean flag indicating newton step (true) or the right hand side (false)

inline bool **getSensiSteadyStateCheck**() const
Returns how convergence checks for steadystate computation are performed.

Returns boolean flag indicating state and sensitivity equations (true) or only state variables (false).

inline void **setNewtonStepSteadyStateCheck**(bool flag)
Sets how convergence checks for steadystate computation are performed.

Parameters **flag** – boolean flag to pick newton step (true) or the right hand side (false, default)

inline void **setSensiSteadyStateCheck**(bool flag)
Sets for which variables convergence checks for steadystate computation are performed.

Parameters **flag** – boolean flag to pick state and sensitivity equations (true, default) or only state variables (false).

Public Members

AmiciApplication ***app** = &*defaultContext*
AMICI context

Protected Functions

virtual void **setStopTime**(*realtype* tstop) const = 0

Sets a timepoint at which the simulation will be stopped.

Parameters **tstop** – timepoint until which simulation should be performed

virtual int **solve**(*realtype* tout, int itask) const = 0

Solves the forward problem until a predefined timepoint.

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP

Returns status flag indicating success of execution

virtual int **solveF**(*realtype* tout, int itask, int *ncheckPtr) const = 0

Solves the forward problem until a predefined timepoint (adjoint only)

Parameters

- **tout** – timepoint until which simulation should be performed
- **itask** – task identifier, can be CV_NORMAL or CV_ONE_STEP
- **ncheckPtr** – pointer to a number that counts the internal checkpoints

Returns status flag indicating success of execution

virtual void **reInitPostProcessF**(*realtype* tnext) const = 0

reInitPostProcessF postprocessing of the solver memory after a discontinuity in the forward problem

Parameters **tnext** – next timepoint (defines integration direction)

virtual void **reInitPostProcessB**(*realtype* tnext) const = 0

reInitPostProcessB postprocessing of the solver memory after a discontinuity in the backward problem

Parameters **tnext** – next timepoint (defines integration direction)

virtual void **getSens**() const = 0

extracts the state sensitivity at the current timepoint from solver memory and writes it to the sx member variable

virtual void **getB**(int which) const = 0

extracts the adjoint state at the current timepoint from solver memory and writes it to the xB member variable

Parameters **which** – index of the backwards problem

virtual void **getQuadB**(int which) const = 0

extracts the adjoint quadrature state at the current timepoint from solver memory and writes it to the xQB member variable

Parameters **which** – index of the backwards problem

virtual void **getQuad**(*realtype* &t) const = 0

extracts the quadrature at the current timepoint from solver memory and writes it to the xQ member variable

Parameters **t** – timepoint for quadrature extraction

virtual void **init**(*realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const = 0

Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **initSteadystate**(*realtype* t0, const *AmiVector* &x0, const *AmiVector* &dx0) const = 0

Initializes the states at the specified initial timepoint.

Parameters

- **t0** – initial timepoint
- **x0** – initial states
- **dx0** – initial derivative states

virtual void **sensInit1**(const *AmiVectorArray* &sx0, const *AmiVectorArray* &sdx0) const = 0

Initializes the forward sensitivities.

Parameters

- **sx0** – initial states sensitivities
- **sdx0** – initial derivative states sensitivities

virtual void **binit**(int which, *realtype* tf, const *AmiVector* &xB0, const *AmiVector* &dxB0) const = 0

Initialize the adjoint states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **tf** – final timepoint
- **xB0** – initial adjoint state
- **dxB0** – initial adjoint derivative state

virtual void **qbinit**(int which, const *AmiVector* &xQB0) const = 0

Initialize the quadrature states at the specified final timepoint.

Parameters

- **which** – identifier of the backwards problem
- **xQB0** – initial adjoint quadrature state

virtual void **rootInit**(int ne) const = 0

Initializes the rootfinding for events.

Parameters **ne** – number of different events

void **initializeNonLinearSolverSens**(const *Model* *model) const

Initialize non-linear solver for sensitivities.

Parameters **model** – *Model* instance

virtual void **setDenseJacFn**() const = 0

Set the dense Jacobian function.

virtual void **setSparseJacFn**() const = 0

sets the sparse Jacobian function

virtual void **setBandJacFn**() const = 0

sets the banded Jacobian function

virtual void **setJacTimesVecFn**() const = 0

sets the Jacobian vector multiplication function

virtual void **setDenseJacFnB**(int which) const = 0

sets the dense Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFnB**(int which) const = 0

sets the sparse Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setBandJacFnB**(int which) const = 0

sets the banded Jacobian function

Parameters **which** – identifier of the backwards problem

virtual void **setJacTimesVecFnB**(int which) const = 0

sets the Jacobian vector multiplication function

Parameters **which** – identifier of the backwards problem

virtual void **setSparseJacFn_ss**() const = 0

sets the sparse Jacobian function for backward steady state case

virtual void **allocateSolver**() const = 0

Create specifies solver method and initializes solver memory for the forward problem.

virtual void **setSStolerances**(double rtol, double atol) const = 0

sets scalar relative and absolute tolerances for the forward problem

Parameters

- **rtol** – relative tolerances
- **atol** – absolute tolerances

virtual void **setSensSStolerances**(double rtol, const double *atol) const = 0

activates sets scalar relative and absolute tolerances for the sensitivity variables

Parameters

- **rtol** – relative tolerances
- **atol** – array of absolute tolerances for every sensitivity variable

virtual void **setSensErrCon**(bool error_corr) const = 0

SetSensErrCon specifies whether error control is also enforced for sensitivities for the forward problem

Parameters **error_corr** – activation flag

virtual void **setQuadErrConB**(int which, bool flag) const = 0

Specifies whether error control is also enforced for the backward quadrature problem.

Parameters

- **which** – identifier of the backwards problem

- **flag** – activation flag

virtual void **setQuadErrCon**(bool flag) const = 0

Specifies whether error control is also enforced for the forward quadrature problem.

Parameters **flag** – activation flag

virtual void **setErrHandlerFn**() const = 0

Attaches the error handler function (errMsgIdAndTxt) to the solver.

virtual void **setUserData**() const = 0

Attaches the user data to the forward problem.

virtual void **setUserDataB**(int which) const = 0

attaches the user data to the backward problem

Parameters **which** – identifier of the backwards problem

virtual void **setMaxNumSteps**(long int mxsteps) const = 0

specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters **mxsteps** – number of steps

virtual void **setMaxNumStepsB**(int which, long int mxstepsB) const = 0

specifies the maximum number of steps for the forward problem

Note: in contrast to the SUNDIALS method, this sets the overall maximum, not the maximum between output times.

Parameters

- **which** – identifier of the backwards problem
- **mxstepsB** – number of steps

virtual void **setStabLimDet**(int stldet) const = 0

activates stability limit detection for the forward problem

Parameters **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setStabLimDetB**(int which, int stldet) const = 0

activates stability limit detection for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **stldet** – flag for stability limit detection (TRUE or FALSE)

virtual void **setId**(const *Model* *model) const = 0

specify algebraic/differential components (DAE only)

Parameters **model** – model specification

virtual void **setSuppressAlg**(bool flag) const = 0

deactivates error control for algebraic components (DAE only)

Parameters **flag** – deactivation flag

virtual void **setSensParams**(const *realtype* *p, const *realtype* *pbar, const int *plist) const = 0
specifies the scaling and indexes for sensitivity computation

Parameters

- **p** – parameters
- **pbar** – parameter scaling constants
- **plist** – parameter index list

virtual void **getDky**(*realtype* t, int k) const = 0
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getDkyB**(*realtype* t, int k, int which) const = 0
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getSensDky**(*realtype* t, int k) const = 0
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **getQuadDkyB**(*realtype* t, int k, int which) const = 0
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order
- **which** – index of backward problem

virtual void **getQuadDky**(*realtype* t, int k) const = 0
interpolates the (derivative of the) solution at the requested timepoint

Parameters

- **t** – timepoint
- **k** – derivative order

virtual void **adjInit**() const = 0
initializes the adjoint problem

virtual void **quadInit**(const *AmiVector* &xQ0) const = 0
initializes the quadratures

Parameters **xQ0** – vector with initial values for xQ

virtual void **allocateSolverB**(int *which) const = 0

Specifies solver method and initializes solver memory for the backward problem.

Parameters **which** – identifier of the backwards problem

virtual void **setSStolerancesB**(int which, *realtype* relTolB, *realtype* absTolB) const = 0

sets relative and absolute tolerances for the backward problem

Parameters

- **which** – identifier of the backwards problem
- **relTolB** – relative tolerances
- **absTolB** – absolute tolerances

virtual void **quadSStolerancesB**(int which, *realtype* reltolQB, *realtype* abstolQB) const = 0

sets relative and absolute tolerances for the quadrature backward problem

Parameters

- **which** – identifier of the backwards problem
- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual void **quadSStolerances**(*realtype* reltolQB, *realtype* abstolQB) const = 0

sets relative and absolute tolerances for the quadrature problem

Parameters

- **reltolQB** – relative tolerances
- **abstolQB** – absolute tolerances

virtual void **getNumSteps**(const void *ami_mem, long int *numsteps) const = 0

reports the number of solver steps

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numsteps** – output array

virtual void **getNumRhsEvals**(const void *ami_mem, long int *numrhsevals) const = 0

reports the number of right hand evaluations

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numrhsevals** – output array

virtual void **getNumErrTestFails**(const void *ami_mem, long int *numerrtestfails) const = 0

reports the number of local error test failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numerrtestfails** – output array

virtual void **getNumNonlinSolvConvFails**(const void *ami_mem, long int *numnonlinsolvconvfails) const = 0

reports the number of nonlinear convergence failures

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **numnonlinsolvconvfails** – output array

virtual void **getLastOrder**(const void *ami_mem, int *order) const = 0

Reports the order of the integration method during the last internal step.

Parameters

- **ami_mem** – pointer to the solver memory instance (can be from forward or backward problem)
- **order** – output array

void **initializeLinearSolver**(const *Model* *model) const

Initializes and sets the linear solver for the forward problem.

Parameters **model** – pointer to the model object

void **initializeNonLinearSolver**() const

Sets the non-linear solver.

virtual void **setLinearSolver**() const = 0

Sets the linear solver for the forward problem.

virtual void **setLinearSolverB**(int which) const = 0

Sets the linear solver for the backward problem.

Parameters **which** – index of the backward problem

virtual void **setNonLinearSolver**() const = 0

Set the non-linear solver for the forward problem.

virtual void **setNonLinearSolverB**(int which) const = 0

Set the non-linear solver for the backward problem.

Parameters **which** – index of the backward problem

virtual void **setNonLinearSolverSens**() const = 0

Set the non-linear solver for sensitivities.

void **initializeLinearSolverB**(const *Model* *model, int which) const

Initializes the linear solver for the backward problem.

Parameters

- **model** – pointer to the model object
- **which** – index of the backward problem

void **initializeNonLinearSolverB**(int which) const

Initializes the non-linear solver for the backward problem.

Parameters **which** – index of the backward problem

virtual const *Model* ***getModel**() const = 0

Accessor function to the model stored in the user data

Returns user data model

bool **getInitDone**() const
checks whether memory for the forward problem has been allocated
Returns proxy for solverMemory->(cvlida)_MallocDone

bool **getSensInitDone**() const
checks whether memory for forward sensitivities has been allocated
Returns proxy for solverMemory->(cvlida)_SensMallocDone

bool **getAdjInitDone**() const
checks whether memory for forward interpolation has been allocated
Returns proxy for solverMemory->(cvlida)_adjMallocDone

bool **getInitDoneB**(int which) const
checks whether memory for the backward problem has been allocated
Parameters **which** – adjoint problem index
Returns proxy for solverMemoryB->(cvlida)_MallocDone

bool **getQuadInitDoneB**(int which) const
checks whether memory for backward quadratures has been allocated
Parameters **which** – adjoint problem index
Returns proxy for solverMemoryB->(cvlida)_QuadMallocDone

bool **getQuadInitDone**() const
checks whether memory for quadratures has been allocated
Returns proxy for solverMemory->(cvlida)_QuadMallocDone

virtual void **diag**() const = 0
attaches a diagonal linear solver to the forward problem

virtual void **diagB**(int which) const = 0
attaches a diagonal linear solver to the backward problem
Parameters **which** – identifier of the backwards problem

void **resetMutableMemory**(int nx, int nplist, int nquad) const
resets solverMemory and solverMemoryB
Parameters

- **nx** – new number of state variables
- **nplist** – new number of sensitivity parameters
- **nquad** – new number of quadratures (only differs from nplist for higher order sensitivity computation)

virtual void ***getAdjBmem**(void *ami_mem, int which) const = 0
Retrieves the solver memory instance for the backward problem.
Parameters

- **which** – identifier of the backwards problem
- **ami_mem** – pointer to the forward solver memory instance

Returns A (void *) pointer to the CVODES memory allocated for the backward problem.

void **applyTolerances**() const
updates solver tolerances according to the currently specified member variables

void **applyTolerancesFSA**() const
 updates FSA solver tolerances according to the currently specified member variables

void **applyTolerancesASA**(int which) const
 updates ASA solver tolerances according to the currently specified member variables

Parameters **which** – identifier of the backwards problem

void **applyQuadTolerancesASA**(int which) const
 updates ASA quadrature solver tolerances according to the currently specified member variables

Parameters **which** – identifier of the backwards problem

void **applyQuadTolerances**() const
 updates quadrature solver tolerances according to the currently specified member variables

void **applySensitivityTolerances**() const
 updates all sensitivity solver tolerances according to the currently specified member variables

void **setInitDone**() const
 sets that memory for the forward problem has been allocated

void **setSensInitDone**() const
 sets that memory for forward sensitivities has been allocated

void **setSensInitOff**() const
 sets that memory for forward sensitivities has not been allocated

void **setAdjInitDone**() const
 sets that memory for forward interpolation has been allocated

void **setInitDoneB**(int which) const
 sets that memory for the backward problem has been allocated

Parameters **which** – adjoint problem index

void **setQuadInitDoneB**(int which) const
 sets that memory for backward quadratures has been allocated

Parameters **which** – adjoint problem index

void **setQuadInitDone**() const
 sets that memory for quadratures has been allocated

void **checkSensitivityMethod**(const *SensitivityMethod* sensi_meth, bool preequilibration) const
 Sets sensitivity method (for simulation or preequilibration)

Parameters

- **sensi_meth** – new value for sensi_meth[_preeq]
- **preequilibration** – flag indicating preequilibration or simulation

Protected Attributes

mutable std::unique_ptr<void, std::function<void(void*)>> **solver_memory_**
pointer to solver memory block

mutable std::vector<std::unique_ptr<void, std::function<void(void*)>>> **solver_memory_B_**
pointer to solver memory block

mutable *user_data_type* **user_data**
Sundials user_data

InternalSensitivityMethod **ism_** = {*InternalSensitivityMethod::simultaneous*}
internal sensitivity method flag used to select the sensitivity solution method. Only applies for Forward Sensitivities.

LinearMultistepMethod **lmm_** = {*LinearMultistepMethod::BDF*}
specifies the linear multistep method.

NonlinearSolverIteration **iter_** = {*NonlinearSolverIteration::newton*}
specifies the type of nonlinear solver iteration

InterpolationType **interp_type_** = {*InterpolationType::hermite*}
interpolation type for the forward problem solution which is then used for the backwards problem.

long int **maxsteps_** = {10000}
maximum number of allowed integration steps

std::chrono::duration<double, std::ratio<1>> **maxtime_** = {std::chrono::duration<double>::max()}
Maximum wall-time for integration in seconds

mutable std::chrono::time_point<std::chrono::system_clock> **starttime_**
Time at which solver timer was started

mutable std::unique_ptr<*SUNLinSolWrapper*> **linear_solver_**
linear solver for the forward problem

mutable std::unique_ptr<*SUNLinSolWrapper*> **linear_solver_B_**
linear solver for the backward problem

mutable std::unique_ptr<*SUNNonLinSolWrapper*> **non_linear_solver_**
non-linear solver for the forward problem

mutable std::unique_ptr<*SUNNonLinSolWrapper*> **non_linear_solver_B_**
non-linear solver for the backward problem

mutable std::unique_ptr<*SUNNonLinSolWrapper*> **non_linear_solver_sens_**
non-linear solver for the sensitivities

mutable bool **solver_was_called_F_** = {false}
flag indicating whether the forward solver has been called


```

mutable bool solver_was_called_B_ = {false}
    flag indicating whether the backward solver has been called

mutable AmiVector x_ = {0}
    state (dimension: nx_solver)

mutable AmiVector dky_ = {0}
    state interface variable (dimension: nx_solver)

mutable AmiVector dx_ = {0}
    state derivative dummy (dimension: nx_solver)

mutable AmiVectorArray sx_ = {0, 0}
    state sensitivities interface variable (dimension: nx_solver x nplist)

mutable AmiVectorArray sdx_ = {0, 0}
    state derivative sensitivities dummy (dimension: nx_solver x nplist)

mutable AmiVector xB_ = {0}
    adjoint state interface variable (dimension: nx_solver)

mutable AmiVector dxB_ = {0}
    adjoint derivative dummy variable (dimension: nx_solver)

mutable AmiVector xQB_ = {0}
    adjoint quadrature interface variable (dimension: nJ x nplist)

mutable AmiVector xQ_ = {0}
    forward quadrature interface variable (dimension: nx_solver)

mutable realtype t_ = {std::nan("")}
    integration time of the forward problem

mutable bool force_reinit_postprocess_F_ = {false}
    flag to force reInitPostProcessF before next call to solve

mutable bool force_reinit_postprocess_B_ = {false}
    flag to force reInitPostProcessB before next call to solveB

mutable bool sens_initialized_ = {false}
    flag indicating whether sensInit1 was called

```

Friends

```
template<class Archive>
friend void serialize(Archive &ar, Solver &s, unsigned int version)
    Serialize Solver (see boost::serialization::serialize)
```

Parameters

- **ar** – Archive to serialize to
- **s** – Data to serialize
- **version** – Version number

```
friend bool operator==(const Solver &a, const Solver &b)
    Check equality of data members excluding solver memory.
```

Parameters

- **a** –
- **b** –

Returns

Class SteadystateProblem

- Defined in file_include_amici_steadystateproblem.h

Class Documentation

class amici::**SteadystateProblem**

The *SteadystateProblem* class solves a steady-state problem using Newton's method and falls back to integration on failure.

Public Functions

```
explicit SteadystateProblem(const Solver &solver, const Model &model)
    constructor
```

Parameters

- **solver** – *Solver* instance
- **model** – *Model* instance

```
void workSteadyStateProblem(const Solver &solver, Model &model, int it)
```

Handles steady state computation in the forward case: tries to determine the steady state of the ODE system and computes steady state sensitivities if requested.

Parameters

- **solver** – pointer to the solver object
- **model** – pointer to the model object
- **it** – integer with the index of the current time step

void **workSteadyStateBackwardProblem**(const *Solver* &solver, *Model* &model, const *BackwardProblem* *bwd)

Integrates over the adjoint state backward in time by solving a linear system of equations, which gives the analytical solution. Computes the gradient via adjoint steady state sensitivities

Parameters

- **solver** – pointer to the solver object
- **model** – pointer to the model object
- **bwd** – backward problem

inline const *SimulationState* &**getFinalSimulationState**() const
Returns the stored *SimulationState*.

Returns stored *SimulationState*

inline const *AmiVector* &**getEquilibrationQuadratures**() const
Returns the quadratures from pre- or postequilibration.

Returns xQB Vector with quadratures

inline const *AmiVector* &**getState**() const
Returns state at steadystate.

Returns x

inline const *AmiVectorArray* &**getStateSensitivity**() const
Returns state sensitivity at steadystate.

Returns sx

inline std::vector<*realtype*> const &**getDJydx**() const
Accessor for dJydx.

Returns dJydx

inline double **getCPUTime**() const
Accessor for run_time of the forward problem.

Returns run_time

inline double **getCPUTimeB**() const
Accessor for run_time of the backward problem.

Returns run_time

inline std::vector<*SteadyStateStatus*> const &**getSteadyStateStatus**() const
Accessor for steady_state_status.

Returns steady_state_status

inline *realtype* **getSteadyStateTime**() const
Get model time at which steadystate was found through simulation.

Returns t

inline *realtype* **getResidualNorm**() const
Accessor for wrms.

Returns wrms

inline const std::vector<int> &**getNumSteps**() const
Accessor for numsteps.

Returns numsteps

inline int **getNumStepsB**() const
Accessor for numstepsB.

Returns numstepsB

void **getAdjointUpdates**(*Model* &model, const *ExpData* &edata)
computes adjoint updates dJydx according to provided model and expdata

Parameters

- **model** – *Model* instance
- **edata** – experimental data

inline *AmiVector* const &**getAdjointState**() const
Return the adjoint state.

Returns xB adjoint state

inline *AmiVector* const &**getAdjointQuadrature**() const
Accessor for xQB.

Returns xQB

inline bool **hasQuadrature**() const
Accessor for hasQuadrature_.

Returns hasQuadrature_

bool **checkSteadyStateSuccess**() const
computes adjoint updates dJydx according to provided model and expdata

Returns convergence of steady state solver

Class SUNLinSolBand

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNLinSolWrapper (*Class* *SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolBand : public amici::SUNLinSolWrapper
SUNDIALS band direct solver.

Public Functions

SUNLinSolBand(N_Vector x, SUNMatrix A)

Create solver using existing matrix A without taking ownership of A.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **A** – square matrix

SUNLinSolBand(*AmiVector* const &x, int ubw, int lbw)

Create new band solver and matrix A.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **ubw** – upper bandwidth of band matrix A
- **lbw** – lower bandwidth of band matrix A

virtual SUNMatrix **getMatrix**() const override

Get the matrix A (matrix solvers only).

Returns A

Class SUNLinSolDense

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolDense : public amici::SUNLinSolWrapper
SUNDIALS dense direct solver.

Public Functions

explicit **SUNLinSolDense**(*AmiVector* const &x)

Create dense solver.

Parameters **x** – A template for cloning vectors needed within the solver.

virtual SUNMatrix **getMatrix**() const override

Get the matrix A (matrix solvers only).

Returns A

Class SUNLinSolKLU

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

```
class amici::SUNLinSolKLU : public amici::SUNLinSolWrapper
    SUNDIALS KLU sparse direct solver.
```

Public Types

```
enum StateOrdering
    KLU state reordering (different from SuperLUMT ordering!)

    Values:

    enumerator AMD
    enumerator COLAMD
    enumerator natural
```

Public Functions

```
SUNLinSolKLU(N_Vector x, SUNMatrix A)
    Create KLU solver with given matrix.
```

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **A** – sparse matrix

```
SUNLinSolKLU(amiVector const &x, int nnz, int sparsetype, StateOrdering ordering)
    Create KLU solver and matrix to operate on.
```

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **nnz** – Number of non-zeros in matrix A
- **sparsetype** – Sparse matrix type (CSC_MAT, CSR_MAT)
- **ordering** –

```
virtual SUNMatrix getMatrix() const override
    Get the matrix A (matrix solvers only).
```

Returns A

void **reInit**(int nnz, int reinit_type)

Reinitializes memory and flags for a new factorization (symbolic and numeric) to be conducted at the next solver setup call.

For more details see sunlinsol/sunlinsol_klu.h

Parameters

- **nnz** – Number of non-zeros
- **reinit_type** – SUNKLU_REINIT_FULL or SUNKLU_REINIT_PARTIAL

void **setOrdering**(*StateOrdering* ordering)

Sets the ordering used by KLU for reducing fill in the linear solve.

Parameters **ordering** –**Class SUNLinSolPCG**

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships**Base Type**

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

```
class amici::SUNLinSolPCG : public amici::SUNLinSolWrapper
```

SUNDIALS scaled preconditioned CG (Conjugate Gradient method) (PCG) solver.

Public Functions

SUNLinSolPCG(N_Vector y, int pretype, int maxl)

Create PCG solver.

Parameters

- **y** –
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

int **setATimes**(void *A_data, ATimesFn ATimes)

Sets the function pointer for ATimes (see sundials/sundials_linearsolver.h).

Parameters

- **A_data** –
- **ATimes** –

Returns

int **setPreconditioner**(void *P_data, PSetupFn Pset, PSolveFn Psol)

Sets function pointers for PSetup and PSolve routines inside of iterative linear solver objects (see sundials/sundials_linearsolver.h).

Parameters

- **P_data** –
- **Pset** –
- **Psol** –

Returns

int **setScalingVectors**(N_Vector s, N_Vector nul)

Sets pointers to left/right scaling vectors for the linear system solve (see sundials/sundials_linearsolver.h).

Parameters

- **s** –
- **nul** –

Returns

int **getNumIters**() const

Returns the number of linear iterations performed in the last ‘Solve’ call.

Returns Number of iterations

realtype **getResNorm**() const

Returns the final residual norm from the last ‘Solve’ call.

Returns residual norm

N_Vector **getResid**() const

Get preconditioned initial residual (see sundials/sundials_linearsolver.h).

Returns**Class SUNLinSolSPBCGS**

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships**Base Type**

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolSPBCGS : public amici::SUNLinSolWrapper
 SUNDIALS scaled preconditioned Bi-CGStab (Bi-Conjugate Gradient Stable method) (SPBCGS) solver.

Public Functions

explicit SUNLinSolSPBCGS(N_Vector x, int pretype = PREC_NONE, int maxl =
 SUNSPBCGS_MAXL_DEFAULT)
SUNLinSolSPBCGS.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

explicit SUNLinSolSPBCGS(*AmiVector* const &x, int pretype = PREC_NONE, int maxl =
 SUNSPBCGS_MAXL_DEFAULT)
SUNLinSolSPBCGS.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

int **setATimes**(void *A_data, ATimesFn ATimes)
 Sets the function pointer for ATimes (see sundials/sundials_linearsolver.h).

Parameters

- **A_data** –
- **ATimes** –

Returns

int **setPreconditioner**(void *P_data, PSetupFn Pset, PSolveFn Psol)
 Sets function pointers for PSetup and PSolve routines inside of iterative linear solver objects (see sundials/sundials_linearsolver.h).

Parameters

- **P_data** –
- **Pset** –
- **Psol** –

Returns

int **setScalingVectors**(N_Vector s, N_Vector nul)
 Sets pointers to left/right scaling vectors for the linear system solve (see sundials/sundials_linearsolver.h).

Parameters

- **s** –

- **nul** –

Returns

int **getNumIters()** const

Returns the number of linear iterations performed in the last ‘Solve’ call.

Returns Number of iterations

realtype **getResNorm()** const

Returns the final residual norm from the last ‘Solve’ call.

Returns residual norm

N_Vector **getResid()** const

Get preconditioned initial residual (see sundials/sundials_linearsolver.h).

Returns

Class SUNLinSolSPFGMR

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolSPFGMR : public amici::SUNLinSolWrapper

SUNDIALS scaled preconditioned FGMRES (Flexible Generalized Minimal Residual method) (SPFGMR) solver.

Public Functions

SUNLinSolSPFGMR(*AmiVector* const &x, int pretype, int maxl)

SUNLinSolSPFGMR.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

int **setATimes**(void *A_data, ATimesFn ATimes)

Sets the function pointer for ATimes (see sundials/sundials_linearsolver.h).

Parameters

- **A_data** –
- **ATimes** –

Returns

int **setPreconditioner**(void *P_data, PSetupFn Pset, PSolveFn Psol)

Sets function pointers for PSetup and PSolve routines inside of iterative linear solver objects (see sundials/sundials_linearsolver.h).

Parameters

- **P_data** –
- **Pset** –
- **Psol** –

Returns

int **setScalingVectors**(N_Vector s, N_Vector nul)

Sets pointers to left/right scaling vectors for the linear system solve (see sundials/sundials_linearsolver.h).

Parameters

- **s** –
- **nul** –

Returns

int **getNumIters**() const

Returns the number of linear iterations performed in the last ‘Solve’ call.

Returns Number of iterations

realtype **getResNorm**() const

Returns the final residual norm from the last ‘Solve’ call.

Returns residual norm

N_Vector **getResid**() const

Get preconditioned initial residual (see sundials/sundials_linearsolver.h).

Returns**Class SUNLinSolSPGMR**

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships**Base Type**

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolSPGMR : public amici::SUNLinSolWrapper
SUNDIALS scaled preconditioned GMRES (Generalized Minimal Residual method) solver (SPGMR).

Public Functions

explicit SUNLinSolSPGMR(*AmiVector* const &x, int pretype = PREC_NONE, int maxl =
SUNSPGMR_MAXL_DEFAULT)

Create SPGMR solver.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

int setATimes(void *A_data, ATimesFn ATimes)

Sets the function pointer for ATimes (see sundials/sundials_linearsolver.h).

Parameters

- **A_data** –
- **ATimes** –

Returns

int setPreconditioner(void *P_data, PSetupFn Pset, PSolveFn Psol)

Sets function pointers for Pset and Psolve routines inside of iterative linear solver objects (see sundials/sundials_linearsolver.h).

Parameters

- **P_data** –
- **Pset** –
- **Psol** –

Returns

int setScalingVectors(N_Vector s, N_Vector nul)

Sets pointers to left/right scaling vectors for the linear system solve (see sundials/sundials_linearsolver.h).

Parameters

- **s** –
- **nul** –

Returns

int getNumIters() const

Returns the number of linear iterations performed in the last ‘Solve’ call.

Returns Number of iterations

realtype getResNorm() const

Returns the final residual norm from the last ‘Solve’ call.

Returns residual norm

N_Vector **getResid()** const

Get preconditioned initial residual (see sundials/sundials_linearsolver.h).

Returns

Class SUNLinSolSPTFQMR

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNLinSolWrapper (*Class SUNLinSolWrapper*)

Class Documentation

class amici::SUNLinSolSPTFQMR : public amici::SUNLinSolWrapper
SUNDIALS scaled preconditioned TFQMR (Transpose-Free Quasi-Minimal Residual method) (SPTFQMR) solver.

Public Functions

explicit SUNLinSolSPTFQMR(N_Vector x, int pretype = PREC_NONE, int maxl = SUNSPTFQMR_MAXL_DEFAULT)

Create SPTFQMR solver.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

explicit SUNLinSolSPTFQMR(*AmiVector* const &x, int pretype = PREC_NONE, int maxl = SUNSPTFQMR_MAXL_DEFAULT)

Create SPTFQMR solver.

Parameters

- **x** – A template for cloning vectors needed within the solver.
- **pretype** – Preconditioner type (PREC_NONE, PREC_LEFT, PREC_RIGHT, PREC_BOTH)
- **maxl** – Maximum number of solver iterations

int **setATimes**(void *A_data, ATimesFn ATimes)

Sets the function pointer for ATimes (see sundials/sundials_linearsolver.h).

Parameters

- **A_data** –
- **ATimes** –

Returns

int **setPreconditioner**(void *P_data, PSetupFn Pset, PSolveFn Psol)

Sets function pointers for PSetup and PSolve routines inside of iterative linear solver objects (see sundials/sundials_linearsolver.h).

Parameters

- **P_data** –
- **Pset** –
- **Psol** –

Returns

int **setScalingVectors**(N_Vector s, N_Vector nul)

Sets pointers to left/right scaling vectors for the linear system solve (see sundials/sundials_linearsolver.h).

Parameters

- **s** –
- **nul** –

Returns

int **getNumIters**() const

Returns the number of linear iterations performed in the last ‘Solve’ call.

Returns Number of iterations

realtype **getResNorm**() const

Returns the final residual norm from the last ‘Solve’ call.

Returns residual norm

N_Vector **getResid**() const

Get preconditioned initial residual (see sundials/sundials_linearsolver.h).

Returns

Class SUNLinSolWrapper

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Derived Types

- public amici::SUNLinSolBand (*Class SUNLinSolBand*)
- public amici::SUNLinSolDense (*Class SUNLinSolDense*)
- public amici::SUNLinSolKLU (*Class SUNLinSolKLU*)
- public amici::SUNLinSolPCG (*Class SUNLinSolPCG*)
- public amici::SUNLinSolSPBCGS (*Class SUNLinSolSPBCGS*)

- public amici::SUNLinSolSPFGMR (*Class SUNLinSolSPFGMR*)
- public amici::SUNLinSolSPGMR (*Class SUNLinSolSPGMR*)
- public amici::SUNLinSolSPTFQMR (*Class SUNLinSolSPTFQMR*)

Class Documentation

class amici::SUNLinSolWrapper

A RAII wrapper for SUNLinearSolver structs.

For details on member functions see documentation in sunlinSol/sundials_linearsolver.h.

Subclassed by *amici::SUNLinSolBand*, *amici::SUNLinSolDense*, *amici::SUNLinSolKLU*, *amici::SUNLinSolPCG*, *amici::SUNLinSolSPBCGS*, *amici::SUNLinSolSPFGMR*, *amici::SUNLinSolSPGMR*, *amici::SUNLinSolSPTFQMR*

Public Functions

SUNLinSolWrapper() = default

explicit **SUNLinSolWrapper**(SUNLinearSolver linsol)
Wrap existing SUNLinearSolver.

Parameters *linsol* –

virtual **~SUNLinSolWrapper()**

SUNLinSolWrapper(const *SUNLinSolWrapper* &other) = delete
Copy constructor.

Parameters *other* –

SUNLinSolWrapper(*SUNLinSolWrapper* &&other) noexcept
Move constructor.

Parameters *other* –

SUNLinSolWrapper &**operator=**(const *SUNLinSolWrapper* &other) = delete
Copy assignment.

Parameters *other* –

Returns

SUNLinSolWrapper &**operator=**(*SUNLinSolWrapper* &&other) noexcept
Move assignment.

Parameters *other* –

Returns

SUNLinearSolver **get**() const
Returns the wrapped SUNLinSol.

Returns SUNLinearSolver

SUNLinearSolver_Type **getType**() const
Returns an identifier for the linear solver type.

Returns

void **setup**(SUNMatrix A) const

Performs any linear solver setup needed, based on an updated system matrix A.

Parameters A –

void **setup**(const *SUNMatrixWrapper* &A) const

Performs any linear solver setup needed, based on an updated system matrix A.

Parameters A –

int **Solve**(SUNMatrix A, N_Vector x, N_Vector b, *realtype* tol) const

Solves a linear system $A \cdot x = b$.

Parameters

- **A** –
- **x** – A template for cloning vectors needed within the solver.
- **b** –
- **tol** – Tolerance (weighted 2-norm), iterative solvers only

Returns error flag

long int **getLastFlag**() const

Returns the last error flag encountered within the linear solver.

Returns error flag

int **space**(long int *lenrwLS, long int *leniwLS) const

Returns the integer and real workspace sizes for the linear solver.

Parameters

- **lenrwLS** – output argument for size of real workspace
- **leniwLS** – output argument for size of integer workspace

Returns workspace size

virtual SUNMatrix **getMatrix**() const

Get the matrix A (matrix solvers only).

Returns A

Protected Functions

int **initialize**()

Performs linear solver initialization (assumes that all solver-specific options have been set).

Returns error code

Protected Attributes

SUNLinearSolver **solver_** = {nullptr}
 Wrapped solver

Class SUNMatrixWrapper

- Defined in file `_include_amici_sundials_matrix_wrapper.h`

Class Documentation

class amici::SUNMatrixWrapper

A RAII wrapper for SUNMatrix structs.

This can create dense, sparse, or banded matrices using the respective constructor.

Public Functions

SUNMatrixWrapper() = default

SUNMatrixWrapper(sunindextype M, sunindextype N, sunindextype NNZ, int sparsetype)
 Create sparse matrix. See SUNSparseMatrix in `sunmatrix_sparse.h`.

Parameters

- **M** – Number of rows
- **N** – Number of columns
- **NNZ** – Number of nonzeros
- **sparsetype** – Sparse type

SUNMatrixWrapper(sunindextype M, sunindextype N)
 Create dense matrix. See SUNDenseMatrix in `sunmatrix_dense.h`.

Parameters

- **M** – Number of rows
- **N** – Number of columns

SUNMatrixWrapper(sunindextype M, sunindextype ubw, sunindextype lbw)
 Create banded matrix. See SUNBandMatrix in `sunmatrix_band.h`.

Parameters

- **M** – Number of rows and columns
- **ubw** – Upper bandwidth
- **lbw** – Lower bandwidth

SUNMatrixWrapper(const *SUNMatrixWrapper* &A, *realtype* droptol, int sparsetype)
 Create sparse matrix from dense or banded matrix. See SUNSparseFromDenseMatrix and SUNSparseFromBandMatrix in `sunmatrix_sparse.h`.

Parameters

- **A** – Wrapper for dense matrix
- **droptol** – tolerance for dropping entries
- **sparsetype** – Sparse type

explicit **SUNMatrixWrapper**(SUNMatrix mat)

Wrap existing SUNMatrix.

Parameters **mat** –

~SUNMatrixWrapper()

SUNMatrixWrapper(const *SUNMatrixWrapper* &other)

Copy constructor.

Parameters **other** –

SUNMatrixWrapper(*SUNMatrixWrapper* &&other)

Move constructor.

Parameters **other** –

SUNMatrixWrapper &**operator=**(const *SUNMatrixWrapper* &other)

Copy assignment.

Parameters **other** –

Returns

SUNMatrixWrapper &**operator=**(*SUNMatrixWrapper* &&other)

Move assignment.

Parameters **other** –

Returns

void **reallocate**(sunindextype nnz)

Reallocate space for sparse matrix according to specified nnz.

Parameters **nnz** – new number of nonzero entries

void **realloc**()

Reallocate space for sparse matrix to used space according to last entry in indexptrs.

SUNMatrix **get**() const

Get the wrapped SUNMatrix.

Note: Even though the returned `matrix_` pointer is const qualified, `matrix_->content` will not be const. This is a shortcoming in the underlying C library, which we cannot address and it is not intended that any of those values are modified externally. If `matrix_->content` is manipulated, `cpp:meth:SUNMatrixWrapper:refresh` needs to be called.

Returns raw SunMatrix object

inline sunindextype **rows**() const

Get the number of rows.

Returns number of rows

inline sunindextype **columns**() const

Get the number of columns.

Returns number of columns

sunindextype **num_nonzeros**() const

Get the number of specified non-zero elements (sparse matrices only)

Note: value will be 0 before `indexptrs` are set.

Returns number of nonzero entries

sunindextype **num_indexptrs**() const

Get the number of `indexptrs` that can be specified (sparse matrices only)

Returns number of `indexptrs`

sunindextype **capacity**() const

Get the number of allocated data elements.

Returns number of allocated entries

realtype ***data**()

Get raw data of a sparse matrix.

Returns pointer to first data entry

const *realtype* ***data**() const

Get const raw data of a sparse matrix.

Returns pointer to first data entry

inline *realtype* **get_data**(sunindextype `idx`) const

Get data of a sparse matrix.

Parameters `idx` – data index

Returns `idx`-th data entry

inline *realtype* **get_data**(sunindextype `irow`, sunindextype `icol`) const

Get data entry for a dense matrix.

Parameters

- `irow` – row
- `icol` – col

Returns `A(irow,icol)`

inline void **set_data**(sunindextype `idx`, *realtype* `data`)

Set data entry for a sparse matrix.

Parameters

- `idx` – data index
- `data` – data for `idx`-th entry

inline void **set_data**(sunindextype `irow`, sunindextype `icol`, *realtype* `data`)

Set data entry for a dense matrix.

Parameters

- `irow` – row
- `icol` – col

- **data** – data for idx-th entry

inline sunindextype **get_indexval**(sunindextype idx) const
Get the index value of a sparse matrix.

Parameters **idx** – data index

Returns row (CSC) or column (CSR) for idx-th data entry

inline void **set_indexval**(sunindextype idx, sunindextype val)
Set the index value of a sparse matrix.

Parameters

- **idx** – data index
- **val** – row (CSC) or column (CSR) for idx-th data entry

inline void **set_indexvals**(const gsl::span<const sunindextype> vals)
Set the index values of a sparse matrix.

Parameters **vals** – rows (CSC) or columns (CSR) for data entries

inline sunindextype **get_indexptr**(sunindextype ptr_idx) const
Get the index pointer of a sparse matrix.

Parameters **ptr_idx** – pointer index

Returns index where the ptr_idx-th column (CSC) or row (CSR) starts

inline void **set_indexptr**(sunindextype ptr_idx, sunindextype ptr)
Set the index pointer of a sparse matrix.

Parameters

- **ptr_idx** – pointer index
- **ptr** – data-index where the ptr_idx-th column (CSC) or row (CSR) starts

inline void **set_indexptrs**(const gsl::span<const sunindextype> ptrs)
Set the index pointers of a sparse matrix.

Parameters **ptrs** – starting data-indices where the columns (CSC) or rows (CSR) start

int **sparsetype**() const
Get the type of sparse matrix.

Returns matrix type

void **scale**(*realtype* a)
multiply with a scalar (in-place)

Parameters **a** – scalar value to multiply matrix

void **multiply**(N_Vector c, *const_N_Vector* b, *realtype* alpha = 1.0) const
N_Vector interface for multiply.

Parameters

- **c** – output vector, may already contain values
- **b** – multiplication vector
- **alpha** – scalar coefficient for matrix

inline void **multiply**(*AmiVector* &c, *AmiVector* const &b, *realtype* alpha = 1.0) const
AmiVector interface for multiply.

Parameters

- **c** – output vector, may already contain values
- **b** – multiplication vector
- **alpha** – scalar coefficient for matrix

void **multiply**(gsl::span<*realtype*> c, gsl::span<const *realtype*> b, const *realtype* alpha = 1.0) const
 Perform matrix vector multiplication $c += \text{alpha} * A * b$.

Parameters

- **c** – output vector, may already contain values
- **b** – multiplication vector
- **alpha** – scalar coefficient

void **multiply**(N_Vector c, const N_Vector b, gsl::span<const int> cols, bool transpose) const
 Perform reordered matrix vector multiplication $c += A[:, \text{cols}] * b$.

Parameters

- **c** – output vector, may already contain values
- **b** – multiplication vector
- **cols** – int vector for column reordering
- **transpose** – bool transpose A before multiplication

void **multiply**(gsl::span<*realtype*> c, gsl::span<const *realtype*> b, gsl::span<const int> cols, bool transpose) const
 Perform reordered matrix vector multiplication $c += A[:, \text{cols}] * b$.

Parameters

- **c** – output vector, may already contain values
- **b** – multiplication vector
- **cols** – int vector for column reordering
- **transpose** – bool transpose A before multiplication

void **sparse_multiply**(SUNMatrixWrapper &C, const SUNMatrixWrapper &B) const
 Perform matrix matrix multiplication $C = A * B$ for sparse A, B, C.

Note: will overwrite existing data, indexptrs, indexvals for C, but will use preallocated space for these vars

Parameters

- **C** – output matrix,
- **B** – multiplication matrix

void **sparse_add**(const SUNMatrixWrapper &A, *realtype* alpha, const SUNMatrixWrapper &B, *realtype* beta)
 Perform sparse matrix matrix addition $C = \text{alpha} * A + \text{beta} * B$.

Note: will overwrite existing data, indexptrs, indexvals for C, but will use preallocated space for these vars

Parameters

- **A** – addition matrix
- **alpha** – scalar A
- **B** – addition matrix
- **beta** – scalar B

```
void sparse_sum(const std::vector<SUNMatrixWrapper> &mats)  
    Perform matrix-matrix addition  $A = \text{sum}(\text{mats}(0) \dots \text{mats}(\text{len}(\text{mats})))$ 
```

Note: will overwrite existing data, `indexptrs`, `indexvals` for A, but will use preallocated space for these vars

Parameters **mats** – vector of sparse matrices

```
sunindextype scatter(const sunindextype k, const realtype beta, sunindextype *w, gsl::span<realtype> x,  
    const sunindextype mark, SUNMatrixWrapper *C, sunindextype nnz) const  
    Compute  $x = x + \text{beta} * A(:,k)$ , where x is a dense vector and  $A(:,k)$  is sparse, and update the sparsity pattern  
    for  $C(:,j)$  if applicable.
```

This function currently has two purposes:

- perform parts of sparse matrix-matrix multiplication $C(:,j)=A(:,k)*B(k,j)$ enabled by passing $\text{beta}=B(k,j)$, $x=C(:,j)$, $C=C$, $w=\text{sparsity of } C(:,j)$ from $B(k,0 \dots j-1)$, $\text{nnz}=\text{nnz}(C(:,0 \dots j-1))$
- add the k-th column of the sparse matrix A multiplied by beta to the dense vector x. enabled by passing $\text{beta}=*$, $x=x$, $C=\text{nullptr}$, $w=\text{nullptr}$, $\text{nnz}=*$

Parameters

- **k** – column index
- **beta** – scaling factor
- **w** – index workspace, ($w[i]<\text{mark}$) indicates non-zerosness of $C(i,j)$ (dimension: m), if this is a nullptr, sparsity pattern of C will not be updated (if applicable).
- **x** – dense output vector (dimension: m)
- **mark** – marker for w to indicate nonzero pattern
- **C** – sparse output matrix, if this is a nullptr, sparsity pattern of C will not be updated
- **nnz** – number of nonzeros that were already written to C

Returns updated number of nonzeros in C

```
void transpose(SUNMatrixWrapper &C, const realtype alpha, sunindextype blocksize) const  
    Compute transpose  $A'$  of sparse matrix A and writes it to the matrix  $C = \text{alpha} * A'$ .
```

Parameters

- **C** – output matrix (sparse or dense)
- **alpha** – scalar multiplier
- **blocksize** – blocksize for transposition. For full matrix transpose set to `ncols/nrows`

void **to_dense**(*SUNMatrixWrapper* &D) const
Writes a sparse matrix A to a dense matrix D.

Parameters **D** – dense output matrix

void **to_diag**(N_Vector v) const
Writes the diagonal of sparse matrix A to a dense vector v.

Parameters **v** – dense output vector

void **zero**()
Set to 0.0, for sparse matrices also resets indexptr/indexvals.

inline SUNMatrix_ID **matrix_id**() const
Get matrix id.

Returns SUNMatrix_ID

void **refresh**()
Update internal cache, needs to be called after external manipulation of matrix_→content.

Class SUNNonLinSolFixedPoint

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNNonLinSolWrapper (*Class SUNNonLinSolWrapper*)

Class Documentation

class amici::SUNNonLinSolFixedPoint : public amici::SUNNonLinSolWrapper
SUNDIALS Fixed point non-linear solver to solve $G(y) = y$.

Public Functions

explicit SUNNonLinSolFixedPoint(*const N_Vector* x, int m = 0)
Create fixed-point solver.

Parameters

- **x** – template for cloning vectors needed within the solver.
- **m** – number of acceleration vectors to use

SUNNonLinSolFixedPoint(int count, *const N_Vector* x, int m = 0)
Create fixed-point solver for use with sensitivity analysis.

Parameters

- **count** – Number of vectors in the nonlinear solve. When integrating a system containing N_s sensitivities the value of count is:
– N_s+1 if using a simultaneous corrector approach.

- Ns if using a staggered corrector approach.
- **x** – template for cloning vectors needed within the solver.
- **m** – number of acceleration vectors to use

int **getSysFn**(SUNNonlinSolSysFn *SysFn) const
 Get function to evaluate the fixed point function $G(y) = y$.

Parameters **SysFn** –

Returns

Class SUNNonLinSolNewton

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Base Type

- public amici::SUNNonLinSolWrapper (*Class SUNNonLinSolWrapper*)

Class Documentation

class amici::SUNNonLinSolNewton : public amici::SUNNonLinSolWrapper
 SUNDIALS Newton non-linear solver to solve $F(y) = 0$.

Public Functions

explicit **SUNNonLinSolNewton**(N_Vector x)
 Create Newton solver.

Parameters **x** – A template for cloning vectors needed within the solver.

SUNNonLinSolNewton(int count, N_Vector x)
 Create Newton solver for enabled sensitivity analysis.

Parameters

- **count** – Number of vectors in the nonlinear solve. When integrating a system containing Ns sensitivities the value of count is:
 - Ns+1 if using a simultaneous corrector approach.
 - Ns if using a staggered corrector approach.
- **x** – A template for cloning vectors needed within the solver.

int **getSysFn**(SUNNonlinSolSysFn *SysFn) const
 Get function to evaluate the nonlinear residual function $F(y) = 0$.

Parameters **SysFn** –

Returns

Class SUNNonLinSolWrapper

- Defined in file_include_amici_sundials_linsol_wrapper.h

Inheritance Relationships

Derived Types

- public amici::SUNNonLinSolFixedPoint (*Class SUNNonLinSolFixedPoint*)
- public amici::SUNNonLinSolNewton (*Class SUNNonLinSolNewton*)

Class Documentation

class amici::SUNNonLinSolWrapper

A RAI wrapper for SUNNonLinearSolver structs which solve the nonlinear system $F(y) = 0$ or $G(y) = y$.

Subclassed by *amici::SUNNonLinSolFixedPoint*, *amici::SUNNonLinSolNewton*

Public Functions

explicit SUNNonLinSolWrapper(SUNNonlinearSolver sol)

SUNNonLinSolWrapper from existing SUNNonlinearSolver.

Parameters sol –

virtual ~SUNNonLinSolWrapper()

SUNNonLinSolWrapper(const *SUNNonLinSolWrapper* &other) = delete

Copy constructor.

Parameters other –

SUNNonLinSolWrapper(*SUNNonLinSolWrapper* &&other) noexcept

Move constructor.

Parameters other –

SUNNonLinSolWrapper &operator=(const *SUNNonLinSolWrapper* &other) = delete

Copy assignment.

Parameters other –

Returns

SUNNonLinSolWrapper &operator=(*SUNNonLinSolWrapper* &&other) noexcept

Move assignment.

Parameters other –

Returns

SUNNonlinearSolver get() const

Get the wrapped SUNNonlinearSolver.

Returns SUNNonlinearSolver

SUNNonlinearSolver_Type **getType()** const
Get type ID of the solver.

Returns

int **setup**(N_Vector y, void *mem)
Setup solver.

Parameters

- **y** – the initial iteration passed to the nonlinear solver.
- **mem** – the sundials integrator memory structure.

Returns

int **Solve**(N_Vector y0, N_Vector y, N_Vector w, *realtype* tol, bool callLSetup, void *mem)
Solve the nonlinear system $F(y) = 0$ or $G(y) = y$.

Parameters

- **y0** – the initial iterate for the nonlinear solve. This must remain unchanged throughout the solution process.
- **y** – the solution to the nonlinear system
- **w** – the solution error weight vector used for computing weighted error norms.
- **tol** – the requested solution tolerance in the weighted root-mean- squared norm.
- **callLSetup** – a flag indicating that the integrator recommends for the linear solver setup function to be called.
- **mem** – the sundials integrator memory structure.

Returns

int **setSysFn**(SUNNonlinSolSysFn SysFn)
Set function to evaluate the nonlinear residual function $F(y) = 0$ or the fixed point function $G(y) = y$.

Parameters SysFn –

Returns

int **setLSetupFn**(SUNNonlinSolLSetupFn SetupFn)
Set linear solver setup function.

Parameters SetupFn –

Returns

int **setLSolveFn**(SUNNonlinSolLSolveFn SolveFn)
Set linear solver solve function.

Parameters SolveFn –

Returns

int **setConvTestFn**(SUNNonlinSolConvTestFn CTestFn, void *ctest_data)
Set function to test for convergence.

Parameters

- **CTestFn** –
- **ctest_data** –

Returns

int **setMaxIters**(int maxiters)

Set maximum number of non-linear iterations.

Parameters **maxiters** –

Returns

long int **getNumIters**() const

getNumIters

Returns

int **getCurIter**() const

getCurIter

Returns

long int **getNumConvFails**() const

getNumConvFails

Returns

Protected Functions

void **initialize**()

initialize

Protected Attributes

SUNNonlinearSolver **solver** = nullptr

the wrapper solver

Enums

Enum BLASLayout

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::**BLASLayout**

BLAS Matrix Layout, affects dgemm and gemv calls

Values:

enumerator **rowMajor**

enumerator **colMajor**

Enum BLASTranspose

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::BLASTranspose

BLAS Matrix Transposition, affects dgemm and gemv calls

Values:

enumerator **noTrans**

enumerator **trans**

enumerator **conjTrans**

Enum FixedParameterContext

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::FixedParameterContext

fixedParameter to be used in condition context

Values:

enumerator **simulation**

enumerator **preequilibration**

enumerator **presimulation**

Enum InternalSensitivityMethod

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::InternalSensitivityMethod

CVODES/IDAS forward sensitivity computation method

Values:

enumerator **simultaneous**

enumerator **staggered**

enumerator **staggered1**

Enum InterpolationType

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::InterpolationType

CVODES/IDAS state interpolation for adjoint sensitivity analysis

Values:

enumerator **hermite**

enumerator **polynomial**

Enum LinearMultistepMethod

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::LinearMultistepMethod

CVODES/IDAS linear multistep method

Values:

enumerator **adams**

enumerator **BDF**

Enum LinearSolver

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::LinearSolver

linear solvers for CVODES/IDAS

Values:

enumerator **dense**

enumerator **band**

enumerator **LAPACKDense**

enumerator **LAPACKBand**

enumerator **diag**

enumerator **SPGMR**

enumerator **SPBCG**

enumerator **SPTFQMR**

enumerator **KLU**

enumerator **SuperLUMT**

Enum **NewtonDampingFactorMode**

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::**NewtonDampingFactorMode**
Damping factor flag for the Newton method
Values:

enumerator **off**

enumerator **on**

Enum **NonlinearSolverIteration**

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::**NonlinearSolverIteration**
CVODES/IDAS Nonlinear Iteration method
Values:

enumerator **functional**

enumerator **fixedpoint**
deprecated

enumerator **newton**

Enum ObservableScaling

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::ObservableScaling
modes for observable scaling

Values:

enumerator **lin**

enumerator **log**

enumerator **log10**

Enum ParameterScaling

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::ParameterScaling
modes for parameter transformations

Values:

enumerator **none**

enumerator **ln**

enumerator **log10**

Enum RDataReporting

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::RDataReporting
Values:

enumerator **full**

enumerator **residuals**

enumerator **likelihood**

Enum SecondOrderMode

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SecondOrderMode
modes for second order sensitivity analysis

Values:

enumerator **none**

enumerator **full**

enumerator **directional**

Enum SensitivityMethod

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SensitivityMethod
methods for sensitivity computation

Values:

enumerator **none**

enumerator **forward**

enumerator **adjoint**

Enum SensitivityOrder

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SensitivityOrder
orders of sensitivity analysis

Values:

enumerator **none**

enumerator **first**

enumerator **second**

Enum SteadyStateContext

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SteadyStateContext

Context for which the sensitivity flag should be computed

Values:

enumerator **newtonSensi**

enumerator **sensiStorage**

enumerator **solverCreation**

Enum SteadyStateSensitivityMode

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SteadyStateSensitivityMode

Sensitivity computation mode in steadyStateProblem

Values:

enumerator **newtonOnly**

enumerator **integrationOnly**

enumerator **integrateIfNewtonFails**

Enum SteadyStateStatus

- Defined in file_include_amici_defines.h

Enum Documentation

enum amici::SteadyStateStatus

State in which the steady state computation finished

Values:

enumerator **failed_too_long_simulation**

enumerator **failed_damping**

enumerator **failed_factorization**

enumerator **failed_convergence**
enumerator **failed**
enumerator **not_run**
enumerator **success**

Functions

Function amici::amici_daxpy

- Defined in file_include_amici_cblas.h

Function Documentation

void amici::amici_daxpy(int n, double alpha, const double *x, int incx, double *y, int incy)
Compute $y = a*x + y$.

Parameters

- **n** – number of elements in y
- **alpha** – scalar coefficient of x
- **x** – vector of length n*incx
- **incx** – x stride
- **y** – vector of length n*incy
- **incy** – y stride

Function amici::amici_dgemm

- Defined in file_include_amici_cblas.h

Function Documentation

void amici::amici_dgemm(*BLASLayout* layout, *BLASTranspose* TransA, *BLASTranspose* TransB, int M, int N, int K, double alpha, const double *A, int lda, const double *B, int ldb, double beta, double *C, int ldc)

CBLAS matrix matrix multiplication (dgemm)

This routines computes $C = \alpha * A * B + \beta * C$ with A: [MxK] B:[KxN] C:[MxN]

Parameters

- **layout** – memory layout.
- **TransA** – flag indicating whether A should be transposed before multiplication
- **TransB** – flag indicating whether B should be transposed before multiplication
- **M** – number of rows in A/C
- **N** – number of columns in B/C

- **K** – number of rows in B, number of columns in A
- **alpha** – coefficient alpha
- **A** – matrix A
- **lda** – leading dimension of A ($\geq M$ or $\geq K$)
- **B** – matrix B
- **ldb** – leading dimension of B ($\geq K$ or $\geq N$)
- **beta** – coefficient beta
- **C** – matrix C
- **ldc** – leading dimension of C ($\geq M$ or $\geq N$)

Function amici::amici_dgemv

- Defined in file_include_amici_cblas.h

Function Documentation

void amici::amici_dgemv(*BLASLayout* layout, *BLASTranspose* TransA, int M, int N, double alpha, const double *A, int lda, const double *X, int incX, double beta, double *Y, int incY)

CBLAS matrix vector multiplication (dgemv).

Computes $y = \alpha * A * x + \beta * y$ with A: [MxN] x:[Nx1] y:[Mx1]

Parameters

- **layout** – Matrix layout, column major or row major.
- **TransA** – flag indicating whether A should be transposed before multiplication
- **M** – number of rows in A
- **N** – number of columns in A
- **alpha** – coefficient alpha
- **A** – matrix A
- **lda** – leading dimension / stride of A ($\geq N$ if row-major, $\geq M$ if col-major)
- **X** – vector X
- **incX** – increment for entries of X
- **beta** – coefficient beta
- **Y** – vector Y
- **incY** – increment for entries of Y

Function amici::backtraceString

- Defined in file_include_amici_misc.h

Function Documentation

std::string amici::backtraceString(int maxFrames)

Returns the current backtrace as std::string.

Parameters **maxFrames** – Number of frames to include

Returns Backtrace

Template Function amici::checkBufferSize

- Defined in file_include_amici_misc.h

Function Documentation

template<class T>

void amici::checkBufferSize(gsl::span<T> buffer, typename gsl::span<T>::index_type expected_size)

local helper to check whether the provided buffer has the expected size

Parameters

- **buffer** – buffer to which values are to be written
- **expected_size** – expected size of the buffer

Function amici::checkSigmaPositivity(std::vector<realtype> const &sigmaVector, const char *vectorName)

- Defined in file_include_amici_edata.h

Function Documentation

void amici::checkSigmaPositivity(std::vector<realtype> const &sigmaVector, const char *vectorName)

checks input vector of sigmas for not strictly positive values

Parameters

- **sigmaVector** – vector input to be checked
- **vectorName** – name of the input

Function amici::checkSigmaPositivity(realtype sigma, const char *sigmaName)

- Defined in file_include_amici_edata.h

Function Documentation

void amici::checkSigmaPositivity(*realtype* sigma, const char *sigmaName)
checks input scalar sigma for not strictly positive value

Parameters

- **sigma** – input to be checked
- **sigmaName** – name of the input

Template Function amici::deserializeFromChar

- Defined in file_include_amici_serialization.h

Function Documentation

template<typename T>
T amici::deserializeFromChar(const char *buffer, int size)
Deserialize object that has been serialized using serializeToChar.

Parameters

- **buffer** – serialized object
- **size** – length of buffer

Returns The deserialized object

Template Function amici::deserializeFromString

- Defined in file_include_amici_serialization.h

Function Documentation

template<typename T>
T amici::deserializeFromString(std::string const &serialized)
Deserialize object that has been serialized using serializeToString.

Parameters **serialized** – serialized object

Returns The deserialized object

Function amici::dotProd

- Defined in file_include_amici_vector.h

Function Documentation

inline *realtype* amici::dotProd(*AmiVector* const &x, *AmiVector* const &y)
 Compute dot product of x and y.

Parameters

- **x** – vector
- **y** – vector

Returns dot product of x and y

Function amici::getScaledParameter

- Defined in file_include_amici_misc.h

Function Documentation

double amici::getScaledParameter(double unscaledParameter, *ParameterScaling* scaling)
 Apply parameter scaling according to scaling

Parameters

- **unscaledParameter** –
- **scaling** – parameter scaling

Returns Scaled parameter

Function amici::getUnscaledParameter

- Defined in file_include_amici_misc.h

Function Documentation

double amici::getUnscaledParameter(double scaledParameter, *ParameterScaling* scaling)
 Remove parameter scaling according to scaling

Parameters

- **scaledParameter** – scaled parameter
- **scaling** – parameter scaling

Returns Unscaled parameter

Function amici::hdf5::attributeExists(H5::H5File const &file, const std::string &optionsObject, const std::string &attributeName)

- Defined in file_include_amici_hdf5.h

Function Documentation

bool amici::hdf5::attributeExists(H5::H5File const &file, const std::string &optionsObject, const std::string &attributeName)

Check whether an attribute with the given name exists on the given dataset.

Parameters

- **file** – The HDF5 file object
- **optionsObject** – Dataset of which attributes should be checked
- **attributeName** – Name of the attribute of interest

Returns true if attribute exists, false otherwise

Function amici::hdf5::attributeExists(H5::H5Object const &object, const std::string &attributeName)

- Defined in file_include_amici_hdf5.h

Function Documentation

bool amici::hdf5::attributeExists(H5::H5Object const &object, const std::string &attributeName)

Check whether an attribute with the given name exists on the given object.

Parameters

- **object** – An HDF5 object
- **attributeName** – Name of the attribute of interest

Returns true if attribute exists, false otherwise

Function amici::hdf5::createAndWriteDouble1DDataset

- Defined in file_include_amici_hdf5.h

Function Documentation

void amici::hdf5::createAndWriteDouble1DDataset(H5::H5File const &file, std::string const &datasetName, gsl::span<const double> buffer)

Create and write to 1-dimensional native double dataset.

Parameters

- **file** – HDF5 file object
- **datasetName** – Name of dataset to create
- **buffer** – Data to write to dataset

Function amici::hdf5::createAndWriteDouble2DDataset

- Defined in file_include_amici_hdf5.h

Function Documentation

```
void amici::hdf5::createAndWriteDouble2DDataset(H5::H5File const &file, std::string const &datasetName,  
                                                gsl::span<const double> buffer, hsize_t m, hsize_t n)
```

Create and write to 2-dimensional native double dataset.

Parameters

- **file** – HDF5 file object
- **datasetName** – Name of dataset to create
- **buffer** – Flattened data to write to dataset (assuming row-major)
- **m** – Number of rows in buffer
- **n** – Number of columns buffer

Function amici::hdf5::createAndWriteDouble3DDataset

- Defined in file_include_amici_hdf5.h

Function Documentation

```
void amici::hdf5::createAndWriteDouble3DDataset(H5::H5File const &file, std::string const &datasetName,  
                                                gsl::span<const double> buffer, hsize_t m, hsize_t n,  
                                                hsize_t o)
```

Create and write to 3-dimensional native double dataset.

Parameters

- **file** – HDF5 file object
- **datasetName** – Name of dataset to create
- **buffer** – Flattened data to write to dataset (assuming row-major)
- **m** – Length of first dimension in buffer
- **n** – Length of first dimension in buffer
- **o** – Length of first dimension in buffer

Function amici::hdf5::createAndWriteInt1DDataset

- Defined in file_include_amici_hdf5.h

Function Documentation

```
void amici::hdf5::createAndWriteInt1DDataset(H5::H5File const &file, std::string const &datasetName,  
                                              gsl::span<const int> buffer)
```

Create and write to 1-dimensional native integer dataset.

Parameters

- **file** – HDF5 file object
- **datasetName** – Name of dataset to create
- **buffer** – Data to write to dataset

Function amici::hdf5::createAndWriteInt2DDataset

- Defined in file_include_amici_hdf5.h

Function Documentation

```
void amici::hdf5::createAndWriteInt2DDataset(H5::H5File const &file, std::string const &datasetName,  
                                              gsl::span<const int> buffer, hsize_t m, hsize_t n)
```

Create and write to 2-dimensional native integer dataset.

Parameters

- **file** – HDF5 file object
- **datasetName** – Name of dataset to create
- **buffer** – Flattened data to write to dataset (assuming row-major)
- **m** – Number of rows in buffer
- **n** – Number of columns buffer

Function amici::hdf5::createGroup

- Defined in file_include_amici_hdf5.h

Function Documentation

```
void amici::hdf5::createGroup(const H5::H5File &file, std::string const &groupPath, bool recursively = true)
```

Create the given group and possibly parents.

Parameters

- **file** – HDF5 file to write to
- **groupPath** – Path to the group to be created
- **recursively** – Create intermediary groups

Function amici::hdf5::createOrOpenForWriting

- Defined in file_include_amici_hdf5.h

Function Documentation

H5::H5File amici::hdf5::createOrOpenForWriting(std::string const &hdf5filename)

Open the given file for writing.

Append if exists, create if not.

Parameters **hdf5filename** – File to open

Returns File object

Function amici::hdf5::getDoubleDataset1D

- Defined in file_include_amici_hdf5.h

Function Documentation

std::vector<double> amici::hdf5::getDoubleDataset1D(const H5::H5File &file, std::string const &name)

Read 1-dimensional native double dataset from HDF5 file.

Parameters

- **file** – HDF5 file object
- **name** – Name of dataset to read

Returns Data read

Function amici::hdf5::getDoubleDataset2D

- Defined in file_include_amici_hdf5.h

Function Documentation

std::vector<double> amici::hdf5::getDoubleDataset2D(const H5::H5File &file, std::string const &name,
hsz_t &m, hsz_t &n)

Read 2-dimensional native double dataset from HDF5 file.

Parameters

- **file** – HDF5 file object
- **name** – Name of dataset to read
- **m** – Number of rows in the dataset
- **n** – Number of columns in the dataset

Returns Flattened data (row-major)

Function amici::hdf5::getDoubleDataset3D

- Defined in file_include_amici_hdf5.h

Function Documentation

`std::vector<double> amici::hdf5::getDoubleDataset3D(const H5::H5File &file, std::string const &name, hsize_t &m, hsize_t &n, hsize_t &o)`

Read 3-dimensional native double dataset from HDF5 file.

Parameters

- **file** – HDF5 file object
- **name** – Name of dataset to read
- **m** – Length of first dimension in dataset
- **n** – Length of first dimension in dataset
- **o** – Length of first dimension in dataset

Returns Flattened data (row-major)

Function amici::hdf5::getDoubleScalarAttribute

- Defined in file_include_amici_hdf5.h

Function Documentation

`double amici::hdf5::getDoubleScalarAttribute(const H5::H5File &file, const std::string &optionsObject, const std::string &attributeName)`

Read scalar native double attribute from HDF5 object.

Parameters

- **file** – HDF5 file
- **optionsObject** – Object to read attribute from
- **attributeName** – Name of attribute to read

Returns Attribute value

Function amici::hdf5::getIntDataset1D

- Defined in file_include_amici_hdf5.h

Function Documentation

`std::vector<int> amici::hdf5::getIntDataset1D(const H5::H5File &file, std::string const &name)`

Read 1-dimensional native integer dataset from HDF5 file.

Parameters

- **file** – HDF5 file object
- **name** – Name of dataset to read

Returns Data read

Function `amici::hdf5::getIntScalarAttribute`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`int amici::hdf5::getIntScalarAttribute(const H5::H5File &file, const std::string &optionsObject, const std::string &attributeName)`

Read scalar native integer attribute from HDF5 object.

Parameters

- **file** – HDF5 file
- **optionsObject** – Object to read attribute from
- **attributeName** – Name of attribute to read

Returns Attribute value

Function `amici::hdf5::getStringAttribute`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`std::string amici::hdf5::getStringAttribute(H5::H5File const &file, std::string const &optionsObject, std::string const &attributeName)`

Read string attribute from HDF5 object.

Parameters

- **file** – HDF5 file
- **optionsObject** – Object to read attribute from
- **attributeName** – Name of attribute to read

Returns Attribute value

Function amici::hdf5::locationExists(std::string const &filename, std::string const &location)

- Defined in file_include_amici_hdf5.h

Function Documentation

bool amici::hdf5::locationExists(std::string const &filename, std::string const &location)

Check if the given location (group, link or dataset) exists in the given file.

Parameters

- **filename** – HDF5 filename
- **location** – Location to test for

Returns true if exists, false otherwise

Function amici::hdf5::locationExists(H5::H5File const &file, std::string const &location)

- Defined in file_include_amici_hdf5.h

Function Documentation

bool amici::hdf5::locationExists(H5::H5File const &file, std::string const &location)

Check if the given location (group, link or dataset) exists in the given file.

Parameters

- **file** – HDF5 file object
- **location** – Location to test for

Returns true if exists, false otherwise

Function amici::hdf5::readModelDataFromHDF5(std::string const &hdfFile, Model &model, std::string const &datasetPath)

- Defined in file_include_amici_hdf5.h

Function Documentation

void amici::hdf5::readModelDataFromHDF5(std::string const &hdfFile, *Model* &model, std::string const &datasetPath)

Read model data from HDF5 file.

Parameters

- **hdfFile** – Name of HDF5 file
- **model** – *Model* to set data on
- **datasetPath** – Path inside the HDF5 file

Function `amici::hdf5::readModelDataFromHDF5(H5::H5File const &file, Model &model, std::string const &datasetPath)`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`void amici::hdf5::readModelDataFromHDF5(H5::H5File const &file, Model &model, std::string const &datasetPath)`

Read model data from HDF5 file.

Parameters

- **file** – HDF5 file handle to read from
- **model** – *Model* to set data on
- **datasetPath** – Path inside the HDF5 file

Function `amici::hdf5::readSimulationExpData`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`std::unique_ptr<ExpData> amici::hdf5::readSimulationExpData(const std::string &hdf5Filename, const std::string &hdf5Root, const Model &model)`

Read AMICI *ExpData* data from HDF5 file.

Parameters

- **hdf5Filename** – Name of HDF5 file
- **hdf5Root** – Path inside the HDF5 file to object having *ExpData*
- **model** – The model for which data is to be read

Returns *ExpData* created from data in the given location

Function `amici::hdf5::readSolverSettingsFromHDF5(const H5::H5File &file, Solver &solver, std::string const &datasetPath)`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`void amici::hdf5::readSolverSettingsFromHDF5`(const H5::H5File &file, *Solver* &solver, std::string const &datasetPath)

Read solver options from HDF5 file.

Parameters

- **file** – HDF5 file to read from
- **solver** – *Solver* to set options on
- **datasetPath** – Path inside the HDF5 file

Function `amici::hdf5::readSolverSettingsFromHDF5`(std::string const &hdffile, *Solver* &solver, std::string const &datasetPath)

- Defined in file_include_amici_hdf5.h

Function Documentation

`void amici::hdf5::readSolverSettingsFromHDF5`(std::string const &hdffile, *Solver* &solver, std::string const &datasetPath)

Read solver options from HDF5 file.

Parameters

- **hdffile** – Name of HDF5 file
- **solver** – *Solver* to set options on
- **datasetPath** – Path inside the HDF5 file

Function `amici::hdf5::writeReturnData`(const *ReturnData* &rdata, H5::H5File const &file, const std::string &hdf5Location)

- Defined in file_include_amici_hdf5.h

Function Documentation

`void amici::hdf5::writeReturnData`(const *ReturnData* &rdata, H5::H5File const &file, const std::string &hdf5Location)

Write *ReturnData* to HDF5 file.

Parameters

- **rdata** – Data to write
- **file** – HDF5 file to write to
- **hdf5Location** – Full dataset path inside the HDF5 file (will be created)

Function `amici::hdf5::writeReturnData(const ReturnData &rdata, std::string const &hdf5Filename, const std::string &hdf5Location)`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`void amici::hdf5::writeReturnData(const ReturnData &rdata, std::string const &hdf5Filename, const std::string &hdf5Location)`

Write *ReturnData* to HDF5 file.

Parameters

- **rdata** – Data to write
- **hdf5Filename** – Filename of HDF5 file
- **hdf5Location** – Full dataset path inside the HDF5 file (will be created)

Function `amici::hdf5::writeReturnDataDiagnosis`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`void amici::hdf5::writeReturnDataDiagnosis(const ReturnData &rdata, H5::H5File const &file, const std::string &hdf5Location)`

Write *ReturnData* diagnosis data to HDF5 file.

Parameters

- **rdata** – Data to write
- **file** – HDF5 file to write to
- **hdf5Location** – Full dataset path inside the HDF5 file (will be created)

Function `amici::hdf5::writeSimulationExpData`

- Defined in `file_include_amici_hdf5.h`

Function Documentation

`void amici::hdf5::writeSimulationExpData(const ExpData &edata, H5::H5File const &file, const std::string &hdf5Location)`

Write AMICI experimental data to HDF5 file.

Parameters

- **edata** – The experimental data which is to be written
- **file** – Name of HDF5 file
- **hdf5Location** – Path inside the HDF5 file to object having *ExpData*

Function amici::hdf5::writeSolverSettingsToHDF5(Solver const &solver, std::string const &hdf5Filename, std::string const &hdf5Location)

- Defined in file_include_amici_hdf5.h

Function Documentation

void amici::hdf5::writeSolverSettingsToHDF5(*Solver* const &solver, std::string const &hdf5Filename, std::string const &hdf5Location)

Write solver options to HDF5 file.

Parameters

- **hdf5Filename** – Name of HDF5 file to write to
- **solver** – *Solver* to write options from
- **hdf5Location** – Path inside the HDF5 file

Function amici::hdf5::writeSolverSettingsToHDF5(Solver const &solver, H5::H5File const &file, std::string const &hdf5Location)

- Defined in file_include_amici_hdf5.h

Function Documentation

void amici::hdf5::writeSolverSettingsToHDF5(*Solver* const &solver, H5::H5File const &file, std::string const &hdf5Location)

Write solver options to HDF5 file.

Parameters

- **file** – File to read from
- **solver** – *Solver* to write options from
- **hdf5Location** – Path inside the HDF5 file

Function amici::linearSum

- Defined in file_include_amici_vector.h

Function Documentation

inline void amici::linearSum(*realtype* a, *AmiVector* const &x, *realtype* b, *AmiVector* const &y, *AmiVector* &z)
Computes $z = a*x + b*y$.

Parameters

- **a** – coefficient for x
- **x** – a vector
- **b** – coefficient for y

- **y** – another vector with same size as **x**
- **z** – result vector of same size as **x** and **y**

Function amici::N_VGetArrayPointerConst

- Defined in file_include_amici_vector.h

Function Documentation

inline const *realttype* *amici::N_VGetArrayPointerConst(const *N_Vector* x)

Function amici::operator==(const Model &a, const Model &b)

- Defined in file_include_amici_model.h

Function Documentation

bool amici::operator==(const *Model* &a, const *Model* &b)

Parameters

- **a** – First model instance
- **b** – Second model instance

Returns Equality

Function amici::operator==(const ModelDimensions &a, const ModelDimensions &b)

- Defined in file_include_amici_model.h

Function Documentation

bool amici::operator==(const *ModelDimensions* &a, const *ModelDimensions* &b)

Function amici::operator==(const SimulationParameters &a, const SimulationParameters &b)

- Defined in file_include_amici_simulation_parameters.h

Function Documentation

`bool amici::operator==(const SimulationParameters &a, const SimulationParameters &b)`

Function `amici::operator==(const Solver &a, const Solver &b)`

- Defined in `file_include_amici_solver.h`

Function Documentation

`bool amici::operator==(const Solver &a, const Solver &b)`

Parameters

- **a** –
- **b** –

Returns

Function `amici::printErrMsgIdAndTxt`

- Defined in `file_include_amici_amici.h`

Function Documentation

`void amici::printErrMsgIdAndTxt(std::string const &id, std::string const &message)`

Prints a specified error message associated with the specified identifier.

Parameters

- **id** – error identifier
- **message** – error message

Function `amici::printfToString`

- Defined in `file_include_amici_misc.h`

Function Documentation

`std::string amici::printfToString(const char *fmt, va_list ap)`

Format printf-style arguments to `std::string`.

Parameters

- **fmt** – Format string
- **ap** – Argument list pointer

Returns Formatted String

Function amici::printWarnMsgIdAndTxt

- Defined in file_include_amici_amici.h

Function Documentation

void amici::printWarnMsgIdAndTxt(std::string const &id, std::string const &message)
Prints a specified warning message associated with the specified identifier.

Parameters

- **id** – warning identifier
- **message** – warning message

Function amici::regexErrorToString

- Defined in file_include_amici_misc.h

Function Documentation

std::string amici::regexErrorToString(std::regex_constants::error_type err_type)
Convert std::regex_constants::error_type to string.

Parameters **err_type** – error type

Returns Error type as string

Function amici::runAmiciSimulation

- Defined in file_include_amici_amici.h

Function Documentation

std::unique_ptr<ReturnData> amici::runAmiciSimulation(*Solver* &solver, const *ExpData* *edata, *Model* &model, bool rethrow = false)

Core integration routine. Initializes the solver and runs the forward and backward problem.

Parameters

- **solver** – *Solver* instance
- **edata** – pointer to experimental data object
- **model** – model specification object
- **rethrow** – rethrow integration exceptions?

Returns rdata pointer to return data object

Function amici::runAmiciSimulations

- Defined in file_include_amici_amici.h

Function Documentation

```
std::vector<std::unique_ptr<ReturnData>> amici::runAmiciSimulations(Solver const &solver, const
                                                                std::vector<ExpData*> &edatas,
                                                                Model const &model, bool failfast, int
                                                                num_threads)
```

Same as runAmiciSimulation, but for multiple *ExpData* instances. When compiled with OpenMP support, this function runs multi-threaded.

Parameters

- **solver** – *Solver* instance
- **edatas** – experimental data objects
- **model** – model specification object
- **failfast** – flag to allow early termination
- **num_threads** – number of threads for parallel execution

Returns vector of pointers to return data objects

Function amici::scaleParameters

- Defined in file_include_amici_misc.h

Function Documentation

```
void amici::scaleParameters(gsl::span<const realtype> bufferUnscaled, gsl::span<const ParameterScaling>
                           pscale, gsl::span<realtype> bufferScaled)
```

Apply parameter scaling according to **scaling**

Parameters

- **bufferUnscaled** –
- **pscale** – parameter scaling
- **bufferScaled** – destination

Template Function amici::serializeToChar

- Defined in file_include_amici_serialization.h

Function Documentation

template<typename T>
char *amici::serializeToChar(*T* const &data, int *size)
Serialize object to char array.

Parameters

- **data** – input object
- **size** – maximum char length

Returns The object serialized as char

Template Function amici::serializeToStdVec

- Defined in file_include_amici_serialization.h

Function Documentation

template<typename T>
std::vector<char> amici::serializeToStdVec(*T* const &data)
Serialize object to std::vector<char>

Parameters **data** – input object

Returns The object serialized as std::vector<char>

Template Function amici::serializeToString

- Defined in file_include_amici_serialization.h

Function Documentation

template<typename T>
std::string amici::serializeToString(*T* const &data)
Serialize object to string.

Parameters **data** – input object

Returns The object serialized as string

Template Function amici::slice(std::vector<T> &data, int index, unsigned size)

- Defined in file_include_amici_misc.h

Function Documentation

template<class **T**>
 gsl::span<**T**> amici::slice(std::vector<**T**> &data, int index, unsigned size)
 creates a slice from existing data

Parameters

- **data** – to be sliced
- **index** – slice index
- **size** – slice size

Returns span of the slice

Template Function amici::slice(const std::vector<**T**> &data, int index, unsigned size)

- Defined in file_include_amici_misc.h

Function Documentation

template<class **T**>
 gsl::span<const **T**> amici::slice(const std::vector<**T**> &data, int index, unsigned size)
 creates a constant slice from existing constant data

Parameters

- **data** – to be sliced
- **index** – slice index
- **size** – slice size

Returns span of the slice

Function amici::unscaleParameters

- Defined in file_include_amici_misc.h

Function Documentation

void amici::unscaleParameters(gsl::span<const *realtype*> bufferScaled, gsl::span<const *ParameterScaling*>
 pscale, gsl::span<*realtype*> bufferUnscaled)

Remove parameter scaling according to the parameter scaling in pscale.

All vectors must be of same length.

Parameters

- **bufferScaled** – scaled parameters
- **pscale** – parameter scaling
- **bufferUnscaled** – unscaled parameters are written to the array

Function amici::wrapErrHandlerFn

- Defined in file_include_amici_solver.h

Function Documentation

void amici::wrapErrHandlerFn(int error_code, const char *module, const char *function, char *msg, void *eh_data)

Extracts diagnosis information from solver memory block and passes them to the specified output function.

Parameters

- **error_code** – error identifier
- **module** – name of the module in which the error occurred
- **function** – name of the function in which the error occurred
- **msg** – error message
- **eh_data** – *amici::Solver* as void*

Template Function amici::writeSlice(const gsl::span<const T> slice, gsl::span<T> buffer)

- Defined in file_include_amici_misc.h

Function Documentation

template<class T>
void amici::writeSlice(const gsl::span<const T> slice, gsl::span<T> buffer)
local helper function to write computed slice to provided buffer (span)

Parameters

- **slice** – computed value
- **buffer** – buffer to which values are to be written

Template Function amici::writeSlice(const std::vector<T> &s, std::vector<T> &b)

- Defined in file_include_amici_misc.h

Function Documentation

template<class T>
void amici::writeSlice(const std::vector<T> &s, std::vector<T> &b)
local helper function to write computed slice to provided buffer (vector)

Parameters

- **s** – computed value
- **b** – buffer to which values are to be written

Template Function amici::writeSlice(const std::vector<T> &s, gsl::span<T> b)

- Defined in file_include_amici_misc.h

Function Documentation

```
template<class T>
void amici::writeSlice(const std::vector<T> &s, gsl::span<T> b)
    local helper function to write computed slice to provided buffer (vector/span)
```

Parameters

- **s** – computed value
- **b** – buffer to which values are to be written

Function amici::writeSlice(const AmiVector &s, gsl::span<realtype> b)

- Defined in file_include_amici_misc.h

Function Documentation

```
void amici::writeSlice(const AmiVector &s, gsl::span<realtype> b)
    local helper function to write computed slice to provided buffer (AmiVector/span)
```

Parameters

- **s** – computed value
- **b** – buffer to which values are to be written

Template Function boost::serialization::archiveVector

- Defined in file_include_amici_serialization.h

Function Documentation

```
template<class Archive, typename T>
void boost::serialization::archiveVector(Archive &ar, T **p, int size)
    Serialize a raw array to a boost archive.
```

Parameters

- **ar** – archive
- **p** – Pointer to array
- **size** – Size of p

Template Function `boost::serialization::serialize(Archive &ar, amici::Model &m, unsigned int version)`

- Defined in `file_include_amici_model.h`

Function Documentation

```
template<class Archive>
void boost::serialization::serialize(Archive &ar, amici::Model &m, unsigned int version)
```

Template Function `boost::serialization::serialize(Archive &ar, amici::ReturnData &r, unsigned int version)`

- Defined in `file_include_amici_rdata.h`

Function Documentation

```
template<class Archive>
void boost::serialization::serialize(Archive &ar, amici::ReturnData &r, unsigned int version)
```

Template Function `boost::serialization::serialize(Archive &ar, amici::Solver &s, unsigned int version)`

- Defined in `file_include_amici_solver.h`

Function Documentation

```
template<class Archive>
void boost::serialization::serialize(Archive &ar, amici::Solver &s, unsigned int version)
```

Template Function `boost::serialization::serialize(Archive &ar, amici::CCodeSolver &s, unsigned int version)`

- Defined in `file_include_amici_solver_ccodes.h`

Function Documentation

```
template<class Archive>
void boost::serialization::serialize(Archive &ar, amici::CNodeSolver &s, unsigned int version)
```

Template Function `boost::serialization::serialize(Archive &ar, amici::IDASolver &s, unsigned int version)`

- Defined in `file_include_amici_solver_idas.h`

Function Documentation

```
template<class Archive>
void boost::serialization::serialize(Archive &ar, amici::IDASolver &s, unsigned int version)
```

Function `gsl::make_span(SUNMatrix m)`

- Defined in `file_include_amici_sundials_matrix_wrapper.h`

Function Documentation

```
inline span<realtype> gsl::make_span(SUNMatrix m)
    Create span from SUNMatrix.
```

Parameters `m` – SUNMatrix

Returns Created span

Function `gsl::make_span(N_Vector nv)`

- Defined in `file_include_amici_vector.h`

Function Documentation

```
inline span<realtype> gsl::make_span(N_Vector nv)
    Create span from N_Vector.
```

Parameters `nv` –

Returns

Variables

Variable amici::AMICI_CONV_FAILURE

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_CONV_FAILURE = -4

Variable amici::AMICI_DAMPING_FACTOR_ERROR

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_DAMPING_FACTOR_ERROR = -86

Variable amici::AMICI_DATA_RETURN

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_DATA_RETURN = 1

Variable amici::AMICI_ERR_FAILURE

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_ERR_FAILURE = -3

Variable amici::AMICI_ERROR

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_ERROR = -99

Variable amici::AMICI_ILL_INPUT

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_ILL_INPUT = -22

Variable amici::AMICI_MAX_TIME_EXCEEDED

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_MAX_TIME_EXCEEDED = -1000

Variable amici::AMICI_NO_STEADY_STATE

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_NO_STEADY_STATE = -81

Variable amici::AMICI_NORMAL

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_NORMAL = 1

Variable amici::AMICI_NOT_IMPLEMENTED

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_NOT_IMPLEMENTED = -999

Variable amici::AMICI_ONE_STEP

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_ONE_STEP = 2

Variable amici::AMICI_ONEOUTPUT

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_ONEOUTPUT = 5

Variable amici::AMICI_PREEQUILIBRATE

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_PREEQUILIBRATE = -1

Variable amici::AMICI_RECOVERABLE_ERROR

- Defined in file_include_amici_defines.h

Variable Documentation

```
constexpr int amici::AMICI_RECOVERABLE_ERROR = 1
```

Variable amici::AMICI_RHSFUNC_FAIL

- Defined in file_include_amici_defines.h

Variable Documentation

```
constexpr int amici::AMICI_RHSFUNC_FAIL = -8
```

Variable amici::AMICI_ROOT_RETURN

- Defined in file_include_amici_defines.h

Variable Documentation

```
constexpr int amici::AMICI_ROOT_RETURN = 2
```

Variable amici::AMICI_SINGULAR_JACOBIAN

- Defined in file_include_amici_defines.h

Variable Documentation

```
constexpr int amici::AMICI_SINGULAR_JACOBIAN = -809
```

Variable amici::AMICI_SUCCESS

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_SUCCESS = 0

Variable amici::AMICI_TOO_MUCH_ACC

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_TOO_MUCH_ACC = -2

Variable amici::AMICI_TOO_MUCH_WORK

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_TOO_MUCH_WORK = -1

Variable amici::AMICI_UNRECOVERABLE_ERROR

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr int amici::AMICI_UNRECOVERABLE_ERROR = -10

Variable amici::defaultContext

- Defined in file_include_amici_model.h

Variable Documentation

AmiciApplication amici::defaultContext

Variable amici::pi

- Defined in file_include_amici_defines.h

Variable Documentation

constexpr double amici::pi = 3.14159265358979323846

Defines

Define _USE_MATH_DEFINES

- Defined in file_include_amici_defines.h

Define Documentation

_USE_MATH_DEFINES

Define AMICI_H5_RESTORE_ERROR_HANDLER

- Defined in file_include_amici_hdf5.h

Define Documentation

AMICI_H5_RESTORE_ERROR_HANDLER

Define AMICI_H5_SAVE_ERROR_HANDLER

- Defined in file_include_amici_hdf5.h

Define Documentation

AMICI_H5_SAVE_ERROR_HANDLER

Define AMICI_VERSION

- Defined in file_include_amici_version.in.h

Define Documentation

AMICI_VERSION

Define M_1_PI

- Defined in file_include_amici_defines.h

Define Documentation

M_1_PI

Define M_2_PI

- Defined in file_include_amici_defines.h

Define Documentation

M_2_PI

Define M_2_SQRTPI

- Defined in file_include_amici_defines.h

Define Documentation

M_2_SQRTPI

Define M_E

- Defined in file_include_amici_defines.h

Define Documentation

M_E

Define M_LN10

- Defined in file_include_amici_defines.h

Define Documentation

M_LN10

Define M_LN2

- Defined in file_include_amici_defines.h

Define Documentation

M_LN2

Define M_LOG10E

- Defined in file_include_amici_defines.h

Define Documentation

M_LOG10E

Define M_LOG2E

- Defined in file_include_amici_defines.h

Define Documentation

M_LOG2E

Define M_PI

- Defined in file_include_amici_defines.h

Define Documentation

M_PI

Define M_PI_2

- Defined in file_include_amici_defines.h

Define Documentation

M_PI_2

Define M_PI_4

- Defined in file_include_amici_defines.h

Define Documentation

M_PI_4

Define M_SQRT1_2

- Defined in file_include_amici_defines.h

Define Documentation

M_SQRT1_2

Define M_SQRT2

- Defined in file_include_amici_defines.h

Define Documentation

M_SQRT2

Typedefs

Typedef amici::const_N_Vector

- Defined in file_include_amici_vector.h

Typedef Documentation

using amici::const_N_Vector = std::add_const_t<typename std::remove_pointer_t<N_Vector>>*

Since const N_Vector is not what we want

Typedef amici::outputFunctionType

- Defined in file_include_amici_defines.h

Typedef Documentation

using amici::outputFunctionType = std::function<void(std::string const &identifier, std::string const &message)>

Type for function to process warnings or error messages.

Typedef amici::realtype

- Defined in file_include_amici_defines.h

Typedef Documentation

using amici::realtype = double

defines variable type for simulation variables (determines numerical accuracy)

MATLAB INTERFACE

12.1 Installing the AMICI MATLAB toolbox

To use AMICI from MATLAB, start MATLAB and add the `AMICI/matlab` directory to the MATLAB path. To add all toolbox directories to the MATLAB path, execute the matlab script:

```
installAMICI.m
```

To store the installation for further MATLAB session, the path can be saved via:

```
savepath
```

For the compilation of `.mex` files, MATLAB needs to be configured with a working C++ compiler. The C++ compiler needs to be installed and configured via:

```
mex -setup c++
```

For a list of supported compilers we refer to the respective MathWorks [documentation](#).

12.2 Using AMICI's MATLAB interface

In the following we will give a detailed overview how to specify models in MATLAB and how to call the generated simulation files.

Note: The MATLAB interface requires the MathWorks [Symbolic Math Toolbox](#) for model import (but not for model simulation).

The Symbolic Math Toolbox requirement can be circumvented by performing model import using the Python interface. The resulting code can then be used from Matlab (see [Compiling a Python-generated model](#)).

Warning: Due to changes in the Symbolic Math Toolbox, the last MATLAB release with working AMICI model import is R2017b (see <https://github.com/AMICI-dev/AMICI/issues/307>).

12.2.1 Specifying models in Matlab

This guide will guide the user on how to specify models in MATLAB. For example implementations see the examples in the `matlab/examples` directory.

Header

The model definition needs to be defined as a function which returns a `struct` with all symbolic definitions and options.

```
function [model] = example_model_syms()
```

Options

Set the options by specifying the respective field of the model struct

```
model.(fieldname) = value
```

The options specify default options for simulation, parametrisation and compilation. All of these options are optional.

field	description	default
.param	default parametrisation 'log'/'log10'/'lin'	'lin'
.debug	flag to compile with debug symbols	false
.forward	flag to activate forward sensitivities	true
.adjoint	flag to activate adjoint sensitivities	true

When set to false, the fields `forward` and `adjoint` will speed up the time required to compile the model but also disable the respective sensitivity computation.

States

Create the respective symbolic variables. The name of the symbolic variable can be chosen arbitrarily.

```
syms state1 state2 state3
```

Create the state vector containing all states:

```
model.sym.x = [ state1 state2 state3 ];
```

Parameters

Create the respective symbolic variables. The name of the symbolic variable can be chosen arbitrarily. Sensitivities will be derived for all *parameters*.

```
syms param1 param2 param3 param4 param5 param6
```

Create the parameters vector

```
model.sym.p = [ param1 param2 param3 param4 param5 param6 ];
```


Constants

Create the respective symbolic variables. The name of the symbolic variable can be chosen arbitrarily. Sensitivities with respect to *constants* will not be derived.

```
syms const1 const2
```

Create the constants vector

```
model.sym.k = [ const1 const2 ];
```

Differential equations

For time-dependent differential equations you can specify a symbolic variable for time. This **needs** to be denoted by `t`.

```
syms t
```

Specify the right hand side of the differential equation `f` or `xdot`

```
model.sym.xdot(1) = [ const1 - param1*state1 ];
model.sym.xdot(2) = [ +param2*state1 + dirac(t-param3) - const2*state2 ];
model.sym.xdot(3) = [ param4*state2 ];
```

or

```
model.sym.f(1) = [ const1 - param1*state1 ];
model.sym.f(2) = [ +param2*state1 + dirac(t-param3) - const2*state2 ];
model.sym.f(3) = [ param4*state2 ];
```

The specification of `f` or `xdot` may depend on states, parameters and constants.

For DAEs also specify the mass matrix.

```
model.sym.M = [1, 0, 0;...
               0, 1, 0;...
               0, 0, 0];
```

The specification of `M` may depend on parameters and constants.

For ODEs the integrator will solve the equation $\dot{x} = f$ and for DAEs the equations $M \cdot \dot{x} = f$. AMICI will decide whether to use CVODES (for ODEs) or IDAS (for DAEs) based on whether the mass matrix is defined or not.

In the definition of the differential equation you can use certain symbolic functions. For a full list of available functions see `src/symbolic_functions.cpp`.

Dirac functions can be used to cause a jump in the respective states at the specified time-point. This is typically used to model injections, or other external stimuli. Spline functions can be used to model time/state dependent response with unknown time/state dependence.

Initial Conditions

Specify the initial conditions. These may depend on parameters on constants and must have the same size as `x`.

```
model.sym.x0 = [ param4, 0, 0 ];
```

Observables

Specify the observables. These may depend on parameters and constants.

```
model.sym.y(1) = state1 + state2;  
model.sym.y(2) = state3 - state2;
```

In the definition of the observable you can use certain symbolic functions. For a full list of available functions see `src/symbolic_functions.cpp`. Dirac functions in observables will have no effect.

Events

Specifying events is optional. Events are specified in terms of a trigger function, a bolus function and an output function. The roots of the trigger function defines the occurrences of the event. The bolus function defines the change in the state on event occurrences. The output function defines the expression which is evaluated and reported by the simulation routine on every event occurrence. The user can create events by constructing a vector of objects of the class [amievent](#).

```
model.sym.event(1) = amievent(state1 - state2,0,[]);
```

Events may depend on states, parameters and constants but *not* on observables.

For more details about event support see:

Fröhlich, F., Theis, F. J., Rädler, J. O., & Hasenauer, J. (2017). Parameter estimation for dynamical systems with discrete events and logical operations. *Bioinformatics*, 33(7), 1049-1056. doi:10.1093/bioinformatics/btw764.

Standard deviation

Specifying standard deviations is optional. It only has an effect when computing adjoint sensitivities. It allows the user to specify standard deviations of experimental data for observables and events.

Standard deviation for observable data is denoted by `sigma_y`

```
model.sym.sigma_y(1) = param5;
```

Standard deviation for event data is denoted by `sigma_t`

```
model.sym.sigma_t(1) = param6;
```

Both `sigma_y` and `sigma_t` can either be a scalar or of the same dimension as the observables / events function. They can depend on time and parameters but must not depend on the states or observables. The values provided in `sigma_y` and `sigma_t` will only be used if the value in `D.Sigma_Y` or `D.Sigma_T` in the user-provided data struct is NaN. See simulation for details.

Objective Function

By default, AMICI assumes a normal noise model and uses the corresponding negative log-likelihood

$$J = 1/2 * \sum(((y_i(t) - my_{ti})/\sigma_{y_i})^2 + \log(2 * \pi * \sigma_{y_i}^2))$$

as objective function. A user provided objective function can be specified in

```
model.sym.Jy
```

As reference see the default specification of `this.sym.Jy` in `amimodel.makeSyms`.

12.2.2 SBML

AMICI can also import SBML models using the command `SBML2AMICI`. This will generate a model specification as described above, which may be edited by the user to apply further changes.

12.2.3 Model Compilation

The model can then be compiled by calling `amiwrap.m`:

```
amiwrap(modelname, 'example_model_syms', dir, o2flag)
```

Here `modelname` should be a string defining the name of the model, `dir` should be a string containing the path to the directory in which simulation files should be placed and `o2flag` is a flag indicating whether second order sensitivities should also be compiled. The user should make sure that the previously defined function `example_model_syms` is in the user path. Alternatively, the user can also call the function `example_model_syms`

```
[model] = example_model_syms()
```

and subsequently provide the generated struct to `amiwrap(...)`, instead of providing the symbolic function:

```
amiwrap(modelname, model, dir, o2flag)
```

In a similar fashion, the user could also generate multiple models and pass them directly to `amiwrap(...)` without generating respective model definition scripts.

Compiling a Python-generated model

For better performance or to avoid the Symbolic Math Toolbox requirement, it might be desirable to import a model in Python and compile the resulting code into a mex file. For Python model import, consult the respective section of the Python documentation. Once the import succeeded, there will be a `compileMexFile.m` script inside the newly created model directory which can be invoked to compile the mex file. This mex file and `simulate_*.m` can be used as if fully created by matlab.

Using Python-AMICI model import from Matlab

With recent matlab versions it is possible to use the AMICI python package from within Matlab. This not quite comfortable yet, but it is possible.

Here for proof of concept:

- Install the python package as described in the documentation
- Ensure pyversion shows the correct python version (3.6 or 3.7)
- Then, from within the AMICI matlab/ directory:

```
sbml_importer = py.amici.SbmlImporter('../python/examples/example_steadystate/model_
↪steadystate_scaled.xml')
sbml_importer.sbml2amici('steadystate', 'steadystate_example_from_python')
model = py.steadystate.getModel()
solver = model.getSolver()
model.setTimepoints(linspace(0, 50, 51))
rdata = py.amici.runAmiciSimulation(model, solver)
result = struct(py.dict(rdata.items()))
t = double(py.array.array('d', result.ts))
x = double(py.array.array('d', result.x.flatten()))
x = reshape(x, flip(double(py.array.array('d', result.x.shape))))
plot(t, x)
```

12.2.4 Model simulation

After the call to `amiwrap(...)` two files will be placed in the specified directory. One is a `_modelname_.mex` and the other is `simulate_*modelname*.m`. The mex file should never be called directly. Instead the MATLAB script, which acts as a wrapper around the .mex simulation file should be used.

The `simulate_ _modelname_.m` itself carries extensive documentation on how to call the function, what it returns and what additional options can be specified. In the following we will give a short overview of possible function calls.

Integration

Define a time vector:

```
t = linspace(0,10,100)
```

Generate a parameter vector:

```
theta = ones(6,1);
```

Generate a constants vector:

```
kappa = ones(2,1);
```

Integrate:

```
sol = simulate_modelname(t,theta,kappa,[],options)
```

The integration status will be indicated by the `sol.status` flag. Negative values indicated failed integration. The states will then be available as `sol.x`. The observables will then be available as `sol.y`. The event outputs will then

be available as `sol.z`. If no event occurred there will be an event at the end of the considered interval with the final value of the root function is stored in `sol.rz`.

Alternatively the integration can also be called via

```
[status,t,x,y] = simulate_modelname(t,theta,kappa,[],options)
```

The integration status will be indicated by the flag `status`. Negative values indicated failed integration. The states will then be available as `x`. The observables will then be available as `y`. No event output will be given.

Forward Sensitivities

Set the sensitivity computation to forward sensitivities and integrate:

```
options.sensi = 1;
options.sensi_meth = 'forward';
sol = simulate_modelname(t,theta,kappa,[],options)
```

The integration status will be indicated by the `sol.status` flag. Negative values indicate failed integration. The states will be available as `sol.x`, with the derivative with respect to the parameters in `sol.sx`. The observables will be available as `sol.y`, with the derivative with respect to the parameters in `sol.sy`. The event outputs will be available as `sol.z`, with the derivative with respect to the parameters in `sol.sz`. If no event occurred there will be an event at the end of the considered interval with the final value of the root function stored in `sol.rz`, with the derivative with respect to the parameters in `sol.srz`.

Alternatively the integration can also be called via

```
[status,t,x,y,sx,sy] = simulate_modelname(t,theta,kappa,[],options)
```

The integration status will be indicated by the `status` flag. Negative values indicate failed integration. The states will then be available as `x`, with derivative with respect to the parameters in `sx`. The observables will then be available as `y`, with derivative with respect to the parameters in `sy`. No event output will be given.

Adjoint sensitivities

Set the sensitivity computation to adjoint sensitivities:

```
options.sensi = 1;
options.sensi_meth = 'adjoint';
```

Define Experimental Data:

```
D.Y = [NaN(1,2)],ones(length(t)-1,2)];
D.Sigma_Y = [0.1*ones(length(t)-1,2),NaN(1,2)];
D.T = ones(1,1);
D.Sigma_T = NaN;
```

The NaN values in `Sigma_Y` and `Sigma_T` will be replaced by the specification in `model.sym.sigma_y` and `model.sym.sigma_t`. Data points with NaN value will be completely ignored.

Integrate:

```
sol = simulate_modelname(t,theta,kappa,D,options)
```

The integration status will be indicated by the `sol.status` flag. Negative values indicate failed integration. The log-likelihood will then be available as `sol.llh` and the derivative with respect to the parameters in `sol.sllh`. Note that for adjoint sensitivities no state, observable and event sensitivities will be available. Yet this approach can be expected to be significantly faster for systems with a large number of parameters.

Steady-state sensitivities

This will compute state sensitivities according to the formula

$$s_k^x = - \left(\frac{\partial f}{\partial x} \right)^{-1} \frac{\partial f}{\partial \theta_k}$$

In the current implementation this formulation does not allow for conservation laws as this would result in a singular Jacobian.

Set the final timepoint as infinity, this will indicate the solver to compute the steadystate:

```
t = Inf;
```

Set the sensitivity computation to steady state sensitivities:

```
options.sensi = 1;
```

Integrate:

```
sol = simulate_modelname(t,theta,kappa,D,options)
```

The states will be available as `sol.x`, with the derivative with respect to the parameters in `sol.sx`. The observables will be available as `sol.y`, with the derivative with respect to the parameters in `sol.sy`. Notice that for steady state sensitivities no event sensitivities will be available. For the accuracy of the computed derivatives it is essential that the system is sufficiently close to a steady state. This can be checked by examining the right hand side of the system at the final time-point via `sol.diagnosis.xdot`.

12.3 FAQ

Q: My model fails to build.

A: Remove the corresponding model directory located in `AMICI/models/yourmodelname` and compile again.

Q: It still does not compile.

A: Remove the directory `AMICI/models/mexext` and compile again.

Q: It still does not compile.

A: Make an [issue](#) and we will have a look.

Q: My Python-generated model does not compile from MATLAB.

A: Try building any of the available examples before. If this succeeds, retry building the original model. Some dependencies might not be built correctly when using only the `compileMexFile.m` script.

Q: I get an out of memory error while compiling my model on a Windows machine.

A: This may be due to an old compiler version. See [issue #161](#) for instructions on how to install a new compiler.

Q: How are events interpreted in a DAE context?

A: Currently we only support impulse free events. Also sensitivities have never been tested. Proceed with care and create an [issue](#) if any problems arise!

Q: The simulation/sensitivities I get are incorrect.

A: There are some known issues, especially with adjoint sensitivities, events and DAEs. If your particular problem is not featured in the [issues](#) list, please add it!

12.4 AMICI Matlab API

AMICI Matlab library functions

12.4.1 Class Hierarchy

12.4.2 File Hierarchy

12.4.3 Full API

Namespaces

Namespace matlab

Contents

- [Namespaces](#)

Namespaces

- [Namespace matlab::mixin](#)

Namespace matlab::mixin

Classes and Structs

Class amidata

- Defined in file_matlab_@amidata_amidata.m

Inheritance Relationships

Base Type

- public handle

Class Documentation

amidata : public handle

AMIDATA provides a data container to pass experimental data to the simulation routine for likelihood computation. when any of the properties are updated, the class automatically checks consistency of dimension and updates related properties and initialises them with NaNs.

Public Functions

amidata::amidata(matlabtypesubstitute varargin)

amidata creates an amidata container for experimental data with specified dimensions amidata.

AMIDATA(amidata) creates a copy of the input container

AMIDATA(struct) tries to creates an amidata container from the input struct. the struct should have the following

AMIDATA(nt,ny,nz,ne,nk) constructs an empty data container with in the provided dimensions intialised with NaNs

fields t [nt,1] Y [nt,ny] Sigma_Y [nt,ny] Z [ne,nz] Sigma_Z [ne,nz] condition [nk,1] conditionPreequilibration [nk,1] if some fields are missing the function will try to initialise them with NaNs with consistent dimensions

param varargin

Public Members

matlabtypesubstitute nt = 0

number of timepoints

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute ny = 0

number of observables

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute nz = 0
number of event observables

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute ne = 0
number of events

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute nk = 0
number of conditions/constants

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute t = `double.empty("")`
timepoints of observations

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute Y = `double.empty("")`
observations

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute Sigma_Y = `double.empty("")`
standard deviation of observations

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute Z = `double.empty("")`
event observations

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute Sigma_Z = `double.empty("")`
standard deviation of event observations

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute condition = `double.empty("")`
experimental condition

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute conditionPreequilibration = `double.empty("")`
experimental condition for preequilibration

Default: `double.empty("")`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute reinitializeStates = `false`
reinitialize states based on fixed parameters after preeq.?

Default: `false`

Class amievent

- Defined in file_matlab_@amievent_amievent.m

Class Documentation

class amievent

AMIEVENT defines events which later on will be transformed into appropriate C code.

Public Functions

amievent::amievent(matlabtypesubstitute trigger, matlabtypesubstitute bolus, matlabtypesubstitute z)

amievent constructs an amievent object from the provided input.

param trigger trigger function, the event will be triggered on at all roots of this function

param bolus the bolus that will be added to all states on every occurrence of the event

param z the event output that will be reported on every occurrence of the event

mlhsInnerSubst<::amievent > amievent::setHflag(matlabtypesubstitute hflag)

setHflag sets the hflag property.

param hflag value for the hflag property, type double

returns this – updated event definition object

Public Members

::symbolic trigger = sym.empty("")

the trigger function activates the event on every zero crossing

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `sym.empty("")`

::symbolic bolus = sym.empty("")

the bolus function defines the change in states that is applied on every event occurrence

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `sym.empty("")`

::symbolic z = sym.empty("")

output function for the event

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `sym.empty("")`

matlabtypesubstitute hflag = `logical.empty("")`

flag indicating that a heaviside function is present, this helps to speed up symbolic computations

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `logical.empty("")`

Class amifun

- Defined in file_matlab_@amifun_amifun.m

Class Documentation

class amifun

AMIFUN defines functions which later on will be transformed into appropriate C code.

Public Functions

amifun::amifun(matlabtypesubstitute funstr, matlabtypesubstitute model)

amievent constructs an amifun object from the provided input.

param funstr name of the requested function

param model amimodel object which carries all symbolic definitions to construct the function

noret::substitute amifun::writeCcode_sensi(::amimodel model, ::fileid fid)

writeCcode_sensi is a wrapper for writeCcode which loops over parameters and reduces overhead by check nonzero values

param model model definition object

param fid file id in which the final expression is written

returns fid – void

noret::substitute amifun::writeCcode(::amimodel model, ::fileid fid)

writeCcode is a wrapper for gccode which initialises data and reduces overhead by check nonzero values

param model model definition object

param fid file id in which the final expression is written

returns fid – void

noret::substitute amifun::writeMcode(::amimodel model)

writeMcode generates matlab evaluable code for specific model functions

param model model definition object

returns model – void

mlhsInnerSubst<::amifun > amifun::gcode(::amimodel model, ::fileid fid)
 gcode transforms symbolic expressions into c code and writes the respective expression into a specified file

param model model definition object

param fid file id in which the expression should be written

returns this – function definition object

mlhsInnerSubst<::amifun > amifun::getDeps(::amimodel model)
 getDeps populates the sensiflag for the requested function

param model model definition object

returns this – updated function definition object

mlhsInnerSubst<::amifun > amifun::getArgs(::amimodel model)
 getFArgs populates the fargstr property with the argument string of the respective model function (if applicable). model functions are not wrapped versions of functions which have a model specific name and for which the call is solver specific.

param model model definition object

returns this – updated function definition object

mlhsInnerSubst<::amifun > amifun::getNVecs()
 getfunargs populates the nvecs property with the names of the N_Vector elements which are required in the execution of the function (if applicable). the information is directly extracted from the argument string

returns this – updated function definition object

mlhsInnerSubst<::amifun > amifun::getCVar()
 getCVar populates the cvar property

returns this – updated function definition object

mlhsInnerSubst<::amifun > amifun::getSensiFlag()
 getSensiFlag populates the sensiflag property

returns this – updated function definition object

mlhsSubst< mlhsInnerSubst<::amifun >, mlhsInnerSubst<::amimodel > > amifun::getSyms(:amimodel model)
 getSyms computes the symbolic expression for the requested function

param model model definition object

returns

- **this** – updated function definition object
- **model** – updated model definition object

Public Members

::symbolic sym = **sym("[]")**
symbolic definition struct
Default: sym("[]")

::symbolic sym_noopt = **sym("[]")**
symbolic definition which was not optimized (no dependencies on w)
Default: sym("[]")

::symbolic strsym = **sym("[]")**
short symbolic string which can be used for the reuse of precomputed values
Default: sym("[]")

::symbolic strsym_old = **sym("[]")**
short symbolic string which can be used for the reuse of old values
Default: sym("[]")

::char funstr = **char.empty("")**
name of the model
Default: char.empty("")

::char cvar = **char.empty("")**
name of the c variable
Default: char.empty("")

::char argstr = **char.empty("")**
argument string (solver specific)
Default: char.empty("")

::cell deps = **cell.empty("")**
dependencies on other functions
Default: cell.empty("")

matlabtypesubstitute nvecs = **cell.empty("")**
nvec dependencies
Default: cell.empty("")

matlabtypesubstitute sensiflag = **logical.empty("")**
indicates whether the function is a sensitivity or derivative with respect to parameters
Default: logical.empty("")

Class amimodel

- Defined in file_matlab_@amimodel_amimodel.m

Inheritance Relationships

Base Type

- public handle

Class Documentation

amimodel : public handle

AMIMODEL carries all model definitions including functions and events.

Public Functions

amimodel::amimodel(::string symfun, ::string modelname)

amimodel initializes the model object based on the provided symfun and modelname

param symfun this is the string to the function which generates the modelstruct. You can also directly pass the struct here

param modelname name of the model

noret::substitute amimodel::updateRHS(matlabtypesubstitute xdot)

updateRHS updates the private fun property .fun.xdot.sym (right hand side of the differential equation)

param xdot new right hand side of the differential equation

returns xdot – void

noret::substitute amimodel::updateModelName(matlabtypesubstitute modelname)

updateModelName updates the modelname

param modelname new modelname

returns modelname – void

noret::substitute amimodel::updateWrapPath(matlabtypesubstitute wrap_path)

updateModelName updates the modelname

param wrap_path new wrap_path

returns wrap_path – void

noret::substitute amimodel::parseModel()

parseModel parses the model definition and computes all necessary symbolic expressions.

returns void –

noret::substitute amimodel::generateC()

generateC generates the c files which will be used in the compilation.

returns void –

noret::substitute amimodel::generateRebuildM()

generateRebuildM generates a Matlab script for recompilation of this model

returns void –

noret::substitute amimodel::compileC()

compileC compiles the mex simulation file

returns void –

noret::substitute amimodel::generateM(::amimodel amimodelo2)

generateM generates the matlab wrapper for the compiled C files.

param amimodelo2 this struct must contain all necessary symbolic definitions for second order sensitivities

returns amimodelo2 – void

noret::substitute amimodel::getFun(::struct HTable, ::string funstr)

getFun generates symbolic expressions for the requested function.

param HTable struct with hashes of symbolic definition from the previous compilation

param funstr function for which symbolic expressions should be computed

returns funstr – void

noret::substitute amimodel::makeEvents()

makeEvents extracts discontinuities from the model right hand side and converts them into events

returns void –

noret::substitute amimodel::makeSyms()

makeSyms extracts symbolic definition from the user provided model and checks them for consistency

returns void –

mlhsInnerSubst<:bool > amimodel::checkDeps(::struct HTable, ::cell deps)

checkDeps checks the dependencies of functions and populates sym fields if necessary

param HTable struct with reference hashes of functions in its fields

param deps cell array with containing a list of dependencies

returns cflag – boolean indicating whether any of the dependencies have changed with respect to the hashes stored in HTable

mlhsInnerSubst<:struct > amimodel::loadOldHashes()

loadOldHashes loads information from a previous compilation of the model.

returns HTable – struct with hashes of symbolic definition from the previous compilation

mlhsInnerSubst< matlabtypesubstitute > amimodel::augmento2()

augmento2 augments the system equation to also include equations for sensitivity equation. This will enable us to compute second order sensitivities in a forward-adjoint or forward-forward approach later on.

returns this – augmented system which contains symbolic definition of the original system and its sensitivities

mlhsInnerSubst<::amimodel > amimodel::augmento2vec()

augmento2 augments the system equation to also include equations for sensitivity equation. This will enable us to compute second order sensitivities in a forward-adjoint or forward-forward approach later on.

returns **modelo2vec** – augmented system which contains symbolic definition of the original system and its sensitivities

Public Members

::struct sym = struct.empty("")

symbolic definition struct

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `struct.empty("")`

::struct fun = struct.empty("")

struct which stores information for which functions c code needs to be generated

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `struct.empty("")`

::amievent event = amievent.empty("")

struct which stores information for which functions c code needs to be generated

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `amievent.empty("")`

::string modelname = char.empty("")

name of the model

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `char.empty("")`

::struct HTable = struct.empty("")

struct that contains hash values for the symbolic model definitions

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `struct.empty("")`

::bool debug = false

flag indicating whether debugging symbols should be compiled

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `false`

::bool adjoint = true

flag indicating whether adjoint sensitivities should be enabled

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `true`

::bool forward = true

flag indicating whether forward sensitivities should be enabled

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `true`

::double t0 = 0

default initial time

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** 0

::string wtype = char.empty("")
type of wrapper (cvcodes/idas)

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** char.empty("")

::int nx = double.empty("")
number of states

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int nxtrue = double.empty("")
number of original states for second order sensitivities

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int ny = double.empty("")
number of observables

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int nytrue = double.empty("")
number of original observables for second order sensitivities

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess =

Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int np = double.empty("")
number of parameters

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int nk = double.empty("")
number of constants

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int ng = double.empty("")
number of objective functions

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int nevent = double.empty("")
number of events

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** double.empty("")

::int nz = double.empty("")
number of event outputs

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::int nztrue = double.empty("")

number of original event outputs for second order sensitivities

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int id = double.empty("")

flag for DAEs

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::int ubw = double.empty("")

upper Jacobian bandwidth

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::int lbw = double.empty("")

lower Jacobian bandwidth

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::int nnz = `double.empty("")`
number of nonzero entries in Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int sparseidx = `double.empty("")`
dataindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int rowvals = `double.empty("")`
rowindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int colptrs = `double.empty("")`
columnindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int sparseidxB = `double.empty("")`
dataindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int rowvalsB = `double.empty("")`
 rowindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*int colptrsB = `double.empty("")`
 columnindexes of sparse Jacobian

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `double.empty("")`

::*cell funs = `cell.empty("")`
 cell array of functions to be compiled

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `cell.empty("")`

::*cell mfuns = `cell.empty("")`
 cell array of matlab functions to be compiled

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** `cell.empty("")`

::string coptim = `"-03"`
 optimisation flag for compilation

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess =`

Public

Note: [Matlab documentation of property attributes](#). **Default:** “-O3”

::string param = "lin"
default parametrisation

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** “lin”

matlabtypesubstitute wrap_path = char.empty("")
path to wrapper

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** char.empty("")

matlabtypesubstitute recompile = false
flag to enforce recompilation of the model

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** false

matlabtypesubstitute cfun = struct.empty("")
storage for flags determining recompilation of individual functions

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** struct.empty("")

matlabtypesubstitute o2flag = 0
flag which identifies augmented models 0 indicates no augmentation 1 indicates augmentation by first order

sensitivities (yields second order sensitivities) 2 indicates augmentation by one linear combination of first order sensitivities (yields hessian-vector product)

Note: This property has non-standard access specifiers: `SetAccess = Private`, `GetAccess = Public`

Note: [Matlab documentation of property attributes](#). **Default:** 0

matlabtypesubstitute z2event = `double.empty("")`

vector that maps outputs to events

Default: `double.empty("")`

matlabtypesubstitute splineflag = `false`

flag indicating whether the model contains spline functions

Default: `false`

matlabtypesubstitute minflag = `false`

flag indicating whether the model contains min functions

Default: `false`

matlabtypesubstitute maxflag = `false`

flag indicating whether the model contains max functions

Default: `false`

::int nw = 0

number of derived variables w, w is used for code optimization to reduce the number of frequently occurring expressions

Default: 0

::int ndwdx = 0

number of derivatives of derived variables w, dwdx

Default: 0

::int ndwdp = 0

number of derivatives of derived variables w, dwdp

Default: 0

Public Static Functions

noret::substitute amimodel::compileAndLinkModel(matlabtypesubstitute modelname, matlabtypesubstitute modelSourceFolder, matlabtypesubstitute coptim, matlabtypesubstitute debug, matlabtypesubstitute funs, matlabtypesubstitute cfun)

compileAndLinkModel compiles the mex simulation file. It does not check if the model files have changed since generating C++ code or whether all files are still present. Use only if you know what you are doing. The safer alternative is rerunning *amiwrap()*.

param modelname name of the model as specified for *amiwrap()*

param modelSourceFolder path to model source directory

param coptim optimization flags

param debug enable debugging

param funs array with names of the model functions, will be guessed from source files if left empty

param cfun struct indicating which files should be recompiled

returns cfun – void

noret::substitute amimodel::generateMatlabWrapper(matlabtypesubstitute nx, matlabtypesubstitute ny, matlabtypesubstitute np, matlabtypesubstitute nk, matlabtypesubstitute nz, matlabtypesubstitute o2flag, ::amimodel amimodelo2, matlabtypesubstitute wrapperFilename, matlabtypesubstitute modelname, matlabtypesubstitute pscale, matlabtypesubstitute forward, matlabtypesubstitute adjoint)

generateMatlabWrapper generates the matlab wrapper for the compiled C files.

param nx number of states

param ny number of observables

param np number of parameters

param nk number of fixed parameters

param nz number of events

param o2flag o2flag

param amimodelo2 this struct must contain all necessary symbolic definitions for second order sensitivities

param wrapperFilename output filename

param modelname name of the model

param pscale default parameter scaling

param forward has forward sensitivity equations

param adjoint has adjoint sensitivity equations

returns adjoint – void

Class amioption

- Defined in file_matlab_@amioption_amioption.m

Inheritance Relationships

Base Type

- public matlab::mixin::CustomDisplay

Class Documentation

amioption : public matlab::mixin::CustomDisplay

AMIOPTION provides an option container to pass simulation parameters to the simulation routine.

Public Functions

amioption::amioption(matlabtypesubstitute varargin)

amioptions Construct a new amioptions object `OPTS = amioption()` creates a set of options with each option set to its default value.

`OPTS = amioption(PARAM, VAL, ...)` creates a set of options with the named parameters altered with the specified values.

`OPTS = amioption(OLDOPTS, PARAM, VAL, ...)` creates a copy of OLDOPTS with the named parameters altered with the specified value

Note: to see the parameters, check the documentation page for amioption

param varargin input to construct amioption object, see function function description

Public Members

matlabtypesubstitute atol = 1e-16

absolute integration tolerace

Default: 1e-16

matlabtypesubstitute rtol = 1e-8

relative integration tolerace

Default: 1e-8

matlabtypesubstitute maxsteps = 1e4

maximum number of integration steps

Default: 1e4

matlabtypesubstitute quad_atol = 1e-12

absolute quadrature tolerace

Default: 1e-12

matlabtypesubstitute quad_rtol = 1e-8
relative quadrature tolerance

Default: 1e-8

matlabtypesubstitute maxstepsB = 0
maximum number of integration steps

Default: 0

matlabtypesubstitute ss_atol = 1e-16
absolute steady state tolerance

Default: 1e-16

matlabtypesubstitute ss_rtol = 1e-8
relative steady state tolerance

Default: 1e-8

matlabtypesubstitute sens_ind = double.empty("")
index of parameters for which the sensitivities are computed

Default: double.empty("")

matlabtypesubstitute tstart = 0
starting time of the simulation

Default: 0

matlabtypesubstitute lmm = 2
linear multistep method.

Default: 2

matlabtypesubstitute iter = 2
iteration method for linear multistep.

Default: 2

matlabtypesubstitute linsol = 9
linear solver

Default: 9

matlabtypesubstitute stldet = true
stability detection flag

Default: true

matlabtypesubstitute interpType = 1
interpolation type

Default: 1

matlabtypesubstitute ism = 1
forward sensitivity mode

Default: 1

matlabtypesubstitute sensi_meth = 1
sensitivity method

Default: 1

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute sensi_meth_preeq = 1
sensitivity method for preequilibration

Default: 1

matlabtypesubstitute sensi = 0
sensitivity order

Default: 0

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute nmaxevent = 10
number of reported events

Default: 10

matlabtypesubstitute ordering = 0
reordering of states

Default: 0

matlabtypesubstitute ss = 0
steady state sensitivity flag

Default: 0

matlabtypesubstitute x0 = double.empty("")
custom initial state

Default: double.empty("")

matlabtypesubstitute sx0 = double.empty("")
custom initial sensitivity

Default: double.empty("")

matlabtypesubstitute newton_maxsteps = 40
newton solver: maximum newton steps

Default: 40

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute z2event = `double.empty("")`
mapping of event outputs to events

Default: `double.empty("")`

matlabtypesubstitute pscale = `[]`

parameter scaling Single value or vector matching `sens_ind`. Valid options are “log”, “log10” and “lin” for log, log10 or unscaled parameters `p`. Use `[]` for default as specified in the model (fallback: `lin`).

Default: `[]`

Note: This property has custom functionality when its value is changed.

matlabtypesubstitute steadyStateSensitivityMode = `0`

Mode for computing sensitivities ({0: Newton}, 1: Simulation)

Default: `0`

Public Static Functions

mlhsInnerSubst< **matlabtypesubstitute** > **amioption::**

getIntegerPScale(**matlabtypesubstitute pscaleString**)

`pscaleInt` converts a parameter scaling string into the corresponding integer representation

param pscaleString parameter scaling string

returns pscaleString – int

Class amised

- Defined in `file_matlab_@amised_amised.m`

Inheritance Relationships

Base Type

- public handle

Class Documentation

amised : public handle

AMISED is a container for SED-ML objects.

Public Functions

amised::amised(matlabtypesubstitute sedname)

amised reads in an SEDML document using the JAVA binding of libSEDML

param sedname name/path of the SEDML document

Public Members

matlabtypesubstitute model = struct("'event',[],'sym',[]")

amimodel from the specified model

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** struct("'event',[],'sym',[]")

matlabtypesubstitute modelname = {""}

cell array of model identifiers

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** {""}

matlabtypesubstitute sedml = struct.empty("")

stores the struct tree from the xml definition

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** struct.empty("")

matlabtypesubstitute outputcount = "[]"

count the number of outputs per model

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** "[]"

matlabtypesubstitute varidx = "[]"
indexes for dataGenerators

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** ""

matlabtypesubstitute varsym = sym("[]")
symbolic expressions for variables

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** sym("")

matlabtypesubstitute datasym = sym("[]")
symbolic expressions for data

Note: This property has non-standard access specifiers: SetAccess = Private, GetAccess = Public

Note: [Matlab documentation of property attributes](#). **Default:** sym("")

Class optsym

- Defined in file_matlab_@optsym_optsym.m

Inheritance Relationships

Base Type

- public sym

Class Documentation

optsym : public sym

OPTSYM is an auxiliary class to gain access to the private symbolic property `s` which is necessary to be able to call `symobj::optimize` on it.

Public Functions

optsym::optsym(::sym symbol)

optsym converts the symbolic object into a optsym object

param symbol symbolic object

mlhsInnerSubst<::sym > optsym::getoptimized()

getoptimized calls `symobj::optimize` on the optsym object

returns out – optimized symbolic object

Functions

Function **am_and**

- Defined in file `_matlab_symbolic_am_and.m`

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_and(::sym a, ::sym b)

`am_and` is the amici implementation of the symbolic and function

param a first input parameter

param b second input parameter

returns fun – logical value, negative for false, positive for true

Function **am_eq**

- Defined in file `_matlab_symbolic_am_eq.m`

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_eq(matlabtypesubstitute varargin)

`am_eq` is currently a placeholder that simply produces an error message

param varargin elements for chain of equalities

returns fun – logical value, negative for false, positive for true

Function `am_ge`

- Defined in `file_matlab_symbolic_am_ge.m`

Function Documentation

mlhsInnerSubst< **matlabtypesubstitute** > **am_ge**(::sym varargin)

`am_ge` is the amici implementation of the n-ary `mathml greaterorequal` function this is an n-ary function, for more than 2 input parameters it will check whether `and(varargin{1} >= varargin{2}, varargin{2} >= varargin{3}, ...)`

param varargin chain of input parameters

returns fun – `a >= b` logical value, negative for false, positive for true

Function `am_gt`

- Defined in `file_matlab_symbolic_am_gt.m`

Function Documentation

mlhsInnerSubst< **matlabtypesubstitute** > **am_gt**(::sym varargin)

`am_gt` is the amici implementation of the n-ary `mathml greaterthan` function this is an n-ary function, for more than 2 input parameters it will check whether `and(varargin{1} > varargin{2}, varargin{2} > varargin{3}, ...)`

param varargin chain of input parameters

returns fun – `a > b` logical value, negative for false, positive for true

Function `am_if`

- Defined in `file_matlab_symbolic_am_if.m`

Function Documentation

mlhsInnerSubst< **matlabtypesubstitute** > **am_if**(::sym condition, ::sym truepart, ::sym falsepart)

`am_if` is the amici implementation of the symbolic if function

param condition logical value

param truepart value if condition is true

param falsepart value if condition is false

returns fun – if condition is true `truepart`, else `falsepart`

Function am_le

- Defined in file_matlab_symbolic_am_le.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_le(::sym varargin)

am_le is the amici implementation of the n-ary mathml lessorequal function this is an n-ary function, for more than 2 input parameters it will check whether and(varargin{1} <= varargin{2}, varargin{2} <= varargin{3},...)

param varargin chain of input parameters

returns fun – a <= b logical value, negative for false, positive for true

Function am_lt

- Defined in file_matlab_symbolic_am_lt.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_lt(::sym varargin)

am_lt is the amici implementation of the n-ary mathml lessthan function this is an n-ary function, for more than 2 input parameters it will check whether and(varargin{1} < varargin{2}, varargin{2} < varargin{3},...)

param varargin chain of input parameters

returns fun – a < b logical value, negative for false, positive for true

Function am_max

- Defined in file_matlab_symbolic_am_max.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_max(::sym a, ::sym b)

am_max is the amici implementation of the symbolic max function

param a first input parameter

param b second input parameter

returns fun – maximum of a and b

Function am_min

- Defined in file_matlab_symbolic_am_min.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_min(::sym a, ::sym b)

am_min is the amici implementation of the symbolic min function

param a first input parameter
param b second input parameter
returns fun – minimum of a and b

Function am_or

- Defined in file_matlab_symbolic_am_or.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_or(::sym a, ::sym b)

am_or is the amici implementation of the symbolic or function

param a first input parameter
param b second input parameter
returns fun – logical value, negative for false, positive for true

Function am_piecewise

- Defined in file_matlab_symbolic_am_piecewise.m

Function Documentation

mlhsInnerSubst< matlabtypesubstitute > am_piecewise(matlabtypesubstitute piece, matlabtypesubstitute condition, matlabtypesubstitute default)

am_piecewise is the amici implementation of the mathml piecewise function

param piece value if condition is true
param condition logical value
param default value if condition is false
returns fun – return value, piece if condition is true, default if not

Function `am_spline`

- Defined in `file_matlab_symbolic_am_spline.m`

Function Documentation

```
mlhsInnerSubst< matlabtypesubstitute > am_spline(matlabtypesubstitute varargin)
```

Function `am_spline_pos`

- Defined in `file_matlab_symbolic_am_spline_pos.m`

Function Documentation

```
mlhsInnerSubst< matlabtypesubstitute > am_spline_pos(matlabtypesubstitute varargin)
```

Function `am_stepfun`

- Defined in `file_matlab_symbolic_am_stepfun.m`

Function Documentation

```
mlhsInnerSubst< matlabtypesubstitute > am_stepfun(::sym t, matlabtypesubstitute tstart,  
matlabtypesubstitute vstart, matlabtypesubstitute tend, matlabtypesubstitute vend)
```

`am_stepfun` is the amici implementation of the step function

param t input variable

param tstart input variable value at which the step starts

param vstart value during the step

param tend input variable value at which the step end

param vend value after the step

returns fun – 0 before `tstart`, `vstart` between `tstart` and `tend` and `vend` after `tend`

Function `am_xor`

- Defined in `file_matlab_symbolic_am_xor.m`

Function Documentation

mlhsInnerSubst < matlabtypesubstitute > **am_xor**(::sym a, ::sym b)

am_xor is the amici implementation of the symbolic exclusive or function

param a first input parameter

param b second input parameter

returns fun – logical value, negative for false, positive for true

Function AMICI2D2D

- Defined in file_matlab_AMICI2D2D.m

Function Documentation

noret::substitute AMICI2D2D(matlabtypesubstitute filename,
matlabtypesubstitute modelname)

Function amiwrap

- Defined in file_matlab_amiwrap.m

Function Documentation

noret::substitute amiwrap(matlabtypesubstitute varargin)

AMIWRAP generates c++ mex files for the simulation of systems of differential equations via CVODES and IDAS.

param varargin

`amiwrap (modelname, symfun, tdir, o2flag)`

Required Parameters for varargin:

- modelname specifies the name of the model which will be later used for the naming of the simulation file
- symfun specifies a function which executes model definition
- tdir target directory where the simulation file should be placed **Default:** \$AMI-CIDIR/models/modelname
- o2flag boolean whether second order sensitivities should be enabled **Default:** false

returns o2flag – void

Function `installAMICI`

- Defined in `file_matlab_installAMICI.m`

Function Documentation

`noret::substitute installAMICI()`

Function `SBML2AMICI`

- Defined in `file_matlab_SBML2AMICI.m`

Function Documentation

`noret::substitute SBML2AMICI(matlabtypesubstitute filename,
matlabtypesubstitute modelname)`

SBML2AMICI generates AMICI model definition files from SBML.

param filename name of the SBML file (withouth extension)

param modelname name of the model, this will define the name of the output file (default: input filename)

returns modelname – void

AMICI DEVELOPER'S GUIDE

This document contains information for AMICI developers, not too relevant to regular users.

13.1 Branches / releases

AMICI roughly follows the [GitFlow](#). All new contributions are merged into `develop`. These changes are regularly merged into `master` as new releases. For release versioning we are trying to follow [semantic versioning](#). New releases are created on Github and are automatically deployed to [Zenodo](#) for archiving and to obtain a digital object identifier (DOI) to make them citable. Furthermore, our [CI pipeline](#) will automatically create and deploy a new release on [PyPI](#).

We try to keep a clean git history. Therefore, feature pull requests are squash-merged to `develop`. Merging of release branches to master is done via merge commits.

13.2 When starting to work on some issue

When starting to work on some Github issue, please assign yourself to let other developers know that you are working on it to avoid duplicate work. If the respective issue is not completely clear, it is generally a good idea to ask for clarification before starting to work on it.

If you want to work on something new, please create a Github issue first.

13.3 Code contributions

When making code contributions, please follow our style guide and the process described below:

- Check if you agree to release your contribution under the conditions provided in `LICENSE`. By opening a pull requests you confirm us that you do agree.
- Start a new branch from `develop` (on your fork, or at the main repository if you have access)
- Implement your changes
- Submit a pull request to the `develop` branch
- Make sure your code is documented appropriately
 - Run `scripts/run-doxygen.sh` to check completeness of your documentation
- Make sure your code is compatible with C++14, gcc and clang (our CI pipeline will do this for you)
- When adding new functionality, please also provide test cases (see `tests/cpp/` and [documentation/CI.md](#))

- Write meaningful commit messages
- Run all tests to ensure nothing was broken ([more details](#))
 - Run `scripts/buildAll.sh && scripts/run-cpp-tests.sh`.
 - If you made changes to the Matlab or C++ code and have a Matlab license, please also run `tests/cpp/wrapTestModels.m` and `tests/testModels.m`
 - If you made changes to the Python or C++ code, run `make python-tests` in `build`
- When all tests are passing and you think your code is ready to merge, request a code review (see also our [code review guideline](#))
- Wait for feedback. If you do not receive feedback to your pull request within a week, please give us a friendly reminder.

13.3.1 Style guide

General

- All files and functions should come with file-level and function-level documentation.
- All new functionality should be covered by unit or integration tests. Runtime of those tests should be kept as short as possible.

Python

- We want to be compatible with Python 3.8
- For the Python code we want to follow [PEP8](#). Although this is not the case for all existing code, any new contributions should do so.
- We use Python [type hints](#) for all functions (but not for class attributes, since they are not supported by the current Python doxygen filter). In Python code type hints should be used instead of doxygen `@type`.

For function docstrings, follow this format:

```
"""One-line description.

Possible a more detailed description

Arguments:
    Argument1: This needs to start on the same line, otherwise the current
        doxygen filter will fail.

Returns:
    Return value

Raises:
    SomeError in case of some error.
"""
```

C++

- We use C++14
- We want to maintain compatibility with g++, clang and the Intel C++ compiler
- For code formatting, we use the settings from `.clang-format` in the root directory
- *Details to be defined*

Matlab

To be defined

13.4 Further topics

13.4.1 AMICI documentation

This file describes how the AMICI documentation is organized and compiled.

Building documentation

Multi-interface documentation

AMICI documentation hosted at [Read the Docs \(RTD\)](#) is generated using [Sphinx](#) and related packages. The legacy GitHub Pages URL <https://amici-dev.github.io/AMICI/> is set up as a redirect to RTD.

The main configuration file is `documentation/conf.py` and the documentation is generated using `scripts/run-sphinx.sh`. The documentation is written to `documentation/_build/`.

The documentation comprises:

- reStructuredText / Markdown files from `documentation/`
- Python API documentation of native Python modules
- Python API documentation of Python generated via SWIG (doxygen-style comments translated to docstrings by SWIG)
- C++ API documentation (doxygen -> exhale -> breathe -> sphinx)
- Matlab API documentation (mtocpp -> doxygen -> exhale -> breathe -> sphinx)

Doxygen-only (legacy)

(Parts of the) AMICI documentation can also be directly created using [doxygen](#) directly. It combines Markdown files from the root directory, from `documentation/` and in-source documentation from the C++ and Matlab source files.

The documentation is generated by running

```
scripts/run-doxygen.sh
```

The resulting HTML and PDF documentation will be created in `doc/`. `scripts/run-doxygen.sh` also checks for any missing in-source documentation.

Doxygen configuration

The main doxygen configuration file is located in `matlab/mtoc/config/Doxyfile.template`. Edit this file for inclusion or exclusion of additional files.

Matlab documentation

Matlab documentation is processed by `mtoc++`. This is configured in `matlab/mtoc/config`.

Python documentation

Python documentation is processed by doxygen and doxypy using the script and filters in `scripts/`.

Writing documentation

Out-of-source documentation

Out-of-source documentation files should be written in reStructuredText if intended for Read the Docs or in Markdown if intended for rendering on GitHub. Files to be included in the Sphinx/RTD documentation live in `documentation/`. Graphics for documentation are kept in `documentation/gfx/`.

When using Markdown

- Note that there are some incompatibilities of GitHub Markdown and Doxygen Markdown. Ideally documentation should be written in a format compatible with both. This affects for example images links which currently cause trouble in Doxygen.
- Where possible, relative links are preferred over absolute links. However, they should work with both Github and Doxygen and ideally with local files for offline use.
- Please stick to the limit of 80 characters per line for readability of raw Markdown files where possible.
However, note that some Markdown interpreters can handle line breaks within links and headings, whereas others cannot. Here, compatibility is preferred over linebreaks.
- Avoid trailing whitespace

Maintaining the list of publications

We want to maintain a list of publications / projects using AMICI. This is located at `documentation/references.md`. This file is created by `documentation/recreate_reference_list.py` based on the bibtex file `documentation/amici_refs.bib`.

After any changes to `documentation/amici_refs.bib`, please run

`documentation/recreate_reference_list.py`

(requires `biblib`)

13.4.2 Code review guide

A guide for reviewing code and having your code reviewed by others.

Everyone

- Don't be too protective of your code
- Accept that, to a large extent, coding decisions are a matter of personal preference
- Don't get personal
- Ask for clarification
- Avoid strong language
- Try to understand your counterpart's perspective
- Clarify how strong you feel about each discussion point

Reviewing code

- If there are no objective advantages, don't force your style on others
- Ask questions instead of making demands
- Assume the author gave his best
- Mind the scope (many things are nice to have, but might be out of scope of the current change - open a new issue)
- The goal is "good enough", not "perfect"
- Be constructive
- You do not always have to request changes

Having your code reviewed

- Don't take it personal - the review is on the code, not on you
- Code reviews take time, appreciate the reviewer's comments
- Assume the reviewer did his best (but might still be wrong)
- Keep code changes small (e.g. separate wide reformatting from actual code changes to facilitate review)
- If the reviewer does not understand your code, probably many others won't either

Checklist

- ☐ Adherence to project-specific style guide
- ☐ The code is self-explanatory
- ☐ The code is concise / expressive
- ☐ Meaningful identifiers are used
- ☐ Corner-cases are covered, cases not covered fail loudly
- ☐ The code can be expected to scale well (enough)

- [] The code is well documented (e.g., input, operation, output), but without trivial comments
- [] The code is **SOLID**
- [] New code is added in the most meaningful place (i.e. matches the current architecture)
- [] No magic numbers
- [] No hard-coded values that should be user inputs
- [] No dead code left
- [] The changes make sense
- [] The changes are not obviously degrading performance
- [] There is no duplicated code
- [] The API is convenient
- [] Code block length and complexity is adequate
- [] Spelling okay
- [] The code is tested

13.4.3 Continuous integration (CI) and tests

AMICI uses a continuous integration pipeline running via <https://github.com/features/actions>. This includes the following steps:

- Checking existence and format of documentation
- Static code analysis (<http://cppcheck.sourceforge.net/>)
- Unit and integration tests
- Memory leak detection

More details are provided in the sections below.

The CI scripts and tests can be found in `tests/` and `scripts/`. Some of the tests are integrated with CMake, see `make help` in the build directory.

C++ unit and integration tests

To run C++ tests, build AMICI with `make` or `scripts/buildAll.sh`, then run `scripts/run-cpp-tests.sh`.

Python unit and integration tests

To run Python tests, run `../scripts/run-python-tests.sh` from anywhere (assumes build directory is `build/`) or run `make python-tests` in your build directory.

SBML Test Suite

We test Python-AMICI SBML support using the test cases from the semantic [SBML Test Suite](#). When making changes to the model import functions, make sure to run these tests.

To run the SBML Test Suite test cases, the easiest way is:

1. Running `scripts/installAmiciSource.sh` which creates a virtual Python environment and performs a development installation of AMICI from the current repository. (This needs to be run only once or after AMICI model generation or C++ changes).
2. Running `scripts/run-SBMLTestsuite.sh`. This will download the test cases if necessary and run them all. A subset of test cases can be selected with an optional argument (e.g. `scripts/run-SBMLTestsuite.sh 1, 3-6, 8`, to run cases 1, 3, 4, 5, 6 and 8).

Once the test cases are available locally, for debugging it might be easier to directly use `pytest` with `tests/testSBMLSuite.py`.

Matlab tests (not included in CI pipeline)

To execute the Matlab test suite, run `tests/testModels.m`.

Model simulation integration tests

Many of our integration tests are model simulations. The simulation results obtained from the Python and C++ are compared to results saved in an HDF5 file (`tests/cpp/expectedResults.h5`). Settings and data for the test simulations are also specified in this file.

Note: The C++ code for the models is included in the repository under `models/`. This code is to be updated whenever `amici::Model` changes.

Regenerating C++ code of the test models

Regeneration of the model code has to be done whenever `amici::Model` or the Matlab model import routines change.

This is done with

```
tests/cpp/wrapTestModels.m
```

Note: This is currently only possible from Matlab < R2018a. This should change as soon as 1) all second-order sensitivity code is ported to C++/Python, 2) a non-SBML import exists for Python and 3) support for events has been added for Python.

Regenerating expected results

To update test results, run `make test` in the build directory, replace `tests/cpp/expectedResults.h5` by `tests/cpp/writeResults.h5.bak` [ONLY DO THIS AFTER TRIPLE CHECKING CORRECTNESS OF RESULTS] Before replacing the test results, confirm that only expected datasets have changed, e.g. using

```
h5diff -v --relative 1e-8 tests/cpp/expectedResults.h5 tests/cpp/writeResults.h5.bak |
↪ less
```

Adding/Updating tests

To add new tests add a new corresponding python script (see, e.g., `./tests/generateTestConfig/example_dirac.py`) and add it to and run `tests/generateTestConfigurationForExamples.sh`. Then regenerate the expected test results (see above).

13.4.4 Debugging AMICI

This document contains some information on how to debug any issues in AMICI, in particular for C++ Python extensions.

Caveman debugging / printf-debugging

The simplest approach may often be adding some print-statements to the code, as this does not require any special tools.

Note that after each change of the C++ files, the AMICI extension *as well as the model extension* (if any model functions are called), need to be recompiled. The simplest and safest approach would be re-installation of the amici package and re-import of the model. As this can be very time-consuming, the following shortcut is possible, assuming you are using a development installation (`pip install -e .`):

```
# rebuild the amici base extension, from within the amici root directory
# (note that this only recompiles the amici source files, NOT third-party
# dependencies such as sundials):
cd python/sdist/
python setup.py build_ext --build-lib .

# rebuild the model, from within the model package directory:
python setup.py build_ext --force --build-lib .
```

Note: Be careful when working interactively, Python may not pick up any changes in already imported modules. The safest is to start a new Python process after any changes.

Using a proper debugger

Debugging with `gdb` (<https://www.sourceware.org/gdb/>) is most convenient with a minimal reproducible example that is directly invoked from `gdb`. For example:

```
# start gdb
gdb --args python -m pytest ../tests/test_sbml_import.py::test_nosensi

# inside gdb, set a meaningful breakpoint and launch:
break amici::runAmiciSimulation
run
# ... (see one of the many gdb tutorials)
```

Alternative, `gdb` can attach to a running process by passing the `--pid` argument.

For many users, it may be more convenient to use `gdb` via some graphical user interface as provided by various C++ IDEs.

Note: For better debugging experience, but at the cost of runtime performance, consider building the amici and model extension with environment variable `ENABLE_AMICI_DEBUGGING=TRUE`. This will include debugging symbols and disable compiler optimizations.

HANDLING OF DISCONTINUITIES

This document provides guidance and rationale on the implementation of events in AMICI. Events include any discontinuities in the right hand side of the differential equation. There are three types of discontinuities:

- **Solution Jump Discontinuities** can be created by SBML events or delta functions in the right hand side.
- **Right-Hand-Side Jump Discontinuities** result in removable discontinuities in the solution and can be created by Piecewise, Heaviside functions and other logical operators in the right hand side.
- **Right-Hand-Side Removable Discontinuities** do not lead to discontinuities in the solution, but may lead to discontinuous higher order temporal derivatives and can be created by functions such as max or min in the right hand side.

14.1 Mathematical Considerations

A detailed mathematical description of the required sensitivity formulas is provided in

- Fröhlich, F., Theis, F. J., Rädler, J. O., & Hasenauer, J. (2017). Parameter estimation for dynamical systems with discrete events and logical operations. *Bioinformatics*, 33(7), 1049-1056. doi:[10.1093/bioinformatics/btw764](https://doi.org/10.1093/bioinformatics/btw764).

14.2 Algorithmic Considerations

14.2.1 Solution Jump Discontinuities

SUNDIALS by itself does not support solution jump discontinuities. We implement support by accessing private SUNDIALS API in `amici::Solver::resetState()`, `amici::Solver::reInitPostProcess()` and `amici::Solver::reInitPostProcessB()`. These functions reset interval variables to initial values to simulate a fresh integration start, but keep/update the solution history, which is important for adjoint solutions.

14.2.2 Right-Hand-Side Jump Discontinuities

In principle these discontinuities do not need any special treatment, but empirically, the solver may overstep or completely ignore the discontinuity, leading to poor solution quality. This is particularly problematic when step size is large and changes in step size, which can be caused by parameter changes, inclusion of forward sensitivities or during backward solves, may alter solutions in unexpected ways. Accordingly, finite difference approximations, forward sensitivities as well as adjoint sensitivities will yield poor derivative approximations.

To address these issues, we use the built-in rootfinding functionality in SUNDIALS, which pauses the solver at the locations of discontinuities and avoids overstepping or ignoring of discontinuities.

Another difficulty comes with the evaluation of Heaviside functions. After or during processing of discontinuities, Heaviside functions need to be evaluated at the left and right hand limit of discontinuities. This is challenging as the solver may slightly over- or understep the discontinuity timepoint by a small epsilon and limits have to be correctly computed in both forward and backward passes.

To address this issue, AMICI uses a vector of Heaviside helper variables h that keeps track of the values of the Heaviside functions that have the respective root function as argument. These will be automatically updated during events and take either 0 or 1 values as appropriate pre/post event limits.

In order to fully support SBML events and Piecewise functions, AMICI uses the SUNDIALS functionality to only track zero crossings from negative to positive. Accordingly, two root functions are necessary to keep track of Heaviside functions and two Heaviside function helper variables will be created, where one corresponds to the value of $\text{Heaviside}(\dots)$ and one to the value of $1 - \text{Heaviside}(\dots)$. To ensure that Heaviside functions are correctly evaluated at the beginning of the simulation, Heaviside functions are implemented as unit steps that evaluate to 1 at 0. The arguments of Heaviside functions are normalized such that respective properties of Piecewise functions are conserved for the first Heaviside function variable. Accordingly, the value of the second helper variable is incorrect when simulation starts when the respective Heaviside function evaluates to zero at initialization and should generally not be used.

14.2.3 Right-Hand-Side Removable Discontinuities

Removable discontinuities do not require any special treatment. Numerically, this may be advantageous, but is currently not implemented.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

a

- `amici`, 140
- `amici.amici`, 142
- `amici.bngl_import`, 218
- `amici.conservated_quantities_demartino`, 278
- `amici.conservated_quantities_rref`, 279
- `amici.gradient_check`, 273
- `amici.import_utils`, 236
- `amici.logging`, 272
- `amici.ode_export`, 240
- `amici.ode_model`, 254
- `amici.pandas`, 268
- `amici.parameter_mapping`, 274
- `amici.petab_import`, 219
- `amici.petab_import_pysb`, 223
- `amici.petab_objective`, 229
- `amici.petab_simulate`, 234
- `amici.plotting`, 267
- `amici.pysb_import`, 216
- `amici.sbml_import`, 210

Symbols

[_USE_MATH_DEFINES](#) (*C macro*), 525
[__init__\(\)](#) (*amici.ModelModule method*), 141
[__init__\(\)](#) (*amici.add_path method*), 141
[__init__\(\)](#) (*amici.amici.ExpData method*), 148
[__init__\(\)](#) (*amici.amici.Model method*), 163
[__init__\(\)](#) (*amici.amici.ModelDimensions method*), 179
[__init__\(\)](#) (*amici.amici.ReturnData method*), 187
[__init__\(\)](#) (*amici.amici.SimulationParameters method*), 194
[__init__\(\)](#) (*amici.amici.Solver method*), 198
[__init__\(\)](#) (*amici.ode_export.ODEExporter method*), 242
[__init__\(\)](#) (*amici.ode_export.ODEModel method*), 246
[__init__\(\)](#) (*amici.ode_export.TemplateAmici method*), 251
[__init__\(\)](#) (*amici.ode_model.ConservationLaw method*), 255
[__init__\(\)](#) (*amici.ode_model.Constant method*), 256
[__init__\(\)](#) (*amici.ode_model.Event method*), 258
[__init__\(\)](#) (*amici.ode_model.Expression method*), 259
[__init__\(\)](#) (*amici.ode_model.LogLikelihood method*), 260
[__init__\(\)](#) (*amici.ode_model.ModelQuantity method*), 261
[__init__\(\)](#) (*amici.ode_model.Observable method*), 262
[__init__\(\)](#) (*amici.ode_model.Parameter method*), 264
[__init__\(\)](#) (*amici.ode_model.SigmaY method*), 265
[__init__\(\)](#) (*amici.ode_model.State method*), 266
[__init__\(\)](#) (*amici.parameter_mapping.ParameterMapping method*), 275
[__init__\(\)](#) (*amici.parameter_mapping.ParameterMapping method*), 276
[__init__\(\)](#) (*amici.petab_import_pysb.PysbPetabProblem method*), 224
[__init__\(\)](#) (*amici.petab_simulate.PetabSimulator method*), 235
[__init__\(\)](#) (*amici.sbml_import.SbmlImporter method*), 212

A

[add_component\(\)](#) (*amici.ode_export.ODEModel method*), 246
[add_conservation_law\(\)](#) (*amici.ode_export.ODEModel method*), 246
[add_d_dt\(\)](#) (*amici.sbml_import.SbmlImporter method*), 212
[add_local_symbol\(\)](#) (*amici.sbml_import.SbmlImporter method*), 213
[add_noise\(\)](#) (*amici.petab_simulate.PetabSimulator method*), 235
[add_path](#) (*class in amici*), 141
[amici](#)
 module, 140
[amici.amici](#)
 module, 142
[amici.bngl_import](#)
 module, 218
[amici.conserved_quantities_demartino](#)
 module, 278
[amici.conserved_quantities_rref](#)
 module, 279
[amici.gradient_check](#)
 module, 273
[amici.import_utils](#)
 module, 236
[amici.logging](#)
 module, 272
[amici.ode_export](#)
 module, 240
[amici.ode_model](#)
 module, 254
[amici.petab_import_pysb](#)
 module, 268
[amici.parameter_mapping](#)
 module, 274
[amici.petab_import](#)
 module, 219
[amici.petab_import_pysb](#)
 module, 223
[amici.petab_objective](#)

module, 229
 amici.petab_simulate
 module, 234
 amici.plotting
 module, 267
 amici.pysb_import
 module, 216
 amici.sbml_import
 module, 210
 amici::AbstractModel (C++ class), 299
 amici::AbstractModel::~~AbstractModel (C++
 function), 300
 amici::AbstractModel::fdeltaqB (C++ function),
 310
 amici::AbstractModel::fdeltasx (C++ function),
 309
 amici::AbstractModel::fdeltax (C++ function),
 308
 amici::AbstractModel::fdeltaxB (C++ function),
 309
 amici::AbstractModel::fdJrzdsigma (C++ func-
 tion), 314
 amici::AbstractModel::fdJrzdz (C++ function),
 313
 amici::AbstractModel::fdJydsigma (C++ func-
 tion), 313
 amici::AbstractModel::fdJydy (C++ function), 312
 amici::AbstractModel::fdJydy_colptrs (C++
 function), 312
 amici::AbstractModel::fdJydy_rowvals (C++
 function), 312
 amici::AbstractModel::fdJzdsigma (C++ func-
 tion), 313
 amici::AbstractModel::fdJzdz (C++ function), 313
 amici::AbstractModel::fdrzdp (C++ function), 308
 amici::AbstractModel::fdrzdx (C++ function), 308
 amici::AbstractModel::fdsigmaydp (C++ func-
 tion), 310
 amici::AbstractModel::fdsigmaydy (C++ func-
 tion), 311
 amici::AbstractModel::fdsigmazdp (C++ func-
 tion), 311
 amici::AbstractModel::fdtotal_cldp (C++ func-
 tion), 317
 amici::AbstractModel::fdtotal_cldx_rdata
 (C++ function), 317
 amici::AbstractModel::fdtotal_cldx_rdata_colptrs
 (C++ function), 317
 amici::AbstractModel::fdtotal_cldx_rdata_rowvals
 (C++ function), 318
 amici::AbstractModel::fdwdp (C++ function), 314,
 315
 amici::AbstractModel::fdwdp_colptrs (C++
 function), 315
 amici::AbstractModel::fdwdp_rowvals (C++
 function), 315
 amici::AbstractModel::fdwdw (C++ function), 316
 amici::AbstractModel::fdwdw_colptrs (C++
 function), 316
 amici::AbstractModel::fdwdw_rowvals (C++
 function), 316
 amici::AbstractModel::fdwdx (C++ function), 315
 amici::AbstractModel::fdwdx_colptrs (C++
 function), 315
 amici::AbstractModel::fdwdx_rowvals (C++
 function), 316
 amici::AbstractModel::fdx0 (C++ function), 304
 amici::AbstractModel::fdx_rdatadp (C++ func-
 tion), 316
 amici::AbstractModel::fdx_rdatadtcl (C++
 function), 317
 amici::AbstractModel::fdx_rdatadtcl_colptrs
 (C++ function), 317
 amici::AbstractModel::fdx_rdatadtcl_rowvals
 (C++ function), 317
 amici::AbstractModel::fdx_rdatadx_solver
 (C++ function), 316
 amici::AbstractModel::fdx_rdatadx_solver_colptrs
 (C++ function), 316
 amici::AbstractModel::fdx_rdatadx_solver_rowvals
 (C++ function), 316
 amici::AbstractModel::fdxdotdp (C++ function),
 302
 amici::AbstractModel::fdydp (C++ function), 305
 amici::AbstractModel::fdydx (C++ function), 306
 amici::AbstractModel::fdzdp (C++ function), 307
 amici::AbstractModel::fdzdx (C++ function), 308
 amici::AbstractModel::fJ (C++ function), 301
 amici::AbstractModel::fJB (C++ function), 301
 amici::AbstractModel::fJDiag (C++ function), 302
 amici::AbstractModel::fJrz (C++ function), 312
 amici::AbstractModel::fJSparse (C++ function),
 302
 amici::AbstractModel::fJSparseB (C++ function),
 302
 amici::AbstractModel::fJSparseB_ss (C++ func-
 tion), 301
 amici::AbstractModel::fJv (C++ function), 303
 amici::AbstractModel::fJy (C++ function), 311
 amici::AbstractModel::fJz (C++ function), 311
 amici::AbstractModel::froot (C++ function), 300
 amici::AbstractModel::frz (C++ function), 307
 amici::AbstractModel::fsigmay (C++ function),
 310
 amici::AbstractModel::fsigmaz (C++ function),
 311
 amici::AbstractModel::fsrz (C++ function), 307
 amici::AbstractModel::fstau (C++ function), 304

amici::AbstractModel::fsx0 (C++ function), 304
 amici::AbstractModel::fsx0_fixedParameters (C++ function), 304
 amici::AbstractModel::fsxdot (C++ function), 300
 amici::AbstractModel::fsz (C++ function), 306
 amici::AbstractModel::fw (C++ function), 314
 amici::AbstractModel::fx0 (C++ function), 303
 amici::AbstractModel::fx0_fixedParameters (C++ function), 303
 amici::AbstractModel::fxBdot_ss (C++ function), 300
 amici::AbstractModel::fxdot (C++ function), 300
 amici::AbstractModel::fy (C++ function), 305
 amici::AbstractModel::fz (C++ function), 306
 amici::AbstractModel::getAmiciCommit (C++ function), 303
 amici::AbstractModel::getAmiciVersion (C++ function), 303
 amici::AbstractModel::getSolver (C++ function), 300
 amici::AbstractModel::isFixedParameterStateReinitialized (C++ function), 303
 amici::AbstractModel::writeSteadystateJB (C++ function), 301
 amici::AMICI_CONV_FAILURE (C++ member), 520
 amici::AMICI_DAMPING_FACTOR_ERROR (C++ member), 520
 amici::AMICI_DATA_RETURN (C++ member), 520
 amici::amici_daxpy (C++ function), 494
 amici::amici_dgemm (C++ function), 494
 amici::amici_dgemv (C++ function), 495
 amici::AMICI_ERR_FAILURE (C++ member), 520
 amici::AMICI_ERROR (C++ member), 521
 amici::AMICI_ILL_INPUT (C++ member), 521
 amici::AMICI_MAX_TIME_EXCEEDED (C++ member), 521
 amici::AMICI_NO_STEADY_STATE (C++ member), 521
 amici::AMICI_NORMAL (C++ member), 522
 amici::AMICI_NOT_IMPLEMENTED (C++ member), 522
 amici::AMICI_ONE_STEP (C++ member), 522
 amici::AMICI_ONEOUTPUT (C++ member), 522
 amici::AMICI_PREEQUILIBRATE (C++ member), 522
 amici::AMICI_RECOVERABLE_ERROR (C++ member), 523
 amici::AMICI_RHSFUNC_FAIL (C++ member), 523
 amici::AMICI_ROOT_RETURN (C++ member), 523
 amici::AMICI_SINGULAR_JACOBIAN (C++ member), 523
 amici::AMICI_SUCCESS (C++ member), 524
 amici::AMICI_TOO_MUCH_ACC (C++ member), 524
 amici::AMICI_TOO_MUCH_WORK (C++ member), 524
 amici::AMICI_UNRECOVERABLE_ERROR (C++ member), 524
 amici::AmiciApplication (C++ class), 318
 amici::AmiciApplication::AmiciApplication (C++ function), 318
 amici::AmiciApplication::checkFinite (C++ function), 319
 amici::AmiciApplication::error (C++ member), 319
 amici::AmiciApplication::errorF (C++ function), 319
 amici::AmiciApplication::runAmiciSimulation (C++ function), 318
 amici::AmiciApplication::runAmiciSimulations (C++ function), 318
 amici::AmiciApplication::warning (C++ member), 319
 amici::AmiciApplication::warningF (C++ function), 319
 amici::AmiException (C++ class), 320
 amici::AmiException::AmiException (C++ function), 320
 amici::AmiException::getBacktrace (C++ function), 320
 amici::AmiException::isAllowed (C++ member), 320
 amici::AmiException::storeBacktrace (C++ function), 320
 amici::AmiException::storeMessage (C++ function), 321
 amici::AmiException::what (C++ function), 320
 amici::AmiVector (C++ class), 321
 amici::AmiVector::~AmiVector (C++ function), 322
 amici::AmiVector::abs (C++ function), 323
 amici::AmiVector::AmiVector (C++ function), 321
 amici::AmiVector::at (C++ function), 323
 amici::AmiVector::begin (C++ function), 322
 amici::AmiVector::copy (C++ function), 323
 amici::AmiVector::data (C++ function), 322
 amici::AmiVector::end (C++ function), 322
 amici::AmiVector::getLength (C++ function), 322
 amici::AmiVector::getNVector (C++ function), 322
 amici::AmiVector::getVector (C++ function), 322
 amici::AmiVector::minus (C++ function), 323
 amici::AmiVector::operator*= (C++ function), 322
 amici::AmiVector::operator/= (C++ function), 322
 amici::AmiVector::operator= (C++ function), 322
 amici::AmiVector::operator[] (C++ function), 323
 amici::AmiVector::set (C++ function), 323
 amici::AmiVector::zero (C++ function), 323
 amici::AmiVectorArray (C++ class), 323
 amici::AmiVectorArray::~AmiVectorArray (C++ function), 324
 amici::AmiVectorArray::AmiVectorArray (C++ function), 324
 amici::AmiVectorArray::at (C++ function), 324
 amici::AmiVectorArray::copy (C++ function), 325
 amici::AmiVectorArray::data (C++ function), 324

`amici::AmiVectorArray::flatten_to_vector` (C++ function), 325

`amici::AmiVectorArray::getLength` (C++ function), 325

`amici::AmiVectorArray::getNVector` (C++ function), 325

`amici::AmiVectorArray::getNVectorArray` (C++ function), 325

`amici::AmiVectorArray::operator=` (C++ function), 324

`amici::AmiVectorArray::operator[]` (C++ function), 325

`amici::AmiVectorArray::zero` (C++ function), 325

`amici::backtraceString` (C++ function), 496

`amici::BackwardProblem` (C++ class), 326

`amici::BackwardProblem::BackwardProblem` (C++ function), 326

`amici::BackwardProblem::getAdjointQuadrature` (C++ function), 326

`amici::BackwardProblem::getAdjointState` (C++ function), 326

`amici::BackwardProblem::getdJydx` (C++ function), 326

`amici::BackwardProblem::gett` (C++ function), 326

`amici::BackwardProblem::getwhich` (C++ function), 326

`amici::BackwardProblem::getwhichptr` (C++ function), 326

`amici::BackwardProblem::workBackwardProblem` (C++ function), 326

`amici::BLASLayout` (C++ enum), 487

`amici::BLASLayout::colMajor` (C++ enumerator), 487

`amici::BLASLayout::rowMajor` (C++ enumerator), 487

`amici::BLASTranspose` (C++ enum), 488

`amici::BLASTranspose::conjTrans` (C++ enumerator), 488

`amici::BLASTranspose::noTrans` (C++ enumerator), 488

`amici::BLASTranspose::trans` (C++ enumerator), 488

`amici::checkBufferSize` (C++ function), 496

`amici::checkSigmaPositivity` (C++ function), 496, 497

`amici::ConditionContext` (C++ class), 327

`amici::ConditionContext::~~ConditionContext` (C++ function), 327

`amici::ConditionContext::applyCondition` (C++ function), 327

`amici::ConditionContext::ConditionContext` (C++ function), 327

`amici::ConditionContext::operator=` (C++ function), 327

`amici::ConditionContext::restore` (C++ function), 327

`amici::const_N_Vector` (C++ type), 529

`amici::ContextManager` (C++ class), 328

`amici::ContextManager::ContextManager` (C++ function), 328

`amici::CvodeException` (C++ class), 329

`amici::CvodeException::CvodeException` (C++ function), 329

`amici::CvodeSolver` (C++ class), 329

`amici::CvodeSolver::~~CvodeSolver` (C++ function), 329

`amici::CvodeSolver::adjInit` (C++ function), 335

`amici::CvodeSolver::allocateSolver` (C++ function), 333

`amici::CvodeSolver::allocateSolverB` (C++ function), 335

`amici::CvodeSolver::binit` (C++ function), 337

`amici::CvodeSolver::boost::serialization::serialize` (C++ function), 338

`amici::CvodeSolver::calcIC` (C++ function), 332

`amici::CvodeSolver::calcICB` (C++ function), 332

`amici::CvodeSolver::clone` (C++ function), 329

`amici::CvodeSolver::diag` (C++ function), 335

`amici::CvodeSolver::diagB` (C++ function), 335

`amici::CvodeSolver::getAdjBmem` (C++ function), 336

`amici::CvodeSolver::getB` (C++ function), 332

`amici::CvodeSolver::getDky` (C++ function), 331

`amici::CvodeSolver::getDkyB` (C++ function), 331

`amici::CvodeSolver::getLastOrder` (C++ function), 336

`amici::CvodeSolver::getModel` (C++ function), 331

`amici::CvodeSolver::getNumErrTestFails` (C++ function), 336

`amici::CvodeSolver::getNumNonlinSolvConvFails` (C++ function), 336

`amici::CvodeSolver::getNumRhsEvals` (C++ function), 336

`amici::CvodeSolver::getNumSteps` (C++ function), 336

`amici::CvodeSolver::getQuad` (C++ function), 332

`amici::CvodeSolver::getQuadB` (C++ function), 332

`amici::CvodeSolver::getQuadDky` (C++ function), 332

`amici::CvodeSolver::getQuadDkyB` (C++ function), 331

`amici::CvodeSolver::getRootInfo` (C++ function), 331

`amici::CvodeSolver::getSens` (C++ function), 332

`amici::CvodeSolver::getSensDky` (C++ function), 331

`amici::CvodeSolver::init` (C++ function), 336

`amici::CvodeSolver::initSteadystate` (C++

function), 337
 amici::CvodeSolver::operator== (C++ *function*), 338
 amici::CvodeSolver::qbinit (C++ *function*), 337
 amici::CvodeSolver::quadInit (C++ *function*), 335
 amici::CvodeSolver::quadReInitB (C++ *function*), 330
 amici::CvodeSolver::quadSStolerances (C++ *function*), 335
 amici::CvodeSolver::quadSStolerancesB (C++ *function*), 335
 amici::CvodeSolver::reInit (C++ *function*), 329
 amici::CvodeSolver::reInitB (C++ *function*), 330
 amici::CvodeSolver::reInitPostProcess (C++ *function*), 333
 amici::CvodeSolver::reInitPostProcessB (C++ *function*), 333
 amici::CvodeSolver::reInitPostProcessF (C++ *function*), 333
 amici::CvodeSolver::resetState (C++ *function*), 334
 amici::CvodeSolver::rootInit (C++ *function*), 337
 amici::CvodeSolver::sensInit1 (C++ *function*), 337
 amici::CvodeSolver::sensReInit (C++ *function*), 330
 amici::CvodeSolver::sensToggleOff (C++ *function*), 330
 amici::CvodeSolver::setBandJacFn (C++ *function*), 337
 amici::CvodeSolver::setBandJacFnB (C++ *function*), 338
 amici::CvodeSolver::setDenseJacFn (C++ *function*), 337
 amici::CvodeSolver::setDenseJacFnB (C++ *function*), 337
 amici::CvodeSolver::setErrHandlerFn (C++ *function*), 334
 amici::CvodeSolver::setId (C++ *function*), 334
 amici::CvodeSolver::setJacTimesVecFn (C++ *function*), 337
 amici::CvodeSolver::setJacTimesVecFnB (C++ *function*), 338
 amici::CvodeSolver::setLinearSolver (C++ *function*), 331
 amici::CvodeSolver::setLinearSolverB (C++ *function*), 331
 amici::CvodeSolver::setMaxNumSteps (C++ *function*), 334
 amici::CvodeSolver::setMaxNumStepsB (C++ *function*), 335
 amici::CvodeSolver::setNonLinearSolver (C++ *function*), 331
 amici::CvodeSolver::setNonLinearSolverB (C++ *function*), 332
 amici::CvodeSolver::setNonLinearSolverSens (C++ *function*), 331
 amici::CvodeSolver::setQuadErrCon (C++ *function*), 333
 amici::CvodeSolver::setQuadErrConB (C++ *function*), 333
 amici::CvodeSolver::setSensErrCon (C++ *function*), 333
 amici::CvodeSolver::setSensParams (C++ *function*), 334
 amici::CvodeSolver::setSensSStolerances (C++ *function*), 333
 amici::CvodeSolver::setSparseJacFn (C++ *function*), 337
 amici::CvodeSolver::setSparseJacFn_ss (C++ *function*), 338
 amici::CvodeSolver::setSparseJacFnB (C++ *function*), 338
 amici::CvodeSolver::setSStolerances (C++ *function*), 333
 amici::CvodeSolver::setSStolerancesB (C++ *function*), 335
 amici::CvodeSolver::setStabLimDet (C++ *function*), 334
 amici::CvodeSolver::setStabLimDetB (C++ *function*), 334
 amici::CvodeSolver::setStopTime (C++ *function*), 331
 amici::CvodeSolver::setSuppressAlg (C++ *function*), 334
 amici::CvodeSolver::setUserData (C++ *function*), 334
 amici::CvodeSolver::setUserDataB (C++ *function*), 334
 amici::CvodeSolver::solve (C++ *function*), 330
 amici::CvodeSolver::solveB (C++ *function*), 330
 amici::CvodeSolver::solveF (C++ *function*), 330
 amici::CvodeSolver::Solver (C++ *function*), 332
 amici::CvodeSolver::turnOffRootFinding (C++ *function*), 331
 amici::defaultContext (C++ *member*), 524
 amici::deserializeFromChar (C++ *function*), 497
 amici::deserializeFromString (C++ *function*), 497
 amici::dotProd (C++ *function*), 498
 amici::ExpData (C++ *class*), 339
 amici::ExpData::~ExpData (C++ *function*), 340
 amici::ExpData::applyDataDimension (C++ *function*), 344
 amici::ExpData::applyDimensions (C++ *function*), 344
 amici::ExpData::applyEventDimension (C++ *function*), 344
 amici::ExpData::checkDataDimension (C++ *function*), 344

tion), 344
 amici::ExpData::checkEventsDimension (C++ function), 344
 amici::ExpData::ExpData (C++ function), 339, 340
 amici::ExpData::getObservedData (C++ function), 341
 amici::ExpData::getObservedDataPtr (C++ function), 341
 amici::ExpData::getObservedDataStdDev (C++ function), 342
 amici::ExpData::getObservedDataStdDevPtr (C++ function), 342
 amici::ExpData::getObservedEvents (C++ function), 342
 amici::ExpData::getObservedEventsPtr (C++ function), 342
 amici::ExpData::getObservedEventsStdDev (C++ function), 343
 amici::ExpData::getObservedEventsStdDevPtr (C++ function), 343
 amici::ExpData::getTimepoint (C++ function), 341
 amici::ExpData::getTimepoints (C++ function), 341
 amici::ExpData::id (C++ member), 343
 amici::ExpData::isSetObservedData (C++ function), 341
 amici::ExpData::isSetObservedDataStdDev (C++ function), 342
 amici::ExpData::isSetObservedEvents (C++ function), 342
 amici::ExpData::isSetObservedEventsStdDev (C++ function), 343
 amici::ExpData::nmaxevent (C++ function), 340
 amici::ExpData::nmaxevent_ (C++ member), 344
 amici::ExpData::nt (C++ function), 340
 amici::ExpData::nytrue (C++ function), 340
 amici::ExpData::nytrue_ (C++ member), 344
 amici::ExpData::nztrue (C++ function), 340
 amici::ExpData::nztrue_ (C++ member), 344
 amici::ExpData::observed_data_ (C++ member), 344
 amici::ExpData::observed_data_std_dev_ (C++ member), 344
 amici::ExpData::observed_events_ (C++ member), 344
 amici::ExpData::observed_events_std_dev_ (C++ member), 344
 amici::ExpData::setObservedData (C++ function), 341
 amici::ExpData::setObservedDataStdDev (C++ function), 341, 342
 amici::ExpData::setObservedEvents (C++ function), 342
 amici::ExpData::setObservedEventsStdDev (C++ function), 343
 amici::ExpData::setTimepoints (C++ function), 340
 amici::FinalStateStorer (C++ class), 345
 amici::FinalStateStorer::~FinalStateStorer (C++ function), 345
 amici::FinalStateStorer::FinalStateStorer (C++ function), 345
 amici::FinalStateStorer::operator= (C++ function), 345
 amici::FixedParameterContext (C++ enum), 488
 amici::FixedParameterContext::preequilibration (C++ enumerator), 488
 amici::FixedParameterContext::presimulation (C++ enumerator), 488
 amici::FixedParameterContext::simulation (C++ enumerator), 488
 amici::ForwardProblem (C++ class), 345
 amici::ForwardProblem::~ForwardProblem (C++ function), 346
 amici::ForwardProblem::edata (C++ member), 348
 amici::ForwardProblem::ForwardProblem (C++ function), 345
 amici::ForwardProblem::getAdjointUpdates (C++ function), 346
 amici::ForwardProblem::getCurrentTimeIteration (C++ function), 347
 amici::ForwardProblem::getDiscontinuities (C++ function), 346
 amici::ForwardProblem::getDJydx (C++ function), 347
 amici::ForwardProblem::getDJzdx (C++ function), 347
 amici::ForwardProblem::getEventCounter (C++ function), 347
 amici::ForwardProblem::getFinalSimulationState (C++ function), 348
 amici::ForwardProblem::getFinalTime (C++ function), 347
 amici::ForwardProblem::getInitialSimulationState (C++ function), 347
 amici::ForwardProblem::getNumberOfRoots (C++ function), 346
 amici::ForwardProblem::getRHSAtDiscontinuities (C++ function), 346
 amici::ForwardProblem::getRHSBeforeDiscontinuities (C++ function), 346
 amici::ForwardProblem::getRootCounter (C++ function), 347
 amici::ForwardProblem::getRootIndexes (C++ function), 346
 amici::ForwardProblem::getSimulationStateEvent (C++ function), 347
 amici::ForwardProblem::getSimulationStateTimepoint

(C++ function), 347
 amici::ForwardProblem::getState (C++ function), 346
 amici::ForwardProblem::getStateDerivative (C++ function), 346
 amici::ForwardProblem::getStateDerivativePointer (C++ function), 347
 amici::ForwardProblem::getStateDerivativeSensitivityPointer (C++ function), 347
 amici::ForwardProblem::getStatePointer (C++ function), 347
 amici::ForwardProblem::getStatesAtDiscontinuities (C++ function), 346
 amici::ForwardProblem::getStateSensitivity (C++ function), 346
 amici::ForwardProblem::getStateSensitivityPointer (C++ function), 347
 amici::ForwardProblem::getTime (C++ function), 346
 amici::ForwardProblem::model (C++ member), 348
 amici::ForwardProblem::solver (C++ member), 348
 amici::ForwardProblem::workForwardProblem (C++ function), 346
 amici::getScaledParameter (C++ function), 498
 amici::getUnscaledParameter (C++ function), 498
 amici::hdf5::attributeExists (C++ function), 499
 amici::hdf5::createAndWriteDouble1DDataset (C++ function), 499
 amici::hdf5::createAndWriteDouble2DDataset (C++ function), 500
 amici::hdf5::createAndWriteDouble3DDataset (C++ function), 500
 amici::hdf5::createAndWriteInt1DDataset (C++ function), 501
 amici::hdf5::createAndWriteInt2DDataset (C++ function), 501
 amici::hdf5::createGroup (C++ function), 501
 amici::hdf5::createOrOpenForWriting (C++ function), 502
 amici::hdf5::getDoubleDataset1D (C++ function), 502
 amici::hdf5::getDoubleDataset2D (C++ function), 502
 amici::hdf5::getDoubleDataset3D (C++ function), 503
 amici::hdf5::getDoubleScalarAttribute (C++ function), 503
 amici::hdf5::getIntDataset1D (C++ function), 504
 amici::hdf5::getIntScalarAttribute (C++ function), 504
 amici::hdf5::getStringAttribute (C++ function), 504
 amici::hdf5::locationExists (C++ function), 505
 amici::hdf5::readModelDataFromHDF5 (C++ function), 505, 506
 amici::hdf5::readSimulationExpData (C++ function), 506
 amici::hdf5::readSolverSettingsFromHDF5 (C++ function), 507
 amici::hdf5::writeReturnData (C++ function), 507
 amici::hdf5::writeReturnDataDiagnosis (C++ function), 508
 amici::hdf5::writeSimulationExpData (C++ function), 508
 amici::hdf5::writeSolverSettingsToHDF5 (C++ function), 509
 amici::IDAException (C++ class), 348
 amici::IDAException::IDAException (C++ function), 348
 amici::IDASolver (C++ class), 349
 amici::IDASolver::~IDASolver (C++ function), 349
 amici::IDASolver::adjInit (C++ function), 354
 amici::IDASolver::allocateSolver (C++ function), 353
 amici::IDASolver::allocateSolverB (C++ function), 355
 amici::IDASolver::binit (C++ function), 357
 amici::IDASolver::calcIC (C++ function), 352
 amici::IDASolver::calcICB (C++ function), 352
 amici::IDASolver::clone (C++ function), 349
 amici::IDASolver::diag (C++ function), 355
 amici::IDASolver::diagB (C++ function), 355
 amici::IDASolver::getAdjBmem (C++ function), 356
 amici::IDASolver::getB (C++ function), 351
 amici::IDASolver::getDky (C++ function), 351
 amici::IDASolver::getDkyB (C++ function), 351
 amici::IDASolver::getLastOrder (C++ function), 356
 amici::IDASolver::getModel (C++ function), 352
 amici::IDASolver::getNumErrTestFails (C++ function), 356
 amici::IDASolver::getNumNonlinSolvConvFails (C++ function), 356
 amici::IDASolver::getNumRhsEvals (C++ function), 355
 amici::IDASolver::getNumSteps (C++ function), 355
 amici::IDASolver::getQuad (C++ function), 352
 amici::IDASolver::getQuadB (C++ function), 351
 amici::IDASolver::getQuadDky (C++ function), 352
 amici::IDASolver::getQuadDkyB (C++ function), 351
 amici::IDASolver::getRootInfo (C++ function), 351
 amici::IDASolver::getSens (C++ function), 351
 amici::IDASolver::getSensDky (C++ function), 351

`amici::IDASolver::init (C++ function), 356`
`amici::IDASolver::initSteadystate (C++ function), 356`
`amici::IDASolver::qbinit (C++ function), 357`
`amici::IDASolver::quadInit (C++ function), 355`
`amici::IDASolver::quadReInitB (C++ function), 350`
`amici::IDASolver::quadSStolerances (C++ function), 350`
`amici::IDASolver::quadSStolerancesB (C++ function), 350`
`amici::IDASolver::reInit (C++ function), 349`
`amici::IDASolver::reInitB (C++ function), 349`
`amici::IDASolver::reInitPostProcess (C++ function), 353`
`amici::IDASolver::reInitPostProcessB (C++ function), 349`
`amici::IDASolver::reInitPostProcessF (C++ function), 349`
`amici::IDASolver::resetState (C++ function), 354`
`amici::IDASolver::rootInit (C++ function), 357`
`amici::IDASolver::sensInit1 (C++ function), 356`
`amici::IDASolver::sensReInit (C++ function), 349`
`amici::IDASolver::sensToggleOff (C++ function), 349`
`amici::IDASolver::setBandJacFn (C++ function), 357`
`amici::IDASolver::setBandJacFnB (C++ function), 357`
`amici::IDASolver::setDenseJacFn (C++ function), 357`
`amici::IDASolver::setDenseJacFnB (C++ function), 357`
`amici::IDASolver::setErrHandlerFn (C++ function), 354`
`amici::IDASolver::setId (C++ function), 354`
`amici::IDASolver::setJacTimesVecFn (C++ function), 357`
`amici::IDASolver::setJacTimesVecFnB (C++ function), 357`
`amici::IDASolver::setLinearSolver (C++ function), 352`
`amici::IDASolver::setLinearSolverB (C++ function), 352`
`amici::IDASolver::setMaxNumSteps (C++ function), 354`
`amici::IDASolver::setMaxNumStepsB (C++ function), 355`
`amici::IDASolver::setNonLinearSolver (C++ function), 352`
`amici::IDASolver::setNonLinearSolverB (C++ function), 352`
`amici::IDASolver::setNonLinearSolverSens (C++ function), 352`
`amici::IDASolver::setQuadErrCon (C++ function), 353`
`amici::IDASolver::setQuadErrConB (C++ function), 353`
`amici::IDASolver::setSensErrCon (C++ function), 353`
`amici::IDASolver::setSensParams (C++ function), 354`
`amici::IDASolver::setSensSStolerances (C++ function), 353`
`amici::IDASolver::setSparseJacFn (C++ function), 357`
`amici::IDASolver::setSparseJacFn_ss (C++ function), 357`
`amici::IDASolver::setSparseJacFnB (C++ function), 357`
`amici::IDASolver::setSStolerances (C++ function), 353`
`amici::IDASolver::setSStolerancesB (C++ function), 355`
`amici::IDASolver::setStabLimDet (C++ function), 354`
`amici::IDASolver::setStabLimDetB (C++ function), 354`
`amici::IDASolver::setStopTime (C++ function), 352`
`amici::IDASolver::setSuppressAlg (C++ function), 354`
`amici::IDASolver::setUserData (C++ function), 354`
`amici::IDASolver::setUserDataB (C++ function), 354`
`amici::IDASolver::solve (C++ function), 350`
`amici::IDASolver::solveB (C++ function), 350`
`amici::IDASolver::solveF (C++ function), 350`
`amici::IDASolver::Solver (C++ function), 352, 353`
`amici::IDASolver::turnOffRootFinding (C++ function), 352`
`amici::IntegrationFailure (C++ class), 358`
`amici::IntegrationFailure::error_code (C++ member), 358`
`amici::IntegrationFailure::IntegrationFailure (C++ function), 358`
`amici::IntegrationFailure::time (C++ member), 358`
`amici::IntegrationFailureB (C++ class), 359`
`amici::IntegrationFailureB::error_code (C++ member), 359`
`amici::IntegrationFailureB::IntegrationFailureB (C++ function), 359`
`amici::IntegrationFailureB::time (C++ member), 359`
`amici::InternalSensitivityMethod (C++ enum), 488`

amici::InternalSensitivityMethod::simultaneous (C++ enumerator), 488
 amici::InternalSensitivityMethod::staggered (C++ enumerator), 488
 amici::InternalSensitivityMethod::staggered1 (C++ enumerator), 488
 amici::InterpolationType (C++ enum), 489
 amici::InterpolationType::hermite (C++ enumerator), 489
 amici::InterpolationType::polynomial (C++ enumerator), 489
 amici::LinearMultistepMethod (C++ enum), 489
 amici::LinearMultistepMethod::adams (C++ enumerator), 489
 amici::LinearMultistepMethod::BDF (C++ enumerator), 489
 amici::LinearSolver (C++ enum), 489
 amici::LinearSolver::band (C++ enumerator), 489
 amici::LinearSolver::dense (C++ enumerator), 489
 amici::LinearSolver::diag (C++ enumerator), 489
 amici::LinearSolver::KLU (C++ enumerator), 490
 amici::LinearSolver::LAPACKBand (C++ enumerator), 489
 amici::LinearSolver::LAPACKDense (C++ enumerator), 489
 amici::LinearSolver::SPBCG (C++ enumerator), 490
 amici::LinearSolver::SPGMR (C++ enumerator), 489
 amici::LinearSolver::SPTFQMR (C++ enumerator), 490
 amici::LinearSolver::SuperLUMT (C++ enumerator), 490
 amici::linearSum (C++ function), 509
 amici::Model (C++ class), 360
 amici::Model::~~Model (C++ function), 360
 amici::Model::addAdjointQuadratureEventUpdate (C++ function), 375
 amici::Model::addAdjointStateEventUpdate (C++ function), 375
 amici::Model::addEventObjective (C++ function), 373
 amici::Model::addEventObjectiveRegularization (C++ function), 373
 amici::Model::addEventObjectiveSensitivity (C++ function), 373
 amici::Model::addObservableObjective (C++ function), 370
 amici::Model::addObservableObjectiveSensitivity (C++ function), 370
 amici::Model::addPartialEventObjectiveSensitivity (C++ function), 373
 amici::Model::addPartialObservableObjectiveSensitivity (C++ function), 370
 amici::Model::addStateEventUpdate (C++ function), 374
 amici::Model::addStateSensitivityEventUpdate (C++ function), 374
 amici::Model::always_check_finite_ (C++ member), 400
 amici::Model::any_state_non_negative_ (C++ member), 400
 amici::Model::app (C++ member), 392
 amici::Model::boost::serialization::serialize (C++ function), 400
 amici::Model::checkFinite (C++ function), 376
 amici::Model::checkLLHBufferSize (C++ function), 392
 amici::Model::clone (C++ function), 360
 amici::Model::computeX_pos (C++ function), 399
 amici::Model::derived_state_ (C++ member), 400
 amici::Model::fdeltaqB (C++ function), 377
 amici::Model::fdeltasx (C++ function), 378
 amici::Model::fdeltax (C++ function), 378
 amici::Model::fdeltaxB (C++ function), 378
 amici::Model::fdJrzdsigma (C++ function), 379, 397
 amici::Model::fdJrzdz (C++ function), 379, 397
 amici::Model::fdJydp (C++ function), 394
 amici::Model::fdJydsigma (C++ function), 379, 394
 amici::Model::fdJydx (C++ function), 394
 amici::Model::fdJydy (C++ function), 380, 393
 amici::Model::fdJydy_colptrs (C++ function), 380
 amici::Model::fdJydy_rowvals (C++ function), 380
 amici::Model::fdJzdp (C++ function), 396
 amici::Model::fdJzdsigma (C++ function), 380, 396
 amici::Model::fdJzdx (C++ function), 396
 amici::Model::fdJzdz (C++ function), 380, 396
 amici::Model::fdrzdp (C++ function), 381, 395
 amici::Model::fdrzdx (C++ function), 381, 395
 amici::Model::fdsigmaydp (C++ function), 381, 393
 amici::Model::fdsigmaydy (C++ function), 382, 393
 amici::Model::fdsigmazdp (C++ function), 382, 395
 amici::Model::fdtotal_cldp (C++ function), 391
 amici::Model::fdtotal_cldx_rdata (C++ function), 391
 amici::Model::fdtotal_cldx_rdata_colptrs (C++ function), 391
 amici::Model::fdtotal_cldx_rdata_rowvals (C++ function), 391
 amici::Model::fdwdp (C++ function), 382, 397
 amici::Model::fdwdp_colptrs (C++ function), 383
 amici::Model::fdwdp_rowvals (C++ function), 383
 amici::Model::fdwdw (C++ function), 383, 398
 amici::Model::fdwdw_colptrs (C++ function), 384
 amici::Model::fdwdw_rowvals (C++ function), 384
 amici::Model::fdwdx (C++ function), 383, 397

`amici::Model::fdwdx_colptrs (C++ function), 383`
`amici::Model::fdwdx_rowvals (C++ function), 383`
`amici::Model::fdx_rdatadp (C++ function), 390`
`amici::Model::fdx_rdatadtcl (C++ function), 390`
`amici::Model::fdx_rdatadtcl_colptrs (C++ function), 391`
`amici::Model::fdx_rdatadtcl_rowvals (C++ function), 391`
`amici::Model::fdx_rdatadx_solver (C++ function), 390`
`amici::Model::fdx_rdatadx_solver_colptrs (C++ function), 390`
`amici::Model::fdx_rdatadx_solver_rowvals (C++ function), 390`
`amici::Model::fdydp (C++ function), 384, 393`
`amici::Model::fdydx (C++ function), 384, 393`
`amici::Model::fdzdp (C++ function), 385, 394`
`amici::Model::fdzdx (C++ function), 385, 394`
`amici::Model::fJrz (C++ function), 385, 397`
`amici::Model::fJy (C++ function), 386, 393`
`amici::Model::fJz (C++ function), 386, 396`
`amici::Model::frz (C++ function), 386, 395`
`amici::Model::fsdx0 (C++ function), 376`
`amici::Model::fsigmay (C++ function), 387, 393`
`amici::Model::fsigmaz (C++ function), 387, 395`
`amici::Model::fsrz (C++ function), 387`
`amici::Model::fstau (C++ function), 387`
`amici::Model::fstotal_cl (C++ function), 399`
`amici::Model::fsx0 (C++ function), 376, 388`
`amici::Model::fsx0_fixedParameters (C++ function), 376, 388`
`amici::Model::fsx_rdata (C++ function), 377, 398`
`amici::Model::fsx_solver (C++ function), 398`
`amici::Model::fsz (C++ function), 388`
`amici::Model::ftotal_cl (C++ function), 399`
`amici::Model::fw (C++ function), 389, 397`
`amici::Model::fx0 (C++ function), 376, 389`
`amici::Model::fx0_fixedParameters (C++ function), 376, 389`
`amici::Model::fx_rdata (C++ function), 376, 398`
`amici::Model::fx_solver (C++ function), 398`
`amici::Model::fy (C++ function), 389, 393`
`amici::Model::fz (C++ function), 390, 394`
`amici::Model::get_dxdotdp (C++ function), 377`
`amici::Model::get_dxdotdp_full (C++ function), 377`
`amici::Model::getAddSigmaResiduals (C++ function), 368`
`amici::Model::getAdjointStateEventUpdate (C++ function), 374`
`amici::Model::getAdjointStateObservableUpdate (C++ function), 371`
`amici::Model::getAlwaysCheckFinite (C++ function), 376`
`amici::Model::getEvent (C++ function), 371`
`amici::Model::getEventRegularization (C++ function), 372`
`amici::Model::getEventRegularizationSensitivity (C++ function), 372`
`amici::Model::getEventSensitivity (C++ function), 371`
`amici::Model::getEventSigma (C++ function), 372`
`amici::Model::getEventSigmaSensitivity (C++ function), 372`
`amici::Model::getEventTimeSensitivity (C++ function), 374`
`amici::Model::getExpression (C++ function), 369`
`amici::Model::getExpressionIds (C++ function), 366`
`amici::Model::getExpressionNames (C++ function), 365`
`amici::Model::getFixedParameterById (C++ function), 364`
`amici::Model::getFixedParameterByName (C++ function), 364`
`amici::Model::getFixedParameterIds (C++ function), 366`
`amici::Model::getFixedParameterNames (C++ function), 365`
`amici::Model::getFixedParameters (C++ function), 364`
`amici::Model::getInitialStates (C++ function), 368`
`amici::Model::getInitialStateSensitivities (C++ function), 368`
`amici::Model::getMinimumSigmaResiduals (C++ function), 367`
`amici::Model::getModelState (C++ function), 367`
`amici::Model::getName (C++ function), 365`
`amici::Model::getObservable (C++ function), 369`
`amici::Model::getObservableIds (C++ function), 366`
`amici::Model::getObservableNames (C++ function), 365`
`amici::Model::getObservableScaling (C++ function), 369`
`amici::Model::getObservableSensitivity (C++ function), 369`
`amici::Model::getObservableSigma (C++ function), 370`
`amici::Model::getObservableSigmaSensitivity (C++ function), 370`
`amici::Model::getParameterById (C++ function), 362`
`amici::Model::getParameterByName (C++ function), 362`
`amici::Model::getParameterIds (C++ function), 366`

```

amici::Model::getParameterList (C++ function), 368
amici::Model::getParameterNames (C++ function), 365
amici::Model::getParameters (C++ function), 362
amici::Model::getParameterScale (C++ function), 362
amici::Model::getReinitializationStateIdxs (C++ function), 377
amici::Model::getReinitializeFixedParameterInitialStates (C++ function), 369
amici::Model::getStateIds (C++ function), 366
amici::Model::getStateIdsSolver (C++ function), 366
amici::Model::getStateIsNonNegative (C++ function), 367
amici::Model::getStateNames (C++ function), 365
amici::Model::getStateNamesSolver (C++ function), 365
amici::Model::getSteadyStateSensitivityMode (C++ function), 369
amici::Model::getTimepoint (C++ function), 367
amici::Model::getTimepoints (C++ function), 367
amici::Model::getUnobservedEventSensitivity (C++ function), 371
amici::Model::getUnscaledParameters (C++ function), 362
amici::Model::hasCustomInitialStates (C++ function), 368
amici::Model::hasCustomInitialStateSensitivities (C++ function), 368
amici::Model::hasExpressionIds (C++ function), 366
amici::Model::hasExpressionNames (C++ function), 365
amici::Model::hasFixedParameterIds (C++ function), 366
amici::Model::hasFixedParameterNames (C++ function), 365
amici::Model::hasObservableIds (C++ function), 366
amici::Model::hasObservableNames (C++ function), 365
amici::Model::hasParameterIds (C++ function), 366
amici::Model::hasParameterNames (C++ function), 365
amici::Model::hasQuadraticLLH (C++ function), 366
amici::Model::hasStateIds (C++ function), 366
amici::Model::hasStateNames (C++ function), 365
amici::Model::idlist (C++ member), 392
amici::Model::initHeaviside (C++ function), 361
amici::Model::initialize (C++ function), 360
amici::Model::initializeB (C++ function), 361
amici::Model::initializeStates (C++ function), 361
amici::Model::initializeStateSensitivities (C++ function), 361
amici::Model::initializeVectors (C++ function), 392
amici::Model::k (C++ function), 362
amici::Model::min_sigma_ (C++ member), 400
amici::Model::Model (C++ function), 360
amici::Model::ncl (C++ function), 362
amici::Model::nk (C++ function), 361
amici::Model::nMaxEvent (C++ function), 362
amici::Model::nmaxevent_ (C++ member), 400
amici::Model::np (C++ function), 361
amici::Model::nplist (C++ function), 361
amici::Model::nt (C++ function), 362
amici::Model::nx_reinit (C++ function), 362
amici::Model::o2mode (C++ member), 392
amici::Model::operator= (C++ function), 360
amici::Model::operator== (C++ function), 400
amici::Model::plist (C++ function), 368
amici::Model::pythonGenerated (C++ member), 392
amici::Model::requireSensitivitiesForAllParameters (C++ function), 369
amici::Model::setAddSigmaResiduals (C++ function), 367
amici::Model::setAllStatesNonNegative (C++ function), 367
amici::Model::setAlwaysCheckFinite (C++ function), 376
amici::Model::setFixedParameterById (C++ function), 364
amici::Model::setFixedParameterByName (C++ function), 364
amici::Model::setFixedParameters (C++ function), 364
amici::Model::setFixedParametersByIdRegex (C++ function), 364
amici::Model::setFixedParametersByNameRegex (C++ function), 364
amici::Model::setInitialStates (C++ function), 368
amici::Model::setInitialStateSensitivities (C++ function), 368
amici::Model::setMinimumSigmaResiduals (C++ function), 367
amici::Model::setModelState (C++ function), 367
amici::Model::setNMaxEvent (C++ function), 362
amici::Model::setParameterById (C++ function), 363
amici::Model::setParameterByName (C++ function), 363

```

`amici::Model::setParameterList (C++ function), 368`
`amici::Model::setParameters (C++ function), 363`
`amici::Model::setParametersByIdRegex (C++ function), 363`
`amici::Model::setParametersByNameRegex (C++ function), 363`
`amici::Model::setParameterScale (C++ function), 362`
`amici::Model::setReinitializationStateIdxs (C++ function), 377`
`amici::Model::setReinitializeFixedParameterInitialStates (C++ function), 369`
`amici::Model::setStateIsNonNegative (C++ function), 367`
`amici::Model::setSteadyStateSensitivityMode (C++ function), 368`
`amici::Model::setT0 (C++ function), 367`
`amici::Model::setTimepoints (C++ function), 367`
`amici::Model::setUnscaledInitialStateSensitivityIndices (C++ function), 368`
`amici::Model::sigma_res_ (C++ member), 400`
`amici::Model::state_ (C++ member), 400`
`amici::Model::state_is_non_negative_ (C++ member), 400`
`amici::Model::steadystate_sensitivity_mode_ (C++ member), 400`
`amici::Model::sx0data_ (C++ member), 400`
`amici::Model::t0 (C++ function), 367`
`amici::Model::updateHeaviside (C++ function), 375`
`amici::Model::updateHeavisideB (C++ function), 375`
`amici::Model::writeLLHSensitivitySlice (C++ function), 392`
`amici::Model::writeSensitivitySliceEvent (C++ function), 392`
`amici::Model::writeSliceEvent (C++ function), 392`
`amici::Model::x0data_ (C++ member), 400`
`amici::Model::z2event_ (C++ member), 400`
`amici::Model_DAE (C++ class), 401`
`amici::Model_DAE::fdxdotdp (C++ function), 407, 409`
`amici::Model_DAE::fJ (C++ function), 402`
`amici::Model_DAE::fJB (C++ function), 402`
`amici::Model_DAE::fJDiag (C++ function), 404`
`amici::Model_DAE::fJSparse (C++ function), 403, 408`
`amici::Model_DAE::fJSparseB (C++ function), 403`
`amici::Model_DAE::fJSparseB_ss (C++ function), 407`
`amici::Model_DAE::fJv (C++ function), 404`
`amici::Model_DAE::fJvB (C++ function), 405`
`amici::Model_DAE::fM (C++ function), 408, 410`
`amici::Model_DAE::fqBdot (C++ function), 406`
`amici::Model_DAE::fqBdot_ss (C++ function), 406`
`amici::Model_DAE::froot (C++ function), 405, 409`
`amici::Model_DAE::fsxdot (C++ function), 407, 408`
`amici::Model_DAE::fxBdot (C++ function), 406`
`amici::Model_DAE::fxBdot_ss (C++ function), 406`
`amici::Model_DAE::fxdot (C++ function), 405, 409`
`amici::Model_DAE::getSolver (C++ function), 408`
`amici::Model_DAE::Model_DAE (C++ function), 401`
`amici::Model_DAE::writeSteadystateJB (C++ function), 407`
`amici::Model_ODE (C++ class), 410`
`amici::Model_ODE::fdxdotdp (C++ function), 418, 420`
`amici::Model_ODE::fdxdotdp_explicit (C++ function), 418`
`amici::Model_ODE::fdxdotdp_explicit_colptrs (C++ function), 419`
`amici::Model_ODE::fdxdotdp_explicit_rowvals (C++ function), 419`
`amici::Model_ODE::fdxdotdw (C++ function), 419, 420`
`amici::Model_ODE::fdxdotdw_colptrs (C++ function), 419`
`amici::Model_ODE::fdxdotdw_rowvals (C++ function), 420`
`amici::Model_ODE::fdxdotdx_explicit (C++ function), 419`
`amici::Model_ODE::fdxdotdx_explicit_colptrs (C++ function), 419`
`amici::Model_ODE::fdxdotdx_explicit_rowvals (C++ function), 419`
`amici::Model_ODE::fJ (C++ function), 411`
`amici::Model_ODE::fJB (C++ function), 411`
`amici::Model_ODE::fJDiag (C++ function), 413`
`amici::Model_ODE::fJSparse (C++ function), 412, 417`
`amici::Model_ODE::fJSparse_colptrs (C++ function), 417`
`amici::Model_ODE::fJSparse_rowvals (C++ function), 417`
`amici::Model_ODE::fJSparseB (C++ function), 412`
`amici::Model_ODE::fJSparseB_ss (C++ function), 415`
`amici::Model_ODE::fJv (C++ function), 413`
`amici::Model_ODE::fJvB (C++ function), 414`
`amici::Model_ODE::fqBdot (C++ function), 415`
`amici::Model_ODE::fqBdot_ss (C++ function), 415`
`amici::Model_ODE::froot (C++ function), 414, 417`
`amici::Model_ODE::fsxdot (C++ function), 416`
`amici::Model_ODE::fxBdot (C++ function), 414`
`amici::Model_ODE::fxBdot_ss (C++ function), 415`
`amici::Model_ODE::fxdot (C++ function), 414, 418`

amici::Model_ODE::getSolver (C++ *function*), 416
 amici::Model_ODE::Model_ODE (C++ *function*), 410
 amici::Model_ODE::writeSteadystateJB (C++ *function*), 415
 amici::ModelContext (C++ *class*), 420
 amici::ModelContext::~~ModelContext (C++ *function*), 421
 amici::ModelContext::ModelContext (C++ *function*), 421
 amici::ModelContext::operator= (C++ *function*), 421
 amici::ModelContext::restore (C++ *function*), 421
 amici::ModelDimensions (C++ *struct*), 291
 amici::ModelDimensions::lbw (C++ *member*), 294
 amici::ModelDimensions::ModelDimensions (C++ *function*), 292
 amici::ModelDimensions::ndJydy (C++ *member*), 294
 amici::ModelDimensions::ndtotal_cldx_rdata (C++ *member*), 294
 amici::ModelDimensions::ndwdp (C++ *member*), 293
 amici::ModelDimensions::ndwdw (C++ *member*), 293
 amici::ModelDimensions::ndwdx (C++ *member*), 293
 amici::ModelDimensions::ndxdotdw (C++ *member*), 293
 amici::ModelDimensions::ndxrdadatdcl (C++ *member*), 294
 amici::ModelDimensions::ndxrdatadxsolver (C++ *member*), 294
 amici::ModelDimensions::ne (C++ *member*), 293
 amici::ModelDimensions::nJ (C++ *member*), 294
 amici::ModelDimensions::nk (C++ *member*), 293
 amici::ModelDimensions::nnz (C++ *member*), 294
 amici::ModelDimensions::np (C++ *member*), 293
 amici::ModelDimensions::nw (C++ *member*), 293
 amici::ModelDimensions::nx_rdata (C++ *member*), 293
 amici::ModelDimensions::nx_solver (C++ *member*), 293
 amici::ModelDimensions::nx_solver_reinit (C++ *member*), 293
 amici::ModelDimensions::nxtrue_rdata (C++ *member*), 293
 amici::ModelDimensions::nxtrue_solver (C++ *member*), 293
 amici::ModelDimensions::ny (C++ *member*), 293
 amici::ModelDimensions::nytrue (C++ *member*), 293
 amici::ModelDimensions::nz (C++ *member*), 293
 amici::ModelDimensions::nztrue (C++ *member*), 293
 amici::ModelDimensions::ubw (C++ *member*), 294
 amici::ModelState (C++ *struct*), 294
 amici::ModelState::fixedParameters (C++ *member*), 295
 amici::ModelState::h (C++ *member*), 294
 amici::ModelState::plist (C++ *member*), 295
 amici::ModelState::stotal_cl (C++ *member*), 294
 amici::ModelState::total_cl (C++ *member*), 294
 amici::ModelState::unscaledParameters (C++ *member*), 295
 amici::ModelStateDerived (C++ *struct*), 295
 amici::ModelStateDerived::deltaqB_ (C++ *member*), 298
 amici::ModelStateDerived::deltasx_ (C++ *member*), 298
 amici::ModelStateDerived::deltax_ (C++ *member*), 298
 amici::ModelStateDerived::deltaxB_ (C++ *member*), 298
 amici::ModelStateDerived::dJrzdsigma_ (C++ *member*), 297
 amici::ModelStateDerived::dJrzdz_ (C++ *member*), 297
 amici::ModelStateDerived::dJydp_ (C++ *member*), 297
 amici::ModelStateDerived::dJydsigma_ (C++ *member*), 296
 amici::ModelStateDerived::dJydx_ (C++ *member*), 297
 amici::ModelStateDerived::dJydy_ (C++ *member*), 296
 amici::ModelStateDerived::dJydy_matlab_ (C++ *member*), 296
 amici::ModelStateDerived::dJzdp_ (C++ *member*), 297
 amici::ModelStateDerived::dJzdsigma_ (C++ *member*), 297
 amici::ModelStateDerived::dJzdx_ (C++ *member*), 297
 amici::ModelStateDerived::dJzdz_ (C++ *member*), 297
 amici::ModelStateDerived::drzdp_ (C++ *member*), 297
 amici::ModelStateDerived::drzdx_ (C++ *member*), 297
 amici::ModelStateDerived::dsigmaydp_ (C++ *member*), 298
 amici::ModelStateDerived::dsigmaydy_ (C++ *member*), 298
 amici::ModelStateDerived::dsigmazdp_ (C++ *member*), 298
 amici::ModelStateDerived::dtotal_cldx_rdata (C++ *member*), 296
 amici::ModelStateDerived::dwdp_ (C++ *member*),

[295](#)
`amici::ModelStateDerived::dwdx_ (C++ member),`
[295](#)
`amici::ModelStateDerived::dx_rdata_tcl (C++`
`member),` [296](#)
`amici::ModelStateDerived::dx_rdata_dx_solver`
`(C++ member),` [296](#)
`amici::ModelStateDerived::dxdotdp (C++ mem-`
`ber),` [296](#)
`amici::ModelStateDerived::dxdotdp_explicit`
`(C++ member),` [296](#)
`amici::ModelStateDerived::dxdotdp_full (C++`
`member),` [296](#)
`amici::ModelStateDerived::dxdotdp_implicit`
`(C++ member),` [296](#)
`amici::ModelStateDerived::dxdotdw_ (C++ mem-`
`ber),` [295](#)
`amici::ModelStateDerived::dxdotdx_explicit`
`(C++ member),` [296](#)
`amici::ModelStateDerived::dxdotdx_implicit`
`(C++ member),` [296](#)
`amici::ModelStateDerived::dydp_ (C++ member),`
[297](#)
`amici::ModelStateDerived::dydx_ (C++ member),`
[297](#)
`amici::ModelStateDerived::dzdp_ (C++ member),`
[297](#)
`amici::ModelStateDerived::dzdx_ (C++ member),`
[297](#)
`amici::ModelStateDerived::J_ (C++ member),` [295](#)
`amici::ModelStateDerived::JB_ (C++ member),`
[295](#)
`amici::ModelStateDerived::M_ (C++ member),` [296](#)
`amici::ModelStateDerived::ModelStateDerived`
`(C++ function),` [295](#)
`amici::ModelStateDerived::rz_ (C++ member),`
[298](#)
`amici::ModelStateDerived::sigmay_ (C++ mem-`
`ber),` [298](#)
`amici::ModelStateDerived::sigmaz_ (C++ mem-`
`ber),` [298](#)
`amici::ModelStateDerived::sx_ (C++ member),`
[297](#)
`amici::ModelStateDerived::sx_rdata_ (C++`
`member),` [298](#)
`amici::ModelStateDerived::w_ (C++ member),` [297](#)
`amici::ModelStateDerived::x_pos_tmp_ (C++`
`member),` [298](#)
`amici::ModelStateDerived::x_rdata_ (C++ mem-`
`ber),` [297](#)
`amici::ModelStateDerived::y_ (C++ member),` [298](#)
`amici::ModelStateDerived::z_ (C++ member),` [298](#)
`amici::N_VGetArrayPointerConst (C++ function),`
[510](#)
`amici::NewtonDampingFactorMode (C++ enum),` [490](#)
`amici::NewtonDampingFactorMode::off (C++ enu-`
`merator),` [490](#)
`amici::NewtonDampingFactorMode::on (C++ enu-`
`merator),` [490](#)
`amici::NewtonFailure (C++ class),` [421](#)
`amici::NewtonFailure::error_code (C++ mem-`
`ber),` [422](#)
`amici::NewtonFailure::NewtonFailure (C++`
`function),` [421](#)
`amici::NewtonSolver (C++ class),` [422](#)
`amici::NewtonSolver::~~NewtonSolver (C++ func-`
`tion),` [423](#)
`amici::NewtonSolver::computeNewtonSensis`
`(C++ function),` [422](#)
`amici::NewtonSolver::dxB_ (C++ member),` [424](#)
`amici::NewtonSolver::getSolver (C++ function),`
[423](#)
`amici::NewtonSolver::getStep (C++ function),` [422](#)
`amici::NewtonSolver::is_singular (C++ func-`
`tion),` [423](#)
`amici::NewtonSolver::NewtonSolver (C++ func-`
`tion),` [422](#)
`amici::NewtonSolver::prepareLinearSystem`
`(C++ function),` [422](#)
`amici::NewtonSolver::prepareLinearSystemB`
`(C++ function),` [423](#)
`amici::NewtonSolver::reinitialize (C++ func-`
`tion),` [423](#)
`amici::NewtonSolver::solveLinearSystem (C++`
`function),` [423](#)
`amici::NewtonSolver::x_ (C++ member),` [423](#)
`amici::NewtonSolver::xB_ (C++ member),` [423](#)
`amici::NewtonSolver::xdot_ (C++ member),` [423](#)
`amici::NewtonSolverDense (C++ class),` [424](#)
`amici::NewtonSolverDense::~~NewtonSolverDense`
`(C++ function),` [424](#)
`amici::NewtonSolverDense::is_singular (C++`
`function),` [425](#)
`amici::NewtonSolverDense::NewtonSolverDense`
`(C++ function),` [424](#)
`amici::NewtonSolverDense::operator= (C++`
`function),` [424](#)
`amici::NewtonSolverDense::prepareLinearSystem`
`(C++ function),` [424](#)
`amici::NewtonSolverDense::prepareLinearSystemB`
`(C++ function),` [424](#)
`amici::NewtonSolverDense::reinitialize (C++`
`function),` [425](#)
`amici::NewtonSolverDense::solveLinearSystem`
`(C++ function),` [424](#)
`amici::NewtonSolverSparse (C++ class),` [425](#)
`amici::NewtonSolverSparse::~~NewtonSolverSparse`
`(C++ function),` [425](#)

`amici::NewtonSolverSparse::is_singular` (C++ function), 426
`amici::NewtonSolverSparse::NewtonSolverSparse` (C++ function), 425
`amici::NewtonSolverSparse::operator=` (C++ function), 425
`amici::NewtonSolverSparse::prepareLinearSystem` (C++ function), 426
`amici::NewtonSolverSparse::prepareLinearSystemB` (C++ function), 426
`amici::NewtonSolverSparse::reinitialize` (C++ function), 426
`amici::NewtonSolverSparse::solveLinearSystem` (C++ function), 425
`amici::NonlinearSolverIteration` (C++ enum), 490
`amici::NonlinearSolverIteration::fixedpoint` (C++ enumerator), 490
`amici::NonlinearSolverIteration::functional` (C++ enumerator), 490
`amici::NonlinearSolverIteration::newton` (C++ enumerator), 490
`amici::ObservableScaling` (C++ enum), 491
`amici::ObservableScaling::lin` (C++ enumerator), 491
`amici::ObservableScaling::log` (C++ enumerator), 491
`amici::ObservableScaling::log10` (C++ enumerator), 491
`amici::operator==` (C++ function), 510, 511
`amici::outputFunctionType` (C++ type), 529
`amici::ParameterScaling` (C++ enum), 491
`amici::ParameterScaling::ln` (C++ enumerator), 491
`amici::ParameterScaling::log10` (C++ enumerator), 491
`amici::ParameterScaling::none` (C++ enumerator), 491
`amici::pi` (C++ member), 525
`amici::printErrMsgIdAndTxt` (C++ function), 511
`amici::printfToString` (C++ function), 511
`amici::printWarnMsgIdAndTxt` (C++ function), 512
`amici::RDataReporting` (C++ enum), 491
`amici::RDataReporting::full` (C++ enumerator), 491
`amici::RDataReporting::likelihood` (C++ enumerator), 491
`amici::RDataReporting::residuals` (C++ enumerator), 491
`amici::realtype` (C++ type), 529
`amici::regexErrorToString` (C++ function), 512
`amici::ReturnData` (C++ class), 426
`amici::ReturnData::~ReturnData` (C++ function), 427
`amici::ReturnData::applyChainRuleFactorToSimulationResults` (C++ function), 434
`amici::ReturnData::boost::serialization::serialize` (C++ function), 436
`amici::ReturnData::chi2` (C++ member), 431
`amici::ReturnData::computingFSA` (C++ function), 434
`amici::ReturnData::cpu_time` (C++ member), 429
`amici::ReturnData::cpu_time_total` (C++ member), 430
`amici::ReturnData::cpu_timeB` (C++ member), 430
`amici::ReturnData::dx_solver_` (C++ member), 435
`amici::ReturnData::fchi2` (C++ function), 433
`amici::ReturnData::fFIM` (C++ function), 434
`amici::ReturnData::FIM` (C++ member), 429
`amici::ReturnData::fres` (C++ function), 433
`amici::ReturnData::fsres` (C++ function), 434
`amici::ReturnData::getDataOutput` (C++ function), 434
`amici::ReturnData::getDataSensisFSA` (C++ function), 434
`amici::ReturnData::getEventOutput` (C++ function), 434
`amici::ReturnData::getEventSensisFSA` (C++ function), 435
`amici::ReturnData::handleSx0Backward` (C++ function), 435
`amici::ReturnData::handleSx0Forward` (C++ function), 435
`amici::ReturnData::id` (C++ member), 428
`amici::ReturnData::initializeFullReporting` (C++ function), 432
`amici::ReturnData::initializeLikelihoodReporting` (C++ function), 432
`amici::ReturnData::initializeObjectiveFunction` (C++ function), 432
`amici::ReturnData::initializeResidualReporting` (C++ function), 432
`amici::ReturnData::invalidate` (C++ function), 434
`amici::ReturnData::invalidateLLH` (C++ function), 434
`amici::ReturnData::invalidateSLLH` (C++ function), 434
`amici::ReturnData::J` (C++ member), 428
`amici::ReturnData::llh` (C++ member), 431
`amici::ReturnData::newton_maxsteps` (C++ member), 431
`amici::ReturnData::nmaxevent` (C++ member), 431
`amici::ReturnData::nplist` (C++ member), 431
`amici::ReturnData::nroots_` (C++ member), 436
`amici::ReturnData::nt` (C++ member), 431
`amici::ReturnData::numerrtestfails` (C++ mem-

ber), 429
 amici::ReturnData::numerrtestfailsB (C++ *member*), 429
 amici::ReturnData::numnonlinsolvconvfails (C++ *member*), 429
 amici::ReturnData::numnonlinsolvconvfailsB (C++ *member*), 429
 amici::ReturnData::numrhsevals (C++ *member*), 429
 amici::ReturnData::numrhsevalsB (C++ *member*), 429
 amici::ReturnData::numsteps (C++ *member*), 429
 amici::ReturnData::numstepsB (C++ *member*), 429
 amici::ReturnData::nx (C++ *member*), 431
 amici::ReturnData::nxtrue (C++ *member*), 431
 amici::ReturnData::o2mode (C++ *member*), 431
 amici::ReturnData::order (C++ *member*), 429
 amici::ReturnData::posteq_cpu_time (C++ *member*), 430
 amici::ReturnData::posteq_cpu_timeB (C++ *member*), 430
 amici::ReturnData::posteq_numsteps (C++ *member*), 430
 amici::ReturnData::posteq_numstepsB (C++ *member*), 430
 amici::ReturnData::posteq_status (C++ *member*), 430
 amici::ReturnData::posteq_t (C++ *member*), 430
 amici::ReturnData::posteq_wrms (C++ *member*), 430
 amici::ReturnData::preeq_cpu_time (C++ *member*), 430
 amici::ReturnData::preeq_cpu_timeB (C++ *member*), 430
 amici::ReturnData::preeq_numsteps (C++ *member*), 430
 amici::ReturnData::preeq_numstepsB (C++ *member*), 430
 amici::ReturnData::preeq_status (C++ *member*), 430
 amici::ReturnData::preeq_t (C++ *member*), 430
 amici::ReturnData::preeq_wrms (C++ *member*), 430
 amici::ReturnData::processBackwardProblem (C++ *function*), 433
 amici::ReturnData::processForwardProblem (C++ *function*), 433
 amici::ReturnData::processPostEquilibration (C++ *function*), 432
 amici::ReturnData::processPreEquilibration (C++ *function*), 432
 amici::ReturnData::processSimulationObjects (C++ *function*), 427
 amici::ReturnData::processSolver (C++ *function*), 433
 amici::ReturnData::pscale (C++ *member*), 431
 amici::ReturnData::rdata_reporting (C++ *member*), 432
 amici::ReturnData::readSimulationState (C++ *function*), 433
 amici::ReturnData::res (C++ *member*), 429
 amici::ReturnData::ReturnData (C++ *function*), 427
 amici::ReturnData::rz (C++ *member*), 428
 amici::ReturnData::s2llh (C++ *member*), 431
 amici::ReturnData::s2rz (C++ *member*), 428
 amici::ReturnData::sensi (C++ *member*), 432
 amici::ReturnData::sensi_meth (C++ *member*), 432
 amici::ReturnData::sigma_offset (C++ *member*), 435
 amici::ReturnData::sigma_res (C++ *member*), 432
 amici::ReturnData::sigmay (C++ *member*), 429
 amici::ReturnData::sigmaz (C++ *member*), 428
 amici::ReturnData::sllh (C++ *member*), 431
 amici::ReturnData::sres (C++ *member*), 429
 amici::ReturnData::srz (C++ *member*), 428
 amici::ReturnData::ssigmay (C++ *member*), 429
 amici::ReturnData::ssigmaz (C++ *member*), 428
 amici::ReturnData::status (C++ *member*), 431
 amici::ReturnData::storeJacobianAndDerivativeInReturnData (C++ *function*), 433
 amici::ReturnData::sx (C++ *member*), 428
 amici::ReturnData::sx0 (C++ *member*), 431
 amici::ReturnData::sx_rdata_ (C++ *member*), 436
 amici::ReturnData::sx_solver_ (C++ *member*), 436
 amici::ReturnData::sx_ss (C++ *member*), 431
 amici::ReturnData::sy (C++ *member*), 429
 amici::ReturnData::sz (C++ *member*), 428
 amici::ReturnData::t_ (C++ *member*), 435
 amici::ReturnData::ts (C++ *member*), 428
 amici::ReturnData::w (C++ *member*), 428
 amici::ReturnData::x (C++ *member*), 428
 amici::ReturnData::x0 (C++ *member*), 431
 amici::ReturnData::x_rdata_ (C++ *member*), 436
 amici::ReturnData::x_solver_ (C++ *member*), 435
 amici::ReturnData::x_ss (C++ *member*), 431
 amici::ReturnData::xdot (C++ *member*), 428
 amici::ReturnData::y (C++ *member*), 429
 amici::ReturnData::z (C++ *member*), 428
 amici::runAmiciSimulation (C++ *function*), 512
 amici::runAmiciSimulations (C++ *function*), 513
 amici::scaleParameters (C++ *function*), 513
 amici::SecondOrderMode (C++ *enum*), 492
 amici::SecondOrderMode::directional (C++ *enumerator*), 492

amici::SecondOrderMode::full (C++ *enumerator*),
 492
 amici::SecondOrderMode::none (C++ *enumerator*),
 492
 amici::SensitivityMethod (C++ *enum*), 492
 amici::SensitivityMethod::adjoint (C++ *enum*), 492
 amici::SensitivityMethod::forward (C++ *enum*), 492
 amici::SensitivityMethod::none (C++ *enumerator*), 492
 amici::SensitivityOrder (C++ *enum*), 492
 amici::SensitivityOrder::first (C++ *enumerator*), 492
 amici::SensitivityOrder::none (C++ *enumerator*), 492
 amici::SensitivityOrder::second (C++ *enumerator*), 492
 amici::serializeToChar (C++ *function*), 514
 amici::serializeToStdVec (C++ *function*), 514
 amici::serializeToString (C++ *function*), 514
 amici::SetupFailure (C++ *class*), 436
 amici::SetupFailure::SetupFailure (C++ *function*), 437
 amici::SimulationParameters (C++ *class*), 437
 amici::SimulationParameters::fixedParameters (C++ *member*), 438
 amici::SimulationParameters::fixedParametersPresim (C++ *member*), 438
 amici::SimulationParameters::fixedParametersPresimASA (C++ *member*), 438
 amici::SimulationParameters::parameters (C++ *member*), 438
 amici::SimulationParameters::plist (C++ *member*), 439
 amici::SimulationParameters::pscale (C++ *member*), 439
 amici::SimulationParameters::reinitialization_state_ids_presim (C++ *member*), 439
 amici::SimulationParameters::reinitialization_state_ids_presimASA (C++ *member*), 439
 amici::SimulationParameters::reinitializeAllFixedParametersDependentInitialStates (C++ *function*), 438
 amici::SimulationParameters::reinitializeAllFixedParametersDependentInitialStatesASA (C++ *function*), 438
 amici::SimulationParameters::reinitializeAllFixedParametersDependentInitialStatesPresim (C++ *function*), 438
 amici::SimulationParameters::reinitializeFixedParametersInitialStates (C++ *member*), 439
 amici::SimulationParameters::SimulationParameters (C++ *function*), 437, 438
 amici::SimulationParameters::sx0 (C++ *member*), 439
 amici::SimulationParameters::t_presim (C++ *member*), 439
 amici::SimulationParameters::ts_ (C++ *member*), 439
 amici::SimulationParameters::tstart_ (C++ *member*), 439
 amici::SimulationParameters::x0 (C++ *member*), 438
 amici::SimulationState (C++ *struct*), 299
 amici::SimulationState::dx (C++ *member*), 299
 amici::SimulationState::state (C++ *member*), 299
 amici::SimulationState::sx (C++ *member*), 299
 amici::SimulationState::t (C++ *member*), 299
 amici::SimulationState::x (C++ *member*), 299
 amici::slice (C++ *function*), 515
 amici::Solver (C++ *class*), 440
 amici::Solver::~Solver (C++ *function*), 440
 amici::Solver::adjInit (C++ *function*), 455
 amici::Solver::allocateSolver (C++ *function*), 453
 amici::Solver::allocateSolverB (C++ *function*), 455
 amici::Solver::app (C++ *member*), 451
 amici::Solver::applyQuadTolerances (C++ *function*), 459
 amici::Solver::applyQuadTolerancesASA (C++ *function*), 459
 amici::Solver::applySensitivityTolerances (C++ *function*), 459
 amici::Solver::applyTolerances (C++ *function*), 458
 amici::Solver::applyTolerancesASA (C++ *function*), 459
 amici::Solver::applyTolerancesFSA (C++ *function*), 458
 amici::Solver::binit (C++ *function*), 452
 amici::Solver::boost::serialization::serialize (C++ *function*), 462
 amici::Solver::calcIC (C++ *function*), 442
 amici::Solver::calcICB (C++ *function*), 442
 amici::Solver::checkSensitivityMethod (C++ *function*), 455
 amici::Solver::clone (C++ *function*), 440
 amici::Solver::computingFSA (C++ *function*), 449
 amici::Solver::diagB (C++ *function*), 458
 amici::Solver::diagB (C++ *member*), 461
 amici::Solver::dx_ (C++ *member*), 461
 amici::Solver::dxB_ (C++ *member*), 461
 amici::Solver::force_reinit_postprocess_B_ (C++ *member*), 461
 amici::Solver::force_reinit_postprocess_F_ (C++ *member*), 461

`amici::Solver::getAbsoluteTolerance` (C++ function), 443
`amici::Solver::getAbsoluteToleranceB` (C++ function), 444
`amici::Solver::getAbsoluteToleranceFSA` (C++ function), 444
`amici::Solver::getAbsoluteToleranceQuadratures` (C++ function), 444
`amici::Solver::getAbsoluteToleranceSteadyState` (C++ function), 444
`amici::Solver::getAbsoluteToleranceSteadyStateSensi` (C++ function), 445
`amici::Solver::getAdjBmem` (C++ function), 458
`amici::Solver::getAdjInitDone` (C++ function), 458
`amici::Solver::getAdjointDerivativeState` (C++ function), 448
`amici::Solver::getAdjointQuadrature` (C++ function), 448
`amici::Solver::getAdjointState` (C++ function), 448
`amici::Solver::getB` (C++ function), 451
`amici::Solver::getCpuTime` (C++ function), 449
`amici::Solver::getCpuTimeB` (C++ function), 449
`amici::Solver::getDerivativeState` (C++ function), 447
`amici::Solver::getDky` (C++ function), 455
`amici::Solver::getDkyB` (C++ function), 455
`amici::Solver::getInitDone` (C++ function), 457
`amici::Solver::getInitDoneB` (C++ function), 458
`amici::Solver::getInternalSensitivityMethod` (C++ function), 446
`amici::Solver::getInterpolationType` (C++ function), 446
`amici::Solver::getLastOrder` (C++ function), 450, 457
`amici::Solver::getLinearMultistepMethod` (C++ function), 446
`amici::Solver::getLinearSolver` (C++ function), 446
`amici::Solver::getMaxSteps` (C++ function), 445
`amici::Solver::getMaxStepsBackwardProblem` (C++ function), 445
`amici::Solver::getMaxTime` (C++ function), 445
`amici::Solver::getModel` (C++ function), 457
`amici::Solver::getNewtonDampingFactorLowerBound` (C++ function), 443
`amici::Solver::getNewtonDampingFactorMode` (C++ function), 443
`amici::Solver::getNewtonMaxSteps` (C++ function), 442
`amici::Solver::getNewtonStepSteadyStateCheck` (C++ function), 450
`amici::Solver::getNonlinearSolverIteration` (C++ function), 446
`amici::Solver::getNumErrTestFails` (C++ function), 450, 456
`amici::Solver::getNumErrTestFailsB` (C++ function), 450
`amici::Solver::getNumNonlinSolvConvFails` (C++ function), 450, 457
`amici::Solver::getNumNonlinSolvConvFailsB` (C++ function), 450
`amici::Solver::getNumRhsEvals` (C++ function), 450, 456
`amici::Solver::getNumRhsEvalsB` (C++ function), 450
`amici::Solver::getNumSteps` (C++ function), 450, 456
`amici::Solver::getNumStepsB` (C++ function), 450
`amici::Solver::getQuad` (C++ function), 452
`amici::Solver::getQuadB` (C++ function), 451
`amici::Solver::getQuadDky` (C++ function), 455
`amici::Solver::getQuadDkyB` (C++ function), 455
`amici::Solver::getQuadInitDone` (C++ function), 458
`amici::Solver::getQuadInitDoneB` (C++ function), 458
`amici::Solver::getQuadrature` (C++ function), 448
`amici::Solver::getRelativeTolerance` (C++ function), 443
`amici::Solver::getRelativeToleranceB` (C++ function), 444
`amici::Solver::getRelativeToleranceFSA` (C++ function), 443
`amici::Solver::getRelativeToleranceQuadratures` (C++ function), 444
`amici::Solver::getRelativeToleranceSteadyState` (C++ function), 444
`amici::Solver::getRelativeToleranceSteadyStateSensi` (C++ function), 445
`amici::Solver::getReturnDataReportingMode` (C++ function), 447
`amici::Solver::getRootInfo` (C++ function), 442
`amici::Solver::getSens` (C++ function), 451
`amici::Solver::getSensDky` (C++ function), 455
`amici::Solver::getSensInitDone` (C++ function), 458
`amici::Solver::getSensiSteadyStateCheck` (C++ function), 450
`amici::Solver::getSensitivityMethod` (C++ function), 442
`amici::Solver::getSensitivityMethodPreequilibration` (C++ function), 442
`amici::Solver::getSensitivityOrder` (C++ function), 443
`amici::Solver::getStabilityLimitFlag` (C++ function), 446

amici::Solver::getState (C++ function), 447
 amici::Solver::getStateOrdering (C++ function), 446
 amici::Solver::getStateSensitivity (C++ function), 447
 amici::Solver::gett (C++ function), 449
 amici::Solver::init (C++ function), 452
 amici::Solver::initializeLinearSolver (C++ function), 457
 amici::Solver::initializeLinearSolverB (C++ function), 457
 amici::Solver::initializeNonLinearSolver (C++ function), 457
 amici::Solver::initializeNonLinearSolverB (C++ function), 457
 amici::Solver::initializeNonLinearSolverSens (C++ function), 452
 amici::Solver::initSteadystate (C++ function), 452
 amici::Solver::interp_type_ (C++ member), 460
 amici::Solver::ism_ (C++ member), 460
 amici::Solver::iter_ (C++ member), 460
 amici::Solver::linear_solver_ (C++ member), 460
 amici::Solver::linear_solver_B_ (C++ member), 460
 amici::Solver::lmm_ (C++ member), 460
 amici::Solver::maxsteps_ (C++ member), 460
 amici::Solver::maxtime_ (C++ member), 460
 amici::Solver::non_linear_solver_ (C++ member), 460
 amici::Solver::non_linear_solver_B_ (C++ member), 460
 amici::Solver::non_linear_solver_sens_ (C++ member), 460
 amici::Solver::nplist (C++ function), 449
 amici::Solver::nquad (C++ function), 449
 amici::Solver::nx (C++ function), 449
 amici::Solver::operator== (C++ function), 462
 amici::Solver::qbinit (C++ function), 452
 amici::Solver::quadInit (C++ function), 455
 amici::Solver::quadReInitB (C++ function), 449
 amici::Solver::quadStolerances (C++ function), 456
 amici::Solver::quadStolerancesB (C++ function), 456
 amici::Solver::reInit (C++ function), 448
 amici::Solver::reInitB (C++ function), 448
 amici::Solver::reInitPostProcessB (C++ function), 451
 amici::Solver::reInitPostProcessF (C++ function), 451
 amici::Solver::resetDiagnosis (C++ function), 449
 amici::Solver::resetMutableMemory (C++ function), 458
 amici::Solver::rootInit (C++ function), 452
 amici::Solver::run (C++ function), 440
 amici::Solver::runB (C++ function), 441
 amici::Solver::sdx_ (C++ member), 461
 amici::Solver::sens_initialized_ (C++ member), 461
 amici::Solver::sensInit1 (C++ function), 452
 amici::Solver::sensReInit (C++ function), 448
 amici::Solver::sensToggleOff (C++ function), 448
 amici::Solver::setAbsoluteTolerance (C++ function), 443
 amici::Solver::setAbsoluteToleranceB (C++ function), 444
 amici::Solver::setAbsoluteToleranceFSA (C++ function), 444
 amici::Solver::setAbsoluteToleranceQuadratures (C++ function), 444
 amici::Solver::setAbsoluteToleranceSteadyState (C++ function), 444
 amici::Solver::setAbsoluteToleranceSteadyStateSensi (C++ function), 445
 amici::Solver::setAdjInitDone (C++ function), 459
 amici::Solver::setBandJacFn (C++ function), 453
 amici::Solver::setBandJacFnB (C++ function), 453
 amici::Solver::setDenseJacFn (C++ function), 452
 amici::Solver::setDenseJacFnB (C++ function), 453
 amici::Solver::setErrHandlerFn (C++ function), 454
 amici::Solver::setId (C++ function), 454
 amici::Solver::setInitDone (C++ function), 459
 amici::Solver::setInitDoneB (C++ function), 459
 amici::Solver::setInternalSensitivityMethod (C++ function), 447
 amici::Solver::setInterpolationType (C++ function), 446
 amici::Solver::setJacTimesVecFn (C++ function), 453
 amici::Solver::setJacTimesVecFnB (C++ function), 453
 amici::Solver::setLinearMultistepMethod (C++ function), 446
 amici::Solver::setLinearSolver (C++ function), 446, 457
 amici::Solver::setLinearSolverB (C++ function), 457
 amici::Solver::setMaxNumSteps (C++ function), 454
 amici::Solver::setMaxNumStepsB (C++ function), 454
 amici::Solver::setMaxSteps (C++ function), 445

`amici::Solver::setMaxStepsBackwardProblem` (C++ function), 445

`amici::Solver::setMaxTime` (C++ function), 445

`amici::Solver::setNewtonDampingFactorLowerBound` (C++ function), 443

`amici::Solver::setNewtonDampingFactorMode` (C++ function), 443

`amici::Solver::setNewtonMaxSteps` (C++ function), 442

`amici::Solver::setNewtonStepSteadyStateCheck` (C++ function), 450

`amici::Solver::setNonLinearSolver` (C++ function), 457

`amici::Solver::setNonLinearSolverB` (C++ function), 457

`amici::Solver::setNonlinearSolverIteration` (C++ function), 446

`amici::Solver::setNonLinearSolverSens` (C++ function), 457

`amici::Solver::setQuadErrCon` (C++ function), 454

`amici::Solver::setQuadErrConB` (C++ function), 453

`amici::Solver::setQuadInitDone` (C++ function), 459

`amici::Solver::setQuadInitDoneB` (C++ function), 459

`amici::Solver::setRelativeTolerance` (C++ function), 443

`amici::Solver::setRelativeToleranceB` (C++ function), 444

`amici::Solver::setRelativeToleranceFSA` (C++ function), 443

`amici::Solver::setRelativeToleranceQuadratures` (C++ function), 444

`amici::Solver::setRelativeToleranceSteadyState` (C++ function), 444

`amici::Solver::setRelativeToleranceSteadyStateSensi` (C++ function), 445

`amici::Solver::setReturnDataReportingMode` (C++ function), 447

`amici::Solver::setSensErrCon` (C++ function), 453

`amici::Solver::setSensInitDone` (C++ function), 459

`amici::Solver::setSensInitOff` (C++ function), 459

`amici::Solver::setSensiSteadyStateCheck` (C++ function), 450

`amici::Solver::setSensitivityMethod` (C++ function), 442

`amici::Solver::setSensitivityMethodPreequilibrium` (C++ function), 442

`amici::Solver::setSensitivityOrder` (C++ function), 443

`amici::Solver::setSensParams` (C++ function), 455

`amici::Solver::setSensSStolerances` (C++ function), 453

`amici::Solver::setSparseJacFn` (C++ function), 453

`amici::Solver::setSparseJacFn_ss` (C++ function), 453

`amici::Solver::setSparseJacFnB` (C++ function), 453

`amici::Solver::setSStolerances` (C++ function), 453

`amici::Solver::setSStolerancesB` (C++ function), 456

`amici::Solver::setStabilityLimitFlag` (C++ function), 446

`amici::Solver::setStabLimDet` (C++ function), 454

`amici::Solver::setStabLimDetB` (C++ function), 454

`amici::Solver::setStateOrdering` (C++ function), 446

`amici::Solver::setStopTime` (C++ function), 451

`amici::Solver::setSuppressAlg` (C++ function), 454

`amici::Solver::setup` (C++ function), 441

`amici::Solver::setupB` (C++ function), 441

`amici::Solver::setupSteadystate` (C++ function), 441

`amici::Solver::setUserData` (C++ function), 454

`amici::Solver::setUserDataB` (C++ function), 454

`amici::Solver::solve` (C++ function), 451

`amici::Solver::solveB` (C++ function), 442

`amici::Solver::solveF` (C++ function), 451

`amici::Solver::Solver` (C++ function), 440

`amici::Solver::solver_memory_` (C++ member), 460

`amici::Solver::solver_memory_B_` (C++ member), 460

`amici::Solver::solver_was_called_B_` (C++ member), 460

`amici::Solver::solver_was_called_F_` (C++ member), 460

`amici::Solver::starttime_` (C++ member), 460

`amici::Solver::startTimer` (C++ function), 445

`amici::Solver::step` (C++ function), 441

`amici::Solver::storeDiagnosis` (C++ function), 449

`amici::Solver::storeDiagnosisB` (C++ function), 449

`amici::Solver::switchForwardSensisOff` (C++ function), 442

`amici::Solver::sx_` (C++ member), 461

`amici::Solver::t_` (C++ member), 461

`amici::Solver::timeExceeded` (C++ function), 445

`amici::Solver::turnOffRootFinding` (C++ function), 442

amici::Solver::updateAndReinitStatesAndSensitivities (C++ function), 462
 (C++ function), 442
 amici::Solver::user_data (C++ member), 460
 amici::Solver::user_data_type (C++ type), 440
 amici::Solver::writeSolution (C++ function), 447
 amici::Solver::writeSolutionB (C++ function), 447
 amici::Solver::x_ (C++ member), 461
 amici::Solver::xB_ (C++ member), 461
 amici::Solver::xQ_ (C++ member), 461
 amici::Solver::xQB_ (C++ member), 461
 amici::SteadyStateContext (C++ enum), 493
 amici::SteadyStateContext::newtonSensi (C++ enumerator), 493
 amici::SteadyStateContext::sensiStorage (C++ enumerator), 493
 amici::SteadyStateContext::solverCreation (C++ enumerator), 493
 amici::SteadystateProblem (C++ class), 462
 amici::SteadystateProblem::checkSteadyStateSuccess (C++ function), 464
 amici::SteadystateProblem::getAdjointQuadrature (C++ function), 464
 amici::SteadystateProblem::getAdjointState (C++ function), 464
 amici::SteadystateProblem::getAdjointUpdates (C++ function), 464
 amici::SteadystateProblem::getCPUTime (C++ function), 463
 amici::SteadystateProblem::getCPUTimeB (C++ function), 463
 amici::SteadystateProblem::getDJydx (C++ function), 463
 amici::SteadystateProblem::getEquilibrationQuadratures (C++ function), 463
 amici::SteadystateProblem::getFinalSimulationState (C++ function), 463
 amici::SteadystateProblem::getNumSteps (C++ function), 463
 amici::SteadystateProblem::getNumStepsB (C++ function), 463
 amici::SteadystateProblem::getResidualNorm (C++ function), 463
 amici::SteadystateProblem::getState (C++ function), 463
 amici::SteadystateProblem::getStateSensitivity (C++ function), 463
 amici::SteadystateProblem::getSteadyStateStatus (C++ function), 463
 amici::SteadystateProblem::getSteadyStateTime (C++ function), 463
 amici::SteadystateProblem::hasQuadrature (C++ function), 464
 amici::SteadystateProblem::SteadystateProblem (C++ function), 463
 amici::SteadystateProblem::workSteadyStateBackwardProblem (C++ function), 463
 amici::SteadystateProblem::workSteadyStateProblem (C++ function), 462
 amici::SteadyStateSensitivityMode (C++ enum), 493
 amici::SteadyStateSensitivityMode::integrateIfNewtonFails (C++ enumerator), 493
 amici::SteadyStateSensitivityMode::integrationOnly (C++ enumerator), 493
 amici::SteadyStateSensitivityMode::newtonOnly (C++ enumerator), 493
 amici::SteadyStateStatus (C++ enum), 493
 amici::SteadyStateStatus::failed (C++ enumerator), 494
 amici::SteadyStateStatus::failed_convergence (C++ enumerator), 493
 amici::SteadyStateStatus::failed_damping (C++ enumerator), 493
 amici::SteadyStateStatus::failed_factorization (C++ enumerator), 493
 amici::SteadyStateStatus::failed_too_long_simulation (C++ enumerator), 493
 amici::SteadyStateStatus::not_run (C++ enumerator), 494
 amici::SteadyStateStatus::success (C++ enumerator), 494
 amici::SUNLinSolBand (C++ class), 464
 amici::SUNLinSolBand::getMatrix (C++ function), 465
 amici::SUNLinSolBand::SUNLinSolBand (C++ function), 465
 amici::SUNLinSolDense (C++ class), 465
 amici::SUNLinSolDense::getMatrix (C++ function), 465
 amici::SUNLinSolDense::SUNLinSolDense (C++ function), 465
 amici::SUNLinSolKLU (C++ class), 466
 amici::SUNLinSolKLU::getMatrix (C++ function), 466
 amici::SUNLinSolKLU::reInit (C++ function), 467
 amici::SUNLinSolKLU::setOrdering (C++ function), 467
 amici::SUNLinSolKLU::StateOrdering (C++ enum), 466
 amici::SUNLinSolKLU::StateOrdering::AMD (C++ enumerator), 466
 amici::SUNLinSolKLU::StateOrdering::COLAMD (C++ enumerator), 466
 amici::SUNLinSolKLU::StateOrdering::natural (C++ enumerator), 466
 amici::SUNLinSolKLU::SUNLinSolKLU (C++ function), 466

`amici::SUNLinSolPCG` (C++ class), 467
`amici::SUNLinSolPCG::getNumIters` (C++ function), 468
`amici::SUNLinSolPCG::getResid` (C++ function), 468
`amici::SUNLinSolPCG::getResNorm` (C++ function), 468
`amici::SUNLinSolPCG::setATimes` (C++ function), 467
`amici::SUNLinSolPCG::setPreconditioner` (C++ function), 468
`amici::SUNLinSolPCG::setScalingVectors` (C++ function), 468
`amici::SUNLinSolPCG::SUNLinSolPCG` (C++ function), 467
`amici::SUNLinSolPBCGS` (C++ class), 469
`amici::SUNLinSolPBCGS::getNumIters` (C++ function), 470
`amici::SUNLinSolPBCGS::getResid` (C++ function), 470
`amici::SUNLinSolPBCGS::getResNorm` (C++ function), 470
`amici::SUNLinSolPBCGS::setATimes` (C++ function), 469
`amici::SUNLinSolPBCGS::setPreconditioner` (C++ function), 469
`amici::SUNLinSolPBCGS::setScalingVectors` (C++ function), 469
`amici::SUNLinSolPBCGS::SUNLinSolPBCGS` (C++ function), 469
`amici::SUNLinSolSPFGMR` (C++ class), 470
`amici::SUNLinSolSPFGMR::getNumIters` (C++ function), 471
`amici::SUNLinSolSPFGMR::getResid` (C++ function), 471
`amici::SUNLinSolSPFGMR::getResNorm` (C++ function), 471
`amici::SUNLinSolSPFGMR::setATimes` (C++ function), 470
`amici::SUNLinSolSPFGMR::setPreconditioner` (C++ function), 471
`amici::SUNLinSolSPFGMR::setScalingVectors` (C++ function), 471
`amici::SUNLinSolSPFGMR::SUNLinSolSPFGMR` (C++ function), 470
`amici::SUNLinSolSPGMR` (C++ class), 472
`amici::SUNLinSolSPGMR::getNumIters` (C++ function), 472
`amici::SUNLinSolSPGMR::getResid` (C++ function), 473
`amici::SUNLinSolSPGMR::getResNorm` (C++ function), 472
`amici::SUNLinSolSPGMR::setATimes` (C++ function), 472
`amici::SUNLinSolSPGMR::setPreconditioner` (C++ function), 472
`amici::SUNLinSolSPGMR::setScalingVectors` (C++ function), 472
`amici::SUNLinSolSPGMR::SUNLinSolSPGMR` (C++ function), 472
`amici::SUNLinSolSPTFQMR` (C++ class), 473
`amici::SUNLinSolSPTFQMR::getNumIters` (C++ function), 474
`amici::SUNLinSolSPTFQMR::getResid` (C++ function), 474
`amici::SUNLinSolSPTFQMR::getResNorm` (C++ function), 474
`amici::SUNLinSolSPTFQMR::setATimes` (C++ function), 473
`amici::SUNLinSolSPTFQMR::setPreconditioner` (C++ function), 474
`amici::SUNLinSolSPTFQMR::setScalingVectors` (C++ function), 474
`amici::SUNLinSolSPTFQMR::SUNLinSolSPTFQMR` (C++ function), 473
`amici::SUNLinSolWrapper` (C++ class), 475
`amici::SUNLinSolWrapper::~SUNLinSolWrapper` (C++ function), 475
`amici::SUNLinSolWrapper::get` (C++ function), 475
`amici::SUNLinSolWrapper::getLastFlag` (C++ function), 476
`amici::SUNLinSolWrapper::getMatrix` (C++ function), 476
`amici::SUNLinSolWrapper::getType` (C++ function), 475
`amici::SUNLinSolWrapper::initialize` (C++ function), 476
`amici::SUNLinSolWrapper::operator=` (C++ function), 475
`amici::SUNLinSolWrapper::setup` (C++ function), 476
`amici::SUNLinSolWrapper::Solve` (C++ function), 476
`amici::SUNLinSolWrapper::solver_` (C++ member), 477
`amici::SUNLinSolWrapper::space` (C++ function), 476
`amici::SUNLinSolWrapper::SUNLinSolWrapper` (C++ function), 475
`amici::SUNMatrixWrapper` (C++ class), 477
`amici::SUNMatrixWrapper::~SUNMatrixWrapper` (C++ function), 478
`amici::SUNMatrixWrapper::capacity` (C++ function), 479
`amici::SUNMatrixWrapper::columns` (C++ function), 478
`amici::SUNMatrixWrapper::data` (C++ function), 479

```

amici::SUNMatrixWrapper::get (C++ function), 478
amici::SUNMatrixWrapper::get_data (C++ function), 479
amici::SUNMatrixWrapper::get_indexptr (C++ function), 480
amici::SUNMatrixWrapper::get_indexval (C++ function), 480
amici::SUNMatrixWrapper::matrix_id (C++ function), 483
amici::SUNMatrixWrapper::multiply (C++ function), 480, 481
amici::SUNMatrixWrapper::num_indexptrs (C++ function), 479
amici::SUNMatrixWrapper::num_nonzeros (C++ function), 479
amici::SUNMatrixWrapper::operator= (C++ function), 478
amici::SUNMatrixWrapper::realloc (C++ function), 478
amici::SUNMatrixWrapper::reallocate (C++ function), 478
amici::SUNMatrixWrapper::refresh (C++ function), 483
amici::SUNMatrixWrapper::rows (C++ function), 478
amici::SUNMatrixWrapper::scale (C++ function), 480
amici::SUNMatrixWrapper::scatter (C++ function), 482
amici::SUNMatrixWrapper::set_data (C++ function), 479
amici::SUNMatrixWrapper::set_indexptr (C++ function), 480
amici::SUNMatrixWrapper::set_indexptrs (C++ function), 480
amici::SUNMatrixWrapper::set_indexval (C++ function), 480
amici::SUNMatrixWrapper::set_indexvals (C++ function), 480
amici::SUNMatrixWrapper::sparse_add (C++ function), 481
amici::SUNMatrixWrapper::sparse_multiply (C++ function), 481
amici::SUNMatrixWrapper::sparse_sum (C++ function), 482
amici::SUNMatrixWrapper::sparsetype (C++ function), 480
amici::SUNMatrixWrapper::SUNMatrixWrapper (C++ function), 477, 478
amici::SUNMatrixWrapper::to_dense (C++ function), 483
amici::SUNMatrixWrapper::to_diag (C++ function), 483
amici::SUNMatrixWrapper::transpose (C++ function), 482
amici::SUNMatrixWrapper::zero (C++ function), 483
amici::SUNNonLinSolFixedPoint (C++ class), 483
amici::SUNNonLinSolFixedPoint::getSysFn (C++ function), 484
amici::SUNNonLinSolFixedPoint::SUNNonLinSolFixedPoint (C++ function), 483
amici::SUNNonLinSolNewton (C++ class), 484
amici::SUNNonLinSolNewton::getSysFn (C++ function), 484
amici::SUNNonLinSolNewton::SUNNonLinSolNewton (C++ function), 484
amici::SUNNonLinSolWrapper (C++ class), 485
amici::SUNNonLinSolWrapper::~SUNNonLinSolWrapper (C++ function), 485
amici::SUNNonLinSolWrapper::get (C++ function), 485
amici::SUNNonLinSolWrapper::getCurIter (C++ function), 487
amici::SUNNonLinSolWrapper::getNumConvFails (C++ function), 487
amici::SUNNonLinSolWrapper::getNumIters (C++ function), 487
amici::SUNNonLinSolWrapper::getType (C++ function), 485
amici::SUNNonLinSolWrapper::initialize (C++ function), 487
amici::SUNNonLinSolWrapper::operator= (C++ function), 485
amici::SUNNonLinSolWrapper::setConvTestFn (C++ function), 486
amici::SUNNonLinSolWrapper::setLSetupFn (C++ function), 486
amici::SUNNonLinSolWrapper::setLSolveFn (C++ function), 486
amici::SUNNonLinSolWrapper::setMaxIters (C++ function), 486
amici::SUNNonLinSolWrapper::setSysFn (C++ function), 486
amici::SUNNonLinSolWrapper::setup (C++ function), 486
amici::SUNNonLinSolWrapper::Solve (C++ function), 486
amici::SUNNonLinSolWrapper::solver (C++ member), 487
amici::SUNNonLinSolWrapper::SUNNonLinSolWrapper (C++ function), 485
amici::unscaleParameters (C++ function), 515
amici::wrapErrorHandlerFn (C++ function), 516
amici::writeSlice (C++ function), 516, 517
AMICI_H5_RESTORE_ERROR_HANDLER (C macro), 525
AMICI_H5_SAVE_ERROR_HANDLER (C macro), 525
amici_to_petab_scale() (in module amici

```

ici.parameter_mapping), 276

AMICI_VERSION (C macro), 526

amievent (built-in class), 542

amifun (built-in class), 544

append() (*amici.parameter_mapping.ParameterMapping* method), 275

apply_template() (in module *amici.ode_export*), 252

assignmentRules2observables() (in module *amici.sbml_import*), 215

B

backtraceString() (in module *amici.amici*), 209

BNGL, 45

bngl2amici() (in module *amici.bngl_import*), 219

BoolVector (class in *amici.amici*), 143

boost::serialization::archiveVector (C++ function), 517

boost::serialization::serialize (C++ function), 518, 519

C

cast_to_sym() (in module *amici.import_utils*), 237

check_derivatives() (in module *amici.gradient_check*), 273

check_event_support() (*amici.sbml_import.SbmlImporter* method), 213

check_finite_difference() (in module *amici.gradient_check*), 273

check_support() (*amici.sbml_import.SbmlImporter* method), 213

clone() (*amici.amici.Model* method), 164

clone() (*amici.amici.Solver* method), 198

colptrs() (*amici.ode_export.ODEModel* method), 247

compile_model() (*amici.ode_export.ODEExporter* method), 243

compiledWithOpenMP() (in module *amici.amici*), 209

compute_moiety_conservation_laws() (in module *amici.conservd_quantities_demartino*), 278

computingASA() (*amici.amici.Solver* method), 198

computingFSA() (*amici.amici.Solver* method), 198

conservation_law_has_multispecies() (*amici.ode_export.ODEModel* method), 247

ConservationLaw (class in *amici.ode_model*), 255

Constant (class in *amici.ode_model*), 256

constant_species_to_parameters() (in module *amici.petab_import*), 220

constructEdataFromDataFrame() (in module *amici.pandas*), 269

count() (*amici.parameter_mapping.ParameterMapping* method), 275

create_dummy_sbml() (in module *amici.petab_import_pysb*), 229

create_edata_for_condition() (in module *amici.petab_objective*), 230

create_edatas() (in module *amici.petab_objective*), 230

create_parameter_df() (*amici.petab_import_pysb.PysbPetabProblem* method), 224

create_parameter_mapping() (in module *amici.petab_objective*), 231

create_parameter_mapping_for_condition() (in module *amici.petab_objective*), 231

create_parameterized_edatas() (in module *amici.petab_objective*), 231

CVODES, 45

D

DAE, 45

DoubleVector (class in *amici.amici*), 144

E

enum() (in module *amici.amici*), 209

eq() (*amici.ode_export.ODEModel* method), 247

Event (class in *amici.ode_model*), 257

ExpData (class in *amici.amici*), 144

ExpDataPtr (class in *amici.amici*), 155

ExpDataPtrVector (class in *amici.amici*), 156

Expression (class in *amici.ode_model*), 258

extract_monomers() (in module *amici.pysb_import*), 216

F

fdsigmaydy() (*amici.amici.Model* method), 164

fdtotal_cldp() (*amici.amici.Model* method), 164

fdtotal_cldx_rdata() (*amici.amici.Model* method), 164

fdx_rdatadp() (*amici.amici.Model* method), 164

fdx_rdatadtcl() (*amici.amici.Model* method), 165

fdx_rdatadx_solver() (*amici.amici.Model* method), 165

fill_in_parameters() (in module *amici.parameter_mapping*), 276

fill_in_parameters_for_condition() (in module *amici.parameter_mapping*), 276

fixed parameters, 45

FixedParameterContext (class in *amici.amici*), 156

free_symbols() (*amici.ode_export.ODEModel* method), 247

from_combine() (*amici.petab_import_pysb.PysbPetabProblem* static method), 225

from_files() (*amici.petab_import_pysb.PysbPetabProblem* static method), 225

from_folder() (*amici.petab_import_pysb.PysbPetabProblem* static method), 225

`from_yaml()` (*amici.petab_import_pysb.PysbPetabProblem* static method), 225

G

`generate_basic_variables()` (*amici.ode_export.ODEModel* method), 247

`generate_flux_symbol()` (in module *amici.import_utils*), 237

`generate_measurement_symbol()` (in module *amici.import_utils*), 237

`generate_model_code()` (*amici.ode_export.ODEExporter* method), 243

`get_appearance_counts()` (*amici.ode_export.ODEModel* method), 247

`get_conservation_laws()` (*amici.ode_export.ODEModel* method), 247

`get_dt()` (*amici.ode_model.State* method), 266

`get_expressions_as_dataframe()` (in module *amici.pandas*), 271

`get_fixed_parameters()` (in module *amici.petab_import*), 220

`get_free_symbols()` (*amici.ode_model.State* method), 266

`get_function_extern_declaration()` (in module *amici.ode_export*), 252

`get_id()` (*amici.ode_model.ConservationLaw* method), 255

`get_id()` (*amici.ode_model.Constant* method), 256

`get_id()` (*amici.ode_model.Event* method), 258

`get_id()` (*amici.ode_model.Expression* method), 259

`get_id()` (*amici.ode_model.LogLikelihood* method), 260

`get_id()` (*amici.ode_model.ModelQuantity* method), 261

`get_id()` (*amici.ode_model.Observable* method), 263

`get_id()` (*amici.ode_model.Parameter* method), 264

`get_id()` (*amici.ode_model.SigmaY* method), 265

`get_id()` (*amici.ode_model.State* method), 267

`get_lb()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_logger()` (in module *amici.logging*), 272

`get_measurement_symbol()` (*amici.ode_model.Observable* method), 263

`get_model_override_implementation()` (in module *amici.ode_export*), 252

`get_model_parameters()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_name()` (*amici.ode_model.ConservationLaw* method), 255

`get_name()` (*amici.ode_model.Constant* method), 256

`get_name()` (*amici.ode_model.Event* method), 258

`get_name()` (*amici.ode_model.Expression* method), 259

`get_name()` (*amici.ode_model.LogLikelihood* method), 260

`get_name()` (*amici.ode_model.ModelQuantity* method), 261

`get_name()` (*amici.ode_model.Observable* method), 263

`get_name()` (*amici.ode_model.Parameter* method), 264

`get_name()` (*amici.ode_model.SigmaY* method), 265

`get_name()` (*amici.ode_model.State* method), 267

`get_noise_distributions()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_observable_ids()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_observable_transformations()` (*amici.ode_export.ODEModel* method), 247

`get_observables()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_observation_model()` (in module *amici.petab_import*), 220

`get_optimization_parameter_scales()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_optimization_parameters()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_optimization_to_simulation_parameter_mapping()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_sigmas()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_simulation_conditions_from_measurement_df()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_solver_indices()` (*amici.ode_export.ODEModel* method), 248

`get_species_initial()` (in module *amici.sbml_import*), 215

`get_sunindex_extern_declaration()` (in module *amici.ode_export*), 252

`get_sunindex_override_implementation()` (in module *amici.ode_export*), 253

`get_ub()` (*amici.petab_import_pysb.PysbPetabProblem* method), 226

`get_val()` (*amici.ode_model.ConservationLaw* method), 255

`get_val()` (*amici.ode_model.Constant* method), 257

`get_val()` (*amici.ode_model.Event* method), 258

`get_val()` (*amici.ode_model.Expression* method), 259

`get_val()` (*amici.ode_model.LogLikelihood* method), 260

`get_val()` (*amici.ode_model.ModelQuantity* method), 261

[get_val\(\)](#) (*amici.ode_model.Observable method*), 263
[get_val\(\)](#) (*amici.ode_model.Parameter method*), 264
[get_val\(\)](#) (*amici.ode_model.SigmaY method*), 265
[get_val\(\)](#) (*amici.ode_model.State method*), 267
[get_x_ids\(\)](#) (*amici.petab_import_pysb.PysbPetabProblem method*), 227
[get_x_nominal\(\)](#) (*amici.petab_import_pysb.PysbPetabProblem method*), 227
[getAbsoluteTolerance\(\)](#) (*amici.amici.Solver method*), 198
[getAbsoluteToleranceB\(\)](#) (*amici.amici.Solver method*), 198
[getAbsoluteToleranceFSA\(\)](#) (*amici.amici.Solver method*), 198
[getAbsoluteToleranceQuadratures\(\)](#) (*amici.amici.Solver method*), 198
[getAbsoluteToleranceSteadyState\(\)](#) (*amici.amici.Solver method*), 199
[getAbsoluteToleranceSteadyStateSensi\(\)](#) (*amici.amici.Solver method*), 199
[getAddSigmaResiduals\(\)](#) (*amici.amici.Model method*), 165
[getAlwaysCheckFinite\(\)](#) (*amici.amici.Model method*), 165
[getAmiciCommit\(\)](#) (*amici.amici.Model method*), 165
[getAmiciVersion\(\)](#) (*amici.amici.Model method*), 166
[getCpuTime\(\)](#) (*amici.amici.Solver method*), 199
[getCpuTimeB\(\)](#) (*amici.amici.Solver method*), 199
[getDataObservablesAsDataFrame\(\)](#) (*in module amici.pandas*), 269
[getEdataFromDataFrame\(\)](#) (*in module amici.pandas*), 270
[getExpressionIds\(\)](#) (*amici.amici.Model method*), 166
[getExpressionNames\(\)](#) (*amici.amici.Model method*), 166
[getFixedParameterById\(\)](#) (*amici.amici.Model method*), 166
[getFixedParameterByName\(\)](#) (*amici.amici.Model method*), 166
[getFixedParameterIds\(\)](#) (*amici.amici.Model method*), 166
[getFixedParameterNames\(\)](#) (*amici.amici.Model method*), 166
[getFixedParameters\(\)](#) (*amici.amici.Model method*), 166
[getInitialStates\(\)](#) (*amici.amici.Model method*), 167
[getInitialStateSensitivities\(\)](#) (*amici.amici.Model method*), 166
[getInternalSensitivityMethod\(\)](#) (*amici.amici.Solver method*), 199
[getInterpolationType\(\)](#) (*amici.amici.Solver method*), 199
[getLastOrder\(\)](#) (*amici.amici.Solver method*), 199
[getLinearMultistepMethod\(\)](#) (*amici.amici.Solver method*), 199
[getLinearSolver\(\)](#) (*amici.amici.Solver method*), 199
[getMaxSteps\(\)](#) (*amici.amici.Solver method*), 200
[getMaxStepsBackwardProblem\(\)](#) (*amici.amici.Solver method*), 200
[getMaxTime\(\)](#) (*amici.amici.Solver method*), 200
[getMinimumSigmaResiduals\(\)](#) (*amici.amici.Model method*), 167
[getModel\(\)](#) (*amici.ModelModule method*), 141
[getName\(\)](#) (*amici.amici.Model method*), 167
[getNewtonDampingFactorLowerBound\(\)](#) (*amici.amici.Solver method*), 200
[getNewtonDampingFactorMode\(\)](#) (*amici.amici.Solver method*), 200
[getNewtonMaxSteps\(\)](#) (*amici.amici.Solver method*), 200
[getNewtonStepSteadyStateCheck\(\)](#) (*amici.amici.Solver method*), 200
[getNonlinearSolverIteration\(\)](#) (*amici.amici.Solver method*), 200
[getNumErrTestFails\(\)](#) (*amici.amici.Solver method*), 200
[getNumErrTestFailsB\(\)](#) (*amici.amici.Solver method*), 200
[getNumNonlinSolvConvFails\(\)](#) (*amici.amici.Solver method*), 201
[getNumNonlinSolvConvFailsB\(\)](#) (*amici.amici.Solver method*), 201
[getNumRhsEvals\(\)](#) (*amici.amici.Solver method*), 201
[getNumRhsEvalsB\(\)](#) (*amici.amici.Solver method*), 201
[getNumSteps\(\)](#) (*amici.amici.Solver method*), 201
[getNumStepsB\(\)](#) (*amici.amici.Solver method*), 201
[getObservableIds\(\)](#) (*amici.amici.Model method*), 167
[getObservableNames\(\)](#) (*amici.amici.Model method*), 167
[getObservableScaling\(\)](#) (*amici.amici.Model method*), 167
[getObservedData\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedDataPtr\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedDataStdDev\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedDataStdDevPtr\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedEvents\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedEventsPtr\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedEventsStdDev\(\)](#) (*amici.amici.ExpData method*), 150
[getObservedEventsStdDevPtr\(\)](#) (*amici.amici.ExpData method*), 150

- getParameterById() (*amici.amici.Model* method), 167
 getParameterByName() (*amici.amici.Model* method), 167
 getParameterIds() (*amici.amici.Model* method), 167
 getParameterList() (*amici.amici.Model* method), 168
 getParameterNames() (*amici.amici.Model* method), 168
 getParameters() (*amici.amici.Model* method), 168
 getParameterScale() (*amici.amici.Model* method), 168
 getReinitializationStateIdxs() (*amici.amici.Model* method), 168
 getReinitializeFixedParameterInitialStates() (*amici.amici.Model* method), 168
 getRelativeTolerance() (*amici.amici.Solver* method), 201
 getRelativeToleranceB() (*amici.amici.Solver* method), 201
 getRelativeToleranceFSA() (*amici.amici.Solver* method), 201
 getRelativeToleranceQuadratures() (*amici.amici.Solver* method), 201
 getRelativeToleranceSteadyState() (*amici.amici.Solver* method), 202
 getRelativeToleranceSteadyStateSensi() (*amici.amici.Solver* method), 202
 getResidualsAsDataFrame() (in module *amici.pandas*), 270
 getReturnDataReportingMode() (*amici.amici.Solver* method), 202
 getScaledParameter() (in module *amici.amici*), 209
 getSensiSteadyStateCheck() (*amici.amici.Solver* method), 202
 getSensitivityMethod() (*amici.amici.Solver* method), 202
 getSensitivityMethodPreequilibration() (*amici.amici.Solver* method), 202
 getSensitivityOrder() (*amici.amici.Solver* method), 202
 getSimulationObservablesAsDataFrame() (in module *amici.pandas*), 270
 getSimulationStatesAsDataFrame() (in module *amici.pandas*), 271
 getSolver() (*amici.amici.Model* method), 168
 getStabilityLimitFlag() (*amici.amici.Solver* method), 202
 getStateIds() (*amici.amici.Model* method), 168
 getStateIdsSolver() (*amici.amici.Model* method), 168
 getStateIsNonNegative() (*amici.amici.Model* method), 169
 getStateNames() (*amici.amici.Model* method), 169
 getStateNamesSolver() (*amici.amici.Model* method), 169
 getStateOrdering() (*amici.amici.Solver* method), 202
 getSteadyStateSensitivityMode() (*amici.amici.Model* method), 169
 gett() (*amici.amici.Solver* method), 203
 getTimepoint() (*amici.amici.ExpData* method), 151
 getTimepoint() (*amici.amici.Model* method), 169
 getTimepoints() (*amici.amici.ExpData* method), 151
 getTimepoints() (*amici.amici.Model* method), 169
 getUnscaledParameter() (in module *amici.amici*), 209
 getUnscaledParameters() (*amici.amici.Model* method), 169
 grouper() (in module *amici.import_utils*), 237
 gsl::make_span (C++ function), 519
- ## H
- has_fixed_parameter_ic() (in module *amici.pysb_import*), 216
 hasCustomInitialStates() (*amici.amici.Model* method), 169
 hasCustomInitialStateSensitivities() (*amici.amici.Model* method), 169
 hasExpressionIds() (*amici.amici.Model* method), 169
 hasExpressionNames() (*amici.amici.Model* method), 170
 hasFixedParameterIds() (*amici.amici.Model* method), 170
 hasFixedParameterNames() (*amici.amici.Model* method), 170
 hasObservableIds() (*amici.amici.Model* method), 170
 hasObservableNames() (*amici.amici.Model* method), 170
 hasParameterIds() (*amici.amici.Model* method), 170
 hasParameterNames() (*amici.amici.Model* method), 170
 hasQuadraticLLH() (*amici.amici.Model* method), 170
 hasStateIds() (*amici.amici.Model* method), 171
 hasStateNames() (*amici.amici.Model* method), 171
- ## I
- IDAS, 45
 import_from_sbml_importer() (*amici.ode_export.ODEModel* method), 248
 import_model() (in module *amici.petab_import*), 220
 import_model_module() (in module *amici*), 142
 import_model_pysb() (in module *amici.petab_import_pysb*), 229
 import_model_sbml() (in module *amici.petab_import*), 221
 import_petab_problem() (in module *amici.petab_import*), 221
 index() (*amici.parameter_mapping.ParameterMapping* method), 275

InternalSensitivityMethod (class in amici.amici), 156

InterpolationType (class in amici.amici), 157

IntVector (class in amici.amici), 156

is_assignment_rule_target() (amici.sbml_import.SbmlImporter method), 213

is_rate_rule_target() (amici.sbml_import.SbmlImporter method), 213

is_valid_identifer() (in module amici.ode_export), 253

isFixedParameterStateReinitializationAllowed() (amici.amici.Model method), 171

isSetObservedData() (amici.amici.ExpData method), 151

isSetObservedDataStdDev() (amici.amici.ExpData method), 151

isSetObservedEvents() (amici.amici.ExpData method), 151

isSetObservedEventsStdDev() (amici.amici.ExpData method), 151

K

k() (amici.amici.Model method), 171

L

LinearMultistepMethod (class in amici.amici), 157

LinearSolver (class in amici.amici), 157

log_execution_time() (in module amici.logging), 272

LogLikelihood (class in amici.ode_model), 259

M

M_1_PI (C macro), 526

M_2_PI (C macro), 526

M_2_SQRTPI (C macro), 526

M_E (C macro), 527

M_LN10 (C macro), 527

M_LN2 (C macro), 527

M_LOG10E (C macro), 527

M_LOG2E (C macro), 527

M_PI (C macro), 528

M_PI_2 (C macro), 528

M_PI_4 (C macro), 528

M_SQRT1_2 (C macro), 528

M_SQRT2 (C macro), 529

main() (in module amici.petab_import), 222

Model (class in amici.amici), 158

ModelDimensions (class in amici.amici), 176

ModelModule (class in amici), 141

ModelPtr (class in amici.amici), 180

ModelQuantity (class in amici.ode_model), 261

module

- amici, 140

- amici.amici, 142
- amici.bngl_import, 218
- amici.conservd_quantities_demartino, 278
- amici.conservd_quantities_rref, 279
- amici.gradient_check, 273
- amici.import_utils, 236
- amici.logging, 272
- amici.ode_export, 240
- amici.ode_model, 254
- amici.pandas, 268
- amici.parameter_mapping, 274
- amici.petab_import, 219
- amici.petab_import_pysb, 223
- amici.petab_objective, 229
- amici.petab_simulate, 234
- amici.plotting, 267
- amici.pysb_import, 216
- amici.sbml_import, 210

N

name() (amici.ode_export.ODEModel method), 248

nc1() (amici.amici.Model method), 171

NewtonDampingFactorMode (class in amici.amici), 181

nk() (amici.amici.Model method), 171

nmaxevent() (amici.amici.ExpData method), 152

nMaxEvent() (amici.amici.Model method), 171

noise_distribution_to_cost_function() (in module amici.import_utils), 238

noise_distribution_to_observable_transformation() (in module amici.import_utils), 239

NonlinearSolverIteration (class in amici.amici), 181

np() (amici.amici.Model method), 171

np1list() (amici.amici.Model method), 171

np1list() (amici.amici.Solver method), 203

nquad() (amici.amici.Solver method), 203

nt() (amici.amici.ExpData method), 152

nt() (amici.amici.Model method), 172

nullspace_by_rref() (in module amici.conservd_quantities_rref), 279

num_cons_law() (amici.ode_export.ODEModel method), 248

num_const() (amici.ode_export.ODEModel method), 248

num_events() (amici.ode_export.ODEModel method), 248

num_expr() (amici.ode_export.ODEModel method), 248

num_obs() (amici.ode_export.ODEModel method), 248

num_par() (amici.ode_export.ODEModel method), 248

num_state_reinits() (amici.ode_export.ODEModel method), 249

num_states_rdata() (amici.ode_export.ODEModel method), 249

`num_states_solver()` (*amici.ode_export.ODEModel* method), 249

`nx()` (*amici.amici.Solver* method), 203

`nx_reinit()` (*amici.amici.Model* method), 172

`nytrue()` (*amici.amici.ExpData* method), 152

`nztrue()` (*amici.amici.ExpData* method), 152

O

Observable (class in *amici.ode_model*), 262

ObservableScaling (class in *amici.amici*), 181

ObservableTransformation (class in *amici.import_utils*), 236

ODE, 45

`ode_model_from_pysb_importer()` (in module *amici.pysb_import*), 216

ODEExporter (class in *amici.ode_export*), 241

ODEModel (class in *amici.ode_export*), 243

P

Parameter (class in *amici.ode_model*), 263

ParameterMapping (class in *amici.parameter_mapping*), 274

ParameterMappingForCondition (class in *amici.parameter_mapping*), 275

ParameterScaling (class in *amici.amici*), 182

`parameterScalingFromIntVector()` (in module *amici.amici*), 209

ParameterScalingVector (class in *amici.amici*), 182

`parse_events()` (*amici.ode_export.ODEModel* method), 249

PETab, 45

`petab_noise_distributions_to_amici()` (in module *amici.petab_import*), 222

`petab_scale_to_amici_scale()` (in module *amici.petab_import*), 222

`petab_to_amici_scale()` (in module *amici.parameter_mapping*), 277

PetabSimulator (class in *amici.petab_simulate*), 234

`pivots()` (in module *amici.conservd_quantities_rref*), 279

`plist()` (*amici.amici.Model* method), 172

`plotObservableTrajectories()` (in module *amici.plotting*), 268

`plotStateTrajectories()` (in module *amici.plotting*), 268

preequilibration, 45

presimulation, 45

`process_conservation_laws()` (*amici.sbml_import.SbmlImporter* method), 213

PySB, 45

`pysb2amici()` (in module *amici.pysb_import*), 217

`pysb_model_from_path()` (in module *amici.pysb_import*), 218

PysbPetabProblem (class in *amici.petab_import_pysb*), 223

R

RDataReporting (class in *amici.amici*), 182

`rdatas_to_measurement_df()` (in module *amici.petab_objective*), 232

`rdatas_to_simulation_df()` (in module *amici.petab_objective*), 232

`reinitializeAllFixedParameterDependentInitialStates()` (*amici.amici.ExpData* method), 152

`reinitializeAllFixedParameterDependentInitialStates()` (*amici.amici.SimulationParameters* method), 194

`reinitializeAllFixedParameterDependentInitialStatesForPres` (*amici.amici.ExpData* method), 152

`reinitializeAllFixedParameterDependentInitialStatesForPres` (*amici.amici.SimulationParameters* method), 195

`reinitializeAllFixedParameterDependentInitialStatesForSimu` (*amici.amici.ExpData* method), 152

`reinitializeAllFixedParameterDependentInitialStatesForSimu` (*amici.amici.SimulationParameters* method), 195

`remove_typedefs()` (in module *amici.ode_export*), 253

`remove_working_dir()` (*amici.petab_simulate.PetabSimulator* method), 235

`replace_logx()` (in module *amici.sbml_import*), 215

`requireSensitivitiesForAllParameters()` (*amici.amici.Model* method), 172

ReturnData (class in *amici.amici*), 182

ReturnDataPtr (class in *amici.amici*), 188

`rowvals()` (*amici.ode_export.ODEModel* method), 249

`rref()` (in module *amici.conservd_quantities_rref*), 279

`runAmiciSimulation()` (in module *amici.amici*), 209

`runAmiciSimulations()` (in module *amici.amici*), 209

S

`safe_substitute()` (*amici.ode_export.TemplateAmici* method), 251

`sample_parameter_startpoints()` (*amici.petab_import_pysb.PysbPetabProblem* method), 227

SBML, 45

`sbml2amici()` (*amici.sbml_import.SbmlImporter* method), 213

SbmlImporter (class in *amici.sbml_import*), 211

`scale_parameter()` (in module *amici.parameter_mapping*), 277

`scale_parameters()` (*amici.petab_import_pysb.PysbPetabProblem* method), 227

`scale_parameters_dict()` (in module `amici.parameter_mapping`), 277
`scaleParameters()` (in module `amici.amici`), 210
`SecondOrderMode` (class in `amici.amici`), 191
`SensitivityMethod` (class in `amici.amici`), 191
`SensitivityOrder` (class in `amici.amici`), 192
`set_conservation_law()` (`amici.ode_model.State` method), 267
`set_dt()` (`amici.ode_model.State` method), 267
`set_log_level()` (in module `amici.logging`), 272
`set_name()` (`amici.ode_export.ODEExporter` method), 243
`set_paths()` (`amici.ode_export.ODEExporter` method), 243
`set_val()` (`amici.ode_model.ConservationLaw` method), 256
`set_val()` (`amici.ode_model.Constant` method), 257
`set_val()` (`amici.ode_model.Event` method), 258
`set_val()` (`amici.ode_model.Expression` method), 259
`set_val()` (`amici.ode_model.LogLikelihood` method), 260
`set_val()` (`amici.ode_model.ModelQuantity` method), 261
`set_val()` (`amici.ode_model.Observable` method), 263
`set_val()` (`amici.ode_model.Parameter` method), 264
`set_val()` (`amici.ode_model.SigmaY` method), 265
`set_val()` (`amici.ode_model.State` method), 267
`setAbsoluteTolerance()` (`amici.amici.Solver` method), 203
`setAbsoluteToleranceB()` (`amici.amici.Solver` method), 203
`setAbsoluteToleranceFSA()` (`amici.amici.Solver` method), 203
`setAbsoluteToleranceQuadratures()` (`amici.amici.Solver` method), 203
`setAbsoluteToleranceSteadyState()` (`amici.amici.Solver` method), 203
`setAbsoluteToleranceSteadyStateSensi()` (`amici.amici.Solver` method), 203
`setAddSigmaResiduals()` (`amici.amici.Model` method), 172
`setAllStatesNonNegative()` (`amici.amici.Model` method), 172
`setAlwaysCheckFinite()` (`amici.amici.Model` method), 172
`setFixedParameterById()` (`amici.amici.Model` method), 172
`setFixedParameterByName()` (`amici.amici.Model` method), 172
`setFixedParameters()` (`amici.amici.Model` method), 173
`setFixedParametersByIdRegex()` (`amici.amici.Model` method), 173
`setFixedParametersByNameRegex()` (`amici.amici.Model` method), 173
`setInitialStates()` (`amici.amici.Model` method), 173
`setInitialStateSensitivities()` (`amici.amici.Model` method), 173
`setInternalSensitivityMethod()` (`amici.amici.Solver` method), 204
`setInterpolationType()` (`amici.amici.Solver` method), 204
`setLinearMultistepMethod()` (`amici.amici.Solver` method), 204
`setLinearSolver()` (`amici.amici.Solver` method), 204
`setMaxSteps()` (`amici.amici.Solver` method), 204
`setMaxStepsBackwardProblem()` (`amici.amici.Solver` method), 204
`setMaxTime()` (`amici.amici.Solver` method), 204
`setMinimumSigmaResiduals()` (`amici.amici.Model` method), 173
`setNewtonDampingFactorLowerBound()` (`amici.amici.Solver` method), 204
`setNewtonDampingFactorMode()` (`amici.amici.Solver` method), 204
`setNewtonMaxSteps()` (`amici.amici.Solver` method), 205
`setNewtonStepSteadyStateCheck()` (`amici.amici.Solver` method), 205
`setNMaxEvent()` (`amici.amici.Model` method), 173
`setNonlinearSolverIteration()` (`amici.amici.Solver` method), 205
`setObservedData()` (`amici.amici.ExpData` method), 152
`setObservedDataStdDev()` (`amici.amici.ExpData` method), 153
`setObservedEvents()` (`amici.amici.ExpData` method), 154
`setObservedEventsStdDev()` (`amici.amici.ExpData` method), 154
`setParameterById()` (`amici.amici.Model` method), 174
`setParameterByName()` (`amici.amici.Model` method), 174
`setParameterList()` (`amici.amici.Model` method), 175
`setParameters()` (`amici.amici.Model` method), 175
`setParametersByIdRegex()` (`amici.amici.Model` method), 175
`setParametersByNameRegex()` (`amici.amici.Model` method), 175
`setParameterScale()` (`amici.amici.Model` method), 175
`setReinitializationStateIdxs()` (`amici.amici.Model` method), 175
`setReinitializeFixedParameterInitialStates()` (`amici.amici.Model` method), 175
`setRelativeTolerance()` (`amici.amici.Solver` method), 205
`setRelativeToleranceB()` (`amici.amici.Solver`

method), 205

setRelativeToleranceFSA() (amici.amici.Solver method), 205

setRelativeToleranceQuadratures() (amici.amici.Solver method), 205

setRelativeToleranceSteadyState() (amici.amici.Solver method), 205

setRelativeToleranceSteadyStateSensi() (amici.amici.Solver method), 205

setReturnDataReportingMode() (amici.amici.Solver method), 206

setSensiSteadyStateCheck() (amici.amici.Solver method), 206

setSensitivityMethod() (amici.amici.Solver method), 206

setSensitivityMethodPreequilibration() (amici.amici.Solver method), 206

setSensitivityOrder() (amici.amici.Solver method), 206

setStabilityLimitFlag() (amici.amici.Solver method), 206

setStateIsNonNegative() (amici.amici.Model method), 176

setStateOrdering() (amici.amici.Solver method), 206

setSteadyStateSensitivityMode() (amici.amici.Model method), 176

setT0() (amici.amici.Model method), 176

setTimepoints() (amici.amici.ExpData method), 155

setTimepoints() (amici.amici.Model method), 176

setUnscaledInitialStateSensitivities() (amici.amici.Model method), 176

show_model_info() (in module amici.petab_import), 222

SigmaY (class in amici.ode_model), 264

simulate() (amici.petab_simulate.PetabSimulator method), 235

simulate_petab() (in module amici.petab_objective), 232

simulate_without_noise() (amici.petab_simulate.PetabSimulator method), 235

SimulationParameters (class in amici.amici), 192

smart_is_zero_matrix() (in module amici.ode_export), 253

smart_jacobian() (in module amici.ode_export), 253

smart_multiply() (in module amici.ode_export), 254

smart_subs() (in module amici.import_utils), 239

smart_subs_dict() (in module amici.import_utils), 239

Solver (class in amici.amici), 195

SolverPtr (class in amici.amici), 207

sparseeq() (amici.ode_export.ODEModel method), 249

sparsesym() (amici.ode_export.ODEModel method), 249

species_to_parameters() (in module amici.petab_import), 222

startTimer() (amici.amici.Solver method), 206

State (class in amici.ode_model), 266

state_has_conservation_law() (amici.ode_export.ODEModel method), 249

state_has_fixed_parameter_initial_condition() (amici.ode_export.ODEModel method), 250

state_is_constant() (amici.ode_export.ODEModel method), 250

SteadyStateSensitivityMode (class in amici.amici), 207

SteadyStateStatus (class in amici.amici), 207

SteadyStateStatusVector (class in amici.amici), 208

StringDoubleMap (class in amici.amici), 208

StringVector (class in amici.amici), 208

strip_pysb() (in module amici.import_utils), 240

subset_call() (in module amici.petab_simulate), 236

subset_dict() (in module amici.petab_objective), 233

substitute() (amici.ode_export.TemplateAmici method), 251

SUNDIALS, 45

SWIG, 45

switchForwardSensisOff() (amici.amici.Solver method), 206

sym() (amici.ode_export.ODEModel method), 250

sym_names() (amici.ode_export.ODEModel method), 250

sym_or_eq() (amici.ode_export.ODEModel method), 250

symbol_with_assumptions() (in module amici.import_utils), 240

T

t0() (amici.amici.Model method), 176

TemplateAmici (class in amici.ode_export), 251

timeExceeded() (amici.amici.Solver method), 207

to_files() (amici.petab_import_pysb.PysbPetabProblem method), 227

to_files_generic() (amici.petab_import_pysb.PysbPetabProblem method), 228

toposort_symbols() (in module amici.import_utils), 240

U

unscale_parameter() (in module amici.parameter_mapping), 277

unscale_parameters() (amici.petab_import_pysb.PysbPetabProblem method), 228

unscale_parameters_dict() (in module amici.parameter_mapping), 278

`unscaleParameters()` (*in module amici.amici*), [210](#)

V

`val()` (*amici.ode_export.ODEModel method*), [250](#)

`var_in_function_signature()` (*in module amici.ode_export*), [254](#)